Plugin Group Mail Core

Introduced in Tiki4
Use this wiki plugin to display GroupMail functions on a wiki page. Usually set up using a plugin alias created by the GroupMail profile.

Parameters

Display GroupMail functions on a page
Introduced in Tiki 4. Required parameters are in **bold**.
Go to the source code
Preferences required: wikiplugin_groupmailcore, feature_trackers

Parameters	Accepted Values	Description	Default	Since
fromEmail		Email address to report.		4.0
accountFId	digits	ID of GroupMail Logs tracker field (usually set up in alias by profile).		4.0
contentFId	digits	ID of GroupMail Logs tracker field (usually set up in alias by profile).		4.0
datetimeFId	digits	ID of GroupMail Logs tracker field (usually set up in alias by profile).		4.0
fromFId	digits	ID of GroupMail Logs tracker field (usually set up in alias by profile).		4.0
messageFId	digits	ID of GroupMail Logs tracker field (usually set up in alias by profile).		4.0
operatorFId	digits	ID of GroupMail Logs tracker field (usually set up in alias by profile).		4.0
subjectFId	digits	ID of GroupMail Logs tracker field (usually set up in alias by profile).		4.0
trackerId	digits	ID of GroupMail Logs tracker (set up in alias by profile).		4.0

Aliases

PlugingroupmailCore | PluginGroupmailcore | Plugin Group Mail Core | Plugin Group mail core