

PluginTabs

Introduced in [Tiki4](#)

Use this [wiki plugin](#) to arrange content into tabs.

Parameters

Arrange content in tabs

Introduced in Tiki 4. Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: `wikiplugin_tabs`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Tabs content, separated by "////"		
<code>tabs</code>	text	Pipe-separated list of tab titles. Example: <code>tab 1 tab 2 tab 3</code>	4.0	
<code>panelbgcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
<code>panelbordercolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
<code>panelborderwidth</code>	text	To change the width of panel border in pixels (1 by default). For example: 3 for 3 pixels	1	25.0
<code>panelfontsize</code>	text	To set the size of the text in pixels. For example: 20 for 20 pixels	16	25.0
<code>paneltextcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
<code>tabactivebgcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
<code>tabactivetextcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
<code>tabbgcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	

<code>tabbordercolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0
<code>tabborderwidth</code>	text	To change the width of tabs border in pixels (1 by default). For example: 3 for 3 pixels	1 25.0
<code>tabfontsize</code>	text	To set the size of the tabs text in pixels. For example: 20 for 20 pixels	16 25.0
<code>tabtextcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0
<code>name</code>	text	Unique tabset name (if you want the last state to be remembered). Example: <code>user_profile_tabs</code>	4.0
<code>inside_pretty</code>	(blank) n y	Parse pretty tracker variables within tabs	n 8.0
<code>panelborderstyle</code>	(blank) none hidden dotted dashed solid double groove ridge inset outset	Determine the kind of border to apply to the panels	none 25.0
<code>panelfontweight</code>	(blank) normal bold bolder lighter 900	Use to define the thickness of the text characters to be displayed in the panels	normal 25.0
<code>paneltextstyle</code>	(blank) normal italic oblique	Use to change the panels text style	normal 25.0

<code>tabborderstyle</code>	(blank) none hidden dotted dashed solid double groove ridge inset outset	Determine the kind of border to apply to the tabs	none	25.0
<code>direction</code>	(blank) horizontal vertical	Change direction of tabs (horizontal by default).	horizontal	25.0
<code>tabfontstyle</code>	(blank) normal italic oblique	Use to specify the font style of the tabs text	normal	25.0
<code>tabfontweight</code>	(blank) normal bold bolder lighter 900	Use to define the thickness of the text characters to be displayed in the tabs	normal	25.0
<code>toggle</code>	(blank) y n	Allow toggling between tabs and no-tabs view	y	8.0

Example

This code:

```
{TABS(name="user_tabset_01" tabs="Title 1|Title 2|Title3")}This is the content of the first tab //// This is the content of the second tab //// This is the content of the third tab {TABS}
```

Would produce:

This is the content of the first tab

This is the content of the second tab

This is the content of the third tab

When clicking on a tab name, the content of each tab is loaded and shown without refreshing the browser window.

And when clicking on the "**No Tabs**" option, the display would change into:



Related pages

- [PluginPageTabs](#)

Aliases

[Plugintabs](#) | [Plugintab](#) | [PluginTab](#) | [Plugin Tabs](#) | [Plugin tabs](#)