

Sortable List of Control blocks

Command

ALTERNATE

body

caption

carousel

Description

used in conjunction with the OUTPUT command it can define an alternative output when an individual item (row) from a search/listing has no value.

wraps the carousel specific parameters and values inside a command OUTPUT with type=carousel

Required **see also**

optional PluginList output control block

optional

optional

optional

Command

column

display

Description

Optionally sed when in the command OUTPUT (embraced) the parameter type=table.

{column ...} defines the specific configuration of each column of the table.

One command per column.

Used to define placement and formatting of individual objects.

{display ...} embraced by the FORMAT command.

Required **see also**

optional

optional PluginList display control block

Command

filter

Description

filter is a required command in the LIST body content and is used to define the search query that will be run to gather a set of results from the complete set of objects that have been indexed by the Unified Search.

A large number of possible individual parameters can be 'filtered' . Multiple filter commands can be applied in an additive manner, ie the equivalent of an AND operation.

Required see also

required

Command

FORMAT

icon

Description

The `FORMAT` command is used to create individually templated objects that can then be used in any of the individual `OUTPUT` methods.

The `FORMAT` command allows to apply a wiki template and store it inside a named value. The value can then be used inside an other wiki template, or more usefully inside a smarty template.

Required **see also**

optional PluginList format control block

optional

Command

list

OUTPUT

Description

Up to Tiki 12.3, replaced by 'pagination'

The LIST plugin will display 50 results by default but depending on the output you might want to decrease the visible amount of results to improve performance.

The OUTPUT command defines what the output 'template' will be for the results.

By placing Wiki syntax directly in the OUTPUT body content, along with the required objects to be displayed, the command allows a template for each row of output to be constructed within the LIST plugin itself.

Required **see also**

optional

optional see the child pages LIST - output command

Command

output

Description

The simplified lower case output plugin-like format can be used ie without separate opening and closing OUTPUT tags since any body content would be ignored when a separate wiki page template is used. Also the use of the FORMAT commands allows individual objects to be 'formatted' and then referenced in the various OUTPUT methods - see LIST - format command for more details.

Required **see also**

optional

Command

pagination

Description

From Tiki 11, replaces 'list'

The LIST plugin will display 50 results by default but depending on the output you might want to decrease the visible amount of results to improve performance.

Required see also

optional

Command

sort

Description

Allows the resultant list of objects to be sorted in a specified order.

Please be warned that sorting is normally based on string. if you are trying to sort by numbers, make sure all your numbers are of the same number of digits. Otherwise 2 will be larger than 12 if doing a string sort. see aswell:

LIST - sort command

There is aswell a parameter 'sort' that can be used in the command 'column'.

Required **see also**

optional

Sortable List of Parameters

Parameter	Command
categories	filter (inline)
code	display (inline)
content	filter (inline)
contributors	filter (inline)

Description

Match on the object's directly associated categories.

Full text search on all of the object's content

Additional field argument can be provided to search for other fields instead of the default ones.

user login to search for as the contributors for the content

Version

Parameter	Command
deepcategories	filter (inline)

Description

Match on the object's categories or their parents, providing deep searching.

Version

Parameter

Command

editable

display (inline)

Description

`editable=inline` will set the field to be editable online.
required: "Inline editing (found in trackers)" and column should be set to `mode=raw`.

example:

```
{column label="First Name" field="firstName"  
mode=raw}
```

...

```
{FORMAT(name="firstName")} {display  
name="tracker_field_firstName" format=trackerrender  
editable=inline} {FORMAT}
```


Version

11.x

Parameter	Command
excludeParents	display (inline)
favorite	filter (inline)
field	column (inline)
field	filter (inline)

Description

Show only the favorited objects of a certain user.

name of the field(s) of this column

corresponds (must be identical) with the parameter

"name" of the command "FORMAT"

to search trackers (for type=trackeritem, specify field;

for instance, for tracker field "Foo Bar" with permanent

name "foobar", you need to write

field=tracker_id_foobar)

object type to filter, example: field=tracker_id

Version

Parameter	Command
field	caption (inline)
field	body (inline)
format	display (inline)
id	carousel (inline)
interval	carousel (inline)
label	column (inline)

Description

plain, objectlink, date, datetime, trackerrender,
reference, snippet, categorylist, wikiplugin,
imagegrabber, ...

Defines the time in milliseconds, until the slides of a
carousel change.

Version

Parameter

Command

language

filter (inline)

list_mode

display (inline)

Description

Search on the object's language (2-letter code) when available. unknown is used when unspecified.

list_mode="y" can be added to use the list display settings for that field.

example:

```
{display name="tracker_field_42"  
format="trackerrender" list_mode="y"}
```

Version

9.x

Parameter

Command

max

pagination (inline)

max

list (inline)

mode

column (inline)

mode

body (inline)

name

display (inline)

Description

numeric

number of displayed results if not the default
(preference *maxRecords* which defaults to 25)

numeric

number of displayed results if not the default
(preference *maxRecords* which defaults to 25)

use for mode=raw to prevent wiki formatting

use for mode=raw to prevent wiki formatting

text identifier of the object to display (ex. a tracker field)

example: name="tracker_field_permanentName"

Version

Parameter

Command

name

FORMAT (embracing)

objecttype

filter (inline)

Description

The name parameter in the FORMAT command defines the name of an object with that is displayed in a specific way. This object reference is then used in the column command embraced by the OUTPUT command.

A similar use of the FORMAT command allows the normal set of smarty variables, eg {user} etc, to be made available in smarty templates, using
name="smarty variable"

tba

Version

Parameter	Command
pagedescription	display (inline)

Description

`pagedescription="y"` will set the page's meta description tag to the contents of the field for the first item found in the results with `pagedescription` set if the `metatag_pagedesc` preference is enabled.

Note: For both `pagedescription` and `pagetitle` no filtering is performed on the content, so use plain text only and avoid non-alphanumeric characters.

Version

9.x

Parameter

Command

pagetitle

display (inline)

pause

carousel (inline)

Description

`pagetitle="y"` will set the browser title to the contents of the field for the first item found in the results with `pagetitle` set (useful for single item result pages)

Note: For both `pagedescription` and `pagetitle` no filtering is performed on the content, so use plain text only and avoid non-alphanumeric characters.

Version

11.x

Parameter

Command

price

display (inline)

qualifier

filter (inline)

range

filter (inline)

Description

depends on displayed object

example:

```
{display name="wikiplugin_addtocart"  
format=wikiplugin price="tracker_field_44" ...}
```

tba

A date range (unix timestamp) must have from and to arguments specified or can take "now" instead of a unix timestamp. You can also set either from or to together with "gap" to specify the one relatively to the other.

Version

Parameter

Command

relation

filter (inline)

requiredParents

display (inline)

separator

display (inline)

singleList

display (inline)

sort

column (inline)

Description

Must have certain relation.

Additional field arguments `objecttype` and `qualifier` (the relationship) must be specified.

Version

1.0.0

1.0.1

1.0.2

1.0.3

1.0.4

1.0.5

1.0.6

1.0.7

1.0.8

1.0.9

1.0.10

1.0.11

1.0.12

1.0.13

1.0.14

Parameter

Command

template

OUTPUT (embracing)

textrange

filter (inline)

Description

A simple built-in templating method can be used by setting the OUTPUT template parameter.

See:

LIST - output command

Note: by placing Wiki syntax directly in the OUTPUT body content, along with the required objects to be displayed, the command allows a template for each row of output to be constructed within the LIST plugin itself.

A text range must have from and to arguments specified.

Version

Parameter

Command

thumb

display (inline)

type

filter (inline)

type

display (inline)

Description

depends on the displayed object

example

```
{display name="wikiplugin_img" format="wikiplugin"  
field="tracker_field_pic" thumb="box" ...}
```

Filter on object type:

wiki page, trackeritem

multiple types by providing a comma separated list

Example: category, freetag, trackeritem

Version

1.0.0

1.0.1

1.0.2

1.0.3

1.0.4

1.0.5

1.0.6

1.0.7

1.0.8

1.0.9

1.0.10

Parameter

Command

wiki

OUTPUT (embracing)

wrap

filter (inline)

Description

The OUTPUT command can specify a wiki page where the wiki '**templating**' will be defined similarly than a pretty tracker template for the wiki plugin trackerlist.

Version

Sortable List of Values

Value

Parameter

Command

carousel

template

OUTPUT (embracing)

Description

Sample using the default Bootstrap Carousel formatting.

See:

LIST - output command

Version

14.x

Value	Parameter	Command
date	format	display (inline)
datetime	format	display (inline)
imagegrabber	format	display (inline)
medialist	template	OUTPUT (embracing)
objectlink	format	display (inline)
plain	format	display (inline)

Description

using the short date format

using the short datetime format

automatically grabs images from a source that is provided.

Sample using the default media list formatting.

See:

LIST - output command

uses the value as the label to a link to the object

as-is, default format

optionally in conjunction with parameter 'separator'

Version

8.x

13.x

Value	Parameter	Command
reference	format	display (inline)

Description

to display a link based on the value
mandatory in conjunction with parameter 'type'
optionally in conjunction with parameter 'separator'

use "format=reference" for tracker fields which are
"page selector" fields, to assure that you link to the
page whose name is contained in the tracker, rather
than to the tracker record.

Version

Value	Parameter	Command
snippet	format	display (inline)
table	template	OUTPUT (embracing)

Description

to display the initial portion of the a large text
optionally in conjunction with parameters 'length' and
'suffix'

Note that the column plugins (within OUTPUT) are
converted to a data array sent to the template. The
table formatting uses smarty formatting and provides
the same capabilities.

See:

LIST - output command

Version

Value	Parameter	Command
trackerrender	format	display (inline)

Description

to render a tracker field (when using trackerrender the Smarty variable "`$context.search_render`" will be "y" and can be used to have different formatting in the trackeroutput Smarty tpl)

Version

1.0.0

1.0.1

1.0.2

1.0.3

1.0.4

1.0.5

1.0.6

1.0.7

1.0.8

1.0.9

1.0.10

Value	Parameter	Command
wikiplugin	format	display (inline)

Description

renders a wiki plugin in the list output

mandatory in conjunction with parameter 'name' <->

plugin name, e.g. wikiplugin_img

optionally in conjunction with parameter 'default' <->

fallback values for any parameters in url query format
(e.g. fileId=42&caption=Not+Found)

optionally in conjunction with other plugin params (Tiki
11)

Version