Requirements

This page lists the minimum requirements and recommended settings to install Tiki.

See also Tiki's Lifecycle and Browser Compatibility.

If you are using a standard shared webhost, your webhost most likely meets these requirements and you should be able to install Tiki with no problems. Tiki is designed to run on shared hosting, using the LAMP stack.

These instructions are useful for people that are configuring their own server for Tiki.

🖸 Â Tip

A Server Check script has been developed that will make everything easier! Just upload a single PHP file to your server before installing Tiki and you will get an advice on your server configuration.

Shared Host

Tiki will run in most shared webhost environments. Many hosts offer Tiki installation via a control panel application (such as Fantastico).

You should verify that your webhost meets the minimum requirements:

- HTTP server
- Database

• PHP

See Tiki Friendly Hosts for a list of working shared host environments.

Requirements

Webserver

You must have a fully operational webserver in order to install and use Tiki. Tiki *should* run on **any** webserver that supports PHP (such as nginx, Windows IIS or lighttpd), but is most widely tested and used with Apache. You may need to make minor modifications for non-Apache webservers.

Your webserver should be configured with the following **minimum** requirements:

• 512 MB RAM

• 100 MB free storage





Tiki requires MariaDB, MySQL or Percona Server for MySQL.

We are moving to a machine readable format: https://gitlab.com/tikiwiki/tiki-manager/-/blob/master/config/tiki_requirements.yml

Tiki Version	MariaDB Versions	
Tiki27 LTS (not released yet)	10.5+	8+

MariaDB 10.2.2+ or MySQL 5.7+ are the versions where the InnoDB row format is by default Dynamic, required for some tables.

Tiki Version	MariaDB Versions	
Tiki21 to Tiki26	5.5+	5.7+
Tiki19 or Tiki20	5.5-10.4	5.5.3-5.7

No known issues as of 2023-06-15

MySQL 5.6+ or MariaDB 10.1+ are recommended. First version to support utf8mb4

Tiki Version	MariaDB Versions	
Tiki18	5.1-10.4	5.0-5.7
LTS		

Tiki155.0-10.15.0-5.6LTS

MySQL 5.6+ or MariaDB 10.1+ are recommended as not all features will be available at lesser versions.

In Tiki 15+ Upgrade scripts in in MariaDB 10.1 / MySQL 5.6 may not work from earlier versions of Tiki.

Tiki Version	MariaDB Versions	
Tiki12 LTS	5.1-5.5	5.0-5.5

The database can be installed in the same physical location of the webserver (that is, as **localhost**) or Tiki can access a remote database.

PHP



We are moving to a machine readable format: https://gitlab.com/tikiwiki/tiki-manager/-/blob/master/config/tiki_requirements.yml

Tiki Version	Minimum PHP Version	Maximum PHP Version
Tiki28 (not released yet)	8.1?	8.4
Tiki27 (not released yet)	8.1	8.3

We'll decide this once Tiki27 is released. Expected to be OK until PHP 9.0

Expected to be OK until PHP 9.0

Tiki Version	Minimum PHP Version	Maximum PHP Version
Tiki26	8.1	8.1 (8.2 and 8.3 as Beta)
Tiki22, Tiki23, Tiki24 LTS and Tiki25	7.4	7.4

Related: PHP 8

Tiki Version	Minimum PHP	Maximum PHP
	Version	Version
Tiki21	7.2	7.3
LTS		

Tiki19 or 7.1 Tiki20 7.2(maybe7.3 aswell)

You can fairly safely use 7.4 if you disregard or suppress the notices and warnings.

There is known issue with Tiki 20.2 where PHP requirement was bumped up to PHP 7.2 accidentally

Tiki Version	Minimum PHP Version	Maximum PHP Version
Tiki18 LTS	5.6	7.2
Tiki15 LTS	5.5	5.6
Tiki12 LTS	5.3	5.6

Interesting links about PHP lifecycle

- http://php.net/supported-versions.php
- https://wiki.php.net/rfc/releaseprocess
- https://w3techs.com/technologies/details/pl-php

Note on PHP Memory Limits:

The default memory_limit in a standard PHP installation is **128M**, and this should be fine for the vast majority of Tiki installations. Some web hosts install PHP with a lower default. Although Tiki may appear to install successfully, you will continually face issues with pages failing to load and system errors.

To review your PHP Memory Limits, access **http://www.example.com/tiki-phpinfo.php** and review the following values:

- max_execution_time = 60 ; Maximum execution time of each script, in seconds
- max_input_time = 60 ; Maximum amount of time each script may spend parsing request data
- memory_limit = 128M ; Maximum amount of memory a script may consume

For some shared webhosts, these values may not be user-configurable and you may need to request changes from your webhost, whereas in other hosts you are allowed to fine tune these settings for your needs. You can try uncommenting the corresponding lines in the .htaccess file at your tiki root folder on the server, like:

increase memory php_value memory_limit 128M # increase execution time... php_value max_execution_time 90

More information

Required PHPÂ Functions

Some webhosts tend to disable some functions which are required for Tiki to run flawlessly.

Function Notes

eval()

Required by Smarty templating engine. Causes "Please contact support about" messages appearing instead of Modules when *eval()* is disabled in php.ini.

Additional Libraries

Library	Notes
libxml	Required
DOM	Required starting from Tiki 19

Library mbstring

Notes

Useful when working with languages that require it mbstring needs to be compiled with --enable-mbregex or otherwise you will be missing functions like mb split() which are needed for example by Smarty. Since Tiki 17, the symfony/polyfillmbstring compatibility library (via symfony-console) is used in core functionality, but mbstring is still required for some functionality.

Library	Notes
ctype	Required
calendar	Required
iconv	Required by certain Zend Framework validation and parsing classes
MySQLi	In Tiki 12+ MySQLI is recommended but the Tiki installer will fall back to the older MySQL driver if MySQLi is unavailable.

zipThe ZipArchive class for php must be installed for some features such as XML Wiki Import-Export and PluginArchiveBuilder	Library	Notes
	zip	installed for some features such as XML Wiki Import-Export and

php.ini Configuration

We recommend using the following configuration in your **php.ini** file:

PHP.INI Setting

memory_limit = 128M

Description

Specify the maximum memory for PHP scripts.

PHP.INI Setting _file_uploads = On

upload_max_filesize =
XXM
post_max_size
session.save path =

/tmp

Description

Required to allow uploads (files, images, etc.) to your Tiki

Specify the maximum upload filesize (in MB).

The directory where PHP stores session information (for the default handler (*files*)). Ensure that the location exists and is writable. In Shared Hosting environments, if you do not have access to **/tmp**, use **temp** (no slash) instead.

PHP.INI Setting

max_execution_time =
60

max_input_time = 60

default_charset =

"utf-8"

mbstring.func_overload = 0

Description

Specify the idle timeout (in seconds). If you experience timeouts (such as when performing Admin functions) you may need to increase these settings.

Specify the default character encoding.

Tiki will not work properly with **mbstring.func_overload = 7**.

The location of the **php.ini** file may vary, depending on your operating sytem. Some common locations include:

- /etc/php.ini
- /etc/php/php.ini
- /etc/php5/apache2/php.ini (Debian)
- /etc/php/7.x/apache2/php.ini

\windows\system\php.ini (Windows)

Optional Software or Libraries

Some Tiki features require the following additional software or libraries:

Feature

Rewrite Tiki's default URLs

Elasticsearch

Manticore Search

Additional Requirements

- Use the Apache Clean URLs to create shorter, or custom, URLs.
- See Elasticsearch page (requirements section)
- See Manticore Search page (requirements section)

Tiki Manager

 Tiki Manager checks which version it can install or upgrade to: https://gitlab.com/tikiwiki/tiki-manager/-/merge_requests/233/diffs

• Here is the current data:

https://gitlab.com/tikiwiki/tiki-manager/-/blob/master/config/tiki_requirements.yml