## **Performance Tab**

Related Topics

## Overview

Use this tab to configure Tiki's general performance features.

## To Access

From the Performance Admin Panel page, click the **Performance** tab.

|   | D C         |
|---|-------------|
| • | Performance |
|   |             |

| Option                           | Description  | Default  |
|----------------------------------|--|----------|
| Monitor Tiki Performance         | Register multiple parameters related to tiki's performance   | Disabled |
| Minify JavaScript                | Compress JavaScript files used in the page into a single file to be distributed statically. Changes to JavaScript files will require cache to be cleared. Uses <a href="http://code.google.com/p/minify/">http://code.google.com/p/minify/</a>   | Disabled |
| Minify late JavaScript           | Compress extra JavaScript files used in the page after tiki-setup into a separate file which may vary from page to page.   | Disabled |
| Use CDN for JavaScript           | Obtain jQuery and jQuery UI libraries through a content delivery network (CDN).<br>∷ None   Google   jQuery  | None     |
| Content delivery networks        | Use alternate domains to serve static files from this Tiki site to avoid sending cookies, improve local caching and generally improve user-experience performance.  List of URI prefixes to include before static files (one per line), for example: <a href="http://cdn1.example.com">http://cdn1.example.com</a>       | None     |
| Content delivery networks in SSL | Use alternate domains to serve static files from this Tiki site to avoid sending cookies, improve local caching and generally improve user-experience performance. Leave empty to disable CDN in SSL mode.  List of URI prefixes to include before static files (one per line), for example: https://sslcdn1.example.com | None     |
| Check CDN files exists           | Check that minified JS and CSS files exist before including them in the page.  | Enabled  |
| Prefix CSS                       | Use -prefix-free JavaScript library to add vendor specific css prefixes. $\blacktriangle$ May be replaced by a server-side option soon. $\blacksquare$   | Disabled |
| Minify CSS                       | Compress CSS files (notably by removing white space). Changes to CSS files will require cache to be cleared. Uses http://code.google.com/p/minify/   | Disabled |
| Minify CSS into a single file    | In addition to reducing the size of the CSS files, reduce the number of files by consolidating them.  A This setting may not work out of the box for all styles. Import needs to use @import url("") and not @import ""  | Disabled |
| GZip output                      | Compress your pages on-the-fly, if the requesting browser supports this  | Enabled  |
| Cache-control header             | Custom HTTP header to use when a session is active $\clubsuit$ Example: no-cache, pre-check=0, post-check=0  | None     |
| Smarty compilation               | Indicates when the template cache should be refreshed.   | Modified |

| Option                            | Description   | Default  |
|-----------------------------------|---|----------|
| Serve profile pictures statically | When enabled, feature checks and permission checks will be skipped. | Enabled  |
| Allow image lazy loading          | Allow that images are loaded in a lazy way                          | Disabled |