

# Plugin Mouseover

Introduced in [Tiki3](#)

Use this [wiki plugin](#) to display hidden content by mousing over text.

## Parameters

Display hidden content by mousing over text

Introduced in *Tiki 3*. Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: `wikiplugin_mouseover`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Hidden content, unless the label parameter is undefined, in which case this is the label.		
<b>label</b>	text	Text displayed on the page. The body is the hidden content.		3.0
url	url	Destination link when mouseover text is clicked. Use <code>http://</code> for external links	<code>javascript:void(0)</code>	3.0
bgcolor	text	Background color to apply to the popup		3.0
class	text	CSS class to apply	<code>plugin-mouseover</code>	4.0
closeDelay	digits	Number of seconds before popup closes	0	5.0
effect	(blank)  none  slide  fade  blind_ui  clip_ui  drop_ui  explode_ui  fold_ui  puff_ui  slide_ui	Set the type of show/hide animation that will be used		4.0
height	digits	Mouseover box height. Default: 200px	200	3.0
offsetx	int	Shifts the overlay to the right by the specified number of pixels relative to the cursor. Default: 5	5	3.0
offsety	int	Shifts the overlay lower by the specified number of pixels relative to the cursor. Default: 0	24	3.0
padding	digits	Padding size in pixels		3.0
tag	word	HTML tag to use for the label. Default <code>a</code>	<code>a</code>	9.2
text	text	DEPRECATED Hidden content. The body contains the label.		3.0
textcolor	text	Color to apply to the text in the popup		3.0
width	digits	Mouseover box width. Default: 400px	400	3.0

speed	(blank) fast slow	Set the speed of the animation.		4.0
parse	(blank) y n	Parse the body of the plugin as wiki content (parsed by default)	y	3.0
parselabel	(blank) y n	Parse the label as wiki content (parsed by default)	y	5.0
sticky	(blank) y n	When enabled, popup stays visible until it is clicked.		3.0

## Examples

### Non-sticky Mouseover

*This code:*

```
{MOUSEOVER(label="Hello" offsetx="4" offsety="15")}Hello over there. It's fine!{MOUSEOVER}
```

*Would produce:*

Hello

### Sticky Mouseover with Tiki Syntax

*This code:*

```
{MOUSEOVER(label="Sticky" sticky="y" parse="y" offsetx="4" offsety="15")}This is a "sticky" popup{MOUSEOVER}
```

*Would produce:*

Sticky