

Note: This is for [Tiki27](#) and beyond, non-functional in [Tiki25](#) and [Tiki26](#) because [Bootstrap Tour](#) has not yet been ported to [Bootstrap 5](#). For [Tiki24](#) and under, look at [PluginTour-Old](#).

# Plugin Tour

Introduced in [Tiki15](#)

Use this [wiki plugin](#) to build your product tours, page component describers and other sequential information displays in a quick and easy way, using [driver.js](#).

## Parameters

Quick and easy way to build your product tours with Driver.js

Introduced in Tiki 15. Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: `wikiplugin_tour`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Content of the step		
<b>title</b>	text	Title of the step		15.0
element	text	Element to show the popup on; if empty, use the plugin location itself		15.0
next_button_text	text	Text to show on the Next button. (Set only in the first step.)	Next	27.0
number_of_steps	int	Number of steps in the tour. (Set only in the first step.)		27.0
overlay_color	text	Set an overlay color to be shown behind the popover and its element, highlighting the current step. (Set only in the first step.)	transparent	27.0
overlay_opacity	int	Set the opacity of the overlay. (Set only in the first step.)	0.5	27.0
prev_button_text	text	Text to show on the Prev button. (Set only in the first step.)	Previous	27.0
progress_text	text	Template for the progress text. You can use the following placeholders in the template: <code>// - :</code> The current step number. <code>// - :</code> Total number of steps. Example: Step of . (Set only in the first step.)	of	27.0
show_restart_button	text	Display a button to restart the tour. Enter the text to appear on the button. (Set only in the first step.)		15.0
tour_id	text	Set a tour ID to be able to only show the tour once. (Set only in the first step.)	default	15.0

align	end start center	The alignment of the popup. (Set only in the first step.)	end	15.0
animate	y n	Animate the popup. (Set only in the first step.)	y	27.0
show_once	(blank) y n	Show automatically only once. tour_id should also be set if there are multiple tours. (Set only in the first step.)	n	15.0
show_progress	y n	Show the progress text in popover. (Set only in the first step.)	n	27.0
side	right top bottom left	The side of the popup. (Set only in the first step.)	right	15.0
start	y n	Start the tour on page load? If "No", then a start button can be made with "Restart Button", below. (Set only in the first step.)	y	15.0
allow_close	y n	Allow closing the popover by clicking on the backdrop. (Set only in the first step.)	y	16.0

## Examples

Let's see an example of a tour with 4 steps  
The first step:

```
{TOUR(title="Welcome to the tour" element="#PluginTour" start="y" tour_id="1" overlay_color="black")}{TOUR}
```

The second step:

```
{TOUR(title="A typical second step")}{TOUR}
```

The third step:

```
{TOUR(element="#module_1 .panel-heading" title="This is a module heading.")}{TOUR}
```

The last step:

```
{TOUR(title="The last step")}{TOUR}
```

## Usage notes

- For each step of the tour, input the Tour plugin syntax as shown above.
- If the tour isn't configured to start on page load (if *start="n"* is set), a start button can be made with the `show_restart_button` parameter.
- Each step will pop over the middle of the page unless the `element` parameter is set correctly.
- The position of the popup relative to the element it pops up over can be set with the `side` parameter.
- To create a step that is positioned other than where the plugin syntax is input, use the `element` parameter to specify an HTML id or other unique selector.

## Adding a tour to a page that doesn't have wiki text content

Normally, as described above, the tour plugins are written into the wiki text of the page(s) on which the tour displays. However, it is possible to have a tour on an admin page or other such page that doesn't have wiki text.

This method uses a [module](#) for the tour plugin text that is assigned to, for example, the pagebottom module zone. Since all the steps of the tour are in the admin page content (and not in the module zone), the *element* parameter is used for each step that needs to be located in the page. But not all page elements in an admin page have unique DOM selectors, or ones that are easy to identify, so the ability to have a tour with complete tour-step placement may be limited for some pages.

Alias names for this page

[Plugin Tour](#) | [Plugin Tours](#) | [PluginTours](#) | [Tour](#) | [Tours](#)