

Trackers Admin

To access: Click the **Tracker** icon  on the [Admin Panel](#) or Access **<http://example.org/tiki-admin.php?page=trackers>**

To administer Trackers, first click the "**Admin (Click!)**" menu to display the Tiki Admin Panel, as shown in this graphic:



Trackers



Trackers

From the Tiki Admin Panel, click the Trackers icon to display its settings panel, the top of which appears like so:



Configure Trackers

Trackers can have attached files. In this panel you can set up where to store attached files (if a tracker allows it). You can store attachments in the database or a directory. The directory **path** can be absolute (example: */foo/bar/uploads/*) or relative to the Tiki directory (example: *files/*). The **trailing slash** is mandatory.

Here you can:

- Set the file storage location to either the Tiki database or a directory on your web server's hard disk.

Use database to store files

Use a directory to store files

Tracker Attachment Storage: Trackers can be set up to allow file attachments, which will be stored in the either the Tiki database or in a directory on your webserver's hard disk. Storing files inside your database is OK for small files or a low volume of files, but a folder is recommended for a high volume site or when your files are relatively large.

Note the **mandatory** trailing forward slash on the path, shown here in red. The path you specify can be absolute:

/home/cogley/www/uploads/tikiimg/rm/

... or relative to your Tiki's install directory:

trackeruploads/

Path characteristic checklist:

- Has a trailing slash.
- For best security, is specified from the root, and is in a separate folder from Tiki.
- Has its permissions set (e.g. via the chmod command from the command line or in your FTP client software) to allow uploads by the webserver user.
- Has enough space to allow storage of your expected file volume.

If you take a look at your folder after uploading some images, you can see that Tiki randomizes the filenames, as shown in this graphic:



Troubleshooting Tip: If you are having trouble with file uploads, you can edit settings in your php.ini, or, place an .htaccess file

in the root of your tiki installation.

```
# Partial .htaccess file sample.
#
# Override PHP.ini variables, which can be viewed using phpinfo:

<IfModule mod_php4.c>
# If you are using Apache 2, you have to use <IfModule sapi_apache2.c>
# instead of <IfModule mod_php4.c>.

php_value max_execution_time      300
php_value upload_max_filesize     "10M"
php_value memory_limit            "32M"
php_value session.cache_expire    20000
php_value session.gc_maxlifetime  20000
php_value session.cookie_lifetime 20000
</IfModule>

# Zero means unlimited request body size:
LimitRequestBody 0
```

More documentation

- [Improve Tracker Forms](#)

Related Information

- To enable Trackers for your site, see [General Admin](#).
- To specify permissions for Tracker users, see [Permissions](#) for the general procedure.
- For information on using Trackers, see [Tracker User](#).
- For technical details, see [Tracker Details](#).
- [Mirror Trackers](#)

Useful Links

- Apache WWW Server htaccess tutorial:
<http://httpd.apache.org/docs/howto/htaccess.html>
- PHP htaccess information:
<http://jp2.php.net/configuration.changes>
- Absolute Path Glossary Entry
http://linux.about.com/cs/linux101/g/absolute_path.htm

Alias

- [Trackers-Admin](#)