

# <œìŠœí...œ êµ¬ì,,±

í°í,¤8 ì—ì,,œ ë,,ìž...ë”

œìŠœí...œ êµ¬ì,,±ì€ ì<œìŠœí...œ ê’œë!—ìžœíœ í•~ì—¬ê, ^ í°í,¤ì~ ì™ ,ë¶œì—ì,,œ ì,, í~,¤ì • ï¼ë¶œë¥¼ œ³œê²½í•~ë,,ëi í•©ë<sup>^</sup>ë<œ. INI íŒŒì¼ì,,œê³œí...œ ìœ½ëœíœí”, ê’œë!—ìžœ”¤ì€ ìžì<sup>^</sup> ë“¤ì~ ë²”ë” í°í,¤ ì,,¤ì1~ì— œŒœí•~ì— ì¤’ì<œ êµ¬ì,,±ì,, œ³’ìœ í• ì~ìžìŠœé<sup>^</sup>ë<œ.

í°í,¤10 ì—ì,,œ ìf<sup>^</sup>ëœ ë,,ìž...ëœ ë, ^ìš©: ì • ìŒŒì¼ëœë¶œí,, œ²”ë”ì,, œiœë”œí•~ëŠ” ì,, ìfì,—í• (í,,œiœí•,, YAML í~•ì<sup>^</sup>ë, ^í—ì,,œ, <http://profiles.tiki.org/Module+Handler> ì™€ ìœ ì,—í•~ê²Œ). ê’œë!—ìŒ”ë,, œ “ë²”ë”^ ìŒŒì¼” ì,, œ²œif‰œí•~ì<œì~¤.

í°í,¤11 ì—ì,,œ ìf<sup>^</sup>ëœ ë,,ìž...ëœ ë, ^ìš©: db/preconfiguration.php ìŒŒì¼ì€ ì²» í°í,¤ ì,,¤ì1~ì<œì— ìœì•~ëœ ë°ì’í,,œ² ììŠœ è³’ì•~ë, ^ìš©ì,, ì—í•~í• ì~ìžœé<sup>^</sup>ë<œ. ì’ëŠ” ê°œìf ì,,œë²,, ìœê³œùžœíœ í•~ì—¬ê, ^ è³ œ°ì’ í°í,¤ ì,,¤ì1~í,,œiœê·,ëž”ì— ì’ê·½í•~ê, ^ ì „ì— mysql ì,, œ°ê, ^ œëœ¥, ^ìž, ^ì~ìž è¹,,œ°œë²^í~, ^ì™€ ì—ìš©ìžœ...ìœ½ëœ ì,—ì,,¤ì •í• ì~ìžë,,ëi í•©ë<sup>^</sup>ë<œ.

## í°í,¤ íŒœ(farm)ê³¼ í~, ^ìŠœíŒ... ìšŒì,—ì,,œ ,—ìš© ê°œëŠ¥í•œÂ ìš©ë²•

- BigBlueButton ê³¼ ê°™ì€ œëœ¥, ^ì,,œë¹,,ìŠœœíœ ì,—ìš©ìžì~ ê°,,ì,—tì’ ì—°ê²°
- ë©¤ì<sup>^</sup>œì™€ ê°™ì€ ê³ œ%,‰ ì,,¤ì •ì,, êµ¬ì,,±
- ì§œì> ê³ „íšì~ ï¼ë¶œ°œ ì•, œŒœ ê, ^œëŠ¥ì,, œ¹,,í™ œì,,±í™”
- ì „ì—ìœ½ëœ ìŠ¹ì • ê, ^œëŠ¥ì,, œ¹,,í™ œì,,±í™”í•~ìœ½ëœì” ê³’ì•~ì±...ìž,,ìžì—ê²Œ ì•Œë¹¼
- tiki\_p\_admin ì,, ìœê³œí...ì§œëŒ ï¼ë¶œ ê, ^œëŠ¥ì,, ì’ê·½ë¶^œ°œëëŠ¥í•~ê²Œ ë§œë”-
- ì„ìŠœíŒ... ìšŒì,—ëŠ” ê²”ë” ê, ^œëŠ¥ì,, ì•œ ê³”ì— ìf’ìž—í•œ ì„ì<œíì,, ìœê³œí•~ê, ^œ¥¼ ìí• ì~ìžì§œëŒ, ë¤œì~ì,—ìš©ì€ ìœí•œí• ì~ìžëœ
- ì¤í—~ì ê, ^œëŠ¥
- ì,,œë²,, ì’ê·½ì,, ì»ê, ^ ìœ,,í•~ì— ì,—ìš©ë ì~ìžëŠ” ê, ^œëŠ¥ (œŒœë¶œë¶,,í~,¤ì1~ì—ì,,œëŠ” ê’œì°®ì§œëŒ, ìœ,,í,¤Œœ(WikiFarm)ì—ì,,œëŠ” ì¢<sup>^</sup>ì€ ï¼ì—ì,,œë<sup>^</sup>ë<œ)
- ì»”ì,,¤Œ... ìšŒì,—ëŠ” ì,—ìš©ìž— œŒœí•~ì— ë” ê<sup>^</sup>œí•œ ê’œë!— ìŒ”ë,,ì,, œ§œë”œê³ ì¶ì—í• ê²fi’ë<œ
- í°í,¤ë¥¼ ììš© ì”,,œiœê·,ëž” œ¹Œë” ([í”,,ë ^ìž,,ì>Œí—](#)) ëiœí” ì,—ìš©

# <œìŠxí...œ êµ¬ì,,±ì,,Â í™ œì,,±í™ "

æìŠxí...œ êµ¬ì,,±ì€ db/local.php íŒŒì¼œé¶€í,,° í™ œì,,±í™ "ë~ì- ì•¼ë§Œ í•©ë<sup>^</sup>ë<sup>^</sup>œ. í°í,¤8 è° ê·, ì` í,,ì—ì,,œ ìƒ„±ëœ ì,,¤ì1~ëŠ" ê, °ë³, ìœ¼ëiœ ìƒ„±ëœ EŒì¼ ë, 'ë¶€í— ìƒ~í"Œì,, ì—í•"í•~ê³ ìž~ìŠµë<sup>^</sup>ë<sup>^</sup>œ.

db/local.php œ, 'ë¶€í~ ìƒ~í"Œ õµ¬ì,,±

```
$system_configuration_file = '/etc/tiki.ini'; $system_configuration_identifier = 'client1.example.com';
```

db/local.php œ, 'ë¶€í~ ìƒ~é¥, ìf~í"Œ õµ¬ì,,±, ìfëŒ€ è²¹/₂ëiœé¥¼ í—í•"

```
$system_configuration_file = 'db/tiki.ini'; $system_configuration_identifier = 'client1.example.com';
```

ì~ì œë¥¼ ì,—ìš©í•~ê²Œ ë~ë© ' .htaccess ê°€ í™ œì,,±í™ "ë~ì- ìžì- ì,,œ tiki.ini ê°€ ì½íž~ì§€ ì•Šë,,ëi í•~ëŠ" ê²fi— ìœ ì~í•~ì~ìœì~œ.  
ì~œì,,±í™ "ë~ë© ' , í°í,¤ëŠ" êµ¬ì,,± íŒŒì¼œé¶€í,,° ì, ìfëœ ì~ë³,,ìžì— ê, °ë~í~ì— ì¶"ë°€ ë~...ë~ì, ì½ì- 'ë~¤ì¼ ê²fiž...ë~ë<sup>^</sup>ë<sup>^</sup>œ. ì~ë³,,ìžëŠ" ìž, ì~ì~ ê²fi¼ ì~~  
~ì§€ë§Œ, ì,—ì'íŠ, ì~ì€ è³,,ìš ìœ' í•~ë, ~ë¥¼ ì§€í •í•~ê, ° ìœ,,í•~ì— ì,—ìš©è ì~~ ìž~ìŠµë<sup>^</sup>ë<sup>^</sup>œ. êµ¬ì,,± íŒŒì¼ ë, 'ë¶€í—ëŠ" ë~ëœ' êµ¬ì,,±ì' ì •ì~ë~ì~  
~ìœ¼ë© ° ìfìtì' ì,—ìš©è ì~~ ìž~ìŠµë<sup>^</sup>ë<sup>^</sup>œ.

## NI êµ¬ì,,±Â íŒŒì¼

if~í"Œ INI íŒŒì¼

```
[global] preference.feature_wysiwyg = "n" preference.feature_sefurl = "y" preference.helpurl = "http://support.example.com/" ; ... more settings ...
[basic : global] preference.feature_wiki = "y" preference.feature_forums = "n" preference.feature_trackers = "n" ; ... more settings ... [pro : global]
preference.feature_wiki = "y" ; BBB configured, but user can still toggle on/off preference.bigbluebutton_server_location = "bbb.example.com"
preference.bigbluebutton_server_salt = "1234abcd1234abcd" ; ... more settings ... [client1.example.com : pro] preference.browsertitle = "Client #1
Intranet" preference.sender_email = client1@example.com
```

In the example above, the following preferences would be set for using the identifier *client1.example.com*:

- feature\_wysiwyg = n
- feature\_sefurl = y
- helpurl = <http://support.example.com/>

- feature\_wiki = y
- bigbluebutton\_server\_location = bbb.example.com
- bigbluebutton\_server\_salt = 1234abcd1234abcd
- browsertitle = Client #1 Intranet
- sender\_email = [client1 at example.com](mailto:client1@example.com)

at the beginning indicates comments.

# Disable classes of preferences

references can be disabled by setting a value to each of them individually. However, this process may be long and will require maintenance with the evolutions of Tiki.

ki allows to set multiple rule priorities, each verification priority can allow or deny a preference. Rules can be specified at various levels, just like the preference overrides above.

## Various rules

```
[global] rules.0 = deny experimental new [pro : global] rules.5 = allow new rules.10 = allow feature wysiwyg
```

„œì—ì,,œ, pro ì<ë³,,ìžë¥¼ ì,–ìš©í•~ëš” ì,–ì’íš,ëš” jf^ ê,°ëš¥ê³¼ wysywyg (ì<æí—~ì,ì’ë¹/₄ê³ ífœê·,ë~ì’~ìž~ìŒ) ì,,ì,–ìš©í•~ë,,ëi í—~ìš©ë ê²fi’ê³ , jf^ æí—~ì, ê,°ëš¥ë“æ,, í~í•~í• ê²fi’ë<æ, í•~ì§ëë§Œ, ê³¼ê±~ì,~ì, ê,°ëš¥ì€ ì—~ì, „íž” ì œí•œë ê²fi’ë<æ. ë³’ë<æ ët’ì€ ìš°ì,, ~ì œìœ,,ê°€ ìš°ì,, ì ìœ¹/₄œìœ „œœìœ” ê³ ífj%œì€ ì¼!~œë, ~ìš©í’~ë°œê²~œ~ë©’~ë©~ì¶œ ê²fi’ë<æ.

raconian ì œê³µìžëŠ" ë<sup>š</sup>ìŒê³¹/₄ ê°™ì€ ê²fi,, ì,¬ìš©í• ì^~ë,, ìž^ëœ

Draconian | ðrə'kōnē̄n | adj.

[global] rules.0 = deny all rules.1 = allow basic

, -ì „éµ-ì„± íŒŒì¹/₄

Í, æ°€ ì, -ì „ ëíæé“œëæ í~”ë”ë©~ë“œ (on-demand)ì<sub>k</sub>~ ê°€if ë”, ì, ì œê³µí• ë•Œ, í~ „íŠxíŒ... íšŒì, -ë“xì€ ê° ì, -ìš©ìžl—ê²Œ ë<æë¥, ë°ì’í, °ë² ì ‘íŠxì™€ -°ê²º ë³’ì•^ë, ’ì—ìœ¼ëíœ mysql ì,, ì œê³µí• ì~” ìž^ë<x.

‘í•¼é ê²fi€ ë“íœíž^ db/preconfiguration.php í— íì ^í•œ í¤„í~ íf¼í„ífífœë¥¼ í• í§éí•~ëŠ” ê²fi’ê³ íì ^í•œ ê°íœí¼éíœ í±„íšëŠ” ê²fi’ë¤:

db/preconfiguration.php