

Í...İŠıİŠ, İœ,,Í,ı-ë¬, ë²•

İ' İŽ~İİŞ€İ—İ,,œ ê•€Í•~ëŠ" İœ,,Í,ı İŽ~İİŞ€İ™ € İœ,,Í,ı İ,,œİİ,, İŞ€İ>Í•~ëŠ" (ê,°İ,¬, ê²œİ<œİœ, ë° ë, "ëİœê,ë"±İ,, İ¬Í•"Í•~ëŠ") ê,°İf€ İİ— İfİ—İ,,œ Í...İŠıİŠ, İ— İ,,œİİ,, İİŠ©Í•~ëŠ" ë²•İ,, ë°İŞ°ê²œ ë©ë^ë<ı.

ëŞ^Í¬İ—... İ¬,İ-´ İœ,,Í,ıÂ ë¬,ë²•

İœ,,Í,ı İŽ~İİŞ€ İfİ—İ,,œ İ¬İŠ©ë~ëŠ" ëŞ^Í¬İ—... İ¬,İ-´ëŠ" İ"İŽ^ İœ,,Í,ı İ< İfİŠı (Syntax, ë¬,ë²•, êµ¬ë¬,)İ'ë¼ê³ ëŒ^ë¼½ë^ë<ı. İ'ëŠ" İ"İŽ^ İ¬İŠ©ë~ëŠ" ë¬,İžë¼ İ"Í•~İŞ€ İ•Şİ€ ë°©ë²•İœ¼ëİœ İ¬İŠ©Í•©ë^ë<ı (İ~¹İ€ İ¼ë~İ İœ¼ëİœ ê°™İ' İ¬İŠ©ë~İŞ€ ä...žë,³ëŠ" ë¬,İž İİ°Í•©İ,, İ'ë£"ê,°ë,, Í•©ë^ë<ı) ê,ë|¬ê³ ê,ëŸ¬Í•œ İİ°Í•© ë°ë°©ë²•İ— İŠ¹ë³,Í•œ İ~ë¬,ê°€ ëŒ€İ—¬ë©ë^ë<ı. İ°ë|ı,,° İİ°Í•©İ~ İ¼ëŒ€ëŠ" Í•œ İı,,İ İ<œİž'ëŒ€ëŒ,,İ—İ,,œëŞœ İž'ë™Í•~ê³ , ë<ıë¼, ê²fİ€ Í...İŠıİŠ, İ İ•,,ë¬´ ê³³İ—ë, İ,½İž...ë İ~ İž^İœ¼ë©°, Í•'ë<¹ ê,°ëŠıİ' ê¼İŞ^ ë•œê¹œİŞ€ İ™œİ,,±İ™" ë~İ-´ İž^ê,°ë,, Í•©ë^ë<ı.

œ,,Í,ı ë¬,ë²•İ€ ëœ€ëŒ€ëŒ,,İ ê,°ëŠıİ—İ,,œ Í•œ İ°ë|ı,,°ê°€ ë'ë²^ ë°~ë³µë~ëŠ" ë°©İİ,, İ¬İŠ©Í•©ë^ë<ı, Í•~İŞ€ëŞœ, 2-İ°ë,° İİ°Í•© ë°©İİ,, İ¼ëŒ€ İ±,,İŠ©Í•~ê,°ë,, Í•©ë^ë<ı. 2-İ°ë|ı,,° İİ°Í•©İ—İ,,œëŠ" İ°ë|ı,,°ë"ıİ´ Í•'ë<¹ ê,°ëŠıİ' ê¼İŞ^ İž^İ,, ë•œ—İ¹İ™~ë~ê,°ë,,Í•©ë^ë<ı. ê³ İ•Íİ¬ê,° Í...İŠıİŠ, (MonoSpaced Text)ê°€ İçİ<İ İ~İ œİ¼ ê²fİž...ë^ë<ı; İœİ^~ ê,°İ~ (-) İ™€ İ¬İ^~ê,°İ~ (+) ëŠ" ê³ İ•Íİ...İŠıİŠ, İİœİž'İ,, İœ,,Í•İ,,œ İ¬İŠ©ë~ê³ İ¬İ^~ (+)İ™€ İœİ^~ (-)ëŠ" ê,°ëŠıİ~ ëİ,, İŞ€İ İ•~ê,°ë,, Í•©ë^ë<ı.

ë<ıİœ İ,,İ...~İ—İ,,œ İ'ë"ıİ~ ëœ€ëŒ€ëŒ,,İ' İ,,ıë³...ë©ë^ë<ı.

Table of contents

- Í...İŠıİŠ, İœ,,Í,ı-ë¬,ë²•
 - ëŞ^Í¬İ—... İ¬,İ-´ İœ,,Í,ı ë¬,ë²•
 - ë¹ ë¼, İ° İİ° - ê,°ë³, Í...İŠıİŠ, İ,,œİİ İŠ©
 - ê,°ë³, Í...İŠıİŠ, İ,,œİİ İŠ©
 - İf%İf İ°İŠ,
 - Web-Safe HTML Colors

- Bold Text
 - Italic Text
 - Underlined Text
 - Strikethrough text
 - Centered Text
 - Monospaced Text for Code
 - Superscript and subscript
 - Text box
 - Plain Text
 - Headings
 - Numbered Headings
 - LineBreak (forced)
 - Indent
 - Using Square Brackets
 - Non-breaking space
 - Comments
 - Wiki Comments
 - HTML Comments
 - Displaying code
 - To Indent a Text Block
 - Useful Links
-

ë¹ ëÿ, ì°, ìi° - ê, °ë³, í...ìšxíš, Â ì,,œì<ì ìš©

>í•~ěš" ì,,œì<	ë¬,ë²•	ê²°ê³¼	ìš€ì>ë²,,ì,,
èµµì€ì²´	__text__	text	
α'•™ì •ë ¬	::text::	text	
f%oìf í°íš,	~~blue:text~~	text	
´ífxè	"text" = 'text'	text	
ê³ ì •í	-+text+-	<u>text</u>	
ë°ìx,,	===text===	<u>text</u>	
...ìšxíš, ìfìž	^text^	<u>text</u>	
,ì œë"	--text--	text	3.0
ë¬,ë²• íœì<œ	~np~__not bold__~/np~	<u>not bold</u>	

ê, °ë³, í...ìšxíš, Â ì,,œì<ì ìš©

ì' ì,,¹ì...~ì-ì,,œ ë³ì-ìš€ěš" ìœ,,í,x ë¬,ë²•ì€ í...ìšxíš,ì~ ì-´ë-x ë¶€ë¶,,ì-ë,, ë†"ì-ìš^ ì^~ ìž^ìœ¼ë-€ëìœ íš¹ì • ë¬,ìž,
ë<"ì-´ í¹ì€ ë¬,ìž¥ì´ ê°•ìi°ë ì^~ ìž^ìšµë<^ë<x.

Web-Safe HTML Colors

[+]

Bold Text

Two Underscore (`_`) characters are used to make text Bold.

Example: `This Text is Bold` produces: **This Text is Bold**

Italic Text

Two Single Quote (') characters are used to make text Italic.

Example: "This Text is Italic" produces: *This Text is Italic*

Underlined Text

Three Equal (=) characters are used to underline text.

Example: ===This Text is Underlined=== produces: This Text is Underlined

Strikethrough text

Example:

--This text uses strikethrough--

produces:

~~This text uses strikethrough.~~

Centered Text

Two Colon (:) characters are used to Center text. The Centered Text can be centered within a Box, a Table, or almost anything else.


Example: ::This Text is Centered:: produces:

This Text is Centered

Monospaced Text for Code

Monospaced Text is useful when displaying Code and can be created in two ways. The easiest is to start a new line with one or more spaces. The Minus (-) and Plus (+) character combination can also be used to specify a Monospaced Text. See also PluginMono for another way to apply the Monospace font.

Example: -+This Text uses a Monospaced Font+- produces: `This Text uses a Monospaced Font`

 *If using a Monospaced Font, be sure to keep the line length short. If the lines are too long, they will push the right column out of the browser display area.*

â— The Leading Space Monospaced Font is disabled on many sites.

Superscript andÂ subscript

Use the {TAG} plugin (also see PluginTag).

Example:

This text is {TAG(tag=>sup)}super{TAG} script.

produces:

This text is ^{super} script.

This text is {TAG(tag=>sub)}sub{TAG} script.

produces:

This text is _{sub} script.

 Another alternative is to use the {SUB} and {SUP} plugins which are documented at PluginSub and PluginSup.

Text box

Apply one caret at start and end of text to be in a box.

Example: ^This Text is in a box^ produces:

This Text is in a box

NOTE: This CSS style is called "simplebox" and may look different or may not exist, depending on your theme CSS.

Plain Text

To turn off tiki formatting, surround your text with 'np' a.k.a. 'no processing' tags

Example: ~np~This "text" is __not__ being ===formatted===~/np~ produces:

This "text" is __not__ being ===formatted===

NOTE: np tags cannot be used within an np block. To display an unprocessed ~np~ tag, escape all the characters (not just the tildes) while in normal processing mode:

~126~~110~~112~~126~ produces: ~np~

~126~~47~~110~~112~~126~ produces: ~/np~

Headings

Headings are formed by starting the line with one, two, or three exclamation marks ("!", "!!", or "!!!").

Note regarding customizing the appearance of headings: If you need to change the CSS property of a heading in the wikitext (by editing the theme stylesheet), be aware that a heading labeled "h1" (made with one exclamation point) is actually an HTML h2 heading, h2 is actually an HTML h3, and so on.

This is because, consistent with semantic layout, there should be only one h1 heading on a page, so in Tiki h1 is reserved for the page title. Although it may seem confusing to map the heading sizes down one level this way, it was decided as better than labeling the wikitext headings something like h2 to h5, with h1 apparently missing.

So to change the appearance of a wikipage's "h2" headings for example, actually it is the h3 selector in the stylesheet that needs to be edited (or .wikitext h3, if the theme has rules for wikitext headings in addition to default heading rules).

Numbered Headings

In tiki 2.0 and above, you can create numbered headings using a combination of the ! and # characters

- !# My Heading will produce "1.0 My Heading"
- !!# My Secondary Heading will produce "1.1 My Secondary Heading"
- !!!# My Tertiary Heading will produce "1.1.1 My Tertiary Heading"

See: [Headings](#)

LineBreak (forced)

Basic WIKI markup language don't include "linebreak" element.

Nevertheless with TIKI you can use special command to force linebreaks into a text :

line break code (%%%), like so:

```
;;text %%% text %%% text
```

will look like this:

text

text

text

Indent

Indent is formed by the combination of the ; and : characters. ; must appear at the beginning of a line and : must appear between introduction text and the indented text. The introduction text portion is useful for forming definition type indentation like Example 1 below. However the introduction text can be eliminated by simply including ;; together followed by the text as shown in Example 2.

Example 1:

;Intro Text: First example of indented text
produces:

Intro Text

First example of indented text

Example 2:

;;2nd example of indented text

2nd example of indented text

Using Square Brackets

If you wish to include square brackets in your text (i.e. as regular text and not a link) simply add an additional open bracket to start. E.g.

```
[[this would not be a link]
```

Would render like this...

```
[this would not be a link]
```

Non-breaking space

Use `~hs~` to add the HTML " " for a non-breaking space.

Comments

Wiki Comments

~tc~ this is a tiki comment ~/tc~

Will be kept in the Wiki source file but not seen when the HTML page is generated or HTML page source is viewed.

HTML Comments

~hc~ this is an HTML comment ~/hc~

Will be kept in the Wiki source file and will generate an HTML comment of the form

An HTML comment will not be seen when the page is viewed but will be seen when the HTML page source is viewed.

Displaying code

You enter code blocks by enclosing the block between

`{CODE()}` and `{CODE}`

This is a WikiPlugin, which extends the WikiSyntax.

To Indent a Text Block

Enclose text in a blockquote using HTML to indent a section / block of text.

text

text

text

This will display as:

text

text

text

You can also use the indent code (;:), and line break code (%%%), like so:

```
;;text %%% text %%% text
```

Useful Links

- The Color Picker II is located at <http://www.pagetutor.com/pagetutor/makapage/picker/>
- WebDevlopper extension for Mozilla Firefox
- The wiki syntax is not standardised across applications. There is an initiative to publish the Wiki-Syntax as an RFC from the IETF. See RFCWik,