

# General Preferences tab

## Overview

Configure site-wide preferences

## To Access

From the [General Admin](#) page, click the **General Preferences** tab.

## Note

Some of these options can be configured during [Installation](#)

 Preference Filters

To see all the settings available on your admin page, you may need to adjust your [Preference Filters](#)

Related Topics

- [Installation](#)
- [System Log](#)
- [Look and Feel](#)


# Option

Server domain name

Browser title

## Description

The value that will be used by default as the server domain name of your Tiki site.

 *Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and require database or shell access to recover it.*

Visible label in the browser's title bar on all pages. Also appears in search engine results.

**Default**

None

None

# Option

Fallback for tiki base URL

Browser title position

## Description

The full URL to the Tiki base URL including protocol, domain and path (example: <https://example.com/tiki/>), used when the current URL can not be determined, example, when executing from the command line.

Position of the browser title in the full browser bar relative to the current page's descriptor.

☰ After current page's descriptor | Before current page's descriptor | No browser title, only current page's descriptor | Only browser title, no current page's descriptor

# Default

None

After current page's descri...

# Option

Browser title display mode

Sender email

Sender full name

Default character set for sending mail



## Description

When breadcrumbs are used, method to display the browser title.

☰ Most-specific first | Least-specific first (site) | Current only |  
Description

Email address that will be used as the sender for outgoing emails.

Real name that will be used as the sender for outgoing emails

Specify the character encoding used by Tiki when sending mail notifications.

☰ utf-8 | iso-8859-1

**Default**

Most-specific first

None

None

utf-8

# Option

Email newline character(s)

Apply site styles to HTML emails

Mail sender

Amazon SES Key

# Description

End-of-line (EOL) character used in outgoing emails

☰ CRLF (standard) | LF (some Unix MTA)

Add site CSS to all HTML formatted emails

Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at `./temp/Mail_yyyymmddhhmmss_randomstring.tmp` ) to send mail notifications.

☰ Sendmail | SMTP | File (debug) | Elastic Email | Mailgun | Mandrill | Postage | Postmark | SendGrid | SparkPost

**Default**

LF (some Unix MTA)

Enabled

Sendmail

None

## Option

Amazon SES Secret

Amazon SES Region

Amazon SES version

Elastic Email Username

Elastic Email Key

Mailgun Domain

Mailgun Key

Mailgun API Endpoint

Mandrill Key

# Description

# Default

None

None

None

None

None

None

None

None

None



# Option

Postage Key

Postmark Key

SendGrid Username

SendGrid Key

SparkPost Key

SMTP server

Authentication

Username

# Description

Mail server authentication

☰ None | LOGIN | PLAIN | CRAM-MD5

# Default

None

None

None

None

None

None

None

None

# Option

Password

Port

Security

Verify HTTPS certificates of remote servers

Local server name

# Description

☰ None | SSL | TLS

When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)

☰ Do not enforce verification | Enforce verification

Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.

# Default

None

25

None

None

Localhost

# Option

Mail delivery

Catch-all email address

Email footer

## Description

When set to Queue, messages will be stored in the database. Requires using the shell script `php console.php mail-queue:send` to be run for actual delivery.

☰ Send immediately | Queue

Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.

Text appended to outgoing emails.



# Default

None

None

None

# Option

Text string used to customise mail templates

Throttle newsletter send rate

Newsletter pause length

Newsletter batch size

Allow sending newsletters through external clients

## Description


Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files

Pause for a given amount of seconds before each batch to avoid overloading the mail server.

Number of seconds delay before each batch

Number of emails to send in each batch

Generate mailto links using the recipients as the BCC list.

 *This will expose the list if email addresses to all users allowed to send newsletters.*

# Default

None

Disabled

60 seconds

5 emails

Disabled

# Option

PHP Error reporting level

PHP errors visible to admin only

## Description

Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.

☰ No error reporting | Report all PHP errors except strict |  
Report all PHP errors | Report all PHP errors except notices |  
According to the PHP configuration

PHP Errors will be shown to only the Admin user.

👉 *During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.*

# Default

Report all PHP errors excep...

Enabled

# Option

Include Smarty notices in the PHP error report


Show generic error message

Generic error message



## Description

Tiki will display **Smarty** notices with the PHP error messages.

 *In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.*

Show a generic error message for non admins users.  
The error is logged to the database.

Message to display to non admin users when an error occurs.

**Default**

Disabled

Disabled

There was an issue with you...

# Option

Disable JavaScript

Log mail in Tiki logs

## Description

Disable JavaScript for the purpose of testing even if enabled in the browser.

 *Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.*

A line of type mail will be included in the System Log with the destination address and subject of each email sent.

 *May impact performance*

**Default**

Disabled

Disabled

# Option

Log SQL

Log queries using more than

Data Source Name (DSN)

## Description

All SQL queries will be registered in the database in the `adodb_logsql` table.

 *Do not enable this feature all the time. It can be very resource intensive and will impact performance.*

Use to log only queries that exceed a specific amount of time.

 *May impact performance*

DSN used for connect to the error tracking service.

**Default**

Disabled

0.05 seconds

None



# Option

Sample rate

Track PHP errors

Track JavaScript errors

## Description

Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)

Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.

Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.

**Default**

1

Disabled

Disabled

# Option

Enabled

How to trigger Web Cron

Run interval

Token

Scheduler

Delay scheduled time (minutes)

# Description

Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.

☰ Calling the Web Cron URL | Adding JavaScript that calls Web Cron | URL and JavaScript

The amount of time of each run

The token to use when running the cron manually

Provides the ability to run tasks at a scheduled time.

When calculating if the jobs should run, take the delay into consideration

**Default**

Disabled

URL and JavaScript

60 seconds

Random Token

Enabled

0

# Option

Scheduler stalled after (minutes)

Notify on stalled schedulers

Users to notify on stalled task

Self healing after (minutes)

## Description

Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.

Send an email notification when a stalled scheduler is detected.

List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing



**Default**

15

Enabled

None

30

# Option

Notify on healed schedulers

Users to notify on healed task

Number of logs to keep

---

## Description

Send an email notification when a stalled scheduler is healed.

List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

0 will keep all logs

---

**Default**

Enabled

None

10000

*Unable to load the jQuery Sortable Tables feature.*


# Option

Server domain name

Browser title

## Description

The value that will be used by default as the server domain name of your Tiki site.

 *Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and require database or shell access to recover it.*

Visible label in the browser's title bar on all pages. Also appears in search engine results.

**Default**

None

None

# Option

Fallback for tiki base URL

Browser title position



## Description

The full URL to the Tiki base URL including protocol, domain and path (example: <https://example.com/tiki/>), used when the current URL can not be determined, example, when executing from the command line.

Position of the browser title in the full browser bar relative to the current page's descriptor.

☰ After current page's descriptor | Before current page's descriptor | No browser title, only current page's descriptor | Only browser title, no current page's descriptor

# Default

None

After current page's descri...

# Option

Browser title display mode

Sender email

Sender full name

Default character set for sending mail

## Description

When breadcrumbs are used, method to display the browser title.

☰ Most-specific first | Least-specific first (site) | Current only |  
Description

Email address that will be used as the sender for outgoing emails.

Real name that will be used as the sender for outgoing emails

Specify the character encoding used by Tiki when sending mail notifications.

☰ utf-8 | iso-8859-1

**Default**

Most-specific first

None

None

utf-8

# Option

Email newline character(s)

Apply site styles to HTML emails

Mail sender

Amazon SES Key

# Description

End-of-line (EOL) character used in outgoing emails

☰ CRLF (standard) | LF (some Unix MTA)

Add site CSS to all HTML formatted emails

Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at `./temp/Mail_yyyymmddhhmmss_randomstring.tmp` ) to send mail notifications.

☰ Sendmail | SMTP | File (debug) | Elastic Email | Mailgun | Mandrill | Postage | Postmark | SendGrid | SparkPost

**Default**

LF (some Unix MTA)

Enabled

Sendmail

None



## **Option**

Amazon SES Secret

Amazon SES Region

Amazon SES version

Elastic Email Username

Elastic Email Key

Mailgun Domain

Mailgun Key

Mailgun API Endpoint

Mandrill Key

# Description

# Default

None

None

None

None

None

None

None

None

None

# Option

Postage Key

Postmark Key

SendGrid Username

SendGrid Key

SparkPost Key

SMTP server

Authentication

Username

# Description

Mail server authentication

☰ None | LOGIN | PLAIN | CRAM-MD5

# Default

None

None

None

None

None

None

None

None

# Option

Password

Port

Security

Verify HTTPS certificates of remote servers

Local server name

# Description

☰ None | SSL | TLS

When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)

☰ Do not enforce verification | Enforce verification

Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.



# Default

None

25

None

None

Localhost

# Option

Mail delivery

Catch-all email address

Email footer

## Description

When set to Queue, messages will be stored in the database. Requires using the shell script `php console.php mail-queue:send` to be run for actual delivery. Only works with SMTP mail.

☰ Send immediately | Queue

Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.

Text appended to outgoing emails.

# Default

None

None

None

# Option

Text string used to customise mail templates

Throttle newsletter send rate

Newsletter pause length

Newsletter batch size

Allow sending newsletters through external clients

## Description


Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files

Pause for a given amount of seconds before each batch to avoid overloading the mail server.

Number of seconds delay before each batch

Number of emails to send in each batch

Generate mailto links using the recipients as the BCC list.

 *This will expose the list if email addresses to all users allowed to send newsletters.*

# Default

None

Disabled

60 seconds

5 emails

Disabled

# Option

PHP Error reporting level

PHP errors visible to admin only



## Description

Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.

☰ No error reporting | Report all PHP errors except strict |  
Report all PHP errors | Report all PHP errors except notices |  
According to the PHP configuration

PHP Errors will be shown to only the Admin user.

👉 *During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.*

# Default

Report all PHP errors excep...

Enabled

# Option


Include Smarty notices in the PHP error report

Show generic error message

Generic error message

## Description

Tiki will display **Smarty** notices with the PHP error messages.

 *In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.*

Show a generic error message for non admins users.  
The error is logged to the database.

Message to display to non admin users when an error occurs.

**Default**

Disabled

Disabled

There was an issue with you...

# Option

Disable JavaScript

Log mail in Tiki logs

## Description

Disable JavaScript for the purpose of testing even if enabled in the browser.

 *Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.*

A line of type mail will be included in the System Log with the destination address and subject of each email sent.

 *May impact performance*

**Default**

Disabled

Disabled



# Option

Log SQL

Log queries using more than

Data Source Name (DSN)

## Description

All SQL queries will be registered in the database in the `adodb_logsql` table.

 *Do not enable this feature all the time. It can be very resource intensive and will impact performance.*

Use to log only queries that exceed a specific amount of time.

 *May impact performance*

DSN used for connect to the error tracking service.

**Default**

Disabled

0.05 seconds

None

# Option

Sample rate

Track PHP errors

Track JavaScript errors

## Description

Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)

Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.

Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.

**Default**

1

Disabled

Disabled

# Option

Enabled

How to trigger Web Cron

Run interval

Token

Scheduler

Delay scheduled time (minutes)

# Description

Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.

☰ Calling the Web Cron URL | Adding JavaScript that calls Web Cron | URL and JavaScript

The amount of time of each run

The token to use when running the cron manually

Provides the ability to run tasks at a scheduled time.

When calculating if the jobs should run, take the delay into consideration



**Default**

Disabled

URL and JavaScript

60 seconds

Random Token

Enabled

0

# Option

Scheduler stalled after (minutes)

Notify on stalled schedulers

Users to notify on stalled task

Self healing after (minutes)

## Description

Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.

Send an email notification when a stalled scheduler is detected.

List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing

**Default**

15

Enabled

None

30

# Option

Notify on healed schedulers

Users to notify on healed task

Number of logs to keep

---

## Description

Send an email notification when a stalled scheduler is healed.

List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

0 will keep all logs

---

**Default**

Enabled

None

10000

*Unable to load the jQuery Sortable Tables feature.*

**Option**

Browser title

---

## **Description**

Visible label in the browser's title bar on all pages. Also appears in search engine results.



**Default**

None

# Option

Fallback for tiki base URL

Browser title position

## Description

The full URL to the Tiki base URL including protocol, domain and path (example: <https://example.com/tiki/>), used when the current URL can not be determined, example, when executing from the command line.

Position of the browser title in the full browser bar relative to the current page's descriptor.

☰ After current page's descriptor | Before current page's descriptor | No browser title, only current page's descriptor | Only browser title, no current page's descriptor

# Default

None

Before current page's descr...

# Option

Browser title display mode

Sender email

Sender full name

Default character set for sending mail

## Description

When breadcrumbs are used, method to display the browser title.

☰ Most-specific first | Least-specific first (site) | Current only |

Description

Email address that will be used as the sender for outgoing emails.

Real name that will be used as the sender for outgoing emails

Specify the character encoding used by Tiki when sending mail notifications.

☰ utf-8 | iso-8859-1

**Default**

Most-specific first

None

None

utf-8

# Option

Email newline character(s)

Apply site styles to HTML emails

Mail sender

Amazon SES Key



# Description

End-of-line (EOL) character used in outgoing emails

☰ CRLF (standard) | LF (some Unix MTA)

Add site CSS to all HTML formatted emails

Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at `./temp/Mail_yyyymmddhhmmss_randomstring.tmp` ) to send mail notifications.

☰ Sendmail | SMTP | File (debug) | Elastic Email | Mailgun | Mandrill | Postage | Postmark | SendGrid | SparkPost

**Default**

LF (some Unix MTA)

Enabled

Sendmail

None

## Option

Amazon SES Secret

Amazon SES Region

Amazon SES version

Elastic Email Username

Elastic Email Key

Mailgun Domain

Mailgun Key

Mailgun API Endpoint

Mandrill Key

# Description

# Default

None

None

None

None

None

None

None

None

None

# Option

Postage Key

Postmark Key

SendGrid Username

SendGrid Key

SparkPost Key

SMTP server

Authentication

Username

# Description

Mail server authentication

☰ None | LOGIN | PLAIN | CRAM-MD5

# Default

None

None

None

None

None

None

None

None



# Option

Password

Port

Security

Verify HTTPS certificates of remote servers

Local server name

# Description

☰ None | SSL | TLS

When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)

☰ Do not enforce verification | Enforce verification

Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.

# Default

None

25

None

None

Localhost

# Option

Mail delivery

Catch-all email address

Email footer

## Description

When set to Queue, messages will be stored in the database. Requires using the shell script `php console.php mail-queue:send` to be run for actual delivery. Only works with SMTP mail.

☰ Send immediately | Queue

Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.

Text appended to outgoing emails.

# Default

None

None

None

# Option

Text string used to customise mail templates

Throttle newsletter send rate

Newsletter pause length

Newsletter batch size

Allow sending newsletters through external clients

## Description


Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files

Pause for a given amount of seconds before each batch to avoid overloading the mail server.

Number of seconds delay before each batch

Number of emails to send in each batch

Generate mailto links using the recipients as the BCC list.

 *This will expose the list if email addresses to all users allowed to send newsletters.*



# Default

None

Disabled

60 seconds

5 emails

Disabled

# Option

PHP Error reporting level

PHP errors visible to admin only

## Description

Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.

☰ No error reporting | Report all PHP errors except strict |  
Report all PHP errors | Report all PHP errors except notices |  
According to the PHP configuration

PHP Errors will be shown to only the Admin user.

👉 *During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.*

# Default

Report all PHP errors excep...

Enabled


# Option

Include Smarty notices in the PHP error report

Disable JavaScript

## Description

Tiki will display **Smarty** notices with the PHP error messages.

 *In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.*

Disable JavaScript for the purpose of testing even if enabled in the browser.

 *Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.*

**Default**

Disabled

Disabled

# Option

Log mail in Tiki logs

Log SQL

Log queries using more than



## Description

A line of type mail will be included in the System Log with the destination address and subject of each email sent.

⚠ *May impact performance*

All SQL queries will be registered in the database in the adodb\_logsql table.

⚠ *Do not enable this feature all the time. It can be very resource intensive and will impact performance.*

Use to log only queries that exceed a specific amount of time.

⚠ *May impact performance*

**Default**

Disabled

Disabled

0.05 seconds

# Option

Data Source Name (DSN)

Track PHP errors

Track JavaScript errors

Enabled

How to trigger Web Cron

## Description

DSN used for connect to the error tracking service.

Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.

Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.

Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.

☰ Calling the Web Cron URL | Adding JavaScript that calls Web Cron | URL and JavaScript

**Default**

None

Disabled

Disabled

Disabled

URL and JavaScript

# Option

Run interval

Token

## Scheduler

Delay scheduled time (minutes)

Scheduler stalled after (minutes)

Notify on stalled schedulers

# Description

The amount of time of each run

The token to use when running the cron manually

Provides the ability to run tasks at a scheduled time.

When calculating if the jobs should run, take the delay into consideration

Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.

Send an email notification when a stalled scheduler is detected.

# Default

60 seconds

Random Token

Enabled

0

15

Enabled



# Option

Users to notify on stalled task

Self healing after (minutes)

Notify on healed schedulers

## Description

List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing

Send an email notification when a stalled scheduler is healed.

**Default**

None

30

Enabled

# Option

Users to notify on healed task

Number of logs to keep

---

## Description

List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

0 will keep all logs

---

# Default

None

10000

*Unable to load the jQuery Sortable Tables feature.*

# Option

Upgrade cycle

---

## Description

Tiki upgrade frequency for this site to check against.

☰ Regular (8 months) | Long-Term Support

**Default**

Regular (8 months)



# Option

Check for updates automatically

Check frequency

## Description

Tiki will automatically check for new updates each time you access the Admin Home page, based on your Check frequency selection.

👉 *Subscribe to the Tiki Newsletter to be notified of new releases. <https://doc.tiki.org/Newsletters>*

How often Tiki should check for updates. This field applies only if "Check for updates automatically" is enabled.

👉 *Click "Check for Updates Now" to perform an update check.*

☰ Each day | Each week | Each month

**Default**

Enabled

Each week

# Option

Browser title

Server domain name

Fallback for tiki base URL

## Description

Visible label in the browser's title bar on all pages. Also appears in search engine results.

The value that will be used by default as the server domain name of your Tiki site.

The full URL to the Tiki base URL including protocol, domain and path (example: <https://example.com/tiki/>), used when the current URL can not be determined, example, when executing from the command line.

# Default

None

None

None

# Option

Browser title position

Browser title display mode

Sender email

## Description

Position of the browser title in the full browser bar relative to the current page's descriptor.

☰ After current page's descriptor | Before current page's descriptor | No browser title, only current page's descriptor | Only browser title, no current page's descriptor

When breadcrumbs are used, method to display the browser title.

☰ Most-specific first | Least-specific first (site) | Current only | Description

Email address that will be used as the sender for outgoing emails.



# Default

Before current page's descr...

Most-specific first

None

# Option

Sender full name

Default character set for sending mail

Email newline character(s)

Apply site styles to HTML emails

## Description

Real name that will be used as the sender for outgoing emails

Specify the character encoding used by Tiki when sending mail notifications.

☰ utf-8 | iso-8859-1

End-of-line (EOL) character used in outgoing emails

☰ CRLF (standard) | LF (some Unix MTA)

Add site CSS to all HTML formatted emails

# Default

None

utf-8

LF (some Unix MTA)

Enabled

# Option

Mail sender

SMTP server

Authentication

Username

## Description

Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at `./temp/Mail_yyyymmddhhmmss_randomstring.tmp` ) to send mail notifications.

☰ Sendmail | SMTP | File (debug)

## Mail server authentication

☰ None | LOGIN | PLAIN | CRAM-MD5

**Default**

Sendmail

None

None

None

# Option

Password

Port

Security

Verify HTTPS certificates of remote servers

Local server name



# Description

☰ None | SSL | TLS

When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)

☰ Do not enforce verification | Enforce verification

Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.

# Default

None

25

None

None

Localhost

# Option

Mail delivery

Email footer

Text string used to customise mail templates

Throttle newsletter send rate

## Description

When set to Queue, messages will be stored in the database. Requires using the shell script `php console.php mail-queue:send` to be run for actual delivery. Only works with SMTP mail.

☰ Send immediately | Queue

Text appended to outgoing emails.

Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files

Pause for a given amount of seconds before each batch to avoid overloading the mail server.

**Default**

None

None

None

**Disabled**

# Option

Newsletter pause length

Newsletter batch size

Allow sending newsletters through external clients


PHP Error reporting level

## Description

Number of seconds delay before each batch

Number of emails to send in each batch

Generate mailto links using the recipients as the BCC list.

 *This will expose the list if email addresses to all users allowed to send newsletters.*

Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.

☰ No error reporting | Report all PHP errors except strict |  
Report all PHP errors | Report all PHP errors except notices |  
According to the PHP configuration

# Default

60 seconds

5 emails

Disabled

Report all PHP errors excep...



# Option

PHP errors visible to admin only

Include Smarty notices in the PHP error report

## Description

PHP Errors will be shown to only the Admin user.

👉 *During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.*

Tiki will display **Smarty** notices with the PHP error messages.

👉 *In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.*

**Default**

Enabled

Disabled


# Option

Disable JavaScript

Log mail in Tiki logs

## Description

Disable JavaScript for the purpose of testing even if enabled in the browser.

 *Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.*

A line of type mail will be included in the System Log with the destination address and subject of each email sent.

 *May impact performance*

**Default**

Disabled

Disabled

# Option

Log SQL

Log queries using more than

Enabled

## Description

All SQL queries will be registered in the database in the `adodb_logsql` table.

**⚠** *Do not enable this feature all the time. It can be very resource intensive and will impact performance.*

Use to log only queries that exceed a specific amount of time.

**⚠** *May impact performance*

Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.



**Default**

Disabled

0.05 seconds

Disabled

# Option

How to trigger Web Cron

Run interval

Token

Scheduler

Scheduler stalled after (minutes)

Notify on stalled schedulers

# Description

☰ Calling the Web Cron URL | Adding JavaScript that calls Web Cron | URL and JavaScript

The amount of time of each run

The token to use when running the cron manually

Provides the ability to run tasks at a scheduled time.

Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.

Send an email notification when a stalled scheduler is detected.

# Default

URL and JavaScript

60 seconds

Random Token

Enabled

15

Enabled

# Option

Users to notify on stalled task

Self healing after (minutes)

Notify on healed schedulers

## Description

List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing

Send an email notification when a stalled scheduler is healed.

**Default**

None

30

Enabled

# Option

Users to notify on healed task

Number of logs to keep

---



## Description

List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

0 will keep all logs

---

**Default**

None

10000

*Unable to load the jQuery Sortable Tables feature.*

related

SMTP