

MODULE LAST_TRACKER_ITEMS

This is a [stub](#). Some [screenshot](#) is needed

PARAMETERS

Displays the value of a field of the specified number of tracker items. If the specified tracker has no main field, either Field name or Field identifier is required.

*Required parameters are in **bold**.*

[Go to the source code](#)

Preferences required: feature_trackers

Parameters Accepted Values

trackerId

int

name

any string except for HTML and PHP tags

Description

Identifier of the tracker from which items are listed.

Example value: 13.

Name of the field from which values are listed. Example value: age.

Default Since

sort_mode

any string except for HTML and PHP tags

status

word

Specifies how the items should be sorted. Possible values include `created` and `created_asc` (equivalent), `created_desc`, `status`, `lastModif`, `createdBy` and `lastModifBy`. Unless `"_desc"` is specified, the sort is ascending. `"created"` sorts on item creation date.

`"lastModif"` sorts on the last modification date of items.

`"lastModif_desc"` sorts in descending order of last modification date. Default value: `created_desc`

If set, limits the listed items to those with the given statuses. Values are combinations of `"o"` (open), `"p"` (pending) and `"c"` (closed). Possible values: `opc`, `oc`, `op`, `pc`, `o`, `p` or `c`. Default value: `opc`

fieldId

int

Identifier of the field from which values are listed. If Field name is set, this parameter is ignored. Example value: 13.

The other traditional modules params apply:

nonums

NOTES

- In `tw` \geq 3.0, You can either give the field name, or the `fieldId`, or indicate no field. In the last case the system will automatically take the first main field.
- Be careful than if you change the name of the field in the tracker administration, the module parameter name will not be changed

SEE ALSO

[Module `last_modif_tracker_items`](#)