MySQL SSL

Added in tiki12

or some system, e.g. cloud based systems such as Windows Azure or AWS Lightsail, it is recommended to use an SS connection to the MySQL database.

To enable a MySQL SSL connection, key files must be specified, in PEM format.

Depending on the case, only the CA can be sufficient to configure an SSL Connection (like for AWS Lightsail and Azure Database for MySQL flexible server) or the following 3 files are required.

- Client key. Filename must end with -key.pem
- Client cert. Filename must end with -cert.pem
- CA cert. Filename must end with -ca.pem

These files are placed in the *tikiroot*/**db/cert** folder. Tiki will detect these files and initiate an SSL connection. The db/cert folder could look something like this (Azure Clear DB sample).

See how you can create SSL certificates and keys using openssl for MySQL.

htaccess
59458e6cf4a0ac-cert.pem
59458e6cf4a0ac-key.pem
cleardb-ca.pem
🗟 web.config

Note: It is assumed that the folder only contains 1 set of keys. The MySQL SSL status can be checked in the Admin / Security panel.

General Security		Spam protection	
	OpenPGP		
MySQL SSL connection is active			
	👿 Smarty Security 🕕 🛦		

Starting in Tiki 12.1, the check can also be run from tiki-check.php If any one of the key files are missing, a regular non-SSL connection is used. Connecting using SSL requires

- PHP extension php_openssl.dll must be enabled
- The MySQL server has activated SSL
- Tiki is configured with the 3 key files.