

Plugin Cypht

This permits to *plug* the [Cypht](#) webmail client in a wiki page.

HISTORY AND STATUS

Tiki and [Cypht](#) webmail interoperability started with [Tiki20](#) (2019). Tiki had a webmail since the early days but it was buggy, lacked features and was not improving. Since it would require too much work (and some specific expertise about email protocols) to get it up to modern standards, it was determined a better strategy to integrate an existing project (despite tradeoffs like feature overlap, integration challenges, etc.). See also: [Why did Tiki pick Cypht?](#) Major work has been done since that time in Cypht, and in Tiki 21, 22, 23, 24, 25 and 26. Work is ongoing, so it's recommended to run the latest 27.x from Git or [Daily Build](#). Most enhancements and many fixes will not be backported as there are lots of changes. Please see this [known issue](#). In [June 2023](#), [Cypht became a community project](#) and Jason (the original author) is [no longer the most active contributor](#). Jason is now more in an advisor mode, and the [activity level has grown quite bit with the influx of Tiki developers](#).

SYNTAX

```
{cypht}
```

PARAMETERS

Embed Cypht webmail and news reader.
Introduced in Tiki 20.0.

[Go to the source code](#)

Preferences required: wikipugin_cyph

Parameters

group

imap_name

imap_password

imap_port

imap_server

imap_username

smtp_name

smtp_password

Accepted Values

any string except for HTML and PHP tags

text

password

text

text

text

text

password

Description

GroupMail: Group (e.g. "Help Team")

Name for the IMAP connection. E.g. "My Mailbox"

Account IMAP password.

Default is 993.

E.g. `imap.example.com`

Account IMAP username.

Name for the SMTP connection. E.g. "My Account"

Account SMTP password.

Default	Since
	20.0
	20.0
	20.0
993	20.0
	20.0
	20.0
	20.0
	21.1

smtp_port

smtp_server

smtp_username

accountFId

contentFId

datetimeFId

fromFId

text

text

text

int

int

int

int

Default is 587.

E.g. smtp.example.com

Account SMTP username.

GroupMail: Account Field (Id of field in tracker to store Webmail account name)

GroupMail: Content Field (Id of field in tracker to store email message body content)

GroupMail: Date Time Field (Id of field in tracker to store email sent timestamp)

GroupMail: From Field (Id of field in tracker to store email From header)

587

20.0

20.0

21.1

20.0

20.0

20.0

20.0

groupmail

imap_tls

messageFId

operatorFId

(blank)

n

y

(blank)

y

n

int


int

Share this mailbox for Groupmail usage or keep it private.

Use secure connection to IMAP server.

GroupMail: Message Field (Id of field in tracker to store email message identifier)

GroupMail: Operator Field (Id of field in tracker to store operator name (username))



smtp_no_auth

smtp_tls

subjectFId

trackerId

(blank)

n

y

(blank)

y

n

int


int

Disable SMTP authentication if your server does not support it.

Use secure TLS/SSL connection to SMTP server.

GroupMail: Subject Field (Id of field in tracker to store email Subject header)

GroupMail: Tracker ID (to store GroupMail activity)



```
use_global_settings
```

(blank)

n

nw

y

Use global Cypht settings available at Tiki Webmail page. Choosing "No" will make this instance of Cypht use its own settings. Useful if this is a Groupmail box or you don't want to mix mailbox server and/or site settings from other pages. There are two modes of non-global settings - default one stores settings per user where each individual Tiki user will have their own copy of the settings whereas the second one stores settings per wiki page. Use per-wiki-page option if you want the plugin Cypht settings shared between users using the plugin on the same wiki page.

n

20.0

RELATED PAGES

- [Webmail](#)
- [Groupmail](#)
- <https://dev.tiki.org/Cypht-integration>
- <http://wikisuite.org/JMAP>
- <https://cypht.org>

ALIASES

[Plugin Cypht](#)
[Plugin Cypth](#)