

# Plugin Mouseover

*Introduced in Tiki3*

Use this [wiki plugin](#) to display hidden content by mousing over text.

## PARAMETERS

Display hidden content by mousing over text

*Introduced in Tiki 3. Required parameters are in **bold**.*

[Go to the source code](#)

*Preferences required: wikiplugin\_mouseover*

Parameters

(body of plugin)

label

## Accepted Values

text

## Description

Hidden content, unless the label parameter is undefined, in which case this is the label.

Text displayed on the page. The body is the hidden content.

Default

Since

3.0

url

bgcolor

class

closeDelay

effect

height

offsetx

url

text

text

digits

(blank)| none| slide| fade| blind\_ui| clip\_ui| drop\_ui|  
explode\_ui| fold\_ui| puff\_ui| slide\_ui

digits

int

Destination link when mouseover text is clicked. Use http:// for external links

Background color to apply to the popup

CSS class to apply

Number of seconds before popup closes

Set the type of show/hide animation that will be used

Mouseover box height. Default: 200px

Shifts the overlay to the right by the specified number of pixels relative to the cursor. Default: 5

javascript:void(0) 3.0

3.0

plugin-mouseover 4.0

0 5.0

4.0

200 3.0

5 3.0

offsety

padding

tag

text

textcolor

width

speed

int

digits

word

text

text

digits

(blank)

fast

slow

Shifts the overlay lower by the specified number of pixels relative to the cursor. Default: `0`

Padding size in pixels

HTML tag to use for the label. Default `a`

DEPRECATED Hidden content. The body contains the label.

Color to apply to the text in the popup

Mouseover box width. Default: `400px`

Set the speed of the animation.

24

3.0

a

3.0

9.2

3.0

3.0

400

3.0

4.0

parse

parselabel

sticky

---

(blank)

y

n

(blank)

y

n

(blank)

y

n


---

Parse the body of the plugin as wiki content (parsed by default)

Parse the label as wiki content (parsed by default)

When enabled, popup stays visible until it is clicked.

---



## EXAMPLES

### NON-STICKY MOUSEOVER

*This code:*

```
{MOUSEOVER(label="Hello" offsetx="4" offsey="15")}{Hello over there. It's fine!}{MOUSEOVER}
```

*Would produce:*

Hello

## STICKY MOUSEOVER WITH TIKI SYNTAX

*This code:*

---

```
{MOUSEOVER(label="Sticky" sticky="y" parse="y" offsetx="4" offsey="15")}{This is a "sticky" popup}{MOUSEOVER}
```

*Would produce:*

Sticky