

Plugin Smarty

Introduced in Tiki5

Use this [wiki plugin](#) to insert a Smarty function in a page. Smarty is the template engine used in Tiki.

PARAMETERS

Insert a Smarty function or variable

*Introduced in Tiki 5. Required parameters are in **bold**.*

[Go to the source code](#)

Preferences required: wikiplugin_smarty

Parameters Accepted Values

name

word

Description

The name of the Smarty function that the plugin will activate.
functions can be found at `lib/smarty_tiki/function.(nab)`
`vendor_bundled/vendor/smarty/smarty/libs/plugins/fu`

Default Since

7.0

In addition, the smarty function parameters that are required or allowed should or may be set. The functions available can be found as separate files on the server for each function (name) as follows:

- `lib/smarty_tiki/function.(name).php`

EXAMPLES

FUNCTION TO ADD A BUTTON

This code:

```
{smarty name="button" href="Search" _text="Search"}
```

Would produce:

[Search](#)

VARIABLES

Smarty variables can be displayed by using the `eval` Smarty function. The available Smarty variables for a page can be viewed by admins by clicking the "Smarty debug window" option in the Quick Administration menu. Or add `?show_smarty_debug=1` to the page address (or `&show_smarty_debug=1` if there are already other url parameters). See below examples.

SMARTY VARIABLES - PAGE NAME

This code:

```
{smarty name="eval" var="{$page}"}
```

Would produce on this page:

SMARTY GLOBAL VARIABLES - DOMAIN NAME

Global variables can be accessed too, such as the domain name -

This code:

```
{smarty name="eval" var="{$smarty.server.HTTP_HOST}"}
```

Would produce on this site:

doc.tiki.org.

PREFERENCES - METATAG KEYWORDS

This code:

```
{smarty name="eval" var="{$prefs.metatag_keywords}"}
```

Would produce on this site:

documentation, tiki, tikiwiki, document, help, install, wiki syntax

RELATED PAGES

- [PluginShowPref](#)