

# Plugin Subscribe Group

*Introduced with Tiki 2*

If you have allowed users to subscribe themselves to (join) a group, you can use this [wiki plugin](#) to allow them to subscribe/unsubscribe to a specific group. Please see [PluginSubscribeGroups](#) for a similar plugin for subscribing/unsubscribing to more than one group.

## SECURITY AND PERMISSIONS

- A user must have the perm `tiki_p_subscribe_group` to be able to see the box  
To set this permission go to *Settings > Groups*
- The group must be set as being a **user choice**  
To set this configuration go to *Settings > Groups*

### ⚠ Security Caution

*Using this plugin, **any registered user will be able to access any group** provided that the group has "User Choice" checked in the settings for the group at **Settings > Groups**.*

## PARAMETERS

Allow users to subscribe to a group

*Introduced in Tiki 2. Required parameters are in **bold**.*

[Go to the source code](#)

*Preferences required:* `wikiplugin_subscribegroup`

# Parameters

# Accepted Values

(body of plugin)

`group`

groupname

`defgroup`

`defgroup_action`

`undefgroup`

`undefgroup_action`

## Description

text displayed before the button

Group name to subscribe to or unsubscribe from

Make this the default group text, containing `%s` as the placeholder for the group name.

Default group button label. Will subscribe to the group first if not already a member.

Stop this being default group text, containing `%s` as the placeholder for the group name.

Stop this being default group button label. Does not unsubscribe from the group.

**Default**

**Since**

2.0

OK

9.1

OK

9.1

OK

9.1

OK

9.1

subscribe\_action

subscribe

unsubscribe\_action

unsubscribe

postsubscribe\_url url

postunsubscribe\_url url

Subscribe button label, containing `%s` as the placeholder for the group name.

Subscribe text, containing `%s` as the placeholder for the group name.

Unsubscribe button label, containing `%0` as the placeholder for the group name.

Unsubscribe text, containing `%s` as the placeholder for the group name.

URL to send the user to after subscribing, if required.

URL to send the user to after unsubscribing, if required.

OK 2.0

Subscribe%s 2.0

OK 2.0

Unsubscribe%s 2.0

8.0

8.0

undefgroup\_group

groupname

allowLeaveNonUserChoice

(blank)

y

n

defgroup\_redirect\_home

(blank)

y

n

---



Group name to set as default when user stops this group being it.

Always allow leaving a group even if the group settings do not allow user choice.

Redirect to new home page after default group change.  
(default is to redirect)

---

|            |     |
|------------|-----|
| Registered | 9.1 |
|------------|-----|

|   |      |
|---|------|
| n | 14.0 |
|---|------|

|   |     |
|---|-----|
| y | 9.1 |
|---|-----|

## USAGE NOTES

- If you use this plugin with the plugin GROUP, be careful that if GROUP is used first, the change will not immediately be shown. GROUP used after SUBSCRIBEGROUP will be fine
- A module with a filter on the group will be affected as soon as the group is changed

# EXAMPLES


## BASIC

*This code:*


---

```
{subscribegroup group="Editors" subscribe="Subscribe to %s" unsubscribe="Leave %s" subscribe_action="Name of subscribe submit button" unsubscribe_action="Name of unsubscribe submit button"}
```

*Would produce:*



or this screen



## ADVANCED

It is possible to make a link to toggle from subscribed/unsubscribed status to some group called **GroupName** by creating a link to a page which contains this plugin and adding the following parameters:

---

group="GroupName&iSubscribeGroup=1&subscribeGroup=text"

Example:

<http://www.example.com/somepage?group=GroupName&iSubscribeGroup=1&subscribeGroup=text>

Of course, this works if the user is logged in, and **GroupName** needs the correct spelling and capitalization.

## RELATED PAGES

- [PluginMemberList](#)

## ALIASES

- [Plugin SubscribeGroup](#)
- [Plugin Subscribe Group](#)