

Forums - Forum listing

Option	Description	Default
Default order		
Section order		
Topics		
Posts		
Posts per day (PPD)		
Last post		
Visits		
Description		
Description length		
Include category selector in forum list	Include a dropdown selector in the forum list to choose a category for the post.	
Forum post categories	Categories available in the category picker for forum posts.	

Option	Description	Default
Default order		
Section order		
Topics		
Posts		
Posts per day (PPD)		
Last post		
Visits		
Description		
Description length		
Include category selector in forum list	Include a dropdown selector in the forum list to choose a category for the post.	
Forum post categories	Categories available in the category picker for forum posts.	

Option	Description	Default
Default order		

Option	Description	Default
Section order		
Topics		
Posts		
Posts per day (PPD)		
Last post		
Visits		
Description		
Description length		
Include category selector in forum list	Include a dropdown selector in the forum list to choose a category for the post.	
Forum post categories	Categories available in the category picker for forum posts.	

Option	Description	Default
Default order		
Section order		
Topics		
Posts		
Posts per day (PPD)		
Last post		
Visits		
Description		
Description length		
Include category selector in forum list	Include a dropdown selector in the forum list to choose a category for the post.	
Forum post categories	Categories available in the category picker for forum posts.	

Option	Description	Default
Default order		
Topics		
Posts		
Posts per day (PPD)		
Last post		

Option	Description	Default
Visits		
Description		
Description length		
Include category selector in forum list	Include a dropdown selector in the forum list to choose a category for the post.	
Forum post categories	Categories available in the category picker for forum posts.	

Forums - General settings

Option	Description	Default
Forums	Threaded or flat discussions.	
Home forum (main forum)		
Forum image file gallery	File gallery used to store images for forums	
Rankings	Users can see several charts or rankings about the page.	
Accept wiki syntax		
Strip wiki markup from outgoing forum emails	Convert outgoing emails from forum posts to plain text.	
Topic archiving		
Quick jumps		
Replies are empty	<i>If disabled, replies will quote the original post</i>	
Allows quoting in flat forums	Allows users to reply.	
Don't display forum thread titles	Titles of posts usually don't change because they are a direct reply to the parent post. This feature turns off the display of titles in edit forms and forum display.	
Do not start messages titles with 'Re:'		
Require reply to have a title	Present an empty title input form and require it to be filled in before the forum post is submitted.	
First post of a thread can have an empty body	<i>Will be a thread title</i>	
Prevent Nesting of Quote wikipugins when replying	Strips quote plugin in reply in order to prevent nesting of quote plugins.	

Option	Description	Default
Allow inbound email posts from anyone	Allow messages from non-users in the forums using incoming messages from any email address.	
Parse HTML in inbound email posts	Attempt to keep the formatting of HTML "rich text" emails if using WYSIWYG.	
	<i>Experimental Has problems with some HTML emails, especially those with table-based layouts.</i>	
Uploaded filenames must match regex		
Send moderation email	Send email to forum moderators when post is queued	
Approve link in moderation email	Include a link for forum moderators to approve queue from email	
Manage thread defaults per-forum		
Display thread configuration bar	<i>Allows users to override the defaults</i>	
Keep settings for all forums during the user session		
Display the thread configuration bar only when the number of posts exceeds		
Number per page		
Default style		
Default sort mode		
Display forum thread or forum post title in the search engine friendly URL		
New email thread for each topic	If enabled each topic a forum will use it's own email thread, instead of all forum posts sharing the same one.	
Forum name search	<i>When listing forums</i>	
Forum content search	<i>When listing forums</i>	
Topic content search		
Unified search for forums and file galleries		
Index posts on forum section change.	Re-indexes forum posts to match the parent section when the section is changed	

Option	Description	Default
Forums	Threaded or flat discussions.	
Home forum (main forum)		

Option	Description	Default
Forum image file gallery	File gallery used to store images for forums	
Rankings	Users can see several charts or rankings about the page.	
Accept wiki syntax		
Strip wiki markup from outgoing forum emails	Convert outgoing emails from forum posts to plain text.	
Topic archiving		
Quick jumps		
Replies are empty	<i>If disabled, replies will quote the original post</i>	
Allows quoting in flat forums	Allows users to reply.	
Don't display forum thread titles	Titles of posts usually don't change because they are a direct reply to the parent post. This feature turns off the display of titles in edit forms and forum display.	
Do not start messages titles with 'Re:'		
Require reply to have a title	Present an empty title input form and require it to be filled in before the forum post is submitted.	
First post of a thread can have an empty body	<i>Will be a thread title</i>	
Prevent Nesting of Quote wikipugins when replying	Strips quote plugin in reply in order to prevent nesting of quote plugins.	
Allow inbound email posts from anyone	Allow messages from non-users in the forums using incoming messages from any email address.	
Parse HTML in inbound email posts	Attempt to keep the formatting of HTML "rich text" emails if using WYSIWYG. <i>Experimental Has problems with some HTML emails, especially those with table-based layouts.</i>	
Uploaded filenames must match regex		
Send moderation email	Send email to forum moderators when post is queued	
Approve link in moderation email	Include a link for forum moderators to approve queue from email	
Manage thread defaults per-forum		
Display thread configuration bar	<i>Allows users to override the defaults</i>	
Keep settings for all forums during the user session		
Display the thread configuration bar only when the number of posts exceeds		

Option	Description	Default
Number per page		
Default style		
Default sort mode		
Display forum thread or forum post title in the search engine friendly URL		
New email thread for each topic	If enabled each topic a forum will use it's own email thread, instead of all forum posts sharing the same one.	
Forum name search	<i>When listing forums</i>	
Forum content search	<i>When listing forums</i>	
Topic content search		
Unified search for forums and file galleries		
Index posts on forum section change.	Re-indexes forum posts to match the parent section when the section is changed	

Option	Description	Default
Forums	Threaded or flat discussions.	
Home forum (main forum)		
Forum image file gallery	File gallery used to store images for forums	
Rankings	Users can see several charts or rankings about the page.	
Accept wiki syntax		
Strip wiki markup from outgoing forum emails	Convert outgoing emails from forum posts to plain text.	
Topic archiving		
Quick jumps		
Replies are empty	<i>If disabled, replies will quote the original post</i>	
Allows quoting in flat forums	Allows users to reply.	
Don't display forum thread titles	Titles of posts usually don't change because they are a direct reply to the parent post. This feature turns off the display of titles in edit forms and forum display.	
Do not start messages titles with 'Re:'		

Option	Description	Default
Require reply to have a title	Present an empty title input form and require it to be filled in before the forum post is submitted.	
First post of a thread can have an empty body	<i>Will be a thread title</i>	
Prevent Nesting of Quote wikipugins when replying	Strips quote plugin in reply in order to prevent nesting of quote plugins.	
Allow inbound email posts from anyone	Allow messages from non-users in the forums using incoming messages from any email address.	
Parse HTML in inbound email posts	Attempt to keep the formatting of HTML "rich text" emails if using WYSIWYG. <i>Experimental Has problems with some HTML emails, especially those with table-based layouts.</i>	
Uploaded filenames must match regex		
Send moderation email	Send email to forum moderators when post is queued	
Approve link in moderation email	Include a link for forum moderators to approve queue from email	
Manage thread defaults per-forum		
Display thread configuration bar	<i>Allows users to override the defaults</i>	
Keep settings for all forums during the user session		
Display the thread configuration bar only when the number of posts exceeds		
Number per page		
Default style		
Default sort mode		
Display forum thread or forum post title in the search engine		
friendly URL		
New email thread for each topic	If enabled each topic a forum will use it's own email thread, instead of all forum posts sharing the same one.	
Forum name search	<i>When listing forums</i>	
Forum content search	<i>When listing forums</i>	
Topic content search		
Unified search for forums and file galleries		

Option	Description	Default
Re-index posts on forum section change.	Re-indexes forum posts to match the parent section when the section is changed	
Option	Description	Default
Forums	Threaded or flat discussions.	
Home forum (main forum)		
Forum image file gallery	File gallery used to store images for forums	
Rankings	Users can see several charts or rankings about the page.	
Accept wiki syntax		
Strip wiki markup from outgoing forum emails	Convert outgoing emails from forum posts to plain text.	
Topic archiving		
Quick jumps		
Replies are empty	<i>If disabled, replies will quote the original post</i>	
Allows quoting in flat forums	Allows users to reply.	
Don't display forum thread titles	Titles of posts usually don't change because they are a direct reply to the parent post. This feature turns off the display of titles in edit forms and forum display.	
Do not start messages titles with 'Re:'		
Require reply to have a title	Present an empty title input form and require it to be filled in before the forum post is submitted.	
First post of a thread can have an empty body	<i>Will be a thread title</i>	
Prevent Nesting of Quote wikipugins when replying	Strips quote plugin in reply in order to prevent nesting of quote plugins.	
Allow inbound email posts from anyone	Allow messages from non-users in the forums using incoming messages from any email address.	
Parse HTML in inbound email posts	Attempt to keep the formatting of HTML "rich text" emails if using WYSIWYG. <i>Experimental Has problems with some HTML emails, especially those with table-based layouts.</i>	
Uploaded filenames must match regex		
Send moderation email	Send email to forum moderators when post is queued	
Approve link in moderation email	Include a link for forum moderators to approve queue from email	

Option	Description	Default
Manage thread defaults per-forum		
Display thread configuration bar	<i>Allows users to override the defaults</i>	
Keep settings for all forums during the user session		
Display the thread configuration bar only when the number of posts exceeds		
Number per page		
Default style		
Default sort mode		
Display forum thread or forum post title in the search engine friendly URL		
New email thread for each topic	If enabled each topic a forum will use it's own email thread, instead of all forum posts sharing the same one.	
Forum name search	<i>When listing forums</i>	
Forum content search	<i>When listing forums</i>	
Topic content search		
Unified search for forums and file galleries		
Index posts on forum section change.	Re-indexes forum posts to match the parent section when the section is changed	

Option	Description	Default
Forums	Threaded or flat discussions.	
Home forum (main forum)		
Forum image file gallery	File gallery used to store images for forums	
Rankings	Users can see several charts or rankings about the page.	
Accept wiki syntax		
Strip wiki markup from outgoing forum emails	Convert outgoing emails from forum posts to plain text.	
Topic archiving		
Quick jumps		
Replies are empty	<i>If disabled, replies will quote the original post</i>	
Allows quoting in flat forums	Allows users to reply.	

Option	Description	Default
Don't display forum thread titles	Titles of posts usually don't change because they are a direct reply to the parent post. This feature turns off the display of titles in edit forms and forum display.	
Do not start messages titles with 'Re:'		
Require reply to have a title	Present an empty title input form and require it to be filled in before the forum post is submitted.	
First post of a thread can have an empty body	<i>Will be a thread title</i>	
Prevent Nesting of Quote wikipugins when replying	Strips quote plugin in reply in order to prevent nesting of quote plugins.	
Allow inbound email posts from anyone	Allow posts from non-users in forums using inbound posts from a specified email address.	
Parse HTML in inbound email posts	Attempt to keep the formatting of HTML "rich text" emails if using WYSIWYG. <i>Experimental Has problems with some HTML emails, especially those with table-based layouts.</i>	
Uploaded filenames must match regex		
Send moderation email	Send email to forum moderators when post is queued	
Approve link in moderation email	Include a link for forum moderators to approve queue from email	
Manage thread defaults per-forum		
Display thread configuration bar	<i>Allows users to override the defaults</i>	
Keep settings for all forums during the user session		
Display the thread configuration bar only when the number of posts exceeds		
Number per page		
Default style		
Default sort mode		
Display forum thread or forum post title in the search engine friendly		
JRL		
Forum name search	<i>When listing forums</i>	
Forum content search	<i>When listing forums</i>	

Option	Description	Default
Topic content search		
Tiki-indexed search		
Use database (full-text) search		
Index posts on forum section change.	Re-indexes forum posts to match the parent section when the section is changed	

Tags

Option	Description	Default
Tags	Enables tags to be set on pages and other items for freeform categorization.	
Plugin Tagged	List similarly tagged objects	
Plugin Add Tag	Provide an input field for adding a tag to an object	
Show tag cloud	Show the full tag cloud in the list-tags screen.	
Maximum number of tags in cloud		
Show tags in middle column	On pages that have content tagged, this option enables the display of the tags at the top of those pages. Tags can be set, among other places, in the properties tab when editing a wiki page..	
Tag Suggestions	Number of tags to show in tag suggestions	
Valid characters pattern	Click on the links below to set or clear a pattern to limit characters accepted in tags. <i>Useful to eliminate characters such as "œ, œ" which users can enter by mistake instead of a space.</i>	
Lowercase tags only	Convert uppercase characters in tags to lowercase, if this is a preferred style for making tags more user-friendly..	
Multilingual tags	Permits translation management of tags	
"More Like This" algorithm	enables tagged material to offer a find potentially related content. Basic will present content where a minimum number of tags match the item or page being viewed. Weighted is the same, but items are presented in Weighted (highest value first) sort order.	
Minimum number of tags in common	The minimum number of matching tags required for an item to be presented in the "More Like This" feature.	
Ordering of tagged objects	Default sort mode for tagged items	
Preload random tag	A random tag will be selected on the tag search page (if no tag is pre-selected)..	

Option	Description	Default
Tags	Enables tags to be set on pages and other items for freeform categorization.	
Plugin Tagged	List similarly tagged objects	
Plugin Add Tag	Provide an input field for adding a tag to an object	
Show tag cloud	Show the full tag cloud in the list-tags screen.	
Maximum number of tags in cloud		
Show tags in middle column	On pages that have content tagged, this option enables the display of the tags at the top of those pages. Tags can be set, among other places, in the properties tab when editing a wiki page..	
Tag Suggestions	Number of tags to show in tag suggestions	
Valid characters pattern	Click on the links below to set or clear a pattern to limit characters accepted in tags. <i>Useful to eliminate characters such as <code>œ,æ</code> which users can enter by mistake instead of a space.</i>	
Lowercase tags only	Convert uppercase characters in tags to lowercase, if this is a preferred style for making tags more user-friendly..	
Multilingual tags	Permits translation management of tags	
'More Like This' algorithm	enables tagged material to offer a find potentially related content. Basic will present content where a minimum number of tags match the item or page being viewed. Weighted is the same, but items are presented in Weighted (highest value first) sort order.	
Minimum number of tags in common	The minimum number of matching tags required for an item to be presented in the "More Like This" feature.	
Ordering of tagged objects	Default sort mode for tagged items	
Preload random tag	A random tag will be selected on the tag search page (if no tag is pre-selected)..	

Option	Description	Default
Tags	Enables tags to be set on pages and other items for freeform categorization.	
Plugin Tagged	List similarly tagged objects	
Plugin Add Tag	Provide an input field for adding a tag to an object	
Show tag cloud	Show the full tag cloud in the list-tags screen.	
Maximum number of tags in cloud		
Show tags in middle column	On pages that have content tagged, this option enables the display of the tags at the top of those pages. Tags can be set, among other places, in the properties tab when editing a wiki page..	
Tag Suggestions	Number of tags to show in tag suggestions	

Option	Description	Default
Valid characters pattern	Click on the links below to set or clear a pattern to limit characters accepted in tags. <i>Useful to eliminate characters such as "œ,€" which users can enter by mistake instead of a space.</i>	
Lowercase tags only	Convert uppercase characters in tags to lowercase, if this is a preferred style for making tags more user-friendly..	
Multilingual tags	Permits translation management of tags	
"More Like This" algorithm	enables tagged material to offer a find potentially related content. Basic will present content where a minimum number of tags match the item or page being viewed. Weighted is the same, but items are presented in Weighted (highest value first) sort order.	
Minimum number of tags in common	The minimum number of matching tags required for an item to be presented in the "More Like This" feature.	
Ordering of tagged objects	Default sort mode for tagged items	
Preload random tag	A random tag will be selected on the tag search page (if no tag is pre-selected)..	

Option	Description	Default
Tags	Enables tags to be set on pages and other items for freeform categorization.	
Plugin Tagged	List similarly tagged objects	
Plugin Add Tag	Provide an input field for adding a tag to an object	
Show tag cloud	Show the full tag cloud in the list-tags screen.	
Maximum number of tags in cloud		
Show tags in middle column	On pages that have content tagged, this option enables the display of the tags at the top of those pages. Tags can be set, among other places, in the properties tab when editing a wiki page..	
Tag Suggestions	Number of tags to show in tag suggestions	
Valid characters pattern	Click on the links below to set or clear a pattern to limit characters accepted in tags. <i>Useful to eliminate characters such as "œ,€" which users can enter by mistake instead of a space.</i>	
Lowercase tags only	Convert uppercase characters in tags to lowercase, if this is a preferred style for making tags more user-friendly..	
Multilingual tags	Permits translation management of tags	
"More Like This" algorithm	enables tagged material to offer a find potentially related content. Basic will present content where a minimum number of tags match the item or page being viewed. Weighted is the same, but items are presented in Weighted (highest value first) sort order.	

Option	Description	Default
Minimum number of tags in common	The minimum number of matching tags required for an item to be presented in the "More Like This" feature.	
Ordering of tagged objects	Default sort mode for tagged items	
Preload random tag	A random tag will be selected on the tag search page (if no tag is pre-selected)..	
Option	Description	Default
Tags	Enables tags to be set on pages and other items for freeform categorization.	
Plugin Tagged	List similarly tagged objects	
Plugin Add Tag	Provide an input field for adding a tag to an object	
Show tag cloud	Show the full tag cloud in the list-tags screen.	
Maximum number of tags in cloud		
Show tags in middle column	On pages that have content tagged, this option enables the display of the tags at the top of those pages. Tags can be set, among other places, in the properties tab when editing a wiki page..	
Tag Suggestions	Number of tags to show in tag suggestions	
Valid characters pattern	Click on the links below to set or clear a pattern to limit characters accepted in tags. <i>Useful to eliminate characters such as "œ,€" which users can enter by mistake instead of a space.</i>	
Lowercase tags only	Convert uppercase characters in tags to lowercase, if this is a preferred style for making tags more user-friendly..	
Multilingual tags	Permits translation management of tags	
'More Like This" algorithm	enables tagged material to offer a find potentially related content. Basic will present content where a minimum number of tags match the item or page being viewed. Weighted is the same, but items are presented in Weighted (highest value first) sort order.	
Minimum number of tags in common	The minimum number of matching tags required for an item to be presented in the "More Like This" feature.	
Ordering of tagged objects	Default sort mode for tagged items	
Preload random tag	A random tag will be selected on the tag search page (if no tag is pre-selected)..	

Galleries - Features

Option	Description	Default
image gallery	Collections of images for viewing or downloading (photo albums)	
Home gallery (main gallery)		
Rankings	Users can see several charts or rankings about the file.	
Image Gallery Comments	Users with permission may post threaded comments. The comments will appear at the bottom of the page.	
Slideshow		
Storage		
Directory path	<i>If you change this directory, move any images to the new directory either manually or using the 'Mover' below.</i>	
Image processing library	<i>GD 2.3.3 detected. Imagick 0 not detected.</i>	
Uploaded image names must match regex		
Uploaded image names cannot match regex		
Enable directory batch loading	Import large number of files by placing them them in a local directory accessible via a network share, scp, ftp, or other protocols. <i>You will need to setup a web-readable directory (outside of your web space is better). Then create a way to upload images to that directory.</i>	
Batch loading directory	<i>Needs to be a web-readable directory.</i>	
Limit image gallery categories to those under this category		
Display image information in a mouseover box		
Set display settings for all galleries		
Maximum rows per page		
Images per row		
Thumbnail width		
Thumbnail height		
Default scale size		
Name		

Option	Description	Default
Parent		
Description		
Created		
Last modified		
User		
Images		
Visits		
Default number of comments per page		
Default order of comments		

General - Date and Time

Option	Description	Default
Time zone	Indicates the default time zone to use for the server.	
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
Long date format	Specify how Tiki displays the date (longer version)	
Short date format	Specify how Tiki displays the date (shorter version)	
Long time format	Specify how Tiki displays the time (longer version)	
Short time format	Specify how Tiki displays the time (shorter version)	
Short JavaScript date format	Used in jQuery-UI date picker fields	
Short JavaScript time format	Used in jQuery-UI datetime picker fields	
Fields display order	The order date field inputs should be listed in.	
Start year	Year to show first in dropdown lists. For example, use "-2" for the current year minus two, or "2010" for a specific year	
End year	Year to show last on dropdown lists. For example, use "+2" for the current year plus two, or "2016" for a specific year	
Select month in Date Picker	Users can select month in the Date Picker instead of seeing month as text.	

Option	Description	Default
Select year in Date Picker	Users can select year in the Date Picker instead of seeing year as text.	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	
Skip date for same day	When displaying short date and time, skip date for today. Only time will be displayed.	
Query Timeago	jQuery plugin for fuzzy timestamps.	
Plugin Now	Show the current date and time	
Plugin Countdown	Display the time until or after a date and time	
Plugin Convene	Suggest meeting dates and times and vote to select one	

Option	Description	Default
Time zone	Indicates the default time zone to use for the server.	
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
Long date format	Specify how Tiki displays the date (longer version)	
Short date format	Specify how Tiki displays the date (shorter version)	
Long time format	Specify how Tiki displays the time (longer version)	
Short time format	Specify how Tiki displays the time (shorter version)	
Short JavaScript date format	Used in jQuery-UI date picker fields	
Short JavaScript time format	Used in jQuery-UI datetime picker fields	
Fields display order	The order date field inputs should be listed in.	
Start year	Year to show first in dropdown lists. For example, use "-2" for the current year minus two, or "2010" for a specific year	
End year	Year to show last on dropdown lists. For example, use "+2" for the current year plus two, or "2016" for a specific year	
Select month in Date Picker	Users can select month in the Date Picker instead of seeing month as text.	
Select year in Date Picker	Users can select year in the Date Picker instead of seeing year as text.	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	
Skip date for same day	When displaying short date and time, skip date for today. Only time will be displayed.	
Query Timeago	jQuery plugin for fuzzy timestamps.	

Option	Description	Default
Plugin Now	Show the current date and time	
Plugin Countdown	Display the time until or after a date and time	
Plugin Convene	Suggest meeting dates and times and vote to select one	

Option	Description	Default
Time zone	Indicates the default time zone to use for the server.	
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
Long date format	Specify how Tiki displays the date (longer version)	
Short date format	Specify how Tiki displays the date (shorter version)	
Long time format	Specify how Tiki displays the time (longer version)	
Short time format	Specify how Tiki displays the time (shorter version)	
Short JavaScript date format	Used in jQuery-UI date picker fields	
Short JavaScript time format	Used in jQuery-UI datetime picker fields	
Fields display order	The order date field inputs should be listed in.	
Start year	Year to show first in dropdown lists. For example, use "-2" for the current year minus two, or "2010" for a specific year	
End year	Year to show last on dropdown lists. For example, use "+2" for the current year plus two, or "2016" for a specific year	
Select month in Date Picker	Users can select month in the Date Picker instead of seeing month as text.	
Select year in Date Picker	Users can select year in the Date Picker instead of seeing year as text.	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	
Skip date for same day	When displaying short date and time, skip date for today. Only time will be displayed.	
Query Timeago	jQuery plugin for fuzzy timestamps.	
Plugin Now	Show the current date and time	
Plugin Countdown	Display the time until or after a date and time	
Plugin Convene	Suggest meeting dates and times and vote to select one	

Option	Description	Default
Time zone	Indicates the default time zone to use for the server.	

Option	Description	Default
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
Long date format	Specify how Tiki displays the date (longer version)	
Short date format	Specify how Tiki displays the date (shorter version)	
Long time format	Specify how Tiki displays the time (longer version)	
Short time format	Specify how Tiki displays the time (shorter version)	
Short JavaScript date format	Used in jQuery-UI date picker fields	
Short JavaScript time format	Used in jQuery-UI datetime picker fields	
Fields display order	The order date field inputs should be listed in.	
Start year	Year to show first in dropdown lists. For example, use "-2" for the current year minus two, or "2010" for a specific year	
End year	Year to show last on dropdown lists. For example, use "+2" for the current year plus two, or "2016" for a specific year	
Select month in Date Picker	Users can select month in the Date Picker instead of seeing month as text.	
Select year in Date Picker	Users can select year in the Date Picker instead of seeing year as text.	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	
Skip date for same day	When displaying short date and time, skip date for today. Only time will be displayed.	
Query Timeago	jQuery plugin for fuzzy timestamps.	
Plugin Now	Show the current date and time.	
Plugin Countdown	Display the time until or after a date and time	
Plugin Convene	Suggest meeting dates and times and vote to select one.	

Option	Description	Default
Time zone	Indicates the default time zone to use for the server.	
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
Long date format	Specify how Tiki displays the date (longer version)	
Short date format	Specify how Tiki displays the date (shorter version)	
Long time format	Specify how Tiki displays the time (longer version)	

Option	Description	Default
Short time format	Specify how Tiki displays the time (shorter version)	
Short JavaScript date format	Used in jQuery-UI date picker fields	
Short JavaScript time format	Used in jQuery-UI datetime picker fields	
Fields display order	The order date field inputs should be listed in.	
Start year	Year to show first in dropdown lists. For example, use "-2" for the current year minus two, or "2010" for a specific year	
End year	Year to show last on dropdown lists. For example, use "+2" for the current year plus two, or "2016" for a specific year	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	
Skip date for same day	When displaying short date and time, skip date for today. Only time will be displayed.	
Query Timeago	jQuery plugin for fuzzy timestamps.	
Plugin Now	Show the current date and time.	
Plugin Countdown	Display the time until or after a date and time	
Plugin TimeSheet	Embed a timesheet into a page	
Plugin Convene	Suggest meeting dates and times and vote to select one.	

General - General preferences

Option	Description	Default
Server domain name	The value that will be used by default as the server domain name of your Tiki site. <i>Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and require database or shell access to recover it.</i>	
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: https://example.com/tiki/), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	

Option	Description	Default
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at ./temp/Mail_yyyymmddhhmmss_randomstring.tmp) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Amazon SES version		
Elastic Email Username		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun API Endpoint		
Mandrill Key		
Postage Key		
Postmark Key		
SendGrid Username		
SendGrid Key		
SparkPost Key		
SMTP server		
Authentication	Mail server authentication	
Username		
Password		
Port		
Security		

Option	Description	Default
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery.	
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	
Include Smarty notices in the PHP error report	Tiki will display Smarty notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	
Show generic error message	Show a generic error message for non admins users. The error is logged to the database.	
Generic error message	Message to display to non admin users when an error occurs.	
Log mail in Tiki logs	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	
Log SQL	All SQL queries will be registered in the database in the tiki_sql_query_logs table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	

Option	Description	Default
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	
Data Source Name (DSN)	DSN used for connect to the error tracking service.	
Sample rate	Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)	
Track PHP errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.	
Track JavaScript errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Delay scheduled time (minutes)	When calculating if the jobs should run, take the delay into consideration	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex: <code>admin,operations@example.com</code> If empty, the email will be sent to all administrators.	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex: <code>admin,operations@example.com</code> If empty, the email will be sent to all administrators.	
Number of logs to keep	0 will keep all logs	

Option	Description	Default
Server domain name	The value that will be used by default as the server domain name of your Tiki site. <i>Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and requite database or shell access to recover it.</i>	
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: <code>https://example.com/tiki/</code>), used when the current URL can not be determined, example, when executing from the command line.	

Option	Description	Default
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at <code>./temp/Mail_yyyymmddhhmmss_randomstring.tmp</code>) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Amazon SES version		
Elastic Email Username		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun API Endpoint		
Mandrill Key		
Postage Key		
Postmark Key		
SendGrid Username		
SendGrid Key		
SparkPost Key		
SMTP server		
Authentication	Mail server authentication	
Username		

Option	Description	Default
Password		
Port		
Security		
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery.	
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	
Include Smarty notices in the PHP error report	Tiki will display Smarty notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	
Show generic error message	Show a generic error message for non admins users. The error is logged to the database.	
Generic error message	Message to display to non admin users when an error occurs.	
Disable JavaScript	Disable JavaScript for the purpose of testing even if enabled in the browser. <i>Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.</i>	

Option	Description	Default
Log mail in Tiki logs	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	
Log SQL	All SQL queries will be registered in the database in the adodb_logsql table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	
Data Source Name (DSN)	DSN used for connect to the error tracking service.	
Sample rate	Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)	
Track PHP errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.	
Track JavaScript errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Delay scheduled time (minutes)	When calculating if the jobs should run, take the delay into consideration	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex: <code>admin,operations@example.com</code> If empty, the email will be sent to all administrators.	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex: <code>admin,operations@example.com</code> If empty, the email will be sent to all administrators.	
Number of logs to keep	0 will keep all logs	

Option	Description	Default
Server domain name	The value that will be used by default as the server domain name of your Tiki site. <i>Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and require database or shell access to recover it.</i>	
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: https://example.com/tiki/), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at ./temp/Mail_yyyymmddhhmmss_randomstring.tmp) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Amazon SES version		
Elastic Email Username		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun API Endpoint		
Mandrill Key		
Postage Key		
Postmark Key		

Option	Description	Default
SendGrid Username		
SendGrid Key		
SparkPost Key		
SMTP server		
Authentication	Mail server authentication	
Username		
Password		
Port		
Security		
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery. Only works with SMTP mail.	
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	

Option	Description	Default
Include Smarty notices in the PHP error report	Tiki will display Smarty notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	
Show generic error message	Show a generic error message for non admins users. The error is logged to the database.	
Generic error message	Message to display to non admin users when an error occurs.	
Disable JavaScript	Disable JavaScript for the purpose of testing even if enabled in the browser. <i>Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.</i>	
Log mail in Tiki logs	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	
Log SQL	All SQL queries will be registered in the database in the adodb_logsql table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	
Data Source Name (DSN)	DSN used for connect to the error tracking service.	
Sample rate	Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)	
Track PHP errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.	
Track JavaScript errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Delay scheduled time (minutes)	When calculating if the jobs should run, take the delay into consideration	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex: <code>admin,operations@example.com</code> If empty, the email will be sent to all administrators.	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	

Option	Description	Default
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed. <code>Ex: admin,operations@example.com</code> If empty, the email will be sent to all administrators.	
Number of logs to keep	0 will keep all logs	

Option	Description	Default
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: <code>https://example.com/tiki/</code>), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at <code>./temp/Mail_yyyymmddhhmmss_randomstring.tmp</code>) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Amazon SES version		
Elastic Email Username		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun API Endpoint		

Option	Description	Default
Mandrill Key		
Postage Key		
Postmark Key		
SendGrid Username		
SendGrid Key		
SparkPost Key		
SMTP server		
Authentication	Mail server authentication	
Username		
Password		
Port		
Security		
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery. Only works with SMTP mail.	
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	

Option	Description	Default
PHP errors visible to admin only	<p>PHP Errors will be shown to only the Admin user.</p> <p><i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i></p>	
Include Smarty notices in the PHP error report	<p>Tiki will display Smarty notices with the PHP error messages.</p> <p><i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i></p>	
Disable JavaScript	<p>Disable JavaScript for the purpose of testing even if enabled in the browser.</p> <p><i>Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.</i></p>	
Log mail in Tiki logs	<p>A line of type mail will be included in the System Log with the destination address and subject of each email sent.</p> <p><i>May impact performance</i></p>	
Log SQL	<p>All SQL queries will be registered in the database in the adodb_logsql table.</p> <p><i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i></p>	
Log queries using more than	<p>Use to log only queries that exceed a specific amount of time.</p> <p><i>May impact performance</i></p>	
Data Source Name (DSN)	<p>DSN used for connect to the error tracking service.</p>	
Track PHP errors	<p>Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.</p>	
Track JavaScript errors	<p>Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.</p>	
Enabled	<p>Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.</p>	
How to trigger Web Cron		
Run interval	<p>The amount of time of each run</p>	
Token	<p>The token to use when running the cron manually</p>	
Scheduler	<p>Provides the ability to run tasks at a scheduled time.</p>	
Delay scheduled time (minutes)	<p>When calculating if the jobs should run, take the delay into consideration</p>	
Scheduler stalled after (minutes)	<p>Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.</p>	
Notify on stalled schedulers	<p>Send an email notification when a stalled scheduler is detected.</p>	
Users to notify on stalled task	<p>List of users/emails separated by comma to be notified when a scheduler task is set to stalled.Ex: admin,operations@example.comIf empty, the email will be sent to all administrators.</p>	
Self healing after (minutes)	<p>Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing</p>	
Notify on healed schedulers	<p>Send an email notification when a stalled scheduler is healed.</p>	

Option	Description	Default
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex: <code>admin,operations@example.com</code> If empty, the email will be sent to all administrators.	
Number of logs to keep	0 will keep all logs	

Option	Description	Default
Upgrade cycle	Tiki upgrade frequency for this site to check against.	
Check for updates automatically	Tiki will automatically check for new updates each time you access the Admin Home page, based on your Check frequency selection. <i>Subscribe to the Tiki Newsletter to be notified of new releases. https://doc.tiki.org/Newsletters</i>	
Check frequency	How often Tiki should check for updates. This field applies only if "Check for updates automatically" is enabled. <i>Click "Check for Updates Now" to perform an update check.</i>	
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Server domain name	The value that will be used by default as the server domain name of your Tiki site.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: https://example.com/tiki/), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at <code>./temp/Mail_yyyymmddhhmmss_randomstring.tmp</code>) to send mail notifications.	
SMTP server		
Authentication	Mail server authentication	
Username		

Option	Description	Default
Password		
Port		
Security		
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery. Only works with SMTP mail.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	
Include Smarty notices in the PHP error report	Tiki will display Smarty notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	
Disable JavaScript	Disable JavaScript for the purpose of testing even if enabled in the browser. <i>Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.</i>	
Log mail in Tiki logs	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	
Log SQL	All SQL queries will be registered in the database in the adodb_logsqli table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	

Option	Description	Default
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex: <code>admin,operations@example.com</code> If empty, the email will be sent to all administrators.	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex: <code>admin,operations@example.com</code> If empty, the email will be sent to all administrators.	
Number of logs to keep	0 will keep all logs	

General - General settings

Option	Description	Default
Temporary directory	Directory on your server, relative to your Tiki installation, for storing temporary files. Tiki must have full read and write access to this directory.	
Use proxy	Specify if this Tiki site requires a proxy to access the internet. If enabled, the proxy Host name (either with or without the http:// prefix), Port settings, Username, and Password can be specified.	
Proxy host name	Proxy host - without http:// or similar, just the host name	
Port	Proxy port	
Proxy username		

Option	Description	Default
Proxy password		
HTTP lookup: skip framesets	When performing an HTTP request to an external source, verify if the result is a frameset and use heuristic to provide the real content.	
Load balancer	Activate this only if the server is behind a load balancer (or reverse proxy). This enables logging the IP of the user rather than the IP of the proxy server	
Tiki is behind a frontend-proxy/load-balancer that rewrites ports	Activate this only if the server is behind a frontend-proxy/load-balancer (or reverse proxy) that rewrites ports. This enables Tiki to use the HTTP_X_FORWARDED_PROTO parameter set by the proxy, to provide correct links.	
Access-Control-Allow-Origin	Domains allowed to make "CORS" (Cross-Origin Resource Sharing or Cross-Domain Ajax) requests from this server. <i>One URI per line, for example, "http://www.example.com" or "*" for any site</i>	
Use CURL for HTTP connections	Use CURL instead of sockets for server to server HTTP connections, when sockets are not available.	
Realtime Tiki	Use built-in websockets server within Tiki to enable realtime communication features of the app. See help page for more information on how to start the server.	
Realtime port	The port used to access this server; if not specified, port 8080 will be used <i>If not specified, port 8080 will be used</i>	
Path to the php binary	Path to the php command line binary to be used by tiki when calling command line programs	
Multi-domain	Enable domain names to be mapped to perspectives and simulate multiple domains hosted with the same Tiki installation.	
Switch domain when switching perspective	Important: Different domains have different login sessions and, even in the case of subdomains, an understanding of session cookies is needed to make it work	
Default domain for non categorized content	The domain (hostname only) to be used when redirecting the user if he tries to read content that is not bound to the category/perspective configured for the current domain.	
Multi-domain Configuration	Comma-separated values mapping the domain name to the perspective ID. <i>One domain per line with a comma separating it from the perspective ID. For example: tiki.org,1</i>	
Session storage location	Select where the session information should be stored. Memcache sessions require memcache to be configured.	
Session lifetime	Session lifetime <i>Expressed as minutes. This is the minimum time logged in. To be the exact time, adjustments must be made in .htaccess session.gc_probability and session.gc_divisor to 1. Be careful - changing the probability may affect server performance.</i>	

Option	Description	Default
Session cookie name	Session cookie name used instead of the PHP default configuration	
Site terminal	Allows users to be directed to a specific perspective depending on the origin IP address. Can be used inside intranets to use different configurations for users depending on their departments or discriminate people in web contexts. Unspecified IPs will fall back to default behavior, including multi-domain handling. Manually selected perspectives take precedence over this.	
Site terminal configuration	Provides the mapping from subnets to perspective. <i>One per line. Network prefix in CIDR notation (address/mask size), separated by comma with the perspective ID. Example: 192.168.12.0/24,12</i>	
Contact us	A basic contact form a visitor can use to contact the site admin <i>You can use Trackers to create custom Contact Us forms.</i>	
Allow anonymous visitors to use the "Contact Us" feature.	Allow anonymous visitors to use the "Contact Us" feature.	
Display contact priority	Display contact priority option	
Contact user	User to contact	
Stats	Record basic statistics about major Tiki features (number of wiki pages, size of file galleries, etc.)	
Referrer stats	Record domain name of sites that send visitors to this Tiki.	
Count admin pageviews	Include pageviews by Admin when reporting stats.	
Terms and Conditions	Automatically present a terms of use page to be accepted by users accessing the site.	
Terms of Use page name	Wiki page for Terms of Use content. The page may be translated using the multilingual feature.	
Minimum age	When presenting the terms of use, request age. <i>0 to ignore age validation</i>	
Help system	Activates links to Tiki documentation. You can specify a Help URL that contains customized help pages. By default, the Help system uses http://doc.tiki.org/	
Help URL	The default help system may not be complete. You can contribute to the Tiki documentation, which is a community-edited wiki.	
Option	Description	Default
Temporary directory	Directory on your server, relative to your Tiki installation, for storing temporary files. Tiki must have full read and write access to this directory.	
Use proxy	Specify if this Tiki site requires a proxy to access the internet. If enabled, the proxy Host name (either with or without the http:// prefix), Port settings, Username, and Password can be specified.	

Option	Description	Default
Proxy host name	Proxy host - without http:// or similar, just the host name	
Port	Proxy port	
Proxy username		
Proxy password		
HTTP lookup: skip framesets	When performing an HTTP request to an external source, verify if the result is a frameset and use heuristic to provide the real content.	
Load balancer	Activate this only if the server is behind a load balancer (or reverse proxy). This enables logging the IP of the user rather than the IP of the proxy server	
Tiki is behind a frontend-proxy/load-balancer that rewrites ports	Activate this only if the server is behind a frontend-proxy/load-balancer (or reverse proxy) that rewrites ports. This enables Tiki to use the HTTP_X_FORWARDED_PROTO parameter set by the proxy, to provide correct links.	
Access-Control-Allow-Origin	Domains allowed to make "CORS" (Cross-Origin Resource Sharing or Cross-Domain Ajax) requests from this server. <i>One URI per line, for example, "http://www.example.com" or "*" for any site</i>	
Use CURL for HTTP connections	Use CURL instead of sockets for server to server HTTP connections, when sockets are not available.	
Realtime Tiki	Use built-in websockets server within Tiki to enable realtime communication features of the app. See help page for more information on how to start the server.	
Realtime port	The port used to access this server; if not specified, port 8080 will be used <i>If not specified, port 8080 will be used</i>	
Path to the php binary	Path to the php command line binary to be used by tiki when calling command line programs	
Multi-domain	Enable domain names to be mapped to perspectives and simulate multiple domains hosted with the same Tiki installation.	
Switch domain when switching perspective	Important: Different domains have different login sessions and, even in the case of subdomains, an understanding of session cookies is needed to make it work	
Default domain for non categorized content	The domain (hostname only) to be used when redirecting the user if he tries to read content that is not bound to the category/perspective configured for the current domain.	
Multi-domain Configuration	Comma-separated values mapping the domain name to the perspective ID. <i>One domain per line with a comma separating it from the perspective ID. For example: tiki.org,1</i>	
Session storage location	Select where the session information should be stored. Memcache sessions require memcache to be configured.	

Option	Description	Default
Session lifetime	<p>Session lifetime</p> <p><i>Expressed as minutes. This is the minimum time logged in. To be the exact time, adjustments must be made in .htaccess session.gc_probability and session.gc_divisor to 1. Be careful - changing the probability may affect server performance.</i></p>	
Session cookie name	Session cookie name used instead of the PHP default configuration	
Site terminal	<p>Allows users to be directed to a specific perspective depending on the origin IP address. Can be used inside intranets to use different configurations for users depending on their departements or discriminate people in web contexts. Unspecified IPs will fall back to default behavior, including multi-domain handling. Manually selected perspectives take precedence over this.</p>	
Site terminal configuration	<p>Provides the mapping from subnets to perspective.</p> <p><i>One per line. Network prefix in CIDR notation (address/mask size), separated by comma with the perspective ID. Example: 192.168.12.0/24,12</i></p>	
Contact us	<p>A basic contact form a visitor can use to contact the site admin</p> <p><i>You can use Trackers to create custom Contact Us forms.</i></p>	
Allow anonymous visitors to use the "Contact Us" feature.	Allow anonymous visitors to use the "Contact Us" feature.	
Display contact priority	Display contact priority option	
Contact user	User to contact	
Stats	Record basic statistics about major Tiki features (number of wiki pages, size of file galleries, etc.)	
Referrer stats	Record domain name of sites that send visitors to this Tiki.	
Count admin pageviews	Include pageviews by Admin when reporting stats.	
Terms and Conditions	Automatically present a terms of use page to be accepted by users accessing the site.	
Terms of Use page name	Wiki page for Terms of Use content. The page may be translated using the multilingual feature.	
Minimum age	<p>When presenting the terms of use, request age.</p> <p><i>0 to ignore age validation</i></p>	
Help system	<p>Activates links to Tiki documentation. You can specify a Help URL that contains customized help pages. By default, the Help system uses http://doc.tiki.org/</p>	
Help URL	The default help system may not be complete. You can contribute to the Tiki documentation, which is a community-edited wiki.	

Option	Description	Default
Temporary directory	Directory on your server, relative to your Tiki installation, for storing temporary files. Tiki must have full read and write access to this directory.	
Use proxy	Specify if this Tiki site requires a proxy to access the internet. If enabled, the proxy Host name (either with or without the http:// prefix), Port settings, Username, and Password can be specified.	
Proxy host name	Proxy host - without http:// or similar, just the host name	
Port	Proxy port	
Proxy username		
Proxy password		
HTTP lookup: skip framesets	When performing an HTTP request to an external source, verify if the result is a frameset and use heuristic to provide the real content.	
Load balancer	Activate this only if the server is behind a load balancer (or reverse proxy). This enables logging the IP of the user rather than the IP of the proxy server	
Tiki is behind a frontend-proxy/load-balancer that rewrites ports	Activate this only if the server is behind a frontend-proxy/load-balancer (or reverse proxy) that rewrites ports. This enables Tiki to use the HTTP_X_FORWARDED_PROTO parameter set by the proxy, to provide correct links.	
Access-Control-Allow-Origin	Domains allowed to make "CORS" (Cross-Origin Resource Sharing or Cross-Domain Ajax) requests from this server. <i>One URI per line, for example, "http://www.example.com" or "*" for any site</i>	
Use CURL for HTTP connections	Use CURL instead of sockets for server to server HTTP connections, when sockets are not available.	
Realtime Tiki	Use built-in websockets server within Tiki to enable realtime communication features of the app. See help page for more information on how to start the server.	
Realtime port	The port used to access this server; if not specified, port 8080 will be used <i>If not specified, port 8080 will be used</i>	
Path to the php binary	Path to the php command line binary to be used by tiki when calling command line programs	
Multi-domain	Enable domain names to be mapped to perspectives and simulate multiple domains hosted with the same Tiki installation.	
Switch domain when switching perspective	Important: Different domains have different login sessions and, even in the case of subdomains, an understanding of session cookies is needed to make it work	

Option	Description	Default
Default domain for non categorized content	The domain (hostname only) to be used when redirecting the user if he tries to read content that is not bound to the category/perspective configured for the current domain.	
Multi-domain Configuration	Comma-separated values mapping the domain name to the perspective ID. <i>One domain per line with a comma separating it from the perspective ID. For example: tiki.org,1</i>	
Session storage location	Select where the session information should be stored. Memcache sessions require memcache to be configured.	
Session lifetime	Session lifetime <i>Expressed as minutes. This is the minimum time logged in. To be the exact time, adjustments must be made in .htaccess session.gc_probability and session.gc_divisor to 1. Be careful - changing the probability may affect server performance.</i>	
Session cookie name	Session cookie name used instead of the PHP default configuration	
Site terminal	Allows users to be directed to a specific perspective depending on the origin IP address. Can be used inside intranets to use different configurations for users depending on their departements or discriminate people in web contexts. Unspecified IPs will fall back to default behavior, including multi-domain handling. Manually selected perspectives take precedence over this.	
Site terminal configuration	Provides the mapping from subnets to perspective. <i>One per line. Network prefix in CIDR notation (address/mask size), separated by comma with the perspective ID. Example: 192.168.12.0/24,12</i>	
Contact us	A basic contact form a visitor can use to contact the site admin <i>You can use Trackers to create custom Contact Us forms.</i>	
Allow anonymous visitors to use the "Contact Us" feature.	Allow anonymous visitors to use the "Contact Us" feature.	
Display contact priority	Display contact priority option	
Contact user	User to contact	
Stats	Record basic statistics about major Tiki features (number of wiki pages, size of file galleries, etc.)	
Referrer stats	Record domain name of sites that send visitors to this Tiki.	
Count admin pageviews	Include pageviews by Admin when reporting stats.	
Terms and Conditions	Automatically present a terms of use page to be accepted by users accessing the site.	
Terms of Use page name	Wiki page for Terms of Use content. The page may be translated using the multilingual feature.	
Minimum age	When presenting the terms of use, request age. <i>0 to ignore age validation</i>	

Option	Description	Default
Help system	Activates links to Tiki documentation. You can specify a Help URL that contains customized help pages. By default, the Help system uses <code>http://doc.tiki.org/</code>	
Help URL	The default help system may not be complete. You can contribute to the Tiki documentation, which is a community-edited wiki.	
Option	Description	Default
Temporary directory	Directory on your server, relative to your Tiki installation, for storing temporary files. Tiki must have full read and write access to this directory.	
Use proxy	Specify if this Tiki site requires a proxy to access the internet. If enabled, the proxy Host name (either with or without the <code>http://</code> prefix), Port settings, Username, and Password can be specified.	
Proxy host name	Proxy host - without <code>http://</code> or similar, just the host name	
Port	Proxy port	
Proxy username		
Proxy password		
HTTP lookup: skip framesets	When performing an HTTP request to an external source, verify if the result is a frameset and use heuristic to provide the real content.	
Load balancer	Activate this only if the server is behind a load balancer (or reverse proxy). This enables logging the IP of the user rather than the IP of the proxy server	
Tiki is behind a frontend-proxy/load-balancer that rewrites ports	Activate this only if the server is behind a frontend-proxy/load-balancer (or reverse proxy) that rewrites ports. This enables Tiki to use the <code>HTTP_X_FORWARDED_PROTO</code> parameter set by the proxy, to provide correct links.	
Access-Control-Allow-Origin	Domains allowed to make "CORS" (Cross-Origin Resource Sharing or Cross-Domain Ajax) requests from this server. <i>One URI per line, for example, "http://www.example.com" or "*" for any site</i>	
Use CURL for HTTP connections	Use CURL instead of sockets for server to server HTTP connections, when sockets are not available.	
Multi-domain	Enable domain names to be mapped to perspectives and simulate multiple domains hosted with the same Tiki installation.	
Switch domain when switching perspective	Important: Different domains have different login sessions and, even in the case of subdomains, an understanding of session cookies is needed to make it work	

Option	Description	Default
Default domain for non categorized content	The domain (hostname only) to be used when redirecting the user if he tries to read content that is not bound to the category/perspective configured for the current domain.	
Multi-domain Configuration	Comma-separated values mapping the domain name to the perspective ID. <i>One domain per line with a comma separating it from the perspective ID. For example: tiki.org,1</i>	
Session storage location	Select where the session information should be stored. Memcache sessions require memcache to be configured.	
Session lifetime	Session lifetime <i>Expressed as minutes. This is the minimum time logged in. To be the exact time, adjustments must be made in .htaccess session.gc_probability and session.gc_divisor to 1. Be careful - changing the probability may affect server performance.</i>	
Session cookie name	Session cookie name used instead of the PHP default configuration	
Site terminal	Allows users to be directed to a specific perspective depending on the origin IP address. Can be used inside intranets to use different configurations for users depending on their departements or discriminate people in web contexts. Unspecified IPs will fall back to default behavior, including multi-domain handling. Manually selected perspectives take precedence over this.	
Site terminal configuration	Provides the mapping from subnets to perspective. <i>One per line. Network prefix in CIDR notation (address/mask size), separated by comma with the perspective ID. Example: 192.168.12.0/24,12</i>	
Contact us	A basic contact form a visitor can use to contact the site admin <i>You can use Trackers to create custom Contact Us forms.</i>	
Allow anonymous visitors to use the "Contact Us" feature.	Allow anonymous visitors to use the "Contact Us" feature.	
Display contact priority	Display contact priority option	
Contact user	User to contact	
Stats	Record basic statistics about major Tiki features (number of wiki pages, size of file galleries, etc.)	
Referrer stats	Record domain name of sites that send visitors to this Tiki.	
Count admin pageviews	Include pageviews by Admin when reporting stats.	
Terms and Conditions	Automatically present a terms of use page to be accepted by users accessing the site.	
Terms of Use page name	Wiki page for Terms of Use content. The page may be translated using the multilingual feature.	

Option	Description	Default
Minimum age	When presenting the terms of use, request age. <i>0 to ignore age validation</i>	
Help system	Activates links to Tiki documentation. You can specify a Help URL that contains customized help pages. By default, the Help system uses <code>http://doc.tiki.org/</code>	
Help URL	The default help system may not be complete. You can contribute to the Tiki documentation, which is a community-edited wiki.	

Option	Description	Default
Temporary directory	Directory on your server, relative to your Tiki installation, for storing temporary files. Tiki must have full read and write access to this directory.	
Use proxy	Specify if this Tiki site requires a proxy to access the internet. If enabled, the proxy Host name (either with or without the <code>http://</code> prefix), Port settings, Username, and Password can be specified.	
Proxy host name	Proxy host - without <code>http://</code> or similar, just the host name	
Port	Proxy port	
Proxy username		
Proxy password		
HTTP lookup: skip framesets	When performing an HTTP request to an external source, verify if the result is a frameset and use heuristic to provide the real content.	
Load balancer	Activate this only if the server is behind a load balancer (or reverse proxy). This enables logging the IP of the user rather than the IP of the proxy server	
Tiki is behind a frontend-proxy/load-balancer that rewrites ports	Activate this only if the server is behind a frontend-proxy/load-balancer (or reverse proxy) that rewrites ports. This enables Tiki to use the <code>HTTP_X_FORWARDED_PROTO</code> parameter set by the proxy, to provide correct links.	
Access-Control-Allow-Origin	Domains allowed to make "CORS" (Cross-Origin Resource Sharing or Cross-Domain Ajax) requests from this server. <i>One URI per line, for example, "<code>http://www.example.com</code>" or "*" for any site</i>	
Use CURL for HTTP connections	Use CURL instead of sockets for server to server HTTP connections, when sockets are not available.	
Multi-domain	Enable domain names to be mapped to perspectives and simulate multiple domains hosted with the same Tiki installation.	

Option	Description	Default
Switch domain when switching perspective	Important: Different domains have different login sessions and, even in the case of subdomains, an understanding of session cookies is needed to make it work	
Default domain for non categorized content	The domain (hostname only) to be used when redirecting the user if he tries to read content that is not bound to the category/perspective configured for the current domain.	
Multi-domain Configuration	Comma-separated values mapping the domain name to the perspective ID. <i>One domain per line with a comma separating it from the perspective ID. For example: tiki.org,1</i>	
Session storage location	Select where the session information should be stored. Memcache sessions require memcache to be configured.	
Session lifetime	Session lifetime <i>Expressed as minutes. This is the minimum time logged in. To be the exact time, adjustments must be made in .htaccess session.gc_probability and session.gc_divisor to 1. Be careful - changing the probability may affect server performance.</i>	
Session cookie name	Session cookie name used instead of the PHP default configuration	
Site terminal	Allows users to be directed to a specific perspective depending on the origin IP address. Can be used inside intranets to use different configurations for users depending on their departements or discriminate people in web contexts. Unspecified IPs will fall back to default behavior, including multi-domain handling. Manually selected perspectives take precedence over this.	
Site terminal configuration	Provides the mapping from subnets to perspective. <i>One per line. Network prefix in CIDR notation (address/mask size), separated by comma with the perspective ID. Example: 192.168.12.0/24,12</i>	
Contact us	A basic contact form a visitor can use to contact the site admin <i>You can use Trackers to create custom Contact Us forms.</i>	
Allow anonymous visitors to use the "Contact Us" feature.	Allow anonymous visitors to use the "Contact Us" feature.	
Display contact priority	Display contact priority option	
Contact user	User to contact	
Stats	Record basic statistics about major Tiki features (number of wiki pages, size of file galleries, etc.)	
Referrer stats	Record domain name of sites that send visitors to this Tiki.	
Count admin pageviews	Include pageviews by Admin when reporting stats.	
Terms and Conditions	Automatically present a terms of use page to be accepted by users accessing the site.	

Option	Description	Default
Terms of Use page name	Wiki page for Terms of Use content. The page may be translated using the multilingual feature.	
Minimum age	When presenting the terms of use, request age. <i>0 to ignore age validation</i>	
Help system	Activates links to Tiki documentation. You can specify a Help URL that contains customized help pages. By default, the Help system uses http://doc.tiki.org/	
Help URL	The default help system may not be complete. You can contribute to the Tiki documentation, which is a community-edited wiki.	

General - Navigation

Option	Description	Default
SmartMenus	Add "SmartMenus" to Bootstrap menus. See smartmenus.org for more.	
Menu user levels	Enables control of the per-group visibility of menu options	
Featured links	A simple menu system to display external web pages in a new browser tab or an iframe within the site, etc.	
Use folder icons for menu section (parent) items	When a menu isn't set as a Bootstrap or CSS menu, use folder icons for menu section items (rather than plus/minus signs).	
Menu icons	Allows icons to be defined for menu entries	
Default path for the icons		
Edit menu icon	Adds an icon on the navbar to edit menu entries	
Use group homepages	Users can be directed to different pages upon logging in, depending on their default group.	
Go to the group homepage only if logging in from the default homepage		
Use the top page of a Tiki feature as the homepage	Select the Tiki feature to provide the site homepage. Only enabled features are listed.	
Use custom homepage	Use the top page of a Tiki feature or another homepage <i>This option will override the Use Tiki feature as homepage setting.</i>	
Homepage URL		

Option	Description	Default
Homepage Browser title	Customize Browser title for the custom homepage	
Wiki homepage	The default home page of the wiki when no other page is specified. The page will be created if it does not already exist.	
Home blog (main blog)		
Home forum (main forum)		
Home file gallery (main file gallery)	Select the default file gallery	
Domain prefix handling	Strip or automatically add the "www." prefix on domain names to standardize URLs.	
Domain redirects	When the site is accessed through specific domain names, redirect to an alternate domain preserving the URL. Useful for domain name transitions, like tikiwiki.org to tiki.org. <i>One entry per line, with each entry a comma-separated list: old domain, new domain</i>	
Redirect on error	On an error, refresh to the homepage as specified on the Admin General page.	
Redirect to similar wiki page	If a requested page doesn't exist, redirect to a similarly named page	
On permission denied, display login module	If an anonymous visitor attempts to access a page for which permission is not granted, Tiki will automatically display the Log-in module. Alternatively, use the Send to URL field to display a specific page (relative to your Tiki installation) instead.	
Send to URL The URL that the anonymous user is redirected to when a page is not found	URL to redirect to on "permission denied"	
URL the user is redirected to after account validation	The default page a Registered user sees after account validation is "tiki-information.php?msg=Account validated successfully". <i>Default: tiki-information.php?msg=Account validated successfully.</i>	
Alternate registration page	Enter URL of a custom registration page. Tiki will automatically redirect default registration page (tiki-register.php) to this page.	
URL Suffix Cleaner	When the requested page does not exist, tests removing 1 or 2 of the last characters from the URL to see if it gets an existing page.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId= <i>(Use for login name and No value assigned for userId)</i>	
Sitemap protocol	Allows generating site maps based on the Sitemap protocol, in the form of XML documents. Mostly used to facilitate indexation of a site by web search engines.	

Option	Description	Default
Close site	Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	
Title Message		
Close site when server load is above the threshold	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	
Maximum average server load threshold in the last minute		
Site Busy Title		
Site Busy Message		
Breadcrumbs	Indicates the navigation path through parent pages to the current page. <i>Unmaintained feature</i>	
Prefix breadcrumbs with "Location : "	Place the term "Location:" in the breadcrumbs.	
Site location bar		
Larger font		
Use page description		
Namespace	Enable namespaces feature for wiki pages.	
Namespace separator	Select the character, symbol, or text to use as the namespace separator.	
Hide namespace indicator in structure path	Hide namespace indicator in structure path. <i>Useful to avoid conflicts with C++ scope operators or default namespace separator</i>	
Center text using instead of		
Page name display stripper	The character(s) to use as a delimiter in the page name. The portion of the name after the character(s) will not be displayed. If the page name display stripper conflicts with the namespace separator, the namespace is used and the page name display is not stripped.	
Option	Description	Default
SmartMenus	Add "SmartMenus" to Bootstrap menus. See smartmenus.org for more.	

Option	Description	Default
Menu user levels	Enables control of the per-group visibility of menu options	
Featured links	A simple menu system to display external web pages in a new browser tab or an iframe within the site, etc.	
Use folder icons for menu section (parent) items	When a menu isn't set as a Bootstrap or CSS menu, use folder icons for menu section items (rather than plus/minus signs).	
Menu icons	Allows icons to be defined for menu entries	
Default path for the icons		
Edit menu icon	Adds an icon on the navbar to edit menu entries	
Use group homepages	Users can be directed to different pages upon logging in, depending on their default group.	
Go to the group homepage only if logging in from the default homepage		
Use the top page of a Tiki feature as the homepage	Select the Tiki feature to provide the site homepage. Only enabled features are listed.	
Use custom homepage	Use the top page of a Tiki feature or another homepage <i>This option will override the Use Tiki feature as homepage setting.</i>	
Homepage URL		
Homepage Browser title	Customize Browser title for the custom homepage	
Wiki homepage	The default home page of the wiki when no other page is specified. The page will be created if it does not already exist.	
Home blog (main blog)		
Home forum (main forum)		
Home file gallery (main file gallery)	Select the default file gallery	
Domain prefix handling	Strip or automatically add the "www." prefix on domain names to standardize URLs.	
Domain redirects	When the site is accessed through specific domain names, redirect to an alternate domain preserving the URL. Useful for domain name transitions, like tikiwiki.org to tiki.org. <i>One entry per line, with each entry a comma-separated list: old domain, new domain</i>	
Redirect on error	On an error, refresh to the homepage as specified on the Admin General page.	
Redirect to similar wiki page	If a requested page doesn't exist, redirect to a similarly named page	

Option	Description	Default
On permission denied, display login module	If an anonymous visitor attempts to access a page for which permission is not granted, Tiki will automatically display the Log-in module. Alternatively, use the Send to URL field to display a specific page (relative to your Tiki installation) instead.	
Send to URL The URL that the anonymous user is redirected to when a page is not found	URL to redirect to on "permission denied"	
URL the user is redirected to after account validation	The default page a Registered user sees after account validation is "tiki-information.php?msg=Account validated successfully". <i>Default: tiki-information.php?msg=Account validated successfully.</i>	
Alternate registration page	Enter URL of a custom registration page. Tiki will automatically redirect default registration page (tiki-register.php) to this page.	
URL Suffix Cleaner	When the requested page does not exist, tests removing 1 or 2 of the last characters from the URL to see if it gets an existing page.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId=No value assigned (<i>Use No value assigned for login name and No value assigned for userId</i>)	
Sitemap protocol	Allows generating site maps based on the Sitemap protocol, in the form of XML documents. Mostly used to facilitate indexation of a site by web search engines.	
Close site	Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	
Title Message		
Close site when server load is above the threshold	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	
Maximum average server load threshold in the last minute		
Site Busy Title		
Site Busy Message		

Option	Description	Default
Breadcrumbs	Indicates the navigation path through parent pages to the current page. <i>Unmaintained feature</i>	
Prefix breadcrumbs with "Location :",	Place the term "Location:" in the breadcrumbs.	
Site location bar		
Larger font		
Use page description		
Namespace	Enable namespaces feature for wiki pages.	
Namespace separator	Select the character, symbol, or text to use as the namespace separator.	
Hide namespace indicator in structure path	Hide namespace indicator in structure path.	
Center text using <code><div style="text-align: center;"></code> instead of <code><div style="text-align: center; width: 100%;"></code>	<i>Useful to avoid conflicts with C++ scope operators or default namespace separator</i>	
Page name display stripper	The character(s) to use as a delimiter in the page name. The portion of the name after the character(s) will not be displayed. If the page name display stripper conflicts with the namespace separator, the namespace is used and the page name display is not stripped.	

Option	Description	Default
SmartMenus	Add "SmartMenus" to Bootstrap menus. See smartmenus.org for more.	
Menu user levels	Enables control of the per-group visibility of menu options	
Featured links	A simple menu system to display external web pages in a new browser tab or an iframe within the site, etc.	
Use folder icons for menu section (parent) items	When a menu isn't set as a Bootstrap or CSS menu, use folder icons for menu section items (rather than plus/minus signs).	
Menu icons	Allows icons to be defined for menu entries	
Default path for the icons		
Edit menu icon	Adds an icon on the navbar to edit menu entries	
Use group homepages	Users can be directed to different pages upon logging in, depending on their default group.	
Go to the group homepage only if logging in from the default homepage		

Option	Description	Default
Use the top page of a Tiki feature as the homepage	Select the Tiki feature to provide the site homepage. Only enabled features are listed.	
Use custom homepage	Use the top page of a Tiki feature or another homepage <i>This option will override the Use Tiki feature as homepage setting.</i>	
Homepage URL		
Homepage Browser title	Customize Browser title for the custom homepage	
Wiki homepage	The default home page of the wiki when no other page is specified. The page will be created if it does not already exist.	
Home blog (main blog)		
Home forum (main forum)		
Home file gallery (main file gallery)	Select the default file gallery	
Domain prefix handling	Strip or automatically add the "www." prefix on domain names to standardize URLs.	
Domain redirects	When the site is accessed through specific domain names, redirect to an alternate domain preserving the URL. Useful for domain name transitions, like tikiwiki.org to tiki.org. <i>One entry per line, with each entry a comma-separated list: old domain, new domain</i>	
Redirect on error	On an error, refresh to the homepage as specified on the Admin General page.	
Redirect to similar wiki page	If a requested page doesn't exist, redirect to a similarly named page	
On permission denied, display login module	If an anonymous visitor attempts to access a page for which permission is not granted, Tiki will automatically display the Log-in module. Alternatively, use the Send to URL field to display a specific page (relative to your Tiki installation) instead.	
Send to URL	URL to redirect to on "permission denied"	
The URL that the anonymous user is redirected to when a page is not found		
URL the user is redirected to after account validation	The default page a Registered user sees after account validation is "tiki-information.php?msg=Account validated successfully". <i>Default: tiki-information.php?msg=Account validated successfully.</i>	
Alternate registration page	Enter URL of a custom registration page. Tiki will automatically redirect default registration page (tiki-register.php) to this page.	
URL Suffix Cleaner	When the requested page does not exist, tests removing 1 or 2 of the last characters from the URL to see if it gets an existing page.	

Option	Description	Default
URL Fragment Guesser	Scroll to the closest anchor when the one indicated in the URL is missing in a page.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId=No value assigned (<i>Use No value assigned for login name and No value assigned for userId</i>)	
Sitemap protocol	Allows generating site maps based on the Sitemap protocol, in the form of XML documents. Mostly used to facilitate indexation of a site by web search engines.	
Close site	Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	
Title		
Message		
Close site when server load is above the threshold	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	
Maximum average server load threshold in the last minute		
Site Busy Title		
Site Busy Message		
Breadcrumbs	Indicates the navigation path through parent pages to the current page. <i>Unmaintained feature</i>	
Prefix breadcrumbs with "Location :"	Place the term "Location:" in the breadcrumbs.	
Site location bar		
Larger font		
Use page description		
Namespace	Enable namespaces feature for wiki pages.	
Namespace separator	Select the character, symbol, or text to use as the namespace separator.	
Hide namespace indicator in structure path	Hide namespace indicator in structure path.	
Center text using instead of	<i>Useful to avoid conflicts with C++ scope operators or default namespace separator</i>	

Option	Description	Default
Page name display stripper	The character(s) to use as a delimiter in the page name. The portion of the name after the character(s) will not be displayed. If the page name display stripper conflicts with the namespace separator, the namespace is used and the page name display is not stripped.	

Option	Description	Default
SmartMenus	Add "SmartMenus" to Bootstrap menus. See smartmenus.org for more.	
CSS menus	Use CSS-styled (Suckerfish) vertical and horizontal menus.	
Superfish	Adds animation effects to CSS "Suckerfish" menus.	
Menu user levels	Enables control of the per-group visibility of menu options	
Featured links	A simple menu system to display external web pages in a new browser tab or an iframe within the site, etc.	
Use folder icons for menu section (parent) items	When a menu isn't set as a Bootstrap or CSS menu, use folder icons for menu section items (rather than plus/minus signs).	
Menu icons	Allows icons to be defined for menu entries	
Default path for the icons		
Edit menu icon	Adds an icon on the navbar to edit menu entries	
Use group homepages	Users can be directed to different pages upon logging in, depending on their default group.	
Go to the group homepage only if logging in from the default homepage		
Use the top page of a Tiki feature as the homepage	Select the Tiki feature to provide the site homepage. Only enabled features are listed.	
Use custom homepage	Use the top page of a Tiki feature or another homepage <i>This option will override the Use Tiki feature as homepage setting.</i>	
Homepage URL		
Homepage Browser title	Customize Browser title for the custom homepage	
Wiki homepage	The default home page of the wiki when no other page is specified. The page will be created if it does not already exist.	
Home blog (main blog)		
Home forum (main forum)		
Home file gallery (main file gallery)	Select the default file gallery	

Option	Description	Default
Domain prefix handling	Strip or automatically add the "www." prefix on domain names to standardize URLs.	
Domain redirects	When the site is accessed through specific domain names, redirect to an alternate domain preserving the URL. Useful for domain name transitions, like tikiwiki.org to tiki.org. <i>One entry per line, with each entry a comma-separated list: old domain, new domain</i>	
Redirect on error	On an error, refresh to the homepage as specified on the Admin General page.	
Redirect to similar wiki page	If a requested page doesn't exist, redirect to a similarly named page	
On permission denied, display login module	If an anonymous visitor attempts to access a page for which permission is not granted, Tiki will automatically display the Log-in module. Alternatively, use the Send to URL field to display a specific page (relative to your Tiki installation) instead.	
Send to URL The URL that the anonymous user is redirected to when a page is not found	URL to redirect to on "permission denied"	
URL the user is redirected to after account validation	The default page a Registered user sees after account validation is "tiki-information.php?msg=Account validated successfully". <i>Default: tiki-information.php?msg=Account validated successfully.</i>	
Alternate registration page	Enter URL of a custom registration page. Tiki will automatically redirect default registration page (tiki-register.php) to this page.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId=No value assigned (<i>Use No value assigned for login name and No value assigned for userId</i>)	
Sitemap protocol	Allows generating site maps based on the Sitemap protocol, in the form of XML documents. Mostly used to facilitate indexation of a site by web search engines.	
Close site Title Message	Use this setting to \"close\" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	
Close site when server load is above the threshold	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	

Option	Description	Default
Maximum average server load threshold in the last minute		
Site Busy Title		
Site Busy Message		
Breadcrumbs	Indicates the navigation path through parent pages to the current page. <i>Unmaintained feature</i>	
Prefix breadcrumbs with "Location : "	Place the term "Location:" in the breadcrumbs.	
Site location bar		
Larger font		
Use page description		
Namespaces	Enable namespaces feature for wiki pages.	
Namespace separator	Select the character, symbol, or text to use as the namespace separator.	
Hide namespace indicator in structure path	Hide namespace indicator in structure path.	
Center text using <code><div style="text-align:center"></code> instead of <code><div style="text-align:center"><div style="text-align:center"></code>	<i>Useful to avoid conflicts with C++ scope operators or default namespace separator</i>	
Page name display stripper	The character(s) to use as a delimiter in the page name. The portion of the name after the character(s) will not be displayed. If the page name display stripper conflicts with the namespace separator, the namespace is used and the page name display is not stripped.	

Option	Description	Default
Use CSS menus	Use CSS-styled (Suckerfish) vertical and horizontal menus.	
Superfish	Adds animation effects to CSS "Suckerfish" menus.	
Menu user levels	Enables control of the per-group visibility of menu options	
Featured links	A simple menu system to display external web pages in a new browser tab or an iframe within the site, etc.	
Use folder icons for menu section (parent) items	When a menu isn't set as a Bootstrap or CSS menu, use folder icons for menu section items (rather than plus/minus signs).	
Menu icons	Allows icons to be defined for menu entries	
Default path for the icons		
Edit menu icon	Adds an icon on the navbar to edit menu entries	

Option	Description	Default
Use group homepages	Users can be directed to different pages upon logging in, depending on their default group.	
Go to the group homepage only if logging in from the default homepage		
Use the top page of a Tiki feature as the homepage	Select the Tiki feature to provide the site homepage. Only enabled features are listed.	
Use custom homepage	Use the top page of a Tiki feature or another homepage <i>This option will override the Use Tiki feature as homepage setting.</i>	
Homepage URL		
Homepage Browser title	Customize Browser title for the custom homepage	
Wiki homepage	The default home page of the wiki when no other page is specified. The page will be created if it does not already exist.	
Home blog (main blog)		
Home forum (main forum)		
Home file gallery (main file gallery)	Select the default file gallery	
Home gallery (main gallery)		
Domain prefix handling	Strip or automatically add the "www." prefix on domain names to standardize URLs.	
Domain redirects	When the site is accessed through specific domain names, redirect to an alternate domain preserving the URL. Useful for domain name transitions, like tikiwiki.org to tiki.org. <i>One entry per line, with each entry a comma-separated list: old domain, new domain</i>	
Redirect on error	On an error, refresh to the homepage as specified on the Admin General page.	
Redirect to similar wiki page	If a requested page doesn't exist, redirect to a similarly named page	
On permission denied, display login module	If an anonymous visitor attempts to access a page for which permission is not granted, Tiki will automatically display the Log-in module. Alternatively, use the Send to URL field to display a specific page (relative to your Tiki installation) instead.	
Send to URL	URL to redirect to on "permission denied"	
The URL that the anonymous user is redirected to when a page is not found		

Option	Description	Default
URL the user is redirected to after account validation	The default page a Registered user sees after account validation is "tiki-information.php?msg=Account validated successfully". <i>Default: tiki-information.php?msg=Account validated successfully.</i>	
Alternate registration page	Enter URL of a custom registration page. Tiki will automatically redirect default registration page (tiki-register.php) to this page.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId=No value assigned (<i>Use No value assigned for login name and No value assigned for userId</i>)	
Sitemap protocol	Allows generating site maps based on the Sitemap protocol, in the form of XML documents. Mostly used to facilitate indexation of a site by web search engines.	
Close site	Use this setting to \"close\" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.	
Title		
Message		
Close site when server load is above the threshold	Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.	
Maximum average server load threshold in the last minute		
Site Busy Title		
Site Busy Message		
Breadcrumbs	Indicates the navigation path through parent pages to the current page. <i>Unmaintained feature</i>	
Prefix breadcrumbs with "Location : "	Place the term "Location:" in the breadcrumbs.	
Site location bar		
Larger font		
Use page description		
Namespace	Enable namespaces feature for wiki pages.	
Namespace separator	Select the character, symbol, or text to use as the namespace separator.	

Option	Description	Default
Hide namespace indicator in structure path	Hide namespace indicator in structure path.	
Center text using instead of	Useful to avoid conflicts with C++ scope operators or default namespace separator. <i>Useful to avoid conflicts with C++ scope operators or default namespace separator</i>	
Page name display stripper	The character(s) to use as a delimiter in the page name. The portion of the name after the character(s) will not be displayed. If the page name display stripper conflicts with the namespace separator, the namespace is used and the page name display is not stripped.	

Internationalization (i18n)

Option	Description	Default
Default language	The site language is used when no other language is specified by the user.	
Default admin language	The site language is used in admin section when no other language is specified by the user.	
Wiki link format	Level of special characters acceptable in wiki links for page names. For example: Page éâî <i>"Strict" includes only basic characters such as a-z and 0-9. A site that uses accented or special characters in page names should not use "strict".</i>	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Multilingual	Enables internationalization features and multilingual support at the site.	
Detect browser language	Look up the user's preferred language through browser preferences.	
Show pages in user's preferred language	When accessing a page which has an equivalent in the user's preferred language, favor the translated page. Based on the user's Tiki preferences.	
Users can choose the language of their interface	Allow users to change the language of the menus and labels.	
Restrict supported languages	Limit the languages made available on the site. <i>Use Ctrl+Click to select multiple languages.</i>	
Available languages	By default, all languages supported by Tiki are available on multilingual sites. This option allows limiting the languages to a subset.	
Language inclusion threshold	When the number of languages is restricted on the site, and is below this number, all languages will be added to the preferred language list, even if unspecified by the user. However, priority will be given to the specified languages.	

Option	Description	Default
Display available translations	Display list of available languages and offer to switch languages or translate. This appears on wiki pages and articles action buttons.	
Display available translations as dropdown	Instead of a simple icon to list available languages or translation options, show a more visible drop-down list.	
Synchronize page and site language	Changing the page language also changes the site language	
Restrict search language by default	Only search content that is in the interface language, otherwise show the language menu.	
Translation assistant	Track translation operations between pages.	
Urgent translation notifications	Enable changes to be flagged as urgent, so translations are marked with a notice visible to all users.	
Incomplete translation notice	When a page is translated to a new language, a notice will automatically be inserted into the page to indicate that the translation is not yet complete.	
Display all languages in a single page	List all languages as options in the page-language dropdown list, to see them all at once.	
Quantify change size	In addition to tracking the changes, track the change size and display approximately how up-to-date the page is.	
Allow minor edits of wiki pages	Minor edits don't flag new content for translation and don't cause watch notifications to be sent (unless "Watch minor edits" is enabled).	
User watches translations		
Multilingual structures	Structures search for equivalent pages in other languages. <i>May cause performance problems with larger structures.</i>	
Multilingual tags	Permits translation management of tags	
Synchronize multilingual categories	Make sure that the categories of the translations are synchronized when modified on any version.	
Synchronized categories	List of categories affected by the multilingual synchronization. Depending on the parent feature, this list will be used as a white list (the only categories allowed) or as a black list (all categories allowed except those specified).	
Multilingual dynamic variables	Make dynamic variable content language-specific.	
Plugin Translate	Translate text to the user language	
Plugin Language	Show alternative content based on the page language	
Plugin Translated	Create multilingual links	
Use database for translation	Use the database to store the translated strings and allow using interactive translation <i>Edit, export and import languages</i>	

Option	Description	Default
Manage contribution of translated strings	Offers to set whether each translated string should be contributed to the Tiki community or kept locally	
Record untranslated strings	Keep track of the unsuccessful attempts to translate strings.	
Machine translation	Uses machine translation to translate the content of the site to other languages. Note that this feature relies on external services that may not be free. Google Translate is a paid service.	
Machine translation implementation	Select between alternate implementations for machine translation. Depending on the implementation, different API keys may be required.	
Google Translate API Key	The key must be generated from the Google console. Choose to create a server key.	
Bing Translate Client ID	The application must be registered.	
Bing Translate Client Secret	The application must be registered.	
Enable machine translation of wiki pages	Makes additional languages available to the list of languages on the page.	
Certain pages redirect to homepage when language is changed		
List of pages that redirect	List of names of pages that always redirect to the homepage when the language is switched <i>Separate page names by commas</i>	
Option	Description	Default
Default language	The site language is used when no other language is specified by the user.	
Default admin language	The site language is used in admin section when no other language is specified by the user.	
Wiki link format	Level of special characters acceptable in wiki links for page names. For example: Page éâ <i>"Strict" includes only basic characters such as a-z and 0-9. A site that uses accented or special characters in page names should not use "strict".</i>	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Multilingual	Enables internationalization features and multilingual support at the site.	
Detect browser language	Look up the user's preferred language through browser preferences.	
Show pages in user's preferred language	When accessing a page which has an equivalent in the user's preferred language, favor the translated page. Based on the user's Tiki preferences.	
Users can choose the language of their interface	Allow users to change the language of the menus and labels.	
Restrict supported languages	Limit the languages made available on the site. <i>Use Ctrl+Click to select multiple languages.</i>	

Option	Description	Default
Available languages	By default, all languages supported by Tiki are available on multilingual sites. This option allows limiting the languages to a subset.	
Language inclusion threshold	When the number of languages is restricted on the site, and is below this number, all languages will be added to the preferred language list, even if unspecified by the user. However, priority will be given to the specified languages.	
Display available translations	Display list of available languages and offer to switch languages or translate. This appears on wiki pages and articles action buttons.	
Display available translations as dropdown	Instead of a simple icon to list available languages or translation options, show a more visible drop-down list.	
Synchronize page and site language	Changing the page language also changes the site language	
Restrict search language by default	Only search content that is in the interface language, otherwise show the language menu.	
Translation assistant	Track translation operations between pages.	
Urgent translation notifications	Enable changes to be flagged as urgent, so translations are marked with a notice visible to all users.	
Incomplete translation notice	When a page is translated to a new language, a notice will automatically be inserted into the page to indicate that the translation is not yet complete.	
Display all languages in a single page	List all languages as options in the page-language dropdown list, to see them all at once.	
Quantify change size	In addition to tracking the changes, track the change size and display approximately how up-to-date the page is.	
Allow minor edits of wiki pages	Minor edits don't flag new content for translation and don't cause watch notifications to be sent (unless "Watch minor edits" is enabled).	
User watches translations		
Multilingual structures	Structures search for equivalent pages in other languages. <i>May cause performance problems with larger structures.</i>	
Multilingual tags	Permits translation management of tags	
Synchronize multilingual categories	Make sure that the categories of the translations are synchronized when modified on any version.	
Synchronized categories	List of categories affected by the multilingual synchronization. Depending on the parent feature, this list will be used as a white list (the only categories allowed) or as a black list (all categories allowed except those specified).	
Multilingual dynamic variables	Make dynamic variable content language-specific.	
Plugin Translate	Translate text to the user language	

Option	Description	Default
Plugin Language	Show alternative content based on the page language	
Plugin Translated	Create multilingual links	
Use database for translation	Use the database to store the translated strings and allow using interactive translation <i>Edit, export and import languages</i>	
Manage contribution of translated strings	Offers to set whether each translated string should be contributed to the Tiki community or kept locally	
Record untranslated strings	Keep track of the unsuccessful attempts to translate strings.	
Machine translation	Uses machine translation to translate the content of the site to other languages. Note that this feature relies on external services that may not be free. Google Translate is a paid service.	
Machine translation implementation	Select between alternate implementations for machine translation. Depending on the implementation, different API keys may be required.	
Google Translate API Key	The key must be generated from the Google console. Choose to create a server key.	
Bing Translate Client ID	The application must be registered.	
Bing Translate Client Secret	The application must be registered.	
Enable machine translation of wiki pages	Makes additional languages available to the list of languages on the page.	
Certain pages redirect to homepage when language is changed		
List of pages that redirect	List of names of pages that always redirect to the homepage when the language is switched <i>Separate page names by commas</i>	

Option	Description	Default
Default language	The site language is used when no other language is specified by the user.	
Default admin language	The site language is used in admin section when no other language is specified by the user.	
Wiki link format	Level of special characters acceptable in wiki links for page names. For example: Page éâ <i>"Strict" includes only basic characters such as a-z and 0-9. A site that uses accented or special characters in page names should not use "strict".</i>	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Multilingual	Enables internationalization features and multilingual support at the site.	
Detect browser language	Look up the user's preferred language through browser preferences.	
Show pages in user's preferred language	When accessing a page which has an equivalent in the user's preferred language, favor the translated page. Based on the user's Tiki preferences.	

Option	Description	Default
Users can choose the language of their interface	Allow users to change the language of the menus and labels.	
Restrict supported languages	Limit the languages made available on the site. <i>Use Ctrl+Click to select multiple languages.</i>	
Available languages	By default, all languages supported by Tiki are available on multilingual sites. This option allows limiting the languages to a subset.	
Language inclusion threshold	When the number of languages is restricted on the site, and is below this number, all languages will be added to the preferred language list, even if unspecified by the user. However, priority will be given to the specified languages.	
Display available translations	Display list of available languages and offer to switch languages or translate. This appears on wiki pages and articles action buttons.	
Display available translations as dropdown	Instead of a simple icon to list available languages or translation options, show a more visible drop-down list.	
Synchronize page and site language	Changing the page language also changes the site language	
Restrict search language by default	Only search content that is in the interface language, otherwise show the language menu.	
Translation assistant	Track translation operations between pages.	
Urgent translation notifications	Enable changes to be flagged as urgent, so translations are marked with a notice visible to all users.	
Incomplete translation notice	When a page is translated to a new language, a notice will automatically be inserted into the page to indicate that the translation is not yet complete.	
Display all languages in a single page	List all languages as options in the page-language dropdown list, to see them all at once.	
Quantify change size	In addition to tracking the changes, track the change size and display approximately how up-to-date the page is.	
Allow minor edits of wiki pages	Minor edits don't flag new content for translation and don't cause watch notifications to be sent (unless "Watch minor edits" is enabled).	
User watches translations		
Multilingual structures	Structures search for equivalent pages in other languages. <i>May cause performance problems with larger structures.</i>	
Multilingual tags	Permits translation management of tags	
Synchronize multilingual categories	Make sure that the categories of the translations are synchronized when modified on any version.	

Option	Description	Default
Synchronized categories	List of categories affected by the multilingual synchronization. Depending on the parent feature, this list will be used as a white list (the only categories allowed) or as a black list (all categories allowed except those specified).	
Multilingual dynamic variables	Make dynamic variable content language-specific.	
Plugin Translate	Translate text to the user language	
Plugin Language	Show alternative content based on the page language	
Plugin Translated	Create multilingual links	
Use database for translation	Use the database to store the translated strings and allow using interactive translation <i>Edit, export and import languages</i>	
Manage contribution of translated strings	Offers to set whether each translated string should be contributed to the Tiki community or kept locally	
Record untranslated strings	Keep track of the unsuccessful attempts to translate strings.	
Machine translation	Uses machine translation to translate the content of the site to other languages. Note that this feature relies on external services that may not be free. Google Translate is a paid service.	
Machine translation implementation	Select between alternate implementations for machine translation. Depending on the implementation, different API keys may be required.	
Google Translate API Key	The key must be generated from the Google console. Choose to create a server key.	
Bing Translate Client ID	The application must be registered.	
Bing Translate Client Secret	The application must be registered.	
Enable machine translation of wiki pages	Makes additional languages available to the list of languages on the page.	
Certain pages redirect to homepage when language is changed		
List of pages that redirect	List of names of pages that always redirect to the homepage when the language is switched <i>Separate page names by commas</i>	

Option	Description	Default
Default language	The site language is used when no other language is specified by the user.	
Default admin language	The site language is used in admin section when no other language is specified by the user.	
Wiki link format	Level of special characters acceptable in wiki links for page names. For example: Page éâî <i>"Strict" includes only basic characters such as a-z and 0-9. A site that uses accented or special characters in page names should not use "strict".</i>	

Option	Description	Default
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Multilingual	Enables internationalization features and multilingual support at the site.	
Detect browser language	Look up the user's preferred language through browser preferences.	
Show pages in user's preferred language	When accessing a page which has an equivalent in the user's preferred language, favor the translated page. Based on the user's Tiki preferences.	
Users can choose the language of their interface	Allow users to change the language of the menus and labels.	
Restrict supported languages	Limit the languages made available on the site. <i>Use Ctrl+Click to select multiple languages.</i>	
Available languages	By default, all languages supported by Tiki are available on multilingual sites. This option allows limiting the languages to a subset.	
Language inclusion threshold	When the number of languages is restricted on the site, and is below this number, all languages will be added to the preferred language list, even if unspecified by the user. However, priority will be given to the specified languages.	
Display available translations	Display list of available languages and offer to switch languages or translate. This appears on wiki pages and articles action buttons.	
Display available translations as dropdown	Instead of a simple icon to list available languages or translation options, show a more visible drop-down list.	
Synchronize page and site language	Changing the page language also changes the site language	
Restrict search language by default	Only search content that is in the interface language, otherwise show the language menu.	
Translation assistant	Track translation operations between pages.	
Urgent translation notifications	Enable changes to be flagged as urgent, so translations are marked with a notice visible to all users.	
Incomplete translation notice	When a page is translated to a new language, a notice will automatically be inserted into the page to indicate that the translation is not yet complete.	
Display all languages in a single page	List all languages as options in the page-language dropdown list, to see them all at once.	
Quantify change size	In addition to tracking the changes, track the change size and display approximately how up-to-date the page is.	
Allow minor edits of wiki pages	Minor edits don't flag new content for translation and don't cause watch notifications to be sent (unless "Watch minor edits" is enabled).	
User watches translations		

Option	Description	Default
Multilingual structures	Structures search for equivalent pages in other languages. <i>May cause performance problems with larger structures.</i>	
Multilingual tags	Permits translation management of tags	
Synchronize multilingual categories	Make sure that the categories of the translations are synchronized when modified on any version.	
Synchronized categories	List of categories affected by the multilingual synchronization. Depending on the parent feature, this list will be used as a white list (the only categories allowed) or as a black list (all categories allowed except those specified).	
Multilingual dynamic variables	Make dynamic variable content language-specific.	
Plugin Translate	Translate text to the user language	
Plugin Language	Show alternative content based on the page language.	
Plugin Translated	Create multilingual links	
Use database for translation	Use the database to store the translated strings and allow using interactive translation <i>Edit, export and import languages</i>	
Manage contribution of translated strings	Offers to set whether each translated string should be contributed to the Tiki community or kept locally	
Record untranslated strings	Keep track of the unsuccessful attempts to translate strings.	
Machine translation	Uses machine translation to translate the content of the site to other languages. Note that this feature relies on external services that may not be free. Google Translate is a paid service.	
Machine translation implementation	Select between alternate implementations for machine translation. Depending on the implementation, different API keys may be required.	
Google Translate API Key	The key must be generated from the Google console. Choose to create a server key.	
Bing Translate Client ID	The application must be registered.	
Bing Translate Client Secret	The application must be registered.	
Enable machine translation of wiki pages	Makes additional languages available to the list of languages on the page.	
Certain pages redirect to homepage when language is changed		
List of pages that redirect	List of names of pages that always redirect to the homepage when the language is switched <i>Separate page names by commas</i>	

Option	Description	Default
Default language	The site language is used when no other language is specified by the user.	

Option	Description	Default
Default admin language	The site language is used in admin section when no other language is specified by the user.	
Wiki link format	Level of special characters acceptable in wiki links for page names. For example: Page éàî <i>"Strict" includes only basic characters such as a-z and 0-9. A site that uses accented or special characters in page names should not use "strict".</i>	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Multilingual	Enables internationalization features and multilingual support at the site.	
Detect browser language	Look up the user's preferred language through browser preferences.	
Show pages in user's preferred language	When accessing a page which has an equivalent in the user's preferred language, favor the translated page. Based on the user's Tiki preferences.	
Users can choose the language of their interface	Allow users to change the language of the menus and labels.	
Restrict supported languages	Limit the languages made available on the site. <i>Use Ctrl+Click to select multiple languages.</i>	
Available languages	By default, all languages supported by Tiki are available on multilingual sites. This option allows limiting the languages to a subset.	
Language inclusion threshold	When the number of languages is restricted on the site, and is below this number, all languages will be added to the preferred language list, even if unspecified by the user. However, priority will be given to the specified languages.	
Display available translations	Display list of available languages and offer to switch languages or translate. This appears on wiki pages and articles action buttons.	
Display available translations as dropdown	Instead of a simple icon to list available languages or translation options, show a more visible drop-down list.	
Synchronize page and site language	Changing the page language also changes the site language	
Restrict search language by default	Only search content that is in the interface language, otherwise show the language menu.	
Translation assistant	Track translation operations between pages.	
Urgent translation notifications	Enable changes to be flagged as urgent, so translations are marked with a notice visible to all users.	
Incomplete translation notice	When a page is translated to a new language, a notice will automatically be inserted into the page to indicate that the translation is not yet complete.	
Display all languages in a single page	List all languages as options in the page-language dropdown list, to see them all at once.	

Option	Description	Default
Quantify change size	In addition to tracking the changes, track the change size and display approximately how up-to-date the page is.	
Allow minor edits of wiki pages	Minor edits don't flag new content for translation and don't cause watch notifications to be sent (unless "Watch minor edits" is enabled).	
User watches translations		
Multilingual structures	Structures search for equivalent pages in other languages. <i>May cause performance problems with larger structures.</i>	
Multilingual tags	Permits translation management of tags	
Synchronize multilingual categories	Make sure that the categories of the translations are synchronized when modified on any version.	
Synchronized categories	List of categories affected by the multilingual synchronization. Depending on the parent feature, this list will be used as a white list (the only categories allowed) or as a black list (all categories allowed except those specified).	
Multilingual dynamic variables	Make dynamic variable content language-specific.	
Plugin Translate	Translate text to the user language	
Plugin Language	Show alternative content based on the page language.	
Plugin Translated	Create multilingual links	
Use database for translation	Use the database to store the translated strings and allow using interactive translation <i>Edit, export and import languages</i>	
Manage contribution of translated strings	Offers to set whether each translated string should be contributed to the Tiki community or kept locally	
Record untranslated strings	Keep track of the unsuccessful attempts to translate strings.	
Machine translation	Uses machine translation to translate the content of the site to other languages. Note that this feature relies on external services that may not be free. Google Translate is a paid service.	
Machine translation implementation	Select between alternate implementations for machine translation. Depending on the implementation, different API keys may be required.	
Google Translate API Key	The key must be generated from the Google console. Choose to create a server key.	
Bing Translate Client ID	The application must be registered.	
Bing Translate Client Secret	The application must be registered.	
Enable machine translation of wiki pages	Makes additional languages available to the list of languages on the page.	

Option	Description	Default
Certain pages redirect to homepage when language is changed		
List of pages that redirect	List of names of pages that always redirect to the homepage when the language is switched <i>Separate page names by commas</i>	

Intertiki -Â Client

Option	Description	Default
Intertiki	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	
Client key for this site	This must match the shared key entered in the Master's key field.	
Intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. <i>The remember me login feature must be on.</i>	
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. <i>Overrides manually registered local users</i>	
Import user preferences	Client Tiki will copy the user preferences from the master server. <i>This will overwrite local user preferences every time the user logs in.</i>	
Import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). <i>This will overwrite local groups every time a user logs in.</i>	
Limit group import	This list will limit the group import feature to only those groups listed here. <i>Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.</i>	

Option	Description	Default
Intertiki	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	
Client key for this site	This must match the shared key entered in the Master's key field.	
Intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. <i>The remember me login feature must be on.</i>	
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. <i>Overrides manually registered local users</i>	

Option	Description	Default
import user preferences	Client Tiki will copy the user preferences from the master server. <i>This will overwrite local user preferences every time the user logs in.</i>	
import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). <i>This will overwrite local groups every time a user logs in.</i>	
limit group import	This list will limit the group import feature to only those groups listed here. <i>Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.</i>	

Option	Description	Default
intertiki	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	
Client key for this site	This must match the shared key entered in the Master's key field.	
intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. <i>The remember me login feature must be on.</i>	
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. <i>Overrides manually registered local users</i>	
import user preferences	Client Tiki will copy the user preferences from the master server. <i>This will overwrite local user preferences every time the user logs in.</i>	
import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). <i>This will overwrite local groups every time a user logs in.</i>	
limit group import	This list will limit the group import feature to only those groups listed here. <i>Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.</i>	

Option	Description	Default
intertiki	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	
Client key for this site	This must match the shared key entered in the Master's key field.	
intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. <i>The remember me login feature must be on.</i>	
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. <i>Overrides manually registered local users</i>	
import user preferences	Client Tiki will copy the user preferences from the master server. <i>This will overwrite local user preferences every time the user logs in.</i>	

Option	Description	Default
import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). <i>This will overwrite local groups every time a user logs in.</i>	
limit group import	This list will limit the group import feature to only those groups listed here. <i>Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.</i>	
Option	Description	Default
intertiki	Allows several Tiki sites (slaves) to get authentication from a master Tiki site	
Client key for this site	This must match the shared key entered in the Master's key field.	
intertiki shared cookie	Causes a user who logs into or out of either the slave or master site to be automatically logged into or out of all other sites. <i>The remember me login feature must be on.</i>	
Master Tiki server	Master Tiki server that this client will obtain user authorizations from. <i>Overrides manually registered local users</i>	
import user preferences	Client Tiki will copy the user preferences from the master server. <i>This will overwrite local user preferences every time the user logs in.</i>	
import user groups	Groups the user belongs to on the master server will be imported (along with their security definitions). <i>This will overwrite local groups every time a user logs in.</i>	
limit group import	This list will limit the group import feature to only those groups listed here. <i>Comma-separated list of case-sensitive imported groups. Leave empty to avoid limitation.</i>	

Intertiki - Master server

Option	Description	Default
This site is a master server		
Access log file	location, from your tiki root dir, where you want the access log file stored.	
Errors log file	location, from your tiki root dir, where you want the error log file stored	
Option	Description	Default
This site is a master server		
Access log file	location, from your tiki root dir, where you want the access log file stored.	
Errors log file	location, from your tiki root dir, where you want the error log file stored	

Option	Description	Default
This site is a master server		
Access log file	location, from your tiki root dir, where you want the access log file stored.	
Errors log file	location, from your tiki root dir, where you want the error log file stored	
Option	Description	Default
This site is a master server		
Access log file	location, from your tiki root dir, where you want the access log file stored.	
Errors log file	location, from your tiki root dir, where you want the error log file stored	
Option	Description	Default
This site is a master server		
Access log file	location, from your tiki root dir, where you want the access log file stored.	
Errors log file	location, from your tiki root dir, where you want the error log file stored	