

# Textarea editing - General settings

Option	Description	Default
Full screen	Allow users to activate full-screen mode.	
Use file galleries to store images	If not enabled, images will be stored in the file system, in the /img/wiki_up directory, instead.	
Dynamic content system	Block of content which can be reused and programmed (timed)	
Search and replace	Enables finding and replacing of content in the edit box	
Code editor (CodeMirror)	CodeMirror code editor, which provides syntax highlighting	
Syntax highlighter (CodeMirror) Theme	CodeMirror themes (clear cache after changing)	
Full WYSIWYG editor	WYSIWYG is an acronym for "What You See Is What You Get". CKEditor is used to provide a word-processor-like editing experience.	
Ajax auto-save	Save content during editing, enabling work to be recovered after any interruption. Also enable a real-time preview. This option is required for WYSIWYG plugin processing.	
Preview Edits	Add a preview tab to text areas.	
Smileys	Also known as emoticons	
Wiki paragraph formatting	When the wiki paragraph formatting feature is on, all groups of non-blank lines are collected into paragraphs. Lines can be of any length, and will be wrapped together with the next line. Paragraphs are separated by blank lines. When the Wiki paragraph formatting feature is off, each line will be presented as you write it. This means that if you want paragraphs to be wrapped properly, a paragraph should be all together on one line.	
Create line breaks within paragraphs	When Wiki paragraph formatting is enabled, this option creates line breaks within paragraphs.	
Parse wiki syntax in comments	Parse wiki syntax in comments in all sections apart from Forums Use "Accept wiki syntax" for forums in admin forums page	
Automonospaced text	Lines indented with spaces will automatically be converted to monospace font.	

Option	Description	Default
variables syntax	<p>for rows &lt;return&gt; for rows Wiki argument variables Allow writing request variables in wiki content using or - special case Preferences - Text editing to Users Dynamic variables Global snippets of text that can be included in wiki pages and edited in place. Single () Double (%No value assigned%) Multilingual dynamic variables Make dynamic variable content language-specific. Multilevel style numbering for ordered lists Make ordered list items display unique numbers for all levels of their sub-items; for example: 1.1, 1.2, 1.2.1, 1.2.2, etc. Convert from absolute to relative link Process wiki text and convert internal links from absolute to relative links Markdown Support markdown syntax. Github-flavored markdown Enable Github-flavored markdown. Default syntax Which syntax to use as the default wiki syntax when a new content block is created. Markdown Enable Typography Features Features to replace normal characters with typographic equivalents Smart "straight" quotes Convert "straight" quotes to curly ones, also convert apostrophe and "single" quotes Convert approximative ASCII quotes Convert plain-ASCII quote substitutes ` ` , &lt;&lt; &gt;&gt; to their typographic equivalent œ œ ž « » Smart em-dash and ellipsis Convert double hyphen — to em-dash " and three consecutive dots . (cont.)</p>	

Option	Description	Default
	(cont'd).. to typographic ellipsis character	
	Smart no-break space Prevents line breaks from occurring at unfortunate places in the text by replacing regular space character with no-break spaces where appropriate: around some punctuation, when used as thousand separator, and between a unit abbreviation and the number preceding it. Plugin Add Bibliography Add bibliography listing in the footer of a wiki page Plugin Add Reference Add a bibliography reference. Plugin Anchor Link Create a link to an anchor Plugin Anchor Name Create an anchor that can be linked to Plugin Box Create a formatted box with a title bar Plugin Button Add a link formatted as a button Plugin Center Center text Plugin Code Display code with syntax highlighting and line numbering. Plugin Countdown Display the time until or after a date and time Plugin Div Define and format sections of a page or text Plugin Definition List Create a definition list Plugin Fade Create a link that shows/hides initially hidden content Plugin Fancy List Create a formatted numbered list Plugin Fancy Table Create a formatted table that can be filtered and sorted Plugin Font Format the font type and size of text Plugin Footnote Create automatically numbered footnotes (together with PluginFootnoteArea) Plugin Footnote Area Create automatically numbered footnotes (together with PluginFootnote) Plugin Gauge Display a horizontal bar gauge Plugin HTML Add HTML to a page Plugin Iframe Include the body of another web page in a scrollable frame within a page Plugin Include Include a portion of another wiki page Plugin Monospace Display text in a monospace font Plugin Mouseover Display hidden content by mousing over text Plugin MediaWiki Table Display a table using MediaWiki syntax Plugin Now Show the current date and time Plugin Quote Format text as a quote Plugin Remarks Box Display a comment, tip, note or warning box Plugin Scroll Show animated text that scrolls up or down Plugin Sort Sort lines of text Plugin Split Arrange content on a page into rows and columns Plugin Superscript Apply superscript font to text Plugin Subscript Apply subscript font to text Plugin Tabs Arrange content in tabs Plugin Tag Apply an HTML tag to content Plugin Table of Contents (Structure) Display a table of contents of pages in a structure Plugin Versions Create tabs for showing alternate versions of content Plugin Show Preference Display the value of public global preferences Plugin CasperJS Enable running CasperJS scripts from this Tiki site.	

**ption**

**Description**

**Default**

(cont'd) Plugin Countdown Display the time until or after a date and time Plugin Div Define and format sections of a page or text Plugin Definition List Create a definition list Plugin Fade Create a link that shows/hides initially hidden content Plugin Fancy List Create a formatted numbered list Plugin Fancy Table Create a formatted table that can be filtered and sorted Plugin Font Format the font type and size of text Plugin Footnote Create automatically numbered footnotes (together with PluginFootnoteArea) Plugin Footnote Area Create automatically numbered footnotes (together with PluginFootnote) Plugin Gauge Display a horizontal bar gauge Plugin HTML Add HTML to a page Plugin Iframe Include the body of another web page in a scrollable frame within a page Plugin Include Include a portion of another wiki page Plugin Monospace Display text in a monospace font Plugin Mouseover Display hidden content by mousing over text Plugin MediaWiki Table Display a table using MediaWiki syntax Plugin Now Show the current date and time Plugin Quote Format text as a quote Plugin Remarks Box Display a comment, tip, note or warning box Plugin Scroll Show animated text that scrolls up or down Plugin Sort Sort lines of text Plugin Split Arrange content on a page into rows and columns Plugin Superscript Apply superscript font to text Plugin Subscript Apply subscript font to text Plugin Tabs Arrange content in tabs Plugin Tag Apply an HTML tag to content Plugin Table of Contents (Structure) Display a table of contents of pages in a structure Plugin Versions Create tabs for showing alternate versions of content Plugin Show Preference Display the value of public global preferences Plugin CasperJS Enable running CasperJS scripts from this Tiki site.

ption

Description

Default

(cont'd) HTML purifier HTML Purifier is a standards-compliant HTML filter library written in PHP and integrated in Tiki. HTML Purifier will not only remove all malicious code (better known as XSS) with a thoroughly audited, secure yet permissive whitelist, it will also ensure that your documents are standards-compliant. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results. If you use HTML in your wiki page and it gets stripped out or rewritten, make sure your HTML is valid, or de-activate this feature. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results. AutoLinks Web (<http://>) and email addresses will automatically be converted to links. Hotwords Open hotwords in new window Characters that limit a hotword Use Quote plugin rather than ">" for quoting Center text using : instead of Useful to avoid conflicts with C++ scope operators or default namespace separator String to use to delimit simplebox Text string used to customise mail templates Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files Wiki Comment box Size (height) of the comment text area.

(cont'd) HTML purifier HTML Purifier is a standards-compliant HTML filter library written in PHP and integrated in Tiki. HTML Purifier will not only remove all malicious code (better known as XSS) with a thoroughly audited, secure yet permissive whitelist, it will also ensure that your documents are standards-compliant. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results. If you use HTML in your wiki page and it gets stripped out or rewritten, make sure your HTML is valid, or de-activate this feature. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results. AutoLinks Web (<http://>) and email addresses will automatically be converted to links. Hotwords Open hotwords in new window Characters that limit a hotword Use Quote plugin rather than ">" for quoting Center text using : instead of Useful to avoid conflicts with C++ scope operators or default namespace separator String to use to delimit simplebox Text string used to customise mail templates Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files Wiki Comment box Size (height) of the comment text area.

Option	Description	Default
	(cont'd) Forum Forum reply Cache external pages Cache external images External link icon External links will be identified with an icon. To customize the icon, change the "link-external" icon in the icon set. Add "rel=nofollow" to external links Nofollow is used to instruct some search engines that the link should not influence the ranking of the link's target in the search engine's index. Open external links in new window Open links to external sites in a new browser tab or window. Allow image lazy loading Allow that images are loaded in a lazy way	
ption Description Default Full screen Allow users to activate full-screen mode. Use file galleries to store images If not enabled, images will be stored in the file system, in the <code>img/wiki_up</code> directory, instead. Dynamic content system Block of content which can be reused and programmed (timed) Search and replace Enables finding and replacing of content in the edit box Code editor (CodeMirror) CodeMirror code editor, which provides syntax highlighting Syntax highlighter (CodeMirror) theme CodeMirror themes (clear cache after changing) Off (but switchable) 3024-day 3024-light ambiance ambiance-mobile base16-dark base16-light blackboard cobalt eclipse elegant erlang-dark lesser-dark mbo midnight monokai neat night paraiso-dark paraiso-light rubyblue solarized the-matrix tomorrow-night-eighties twilight vibrant-ink xq-dark xq-light Full WYSIWYG editor WYSIWYG is an acronym for "What You See Is What You Get". CKEditor is used to provide a word-processor-like editing experience. (cont.)		

Option	Description	Default
<p>cont'd) Ajax auto-save Save content during editing, enabling work to be recovered after any interruption. Also enable a real-time preview.</p> <p>his option is required for WYSIWYG plugin processing. Preview Edits Add a preview tab to text areas. Enable Vue.js Toolbar Dialogs</p> <p>Smileys Also known as emoticons Wiki</p> <p>Paragraph formatting When the wiki paragraph formatting feature is on, all groups of non-blank lines are collected into paragraphs. Lines can be of any length, and will be wrapped together with the next line. Paragraphs are separated by blank lines. When the Wiki paragraph formatting feature is off, each line will be presented as you write it. This means that if you want paragraphs to be wrapped properly, a paragraph should be all together on one line.</p> <p>Create line breaks within paragraphs When Wiki paragraph formatting is enabled, this option creates line breaks within paragraphs. Parse wiki syntax in comments Parse wiki syntax in comments in all sections apart from Forums</p> <p>Use "Accept wiki syntax" for forums in admin forums page Automonospaced text Lines indented with spaces will automatically be converted to monospace font.</p> <p>cont'd) Tables syntax for rows   &lt;return&gt; for rows</p>		
Wiki argument variables	Allow writing request variables in wiki content using or - special case Preferences - Text editing to Users	
Dynamic variables	Global snippets of text that can be included in wiki pages and edited in place.	
Multilingual dynamic variables	Make dynamic variable content language-specific.	
Multilevel style numbering for ordered lists	Make ordered list items display unique numbers for all levels of their sub-items; for example: 1.1, 1.2, 1.2.1, 1.2.2, etc.	
Convert from absolute to relative link	Process wiki text and convert internal links from absolute to relative links	
Markdown	Support markdown syntax.	
Github-flavored markdown	Enable Github-flavored markdown.	
Default syntax	Which syntax to use as the default wiki syntax when a new content block is created.	
Enable Typography Features	Features to replace normal characters with typographic equivalents	
Smart "œcurly" quotes	Convert "straight" quotes to "œcurly" ones, also convert "™" apostrophe and "single"™ quotes	
Convert approximative ASCII quotes	Convert plain-ASCII quote substitutes ` ` , , << >> to their typographic equivalent "œ œ "œž "« "»	
Smart em-dash and ellipsis	Convert double hyphen — to em-dash "œ" and three consecutive dots ... to typographic ellipsis character"œ;	

Option	Description	Default
Plugin No-Break Space	Prevents line breaks from occurring at unfortunate places in the text by replacing regular space character with no-break spaces where appropriate: around some punctuation, when used as thousand separator, and between a unit abbreviation and the number preceding it.	
Plugin Add Bibliography	Add bibliography listing in the footer of a wiki page	
Plugin Add Reference	Add a bibliography reference.	
Plugin Anchor Link	Create a link to an anchor	
Plugin Anchor Name	Create an anchor that can be linked to	
Plugin Box	Create a formatted box with a title bar	
Plugin Button	Add a link formatted as a button	
Plugin Center	Center text	
Plugin Code	Display code with syntax highlighting and line numbering.	
Plugin Countdown	Display the time until or after a date and time	
Plugin Div	Define and format sections of a page or text	
Plugin Definition List	Create a definition list	
Plugin Fade	Create a link that shows/hides initially hidden content	
Plugin Fancy List	Create a formatted numbered list	
Plugin Fancy Table	Create a formatted table that can be filtered and sorted	
Plugin Font	Format the font type and size of text	
Plugin Footnote	Create automatically numbered footnotes (together with PluginFootnoteArea)	
Plugin Footnote Area	Create automatically numbered footnotes (together with PluginFootnote)	
Plugin Gauge	Display a horizontal bar gauge	
Plugin HTML	Add HTML to a page	
Plugin Iframe	Include the body of another web page in a scrollable frame within a page	
Plugin Include	Include a portion of another wiki page	
Plugin Monospace	Display text in a monospace font	
Plugin Mouseover	Display hidden content by mousing over text	
Plugin MediaWiki Table	Display a table using MediaWiki syntax	
Plugin Now	Show the current date and time	
Plugin Quote	Format text as a quote	
Plugin Remarks Box	Display a comment, tip, note or warning box	
Plugin Scroll	Show animated text that scrolls up or down	
Plugin Sort	Sort lines of text	
Plugin Split	Arrange content on a page into rows and columns	
Plugin Superscript	Apply superscript font to text	
Plugin Subscript	Apply subscript font to text	
Plugin Tabs	Arrange content in tabs	
Plugin Tag	Apply an HTML tag to content	



Option	Description	Default
Plugin Table of Contents (Structure)	Display a table of contents of pages in a structure	
Plugin Versions	Create tabs for showing alternate versions of content	
Plugin Show Preference	Display the value of public global preferences	
Plugin CasperJS	Enable running CasperJS scripts from this Tiki site.	
HTML purifier	<p>HTML Purifier is a standards-compliant HTML filter library written in PHP and integrated in Tiki. HTML Purifier will not only remove all malicious code (better known as XSS) with a thoroughly audited, secure yet permissive whitelist, it will also ensure that your documents are standards-compliant. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results.</p> <p><i>If you use HTML in your wiki page and it gets stripped out or rewritten, make sure your HTML is valid, or de-activate this feature. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results.</i></p>	
AutoLinks	Web (http://) and email addresses will automatically be converted to links.	
Hotwords		
Open hotwords in new window		
Characters that limit a hotword		
Use Quote plugin rather than ">" for quoting		
Enter text using instead of	<i>Useful to avoid conflicts with C++ scope operators or default namespace separator</i>	
String to use to delimit simplebox		
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Wiki		
Comment box	Size (height) of the comment text area.	
Forum		
Forum reply		
Cache external pages		
Cache external images		
External link icon	External links will be identified with an icon. To customize the icon, change the "link-external" icon in the icon set.	
Add "rel=nofollow" to external links	Nofollow is used to instruct some search engines that the link should not influence the ranking of the link's target in the search engine's index.	
Open external links in new window	Open links to external sites in a new browser tab or window.	
Allow image lazy loading	Allow that images are loaded in a lazy way	

Option	Description	Default
--------	-------------	---------

Option	Description	Default
Full screen	Allow users to activate full-screen mode.	
Use file galleries to store images	If not enabled, images will be stored in the file system, in the <code>/img/wiki_up</code> directory, instead.	
Dynamic content system	Block of content which can be reused and programmed (timed)	
Search and replace	Enables finding and replacing of content in the edit box	
Code editor (CodeMirror)	CodeMirror code editor, which provides syntax highlighting	
Syntax highlighter (CodeMirror) Theme	CodeMirror themes (clear cache after changing)	
Full WYSIWYG editor	WYSIWYG is an acronym for "What You See Is What You Get". CKEditor is used to provide a word-processor-like editing experience.	
Ajax auto-save	Save content during editing, enabling work to be recovered after any interruption. Also enable a real-time preview. This option is required for WYSIWYG plugin processing.	
Preview Edits	Add a preview tab to text areas.	
Enable Vue.js Toolbar Dialogs		
Emoticons	Also known as emoticons	
Wiki paragraph formatting	When the wiki paragraph formatting feature is on, all groups of non-blank lines are collected into paragraphs. Lines can be of any length, and will be wrapped together with the next line. Paragraphs are separated by blank lines. When the Wiki paragraph formatting feature is off, each line will be presented as you write it. This means that if you want paragraphs to be wrapped properly, a paragraph should be all together on one line.	
Create line breaks within paragraphs	When Wiki paragraph formatting is enabled, this option creates line breaks within paragraphs.	
Parse wiki syntax in comments	Parse wiki syntax in comments in all sections apart from Forums Use "Accept wiki syntax" for forums in admin forums page	
Automonospaced text	Lines indented with spaces will automatically be converted to monospace font.	

Option	Description	Default
variables syntax	for rows <return> for rows Wiki argument variables Allow writing request variables in wiki content using or - special case Preferences - Text editing to Users Dynamic variables Global snippets of text that can be included in wiki pages and edited in place. Single (No value assigned) Double (%No value assigned%) Multilingual dynamic variables Make dynamic variable content language-specific. Multilevel style numbering for ordered lists Make ordered list items display unique numbers for all levels of their sub-items; for example: 1.1, 1.2, 1.2.1, 1.2.2, etc. Convert from absolute to relative link Process wiki text and convert internal links from absolute to relative links Markdown Support markdown syntax. Github-flavored markdown Enable Github-flavored markdown. Default syntax Which syntax to use as the default wiki syntax when a new content block is created. Markdown Enable Typography Features Features to replace normal characters with typographic equivalents Smart "straight" quotes ones, also convert apostrophe and quotes Convert approximative ASCII quotes Convert plain-ASCII quote substitutes ` , < > to their typographic equivalent and ellipsis Convert double hyphen — to em-dash and three consecutive dots . (cont.)	

ption	Description	Default
	<p>(cont'd).. to typographic ellipsis character&amp;#x2014; Smart no-break space Prevents line breaks from occurring at unfortunate places in the text by replacing regular space character with no-break spaces where appropriate: around some punctuation, when used as thousand separator, and between a unit abbreviation and the number preceding it. Plugin Add Bibliography Add bibliography listing in the footer of a wiki page Plugin Add Reference Add a bibliography reference. Plugin Anchor Link Create a link to an anchor Plugin Anchor Name Create an anchor that can be linked to Plugin Box Create a formatted box with a title bar Plugin Button Add a link formatted as a button Plugin Center Center text Plugin Code Display code with syntax highlighting and line numbering. Plugin Countdown Display the time until or after a date and time Plugin Div Define and format sections of a page or text Plugin Definition List Create a definition list Plugin Fade Create a link that shows/hides initially hidden content Plugin Fancy List Create a formatted numbered list Plugin Fancy Table Create a formatted table that can be filtered and sorted Plugin Font Format the font type and size of text Plugin Footnote Create automatically numbered footnotes (together with PluginFootnoteArea) Plugin Footnote Area Create automatically numbered footnotes (together with PluginFootnote) Plugin Gauge Display a horizontal bar gauge Plugin HTML Add HTML to a page Plugin Iframe Include the body of another web page in a scrollable frame within a page Plugin Include Include a portion of another wiki page Plugin Monospace Display text in a monospace font Plugin Mouseover Display hidden content by mousing over text Plugin MediaWiki Table Display a table using MediaWiki syntax Plugin Now Show the current date and time Plugin Quote Format text as a quote Plugin Remarks Box Display a comment, tip, note or warning box Plugin Scroll Show animated text that scrolls up or down Plugin Sort Sort lines of text Plugin Split Arrange content on a page into rows and columns Plugin Superscript Apply superscript font to text Plugin Subscript Apply subscript font to text Plugin Tabs Arrange content in tabs Plugin Tag Apply an HTML tag to content Plugin Table of Contents (Structure) Display a table of contents of pages in a structure Plugin Versions Create tabs for showing alternate versions of content Plugin Show Preference Display the value of public global preferences Plugin CasperJS Enable running CasperJS scripts from this Tiki site.</p>	

**ption**

**Description**

**Default**

(cont'd) Plugin Countdown Display the time until or after a date and time Plugin Div Define and format sections of a page or text Plugin Definition List Create a definition list Plugin Fade Create a link that shows/hides initially hidden content Plugin Fancy List Create a formatted numbered list Plugin Fancy Table Create a formatted table that can be filtered and sorted Plugin Font Format the font type and size of text Plugin Footnote Create automatically numbered footnotes (together with PluginFootnoteArea) Plugin Footnote Area Create automatically numbered footnotes (together with PluginFootnote) Plugin Gauge Display a horizontal bar gauge Plugin HTML Add HTML to a page Plugin Iframe Include the body of another web page in a scrollable frame within a page Plugin Include Include a portion of another wiki page Plugin Monospace Display text in a monospace font Plugin Mouseover Display hidden content by mousing over text Plugin MediaWiki Table Display a table using MediaWiki syntax Plugin Now Show the current date and time Plugin Quote Format text as a quote Plugin Remarks Box Display a comment, tip, note or warning box Plugin Scroll Show animated text that scrolls up or down Plugin Sort Sort lines of text Plugin Split Arrange content on a page into rows and columns Plugin Superscript Apply superscript font to text Plugin Subscript Apply subscript font to text Plugin Tabs Arrange content in tabs Plugin Tag Apply an HTML tag to content Plugin Table of Contents (Structure) Display a table of contents of pages in a structure Plugin Versions Create tabs for showing alternate versions of content Plugin Show Preference Display the value of public global preferences Plugin CasperJS Enable running CasperJS scripts from this Tiki site.

ption

Description

Default

(cont'd) HTML purifier HTML Purifier is a standards-compliant HTML filter library written in PHP and integrated in Tiki. HTML Purifier will not only remove all malicious code (better known as XSS) with a thoroughly audited, secure yet permissive whitelist, it will also ensure that your documents are standards-compliant. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results. If you use HTML in your wiki page and it gets stripped out or rewritten, make sure your HTML is valid, or de-activate this feature. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results. AutoLinks Web (<http://>) and email addresses will automatically be converted to links. Hotwords Open hotwords in new window Characters that limit a hotword Use Quote plugin rather than ">" for quoting Center text using : instead of Useful to avoid conflicts with C++ scope operators or default namespace separator String to use to delimit simplebox Text string used to customise mail templates Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files Wiki Comment box Size (height) of the comment text area.

(cont'd) HTML purifier HTML Purifier is a standards-compliant HTML filter library written in PHP and integrated in Tiki. HTML Purifier will not only remove all malicious code (better known as XSS) with a thoroughly audited, secure yet permissive whitelist, it will also ensure that your documents are standards-compliant. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results. If you use HTML in your wiki page and it gets stripped out or rewritten, make sure your HTML is valid, or de-activate this feature. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results. AutoLinks Web (<http://>) and email addresses will automatically be converted to links. Hotwords Open hotwords in new window Characters that limit a hotword Use Quote plugin rather than ">" for quoting Center text using : instead of Useful to avoid conflicts with C++ scope operators or default namespace separator String to use to delimit simplebox Text string used to customise mail templates Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files Wiki Comment box Size (height) of the comment text area.

Option	Description	Default
	<p>(cont'd) Forum Forum reply Cache external pages Cache external images External link icon External links will be identified with an icon. To customize the icon, change the "link-external" icon in the icon set. Add "rel=nofollow" to external links Nofollow is used to instruct some search engines that the link should not influence the ranking of the link's target in the search engine's index. Open external links in new window Open links to external sites in a new browser tab or window. Allow image lazy loading Allow that images are loaded in a lazy way</p>	
<p>ption Description Default Full screen Allow users to activate full-screen mode. Use file galleries to store images If not enabled, images will be stored in the file system, in the <code>img/wiki_up</code> directory, instead. Dynamic content system Block of content which can be reused and programmed (timed) Search and replace Enables finding and replacing of content in the edit box Code editor (CodeMirror) CodeMirror code editor, which provides syntax highlighting Syntax highlighter (CodeMirror) theme CodeMirror themes (clear cache after changing) Off (but switchable) 3024-day 3024-light ambiance ambiance-mobile base16-dark base16-light blackboard cobalt eclipse elegant erlang-dark lesser-dark mbo midnight monokai neat night paraiso-dark paraiso-light rubyblue solarized the-matrix tomorrow-night-eighties twilight vibrant-ink xq-dark xq-light Full WYSIWYG editor WYSIWYG is an acronym for "What You See Is What You Get". CKEditor is used to provide a word-processor-like editing experience. (cont.)</p>		

Option	Description	Default
<p>cont'd) Ajax auto-save Save content during editing, enabling work to be recovered after any interruption. Also enable a real-time preview.</p> <p>his option is required for WYSIWYG plugin processing. Preview Edits Add a preview tab to text areas. Smileys Also known as emoticons</p> <p>iki paragraph formatting When the wiki paragraph formatting feature is on, all groups of non-blank lines are collected into paragraphs. Lines can be of any length, and will be wrapped together with the next line. Paragraphs are separated by blank lines. When the Wiki paragraph formatting feature is off, each line will be presented as you write it. This means that if you want paragraphs to be wrapped properly, a paragraph should be all together on one line. Create line breaks within paragraphs</p> <p>hen Wiki paragraph formatting is enabled, this option creates line breaks within paragraphs. Parse wiki syntax in comments</p> <p>Parse wiki syntax in comments in all sections</p> <p>part from Forums Use "Accept wiki syntax" for forums in admin forums page Automonospaced text Lines indented with spaces will automatically be converted to monospace font.</p> <p>cont'd) Tables syntax for rows   &lt;return&gt; for rows</p>		
Wiki argument variables	Allow writing request variables in wiki content using or - special case	Preferences - Text editing to Users
Dynamic variables	Global snippets of text that can be included in wiki pages and edited in place.	
Multilingual dynamic variables	Make dynamic variable content language-specific.	
Multilevel style numbering for ordered lists	Make ordered list items display unique numbers for all levels of their sub-items; for example: 1.1, 1.2, 1.2.1, 1.2.2, etc.	
Convert from absolute to relative link	Process wiki text and convert internal links from absolute to relative links	
Enable Typography Features	Features to replace normal characters with typographic equivalents	
Smart "œcurly" quotes	Convert "straight" quotes to "œcurly" ones, also convert "™" apostrophe and "single"™ quotes	
Convert approximative ASCII quotes	Convert plain-ASCII quote substitutes ` ` , , << >> to their typographic equivalent "œ œ "œž "« "»	
Smart em-dash and ellipsis	Convert double hyphen — to em-dash "œ" and three consecutive dots ... to typographic ellipsis character"œ;	



Option	Description	Default
Plugin No-Break Space	Prevents line breaks from occurring at unfortunate places in the text by replacing regular space character with no-break spaces where appropriate: around some punctuation, when used as thousand separator, and between a unit abbreviation and the number preceding it.	
Plugin Add Bibliography	Add bibliography listing in the footer of a wiki page	
Plugin Add Reference	Add a bibliography reference.	
Plugin Anchor Link	Create a link to an anchor	
Plugin Anchor Name	Create an anchor that can be linked to	
Plugin Box	Create a formatted box with a title bar	
Plugin Button	Add a link formatted as a button	
Plugin Center	Center text	
Plugin Code	Display code with syntax highlighting and line numbering.	
Plugin Countdown	Display the time until or after a date and time	
Plugin Div	Define and format sections of a page or text	
Plugin Definition List	Create a definition list	
Plugin Fade	Create a link that shows/hides initially hidden content	
Plugin Fancy List	Create a formatted numbered list	
Plugin Fancy Table	Create a formatted table that can be filtered and sorted	
Plugin Font	Format the font type and size of text	
Plugin Footnote	Create automatically numbered footnotes (together with PluginFootnoteArea)	
Plugin Footnote Area	Create automatically numbered footnotes (together with PluginFootnote)	
Plugin Gauge	Display a horizontal bar gauge	
Plugin HTML	Add HTML to a page	
Plugin Iframe	Include the body of another web page in a scrollable frame within a page	
Plugin Include	Include a portion of another wiki page	
Plugin Monospace	Display text in a monospace font	
Plugin Mouseover	Display hidden content by mousing over text	
Plugin MediaWiki Table	Display a table using MediaWiki syntax	
Plugin Now	Show the current date and time.	
Plugin Quote	Format text as a quote	
Plugin Remarks Box	Display a comment, tip, note or warning box	
Plugin Scroll	Show animated text that scrolls up or down	
Plugin Slider	Embed a mini-slideshow of content on a page	
Plugin Sort	Sort lines of text	
Plugin Split	Arrange content on a page into rows and columns	
Plugin Superscript	Apply superscript font to text	
Plugin Subscript	Apply subscript font to text	
Plugin Tabs	Arrange content in tabs	

Option	Description	Default
Plugin Tag	Apply an HTML tag to content	
Plugin Table of Contents (Structure)	Display a table of contents of pages in a structure	
Plugin Versions	Create tabs for showing alternate versions of content	
Plugin Show Preference	Display the value of public global preferences	
Plugin CasperJS	Enable running CasperJS scripts from this Tiki site.	
HTML purifier	<p>HTML Purifier is a standards-compliant HTML filter library written in PHP and integrated in Tiki. HTML Purifier will not only remove all malicious code (better known as XSS) with a thoroughly audited, secure yet permissive whitelist, it will also ensure that your documents are standards-compliant. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results.</p> <p><i>If you use HTML in your wiki page and it gets stripped out or rewritten, make sure your HTML is valid, or de-activate this feature. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results.</i></p>	
AutoLinks	Web (http://) and email addresses will automatically be converted to links.	
Hotwords		
Open hotwords in new window		
Characters that limit a hotword		
Use Quote plugin rather than ">" for quoting		
Enter text using		
instead of	<i>Useful to avoid conflicts with C++ scope operators or default namespace separator</i>	
String to use to delimit simplebox		
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Wiki		
Comment box	Size (height) of the comment text area.	
Forum		
Forum reply		
Cache external pages		
Cache external images		
External link icon	External links will be identified with an icon. To customize the icon, change the "link-external" icon in the icon set.	
Add "rel=nofollow" to external links	Nofollow is used to instruct some search engines that the link should not influence the ranking of the link's target in the search engine's index.	
Open external links in new window	Open links to external sites in a new browser tab or window.	
Allow image lazy loading	Allow that images are loaded in a lazy way	

Option	Description	Default
Full screen	Allow users to activate full-screen mode.	
Use file galleries to store images	If not enabled, images will be stored in the file system, in the /img/wiki_up directory, instead.	
Dynamic content system	Block of content which can be reused and programmed (timed)	
Search and replace	Enables finding and replacing of content in the edit box	
Code editor (CodeMirror)	CodeMirror code editor, which provides syntax highlighting	
Syntax highlighter (CodeMirror) Theme	CodeMirror themes (clear cache after changing)	
Full WYSIWYG editor	WYSIWYG is an acronym for "What You See Is What You Get". CKEditor is used to provide a word-processor-like editing experience.	
Ajax auto-save	Save content during editing, enabling work to be recovered after any interruption. Also enable a real-time preview. This option is required for WYSIWYG plugin processing.	
Smileys	Also known as emoticons	
Wiki paragraph formatting	When the wiki paragraph formatting feature is on, all groups of non-blank lines are collected into paragraphs. Lines can be of any length, and will be wrapped together with the next line. Paragraphs are separated by blank lines. When the Wiki paragraph formatting feature is off, each line will be presented as you write it. This means that if you want paragraphs to be wrapped properly, a paragraph should be all together on one line.	
Create line breaks within paragraphs	When Wiki paragraph formatting is enabled, this option creates line breaks within paragraphs.	
Parse wiki syntax in comments	Parse wiki syntax in comments in all sections apart from Forums Use "Accept wiki syntax" for forums in admin forums page	
Automonospaced text	Lines indented with spaces will automatically be converted to monospace font.	
Tables syntax		
Wiki argument variables	Allow writing request variables in wiki content using or - special case Preferences - Text editing to Users	
Dynamic variables	Global snippets of text that can be included in wiki pages and edited in place.	
Multilingual dynamic variables	Make dynamic variable content language-specific.	
Multilevel style numbering for ordered lists	Make ordered list items display unique numbers for all levels of their sub-items; for example: 1.1, 1.2, 1.2.1, 1.2.2, etc.	
Convert from absolute to relative link	Process wiki text and convert internal links from absolute to relative links	
Enable Typography Features	Features to replace normal characters with typographic equivalents	

Option	Description	Default
Smart "curly" quotes	Convert \"straight\" quotes to "curly" ones, also convert "™" apostrophe and "single"™ quotes	
Convert approximative ASCII quotes	Convert plain-ASCII quote substitutes ``" ,, << >> to their typographic equivalent œ œ ž « »	
Smart em-dash and ellipsis	Convert double hyphen -- to em-dash " and three consecutive dots... to typographic ellipsis character!	
Smart no-break space	Prevents line breaks from occurring at unfortunate places in the text by replacing regular space character with no-break spaces where appropriate: around some punctuation, when used as thousand separator, and between a unit abbreviation and the number preceding it.	
Plugin Add Bibliography	Add bibliography listing in the footer of a wiki page	
Plugin Add Reference	Add a bibliography reference.	
Plugin Anchor Link	Create a link to an anchor	
Plugin Anchor Name	Create an anchor that can be linked to	
Plugin Box	Create a formatted box with a title bar	
Plugin Button	Add a link formatted as a button	
Plugin Center	Center text	
Plugin Code	Display code with syntax highlighting and line numbering.	
Plugin Countdown	Display the time until or after a date and time	
Plugin Div	Define and format sections of a page or text	
Plugin Definition List	Create a definition list	
Plugin Fade	Create a link that shows/hides initially hidden content	
Plugin Fancy List	Create a formatted numbered list	
Plugin Fancy Table	Create a formatted table that can be filtered and sorted	
Plugin Font	Format the font type and size of text	
Plugin Footnote	Create automatically numbered footnotes (together with PluginFootnoteArea)	
Plugin Footnote Area	Create automatically numbered footnotes (together with PluginFootnote)	
Plugin Gauge	Display a horizontal bar gauge	
Plugin HTML	Add HTML to a page	
Plugin Iframe	Include the body of another web page in a scrollable frame within a page	

Option	Description	Default
Plugin Include	Include a portion of another wiki page	
Plugin Monospace	Display text in a monospace font	
Plugin Mouseover	Display hidden content by mousing over text	
Plugin MediaWiki Table	Display a table using MediaWiki syntax	
Plugin Now	Show the current date and time.	
Plugin Quote	Format text as a quote	
Plugin Remarks Box	Display a comment, tip, note or warning box	
Plugin Scroll	Show animated text that scrolls up or down	
Plugin Slider	Embed a mini-slideshow of content on a page	
Plugin Sort	Sort lines of text	
Plugin Split	Arrange content on a page into rows and columns	
Plugin Superscript	Apply superscript font to text	
Plugin Subscript	Apply subscript font to text	
Plugin Tabs	Arrange content in tabs	
Plugin Tag	Apply an HTML tag to content	
Plugin Table of Contents (Structure)	Display a table of contents of pages in a structure	
Plugin Versions	Create tabs for showing alternate versions of content	
Plugin Show Preference	Display the value of public global preferences	
Plugin CasperJS	Enable running CasperJS scripts from this Tiki site.	
HTML purifier	HTML Purifier is a standards-compliant HTML filter library written in PHP and integrated in Tiki.	
	HTML Purifier will not only remove all malicious code (better known as XSS) with a thoroughly audited, secure yet permissive whitelist, it will also ensure that your documents are standards-compliant. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results.	
	<i>If you use HTML in your wiki page and it gets stripped out or rewritten, make sure your HTML is valid, or de-activate this feature. Keep in mind that HTML Purifier is not HTML5 compatible and may rewrite HTML5 syntax and produce unwanted results.</i>	
AutoLinks	Web ( <a href="http://">http://</a> ) and email addresses will automatically be converted to links.	
Hotwords		
Open hotwords in new window		

Option	Description	Default
Characters that limit a hotword		
Use Quote plugin rather than ">" for quoting		
Center text using instead of	Useful to avoid conflicts with C++ scope operators or default namespace separator. <i>Useful to avoid conflicts with C++ scope operators or default namespace separator</i>	
String to use to delimit simplebox		
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Wiki		
Comment box	Size (height) of the comment text area.	
Forum		
Forum reply		
Cache external pages		
Cache external images		
External link icon	External links will be identified with an icon. To customize the icon, change the "link-external" icon in the icon set.	
Add "rel=nofollow" to external links	Nofollow is used to instruct some search engines that the link should not influence the ranking of the link's target in the search engine's index.	
Open external links in new window	Open links to external sites in a new browser tab or window.	
Allow image lazy loading	Allow that images are loaded in a lazy way	

## Textarea editing - Plugins

Option	Description	Default
Automatically approve wiki-plugins on pages installed by profiles	Some wiki-plugins require admin approval before they are executable. If turned on, then all wiki-plugins that are on wiki pages created via profiles are automatically approved. <i>Make sure your profiles are not executable or editable by untrusted users.</i>	
Plugin pending approval notification	Send an email alert to users with permission to approve plugins when a plugin approval is pending	

Option	Description	Default
Default for img-fluid class used in the IMG plugin	Default option for whether an image produced with the IMG plugin has the img-fluid class - a plugin parameter allows this to be overridden	
Maximum plugin parsing passes	Affects the number of wiki plugins that can be used. The default of 500 allows for 1 plugin nested seven times, or 44 plugins nested once. A value of 1200 is required for 1 eighth level plugin. <i>Setting this to a higher value than the default of 500 may have performance implications.</i>	
Allow plugin-specific edits	Add an icon next to each plugin usage to enable editing the plugin in a popup form, without needing to edit the whole page. This feature is unavailable outside wiki pages, whether or not this preference is enabled.	
Only display focused edit icons (for sections and/or plugins) on request	Focused edit icons will only display after a per-session "Edit icons" preference is enabled. This preference is defined directly from any wiki page.	
GUI for the list plugin	Experimental GUI for the list plugin in popup plugin edit forms. (listgui)	
Plugin trackerlist converter	Button on trackerlist and trackerfilter plugins edit form to convert them to use the list plugin instead.	
Plugins tab of the textarea control panel loads with an empty list	Improve the performance of the textarea control panel by avoiding the loading of all plugins initially <i>Some plugins may not appear. When using the MySQL engine, can have problems with short plugin names (for MyISAM, those under "ft_min_word_len").</i>	

Option	Description	Default
Automatically approve wiki-plugins on pages installed by profiles	Some wiki-plugins require admin approval before they are executable. If turned on, then all wiki-plugins that are on wiki pages created via profiles are automatically approved. <i>Make sure your profiles are not executable or editable by untrusted users.</i>	
Plugin pending approval notification	Send an email alert to users with permission to approve plugins when a plugin approval is pending	
Default for img-fluid class used in the IMG plugin	Default option for whether an image produced with the IMG plugin has the img-fluid class - a plugin parameter allows this to be overridden	
Maximum plugin parsing passes	Affects the number of wiki plugins that can be used. The default of 500 allows for 1 plugin nested seven times, or 44 plugins nested once. A value of 1200 is required for 1 eighth level plugin. <i>Setting this to a higher value than the default of 500 may have performance implications.</i>	
Allow plugin-specific edits	Add an icon next to each plugin usage to enable editing the plugin in a popup form, without needing to edit the whole page. This feature is unavailable outside wiki pages, whether or not this preference is enabled.	
Only display focused edit icons (for sections and/or plugins) on request	Focused edit icons will only display after a per-session "Edit icons" preference is enabled. This preference is defined directly from any wiki page.	
GUI for the list plugin	Experimental GUI for the list plugin in popup plugin edit forms. (listgui)	

Option	Description	Default
Plugin trackerlist converter	Button on trackerlist and trackerfilter plugins edit form to convert them to use the list plugin instead.	
Plugins tab of the textarea control panel loads with an empty list	Improve the performance of the textarea control panel by avoiding the loading of all plugins initially <i>Some plugins may not appear. When using the MySQL engine, can have problems with short plugin names (for MyISAM, those under "ft_min_word_len").</i>	
Option	Description	Default
Automatically approve wiki-plugins on pages installed by profiles	Some wiki-plugins require admin approval before they are executable. If turned on, then all wiki-plugins that are on wiki pages created via profiles are automatically approved. <i>Make sure your profiles are not executable or editable by untrusted users.</i>	
Plugin pending approval notification	Send an email alert to users with permission to approve plugins when a plugin approval is pending	
Default for img-fluid class used in the IMG plugin	Default option for whether an image produced with the IMG plugin has the img-fluid class - a plugin parameter allows this to be overridden	
Maximum plugin parsing passes	Affects the number of wiki plugins that can be used. The default of 500 allows for 1 plugin nested seven times, or 44 plugins nested once. A value of 1200 is required for 1 eighth level plugin. <i>Setting this to a higher value than the default of 500 may have performance implications.</i>	
Allow plugin-specific edits	Add an icon next to each plugin usage to enable editing the plugin in a popup form, without needing to edit the whole page. This feature is unavailable outside wiki pages, whether or not this preference is enabled.	
Only display focused edit icons (for sections and/or plugins) on request	Focused edit icons will only display after a per-session "Edit icons" preference is enabled. This preference is defined directly from any wiki page.	
GUI for the list plugin	Experimental GUI for the list plugin in popup plugin edit forms. (listgui)	
Plugin trackerlist converter	Button on trackerlist and trackerfilter plugins edit form to convert them to use the list plugin instead.	
Plugins tab of the textarea control panel loads with an empty list	Improve the performance of the textarea control panel by avoiding the loading of all plugins initially <i>Some plugins may not appear. When using the MySQL engine, can have problems with short plugin names (for MyISAM, those under "ft_min_word_len").</i>	
Option	Description	Default
Automatically approve wiki-plugins on pages installed by profiles	Some wiki-plugins require admin approval before they are executable. If turned on, then all wiki-plugins that are on wiki pages created via profiles are automatically approved. <i>Make sure your profiles are not executable or editable by untrusted users.</i>	
Plugin pending approval notification	Send an email alert to users with permission to approve plugins when a plugin approval is pending	



Option	Description	Default
Default for img-fluid class used in the IMG plugin	Default option for whether an image produced with the IMG plugin has the img-fluid class - a plugin parameter allows this to be overridden	
Maximum plugin parsing passes	Affects the number of wiki plugins that can be used. The default of 500 allows for 1 plugin nested seven times, or 44 plugins nested once. A value of 1200 is required for 1 eighth level plugin. <i>Setting this to a higher value than the default of 500 may have performance implications.</i>	
Allow plugin-specific edits	Add an icon next to each plugin usage to enable editing the plugin in a popup form, without needing to edit the whole page. This feature is unavailable outside wiki pages, whether or not this preference is enabled.	
Only display focused edit icons (for sections and/or plugins) on request	Focused edit icons will only display after a per-session "Edit icons" preference is enabled. This preference is defined directly from any wiki page.	
GUI for the list plugin	Experimental GUI for the list plugin in popup plugin edit forms. (listgui)	
Plugin trackerlist converter	Button on trackerlist and trackerfilter plugins edit form to convert them to use the list plugin instead.	
Plugins tab of the textarea control panel loads with an empty list	Improve the performance of the textarea control panel by avoiding the loading of all plugins initially <i>Some plugins may not appear. When using the MySQL engine, can have problems with short plugin names (for MyISAM, those under "ft_min_word_len").</i>	

Option	Description	Default
Automatically approve wiki-plugins on pages installed by profiles	Some wiki-plugins require admin approval before they are executable. If turned on, then all wiki-plugins that are on wiki pages created via profiles are automatically approved. <i>Make sure your profiles are not executable or editable by untrusted users.</i>	
Plugin pending approval notification	Send an email alert to users with permission to approve plugins when a plugin approval is pending	
Default for img-fluid class used in the IMG plugin	Default option for whether an image produced with the IMG plugin has the img-fluid class - a plugin parameter allows this to be overridden	
Maximum plugin parsing passes	Affects the number of wiki plugins that can be used. The default of 500 allows for 1 plugin nested seven times, or 44 plugins nested once. A value of 1200 is required for 1 eighth level plugin. <i>Setting this to a higher value than the default of 500 may have performance implications.</i>	
Allow plugin-specific edits	Add an icon next to each plugin usage to enable editing the plugin in a popup form, without needing to edit the whole page. This feature is unavailable outside wiki pages, whether or not this preference is enabled.	
Only display focused edit icons (for sections and/or plugins) on request	Focused edit icons will only display after a per-session "Edit icons" preference is enabled. This preference is defined directly from any wiki page.	
GUI for the list plugin	Experimental GUI for the list plugin in popup plugin edit forms. (listgui)	

Option	Description	Default
Plugin trackerlist converter	Button on trackerlist and trackerfilter plugins edit form to convert them to use the list plugin instead.	
Plugins tab of the textarea control panel loads with an empty list	Improve the performance of the textarea control panel by avoiding the loading of all plugins initially <i>Some plugins may not appear. When using the MySQL engine, can have problems with short plugin names (for MyISAM, those under "ft_min_word_len").</i>	

# Trackers - Plugins

Option	Description	Default
Plugin Insert Tracker Item	Create a tracker item when the plugin is inserted in the page. The plugin code is removed and replaced by a link to the newly created item.	
Trackers available for insertion from wiki pages	List of tracker IDs made available when attempting to insert	
Plugin Tracker	Embed a form to populate a tracker	
Plugin Tracker List	List, filter and sort the items in a tracker	
Plugin Tracker Filter	Create a form to filter tracker fields	
Plugin Tracker If	Display content based on results of a tracker field test	
Plugin Tracker Stats	Display statistics about a tracker.	
Plugin Mini Quiz	Create a quiz using a tracker	
Plugin Vote	Create a tracker for voting	
Plugin Tracker Comments	Display the number of comments for a tracker	
Plugin Tracker Item Field	Display or test the value of a tracker item field	
Plugin Tracker Prefill	Create a button to prefill tracker fields	
Plugin Tracker Timeline	Show a timeline view of a tracker	
Plugin Tracker Toggle	Adjust the visibility of content based on a tracker field's value, possibly dynamically	
Plugin Copy Tracker Item	Copy a tracker item	
Plugin Tracker Query Template	Generate a form from tracker data	

Option	Description	Default
Plugin Insert Tracker Item	Create a tracker item when the plugin is inserted in the page. The plugin code is removed and replaced by a link to the newly created item.	
Trackers available for insertion from wiki pages	List of tracker IDs made available when attempting to insert	
Plugin Tracker	Embed a form to populate a tracker	
Plugin Tracker List	List, filter and sort the items in a tracker	
Plugin Tracker Filter	Create a form to filter tracker fields	
Plugin Tracker If	Display content based on results of a tracker field test	
Plugin Tracker Stats	Display statistics about a tracker.	
Plugin Mini Quiz	Create a quiz using a tracker	
Plugin Vote	Create a tracker for voting	
Plugin Tracker Comments	Display the number of comments for a tracker	
Plugin Tracker Item Field	Display or test the value of a tracker item field	
Plugin Tracker Prefill	Create a button to prefill tracker fields	
Plugin Tracker Timeline	Show a timeline view of a tracker	
Plugin Tracker Toggle	Adjust the visibility of content based on a tracker field's value, possibly dynamically	
Plugin Copy Tracker Item	Copy a tracker item	
Plugin Tracker Query Template	Generate a form from tracker data	
Option	Description	Default
Plugin Insert Tracker Item	Create a tracker item when the plugin is inserted in the page. The plugin code is removed and replaced by a link to the newly created item.	
Trackers available for insertion from wiki pages	List of tracker IDs made available when attempting to insert	
Plugin Tracker	Embed a form to populate a tracker	
Plugin Tracker List	List, filter and sort the items in a tracker	
Plugin Tracker Filter	Create a form to filter tracker fields	
Plugin Tracker If	Display content based on results of a tracker field test	
Plugin Tracker Stats	Display statistics about a tracker.	
Plugin Mini Quiz	Create a quiz using a tracker	
Plugin Vote	Create a tracker for voting	

Option	Description	Default
Plugin Tracker Comments	Display the number of comments for a tracker	
Plugin Tracker Item Field	Display or test the value of a tracker item field	
Plugin Tracker Prefill	Create a button to prefill tracker fields	
Plugin Tracker Timeline	Show a timeline view of a tracker	
Plugin Tracker Toggle	Adjust the visibility of content based on a tracker field's value, possibly dynamically	
Plugin Copy Tracker Item	Copy a tracker item	
Plugin Tracker Query Template	Generate a form from tracker data	

Option	Description	Default
Plugin Insert Tracker Item	Create a tracker item when the plugin is inserted in the page. The plugin code is removed and replaced by a link to the newly created item.	
Trackers available for insertion from wiki pages	List of tracker IDs made available when attempting to insert	
Plugin Tracker	Embed a form to populate a tracker	
Plugin Tracker List	List, filter and sort the items in a tracker	
Plugin Tracker Filter	Create a form to filter tracker fields	
Plugin Tracker If	Display content based on results of a tracker field test	
Plugin Tracker Stats	Display statistics about a tracker.	
Plugin Mini Quiz	Create a quiz using a tracker	
Plugin Vote	Create a tracker for voting	
Plugin Tracker Comments	Display the number of comments for a tracker	
Plugin Tracker Item Field	Display or test the value of a tracker item field	
Plugin Tracker Prefill	Create a button to prefill tracker fields	
Plugin Tracker Timeline	Show a timeline view of a tracker	
Plugin Tracker Toggle	Adjust the visibility of content based on a tracker field's value, possibly dynamically	
Plugin Copy Tracker Item	Copy a tracker item	
Plugin Tracker Query Template	Generate a form from tracker data	

Option	Description	Default
Plugin Insert Tracker Item	Create a tracker item when the plugin is inserted in the page. The plugin code is removed and replaced by a link to the newly created item.	

Option	Description	Default
Trackers available for insertion from wiki pages	List of tracker IDs made available when attempting to insert	
Plugin Tracker	Embed a form to populate a tracker	
Plugin Tracker List	List, filter and sort the items in a tracker	
Plugin Tracker Filter	Create a form to filter tracker fields	
Plugin Tracker If	Display content based on results of a tracker field test	
Plugin Tracker Stats	Display statistics about a tracker.	
Plugin Mini Quiz	Create a quiz using a tracker	
Plugin Vote	Create a tracker for voting	
Plugin Tracker Comments	Display the number of comments for a tracker	
Plugin Tracker Item Field	Display or test the value of a tracker item field	
Plugin Tracker Prefill	Create a button to prefill tracker fields	
Plugin Tracker Timeline	Show a timeline view of a tracker	
Plugin Tracker Toggle	Adjust the visibility of content based on a tracker field's value, possibly dynamically	
Plugin Pretty Tracker View Tracking	Store tiki.tracker.pretty.views attribute for a trackeritem	
Plugin Check Tracker Passcodes	Verify a tracker passcode	
Plugin Copy Tracker Item	Copy a tracker item	
Plugin Tracker Query Template	Generate a form from tracker data	

# Trackers - Settings

Option	Description	Default
Trackers	Database and form generator	
Synchronize remote tracker	Enable a tracker to be cloned on a remote host, and synchronize the data locally on demand.	
Tracker Import-Export	Allows management of import/export tracker profiles and management of custom list formats.	

Option	Description	Default
Duplicate tracker items	Allow copying tracker item information to a new tracker item. If the item has an item-link linked, it will automatically create new child item. This last can be turned on and off per case on the item-link tracker fields options.	
Tracker item export memory limit	Temporarily adjust the memory limit to use during Tracker item export. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server. <i>for example: 256M</i>	
Tracker item export time limit	Temporarily adjust the time limit to use during Tracker item export. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Tracker item import memory limit	Temporarily adjust the memory limit to use during Tracker item import. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server. <i>for example: 256M</i>	
Tracker item import time limit	Temporarily adjust the time limit to use during Tracker item import. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Tracker clear time limit	Temporarily adjust the time limit to use during Tracker clear. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Warn on edit conflict	When another user is editing a page, spreadsheet or tracker item, you will be warned about a possible conflict. This feature is useful to prevent collisions when editing.	
Inline editing	Enable inline editing of certain values. Currently limited to tracker item fields.	
Tracker list inline editing	Enable inline editing of all fields on the tracker list page.	
Tracker report resize button	Add a button to resize long tracker reports.	
Show comments below items	Show comments for a tracker item below the item itself as in other trackers, instead of enclosed in a tab	
Insert and edit items in a tab	Edit tracker items in a tab instead of a popup dialog.	

Option	Description	Default
Show tracker status in objectlink	Show the status when doing an objectlink. This can be used to show the status in tracker screens but not in outputs.	
Always notify watchers	Send item updated notifications to watchers even if nothing has changed.	
Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page	This redirection uses the wiki prefix alias feature	
Tracker item links use prefix alias	Links for tracker items will use the prefix alias automatically everywhere.	
Tracker title in SEFURL	To display the title, you should disable `Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page`	
Tracker list order	Default order for the main tracker list.	
Tracker History Diff Style	Default style for tracker history.	
Maximum users in drop-down lists	Use jQuery autocomplete text input to prevent out-of-memory errors and performance issues when the user list is very large.	
Show user's real name	Use the user's real name instead of log-in name in the autocomplete selector in trackers <i>This is a global switch for the parameter "Show real name if possible". Requires activation in the options of each User Selector field independently.</i>	
Object selector threshold	Number of records after which the object selectors will request searching instead of selecting from a list.	
Object selector search field	Field or (comma separated) fields to search when filtering in an object selector. e.g. "content" (default "title")	
Object selector wildcard search		
Refresh item link items when the master is modified	To be used when item link is used in trackers so that the index remains in good shape when data on the master that is indexed with the detail is modified and used to search on.	
Refresh items list items when related items are created or modified	Use this to enable the ItemsList fields to refresh their content in the search index when related tracker items are created or modified.	
Allow searching for existing files in the tracker files field	Search files using the search index.	
Index Tracker Category names	Index the names and paths of category field values <i>Requires reindexing</i>	
Change field types	Allow field type to be changed after creation. <i>Use with care!</i>	

Option	Description	Default
Tracker Field Rules	Conditional rules for tracker fields. <i>Experimental new feature, expect some issues.</i>	
Numeric field data modification via scroll	Allow the numeric field data to be changed on movement of mousepad or mouse scroll	
Allow autoincrement fields start value to be reset to a new value	In some use cases like sequential numbers that begin by the current year, e.g. 20210001, the autoincrement value may have to be annually reset. In this case, just update the start value in the field definition. <i>Use with care, potential for data loss.</i>	
Default locale for currency formatting	Currency fields use a system locale to format the output of currency values. Set the default one here when none is selected in the field themselves. Visit "Server Check" page for a list of available system locales.	
Sync wiki page name to linked tracker field	When the wiki page is renamed or when the value of the tracker field that is linked to the wiki page is changed, make the corresponding change as well to the other linked via tiki.wiki.linkedfield relation.	
Redirect page views to the linked tracker item	Redirect the user to the tracker item when trying to view a wiki page that has a linked tracker item via tiki.wiki.linkeditem relation. Can be bypassed by adding &admin (?admin in sefurl) to the URL. <i>To get to the wiki page after activation, you can add &amp;admin (?admin in sefurl) to the URL.</i>	
Storage Directory path	Location where tracker attachment files are stored Path of a directory on Tiki's host, such as /var/www/. For confidentiality, this directory should not be web accessible. PHP must be able to read/write to the directory.	
Require users to fill in tracker information	Require users to fill in a tracker form if not done already by prompting them with a modal dialog.	
Tracker ID of tracker required to be filled in Mandatory tracker field to check for required filling in	A tracker for articles must contain an "Articles" field The permname of field that is checked to see if user has completed the form. If field is empty, user has not completed it.	
Fields that are asked for in the modal for force-filling	Comma-separated permanent names of fields that are requested in the modal for required filling in. If empty, all fields are requested	
Force users to upload an avatar.	Require the user to upload a profile picture if they haven't done so already by prompting them with a modal popup.	
Option	Description	Default
Trackers	Database and form generator	



Option	Description	Default
Synchronize remote tracker	Enable a tracker to be cloned on a remote host, and synchronize the data locally on demand.	
Tracker Import-Export	Allows management of import/export tracker profiles and management of custom list formats.	
Duplicate tracker items	Allow copying tracker item information to a new tracker item. If the item has an item-link linked, it will automatically create new child item. This last can be turned on and off per case on the item-link tracker fields options.	
Tracker item export memory limit	Temporarily adjust the memory limit to use during Tracker item export. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server. <i>for example: 256M</i>	
Tracker item export time limit	Temporarily adjust the time limit to use during Tracker item export. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Tracker item import memory limit	Temporarily adjust the memory limit to use during Tracker item import. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server. <i>for example: 256M</i>	
Tracker item import time limit	Temporarily adjust the time limit to use during Tracker item import. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Tracker clear time limit	Temporarily adjust the time limit to use during Tracker clear. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Warn on edit conflict	When another user is editing a page, spreadsheet or tracker item, you will be warned about a possible conflict. This feature is useful to prevent collisions when editing.	
Inline editing	Enable inline editing of certain values. Currently limited to tracker item fields.	
Tracker list inline editing	Enable inline editing of all fields on the tracker list page.	

Option	Description	Default
Tracker report resize button	Add a button to resize long tracker reports.	
Show comments below items	Show comments for a tracker item below the item itself as in other trackers, instead of enclosed in a tab	
Insert and edit items in a tab	Edit tracker items in a tab instead of a popup dialog.	
Show tracker status in objectlink	Show the status when doing an objectlink. This can be used to show the status in tracker screens but not in outputs.	
Always notify watchers	Send item updated notifications to watchers even if nothing has changed.	
Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page	This redirection uses the wiki prefix alias feature	
Tracker item links use prefix alias	Links for tracker items will use the prefix alias automatically everywhere.	
Tracker title in SEFURL	To display the title, you should disable `Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page`	
Tracker list order	Default order for the main tracker list.	
Tracker History Diff Style	Default style for tracker history.	
Maximum users in drop-down lists	Use jQuery autocomplete text input to prevent out-of-memory errors and performance issues when the user list is very large.	
Show user's real name	Use the user's real name instead of log-in name in the autocomplete selector in trackers <i>This is a global switch for the parameter "Show real name if possible". Requires activation in the options of each User Selector field independently.</i>	
Object selector threshold	Number of records after which the object selectors will request searching instead of selecting from a list.	
Object selector search field	Field or (comma separated) fields to search when filtering in an object selector. e.g. "content" (default "title")	
Object selector wildcard search		
Refresh item link items when the master is modified	To be used when item link is used in trackers so that the index remains in good shape when data on the master that is indexed with the detail is modified and used to search on.	
Refresh items list items when related items are created or modified	Use this to enable the ItemsList fields to refresh their content in the search index when related tracker items are created or modified.	
Allow searching for existing files in the tracker files field	Search files using the search index.	
Format to use for tracker field keys	Choose between field IDs and permanent names for the tracker indexing	

Option	Description	Default
Index Tracker Category names	Index the names and paths of category field values <i>Requires reindexing</i>	
Change field types	Allow field type to be changed after creation. <i>Use with care!</i>	
Tracker Field Rules	Conditional rules for tracker fields. <i>Experimental new feature, expect some issues.</i>	
Numeric field data modification via scroll	Allow the numeric field data to be changed on movement of mousepad or mouse scroll	
Allow autoincrement fields start value to be reset to a new value	In some use cases like sequential numbers that begin by the current year, e.g. 20210001, the autoincrement value may have to be annually reset. In this case, just update the start value in the field definition. <i>Use with care, potential for data loss.</i>	
Default locale for currency formatting	Currency fields use a system locale to format the output of currency values. Set the default one here when none is selected in the field themselves. Visit "Server Check" page for a list of available system locales.	
Sync wiki page name to linked tracker field	When the wiki page is renamed or when the value of the tracker field that is linked to the wiki page is changed, make the corresponding change as well to the other linked via tiki.wiki.linkedfield relation.	
Redirect page views to the linked tracker item	Redirect the user to the tracker item when trying to view a wiki page that has a linked tracker item via tiki.wiki.linkeditem relation. Can be bypassed by adding &admin (?admin in sefurl) to the URL. <i>To get to the wiki page after activation, you can add &amp;admin (?admin in sefurl) to the URL.</i>	
Storage	Location where tracker attachment files are stored	
Directory path	Path of a directory on Tiki's host, such as /var/www/. For confidentiality, this directory should not be web accessible. PHP must be able to read/write to the directory.	
Require users to fill in tracker information	Require users to fill in a tracker form if not done already by prompting them with a modal dialog.	
Tracker ID of tracker required to be filled in	A tracker for articles must contain an "Articles" field	
Mandatory tracker field to check for required filling in	The permname of field that is checked to see if user has completed the form. If field is empty, user has not completed it.	
Fields that are asked for in the modal for force-filling	Comma-separated permanent names of fields that are requested in the modal for required filling in. If empty, all fields are requested	

Option	Description	Default
Force users to upload an avatar.	Require the user to upload a profile picture if they haven't done so already by prompting them with a modal popup.	
<b>Option</b>	<b>Description</b>	<b>Default</b>
Trackers	Database and form generator	
Synchronize remote tracker	Enable a tracker to be cloned on a remote host, and synchronize the data locally on demand.	
Tracker Import-Export	Allows management of import/export tracker profiles and management of custom list formats.	
Duplicate tracker items	Allow copying tracker item information to a new tracker item. If the item has an item-link linked, it will automatically create new child item. This last can be turned on and off per case on the item-link tracker fields options.	
Tracker item export memory limit	Temporarily adjust the memory limit to use during Tracker item export. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server. <i>for example: 256M</i>	
Tracker item export time limit	Temporarily adjust the time limit to use during Tracker item export. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Tracker item import memory limit	Temporarily adjust the memory limit to use during Tracker item import. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server. <i>for example: 256M</i>	
Tracker item import time limit	Temporarily adjust the time limit to use during Tracker item import. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Tracker clear time limit	Temporarily adjust the time limit to use during Tracker clear. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	

Option	Description	Default
Warn on edit conflict	When another user is editing a page, spreadsheet or tracker item, you will be warned about a possible conflict. This feature is useful to prevent collisions when editing.	
Inline editing	Enable inline editing of certain values. Currently limited to tracker item fields.	
Tracker list inline editing	Enable inline editing of all fields on the tracker list page.	
Tracker report resize button	Add a button to resize long tracker reports.	
Show comments below items	Show comments for a tracker item below the item itself as in other trackers, instead of enclosed in a tab	
Use legacy tracker insertion screen	Use the legacy tracker insertion screen (a tab) instead of a popup dialog. Useful for older trackers using deprecated fields such as Image and File or when more insertion space is useful	
Show tracker status in objectlink	Show the status when doing an objectlink. This can be used to show the status in tracker screens but not in outputs.	
Always notify watchers	Send item updated notifications to watchers even if nothing has changed.	
Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page	This redirection uses the wiki prefix alias feature	
Tracker item links use prefix alias	Links for tracker items will use the prefix alias automatically everywhere.	
Tracker title in SEFURL	To display the title, you should disable `Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page`	
Tracker list order	Default order for the main tracker list.	
Tracker History Diff Style	Default style for tracker history.	
Maximum users in drop-down lists	Use jQuery autocomplete text input to prevent out-of-memory errors and performance issues when the user list is very large.	
Show user's real name	Use the user's real name instead of log-in name in the autocomplete selector in trackers <i>This is a global switch for the parameter "Show real name if possible". Requires activation in the options of each User Selector field independently.</i>	
Object selector threshold	Number of records after which the object selectors will request searching instead of selecting from a list.	
Object selector search field	Field or (comma separated) fields to search when filtering in an object selector. e.g. "content" (default "title")	
Refresh item link items when the master is modified	To be used when item link is used in trackers so that the index remains in good shape when data on the master that is indexed with the detail is modified and used to search on.	

Option	Description	Default
Refresh items list items when related items are created or modified	Use this to enable the ItemsList fields to refresh their content in the search index when related tracker items are created or modified.	
Allow searching for existing files in the tracker files field	Search files using the search index.	
Format to use for tracker field keys	Choose between field IDs and permanent names for the tracker indexing	
Index Tracker Category names	Index the names and paths of category field values <i>Requires reindexing</i>	
Change field types	Allow field type to be changed after creation. <i>Use with care!</i>	
Tracker Field Rules	Conditional rules for tracker fields. <i>Experimental new feature, expect some issues.</i>	
Numeric field data modification via scroll	Allow the numeric field data to be changed on movement of mousepad or mouse scroll	
Allow autoincrement fields start value to be reset to a new value	In some use cases like sequential numbers that begin by the current year, e.g. 20210001, the autoincrement value may have to be annually reset. In this case, just update the start value in the field definition. <i>Use with care, potential for data loss.</i>	
Default locale for currency formatting	Currency fields use a system locale to format the output of currency values. Set the default one here when none is selected in the field themselves. Visit "Server Check" page for a list of available system locales.	
Sync wiki page name to linked tracker field	When the wiki page is renamed or when the value of the tracker field that is linked to the wiki page is changed, make the corresponding change as well to the other linked via tiki.wiki.linkedfield relation.	
Redirect page views to the linked tracker item	Redirect the user to the tracker item when trying to view a wiki page that has a linked tracker item via tiki.wiki.linkeditem relation. Can be bypassed by adding &admin (?admin in sefurl) to the URL. <i>To get to the wiki page after activation, you can add &amp;admin (?admin in sefurl) to the URL.</i>	
Storage	Location where tracker attachment files are stored	
Directory path	Path of a directory on Tiki's host, such as /var/www/. For confidentiality, this directory should not be web accessible. PHP must be able to read/write to the directory.	
Require users to fill in tracker information	Require users to fill in a tracker form if not done already by prompting them with a modal dialog.	
Tracker ID of tracker required to be filled in	A tracker for articles must contain an "Articles" field	

Option	Description	Default
Mandatory tracker field to check for required filling in	The permname of field that is checked to see if user has completed the form. If field is empty, user has not completed it.	
Fields that are asked for in the modal for force-filling	Comma-separated permanent names of fields that are requested in the modal for required filling in. If empty, all fields are requested	
Force users to upload an avatar.	Require the user to upload a profile picture if they haven't done so already by prompting them with a modal popup.	

Option	Description	Default
Trackers	Database and form generator	
Synchronize remote tracker	Enable a tracker to be cloned on a remote host, and synchronize the data locally on demand.	
Tracker tabular	Allows management of import/export tracker profiles and management of custom list formats.	
Clone tracker items	Allow copying tracker item information to a new tracker item.	
Tracker item export memory limit	Temporarily adjust the memory limit to use during Tracker item export. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server. <i>for example: 256M</i>	
Tracker item export time limit	Temporarily adjust the time limit to use during Tracker item export. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Tracker item import memory limit	Temporarily adjust the memory limit to use during Tracker item import. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server. <i>for example: 256M</i>	
Tracker item import time limit	Temporarily adjust the time limit to use during Tracker item import. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	

Option	Description	Default
Tracker clear time limit	Temporarily adjust the time limit to use during Tracker clear. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Warn on edit conflict	When another user is editing a page, spreadsheet or tracker item, you will be warned about a possible conflict. This feature is useful to prevent collisions when editing.	
Inline editing	Enable inline editing of certain values. Currently limited to tracker item fields.	
Tracker list inline editing	Enable inline editing of all fields on the tracker list page.	
Tracker report resize button	Add a button to resize long tracker reports.	
Show comments below items	Show comments for a tracker item below the item itself as in other trackers, instead of enclosed in a tab	
Use legacy tracker insertion screen	Use the legacy tracker insertion screen (a tab) instead of a popup dialog. Useful for older trackers using deprecated fields such as Image and File or when more insertion space is useful	
Show tracker status in objectlink	Show the status when doing an objectlink. This can be used to show the status in tracker screens but not in outputs.	
Always notify watchers	Send item updated notifications to watchers even if nothing has changed.	
Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page	This redirection uses the wiki prefix alias feature	
Tracker item links use prefix alias	Links for tracker items will use the prefix alias automatically everywhere.	
Tracker title in SEFURL	To display the title, you should disable `Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page`	
Tracker list order	Default order for the main tracker list.	
Tracker History Diff Style	Default style for tracker history.	
Maximum users in drop-down lists	Use jQuery autocomplete text input to prevent out-of-memory errors and performance issues when the user list is very large.	
Show user's real name	Use the user's real name instead of log-in name in the autocomplete selector in trackers <i>This is a global switch for the parameter "Show real name if possible". Requires activation in the options of each User Selector field independently.</i>	
Object selector threshold	Number of records after which the object selectors will request searching instead of selecting from a list.	



Option	Description	Default
Object selector search field	Field or (comma separated) fields to search when filtering in an object selector. e.g. "content" (default "title")	
Refresh item link items when the master is modified	To be used when item link is used in trackers so that the index remains in good shape when data on the master that is indexed with the detail is modified and used to search on.	
Refresh items list items when related items are created or modified	Use this to enable the ItemsList fields to refresh their content in the search index when related tracker items are created or modified.	
Allow searching for existing files in the tracker files field	Search files using the search index.	
Format to use for tracker field keys	Choose between field IDs and permanent names for the tracker indexing	
Index Tracker Category names	Index the names and paths of category field values <i>Requires reindexing</i>	
Change field types	Allow field type to be changed after creation. <i>Use with care!</i>	
Tracker Field Rules	Conditional rules for tracker fields. <i>Experimental new feature, expect some issues.</i>	
Numeric field data modification via scroll	Allow the numeric field data to be changed on movement of mousepad or mouse scroll	
Allow autoincrement fields start value to be reset to a new value	In some use cases like sequential numbers that begin by the current year, e.g. 20210001, the autoincrement value may have to be annually reset. In this case, just update the start value in the field definition. <i>Use with care, potential for data loss.</i>	
Default locale for currency formatting	Currency fields use a system locale to format the output of currency values. Set the default one here when none is selected in the field themselves. Visit "Server Check" page for a list of available system locales.	
Sync wiki page name to linked tracker field	When the wiki page is renamed or when the value of the tracker field that is linked to the wiki page is changed, make the corresponding change as well to the other linked via tiki.wiki.linkedfield relation.	
Redirect page views to the linked tracker item	Redirect the user to the tracker item when trying to view a wiki page that has a linked tracker item via tiki.wiki.linkeditem relation. Can be bypassed by adding &admin (?admin in sefurl) to the URL. <i>To get to the wiki page after activation, you can add &amp;admin (?admin in sefurl) to the URL.</i>	
Storage	Location where tracker attachment files are stored	

Option	Description	Default
Directory path	Path of a directory on Tiki's host, such as /var/www/. For confidentiality, this directory should not be web accessible. PHP must be able to read/write to the directory.	
Require users to fill in tracker information	Require users to fill in a tracker form if not done already by prompting them with a modal dialog.	
Tracker ID of tracker required to be filled in	A tracker for articles must contain an "Articles" field	
Mandatory tracker field to check for required filling in	The permname of field that is checked to see if user has completed the form. If field is empty, user has not completed it.	
Fields that are asked for in the modal for force-filling	Comma-separated permanent names of fields that are requested in the modal for required filling in. If empty, all fields are requested	
Force users to upload an avatar.	Require the user to upload a profile picture if they haven't done so already by prompting them with a modal popup.	
Exchange rates tracker	Allow defining a specific tracker to hold the exchange rates for currency calculations. You should manually create a tracker with at least 3 fields to hold Currency, Rate and Date.	
Choose tracker	Choose which tracker will store the currency conversion rates used for currency calculations.	
Rate field	Choose the field that stores the exchange rate in the system currency tracker.	
Currency field	Choose the field that stores the currency in the system currency tracker.	
Date field	Choose the field that stores the exchange rate date in the system currency tracker.	
Rate direction	Straight means Base currency is equal to Target multiplied by the exchange rate. Reverse means Base is equal to Target divided by the exchange rate. In both cases, the Base currency should have an exchange rate of 1.00	

Option	Description	Default
Trackers	Database and form generator	
Synchronize remote tracker	Enable a tracker to be cloned on a remote host, and synchronize the data locally on demand.	
Tracker tabular	Allows management of import/export tracker profiles and management of custom list formats.	
Clone tracker items	Allow copying tracker item information to a new tracker item.	

Option	Description	Default
Tracker item export memory limit	Temporarily adjust the memory limit to use during Tracker item export. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server. <i>for example: 256M</i>	
Tracker item export time limit	Temporarily adjust the time limit to use during Tracker item export. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Tracker clear time limit	Temporarily adjust the time limit to use during Tracker clear. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values. <i>for example: 30</i>	
Inline editing	Enable inline editing of certain values. Currently limited to tracker item fields.	
Tracker list inline editing	Enable inline editing of all fields on the tracker list page.	
Tracker report resize button	Add a button to resize long tracker reports.	
Show comments below items	Show comments for a tracker item below the item itself as in other trackers, instead of enclosed in a tab	
Use legacy tracker insertion screen	Use the legacy tracker insertion screen (a tab) instead of a popup dialog. Useful for older trackers using deprecated fields such as Image and File or when more insertion space is useful	
Show tracker status in objectlink	Show the status when doing an objectlink. This can be used to show the status in tracker screens but not in outputs.	
Always notify watchers	Send item updated notifications to watchers even if nothing has changed.	
Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page	This redirection uses the wiki prefix alias feature	
Tracker item links use prefix alias	Links for tracker items will use the prefix alias automatically everywhere.	
Tracker title in SEFURL	To display the title, you should disable `Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page`	
Tracker list order	Default order for the main tracker list.	
Tracker History Diff Style	Default style for tracker history.	

Option	Description	Default
Maximum users in drop-down lists	Use jQuery autocomplete text input to prevent out-of-memory errors and performance issues when the user list is very large.	
Show user's real name	Use the user's real name instead of log-in name in the autocomplete selector in trackers <i>This is a global switch for the parameter "Show real name if possible". Requires activation in the options of each User Selector field independently.</i>	
Object selector threshold	Number of records after which the object selectors will request searching instead of selecting from a list.	
Object selector search field	Field or (comma separated) fields to search when filtering in an object selector. e.g. "content" (default "title")	
Refresh item link items when the master is modified	To be used when item link is used in trackers so that the index remains in good shape when data on the master that is indexed with the detail is modified and used to search on.	
Refresh items list items when related items are created or modified	Use this to enable the ItemsList fields to refresh their content in the search index when related tracker items are created or modified.	
Allow searching for existing files in the tracker files field	Search files using the search index.	
Format to use for tracker field keys	Choose between field IDs and permanent names for the tracker indexing	
Index Tracker Category names	Index the names and paths of category field values <i>Requires reindexing</i>	
Change field types	Allow field type to be changed after creation. <i>Use with care!</i>	
Tracker Field Rules	Conditional rules for tracker fields. <i>Experimental new feature, expect some issues.</i>	
Numeric field data modification via scroll	Allow the numeric field data to be changed on movement of mousepad or mouse scroll	
Allow autoincrement fields start value to be reset to a new value	In some use cases like sequential numbers that begin by the current year, e.g. 20210001, the autoincrement value may have to be annually reset. In this case, just update the start value in the field definition. <i>Use with care, potential for data loss.</i>	
Sync wiki page name to linked tracker field	When the wiki page is renamed or when the value of the tracker field that is linked to the wiki page is changed, make the corresponding change as well to the other linked via tiki.wiki.linkedfield relation.	

Option	Description	Default
Redirect page views to the linked tracker item	Redirect the user to the tracker item when trying to view a wiki page that has a linked tracker item via tiki.wiki.linkeditem relation. Can be bypassed by adding &admin (?admin in sefurl) to the URL. <i>To get to the wiki page after activation, you can add &amp;admin (?admin in sefurl) to the URL.</i>	
Storage	Location where tracker attachment files are stored	
Directory path	Path of a directory on Tiki's host, such as /var/www/. For confidentiality, this directory should not be web accessible. PHP must be able to read/write to the directory.	
Require users to fill in tracker information	Require users to fill in a tracker form if not done already by prompting them with a modal dialog.	
Tracker ID of tracker required to be filled in	A tracker for articles must contain an "Articles" field	
Mandatory tracker field to check for required filling in	The permname of field that is checked to see if user has completed the form. If field is empty, user has not completed it.	
Fields that are asked for in the modal for force-filling	Comma-separated permanent names of fields that are requested in the modal for required filling in. If empty, all fields are requested	
Force users to upload an avatar.	Require the user to upload a profile picture if they haven't done so already by prompting them with a modal popup.	

# Users - Messaging and Notifications

Option	Description	Default
Character set for mail		
User messages	Enables inter-user messages (for this to work for new users, the tiki_p_messages permission must be assigned to at least the Registered group)..	
Messages per page		
Allow messages from other users		
Notify sender when reading mail		
Send me an email for messages with priority equal to or greater than		

Option	Description	Default
Auto-archive read messages after Notifications	The number of days after which Tiki will archive the messages that have been read by the user.	
Clear individual notifications	Allow users to control the notifications they receive based on content changes.	
Notification count refresh interval	Allow users to selectively clear notifications instead of simply having a clear-all button.	
Notification reply-to email pattern	Show unread notification count and refresh every x seconds. <i>0 to disable, every refresh causes a hit on the server, try to leave this above 60 seconds.</i>	
Notification digests	Email model to use for the notification email reply-to address. <i>noreply+PLACEHOLDER@example.com</i>	
Disable indexing of activity stream log	Enable digest notifications (requires a cron job)	
User watches	Activity stream log in the search index is controlled by the presence of custom or basic activity events and also by enabling monitoring of events by users. Larger activity streams can cause problems with certain search engines. If you have such problems, you can disable indexing of activity stream here.	
Group watches	Receive email notification of changes. Each user can choose to be notified of changes to specific items	
Daily reports for user watches	All users in a group selected by a users admin (tiki_p_admin_users) will receive email notification of changes to specific items. Users cannot choose to stop receiving those notifications while they are members of that group	
Enable daily reports for new users	Allows you to schedule daily reports of watches to be sent (batched) at specific times.	
User watches translations	Determines if daily reports will be automatically enabled for new users.	
Group alert	With this feature you can choose the user in the group to be alerted about some changes in the Tiki site: Calendar items, Tracker changes, Tracker item changes, File gallery changes	
Webmail	Provides a webmail interface for site users' own IMAP or POP accounts.	
User mention notifications	Add support for @username mentions notifications	

Option	Description	Default
Character set for mail		
User messages	Enables inter-user messages (for this to work for new users, the tiki_p_messages permission must be assigned to at least the Registered group)..	
Messages per page		
Allow messages from other users		
Notify sender when reading mail		

Option	Description	Default
Send me an email for messages with priority equal to or greater than		
Auto-archive read messages after	The number of days after which Tiki will archive the messages that have been read by the user.	
Notifications	Allow users to control the notifications they receive based on content changes.	
Clear individual notifications	Allow users to selectively clear notifications instead of simply having a clear-all button.	
Notification count refresh interval	Show unread notification count and refresh every x seconds. <i>0 to disable, every refresh causes a hit on the server, try to leave this above 60 seconds.</i>	
Notification reply-to email pattern	Email model to use for the notification email reply-to address. <i>noreply+PLACEHOLDER@example.com</i>	
Notification digests	Enable digest notifications (requires a cron job)	
Disable indexing of activity stream log	Activity stream log in the search index is controlled by the presence of custom or basic activity events and also by enabling monitoring of events by users. Larger activity streams can cause problems with certain search engines. If you have such problems, you can disable indexing of activity stream here.	
User watches	Receive email notification of changes. Each user can choose to be notified of changes to specific items	
Group watches	All users in a group selected by a users admin (tiki_p_admin_users) will receive email notification of changes to specific items. Users cannot choose to stop receiving those notifications while they are members of that group	
Daily reports for user watches	Allows you to schedule daily reports of watches to be sent (batched) at specific times.	
Enable daily reports for new users	Determines if daily reports will be automatically enabled for new users.	
User watches translations		
Group alert	With this feature you can choose the user in the group to be alerted about some changes in the Tiki site: Calendar items, Tracker changes, Tracker item changes, File gallery changes	
Webmail	Provides a webmail interface for site users' own IMAP or POP accounts.	
User mention notifications	Add support for @username mentions notifications	

Option	Description	Default
Character set for mail		
User messages	Enables inter-user messages (for this to work for new users, the tiki_p_messages permission must be assigned to at least the Registered group)..	
Messages per page		

Option	Description	Default
Allow messages from other users		
Notify sender when reading mail		
Send me an email for messages with priority equal to or greater than		
Auto-archive read messages after Notifications	The number of days after which Tiki will archive the messages that have been read by the user. Allow users to control the notifications they receive based on content changes.	
Clear individual notifications	Allow users to selectively clear notifications instead of simply having a clear-all button.	
Notification count refresh interval	Show unread notification count and refresh every x seconds. <i>0 to disable, every refresh causes a hit on the server, try to leave this above 60 seconds.</i>	
Notification reply-to email pattern	Email model to use for the notification email reply-to address. <i>noreply+PLACEHOLDER@example.com</i>	
Notification digests	Enable digest notifications (requires a cron job)	
Disable indexing of activity stream log	Activity stream log in the search index is controlled by the presence of custom or basic activity events and also by enabling monitoring of events by users. Larger activity streams can cause problems with certain search engines. If you have such problems, you can disable indexing of activity stream here.	
User watches	Receive email notification of changes. Each user can choose to be notified of changes to specific items	
Group watches	All users in a group selected by a users admin (tiki_p_admin_users) will receive email notification of changes to specific items. Users cannot choose to stop receiving those notifications while they are members of that group	
Daily reports for user watches	Allows you to schedule daily reports of watches to be sent (batched) at specific times.	
Enable daily reports for new users	Determines if daily reports will be automatically enabled for new users.	
User watches translations		
Group alert	With this feature you can choose the user in the group to be alerted about some changes in the Tiki site: Calendar items, Tracker changes, Tracker item changes, File gallery changes	
Webmail	Provides a webmail interface for site users' own IMAP or POP accounts.	
User mention notifications	Add support for @username mentions notifications	

Option	Description	Default
--------	-------------	---------

Character set for mail		
------------------------	--	--



Option	Description	Default
User messages	Enables inter-user messages (for this to work for new users, the tiki_p_messages permission must be assigned to at least the Registered group)..	
Messages per page		
Allow messages from other users		
Notify sender when reading mail		
Send me an email for messages with priority equal to or greater than		
Auto-archive read messages after	The number of days after which Tiki will archive the messages that have been read by the user.	
Notifications	Allow users to control the notifications they receive based on content changes.	
Clear individual notifications	Allow users to selectively clear notifications instead of simply having a clear-all button.	
Notification count refresh interval	Show unread notification count and refresh every x seconds. <i>0 to disable, every refresh causes a hit on the server, try to leave this above 60 seconds.</i>	
Notification reply-to email pattern	Email model to use for the notification email reply-to address. <i>noreply+PLACEHOLDER@example.com</i>	
Notification digests	Enable digest notifications (requires a cron job)	
User watches	Receive email notification of changes. Each user can choose to be notified of changes to specific items	
Group watches	All users in a group selected by a users admin (tiki_p_admin_users) will receive email notification of changes to specific items. Users cannot choose to stop receiving those notifications while they are members of that group	
Daily reports for user watches	Allows you to schedule daily reports of watches to be sent (batched) at specific times.	
Enable daily reports for new users	Determines if daily reports will be automatically enabled for new users.	
User watches translations		
Group alert	With this feature you can choose the user in the group to be alerted about some changes in the Tiki site: Calendar items, Tracker changes, Tracker item changes, File gallery changes	
Webmail	Provides a webmail interface for site users' own IMAP or POP accounts.	
User mention notifications	Add support for @username mentions notifications	

Option	Description	Default
Character set for mail		
User messages	Enables inter-user messages (for this to work for new users, the tiki_p_messages permission must be assigned to at least the Registered group)..	

Option	Description	Default
Messages per page		
Allow messages from other users		
Notify sender when reading mail		
Send me an email for messages with priority equal to or greater than		
Auto-archive read messages after	The number of days after which Tiki will archive the messages that have been read by the user.	
Notifications	Allow users to control the notifications they receive based on content changes.	
Clear individual notifications	Allow users to selectively clear notifications instead of simply having a clear-all button.	
Notification count refresh interval	Show unread notification count and refresh every x seconds. <i>0 to disable, every refresh causes a hit on the server, try to leave this above 60 seconds.</i>	
Notification reply-to email pattern	Email model to use for the notification email reply-to address. <i>noreply+PLACEHOLDER@example.com</i>	
Notification digests	Enable digest notifications (requires a cron job)	
User watches	Receive email notification of changes. Each user can choose to be notified of changes to specific items	
Group watches	All users in a group selected by a users admin (tiki_p_admin_users) will receive email notification of changes to specific items. Users cannot choose to stop receiving those notifications while they are members of that group	
Daily reports for user watches	Allows you to schedule daily reports of watches to be sent (batched) at specific times.	
Enable daily reports for new users	Determines if daily reports will be automatically enabled for new users.	
User watches translations		
Group alert	With this feature you can choose the user in the group to be alerted about some changes in the Tiki site: Calendar items, Tracker changes, Tracker item changes, File gallery changes	
Webmail	Provides a webmail interface for site users' own IMAP or POP accounts.	
User mention notifications	Add support for @username mentions notifications	

# Users - User features

Option	Description	Default
User wizard	Wizard to help users set up their basic settings and account details	
Mini calendar	Displays a personal calendar for each user.	
User tasks		
User notepad		
My bookmarks		
User favorites	Enable users to flag content as their favorite.	
User contacts		
User menu	<i>Unmaintained feature</i>	
Menu user levels	Enables control of the per-group visibility of menu options	
Tagging users	Add support for @username mentions	
User's information page	A personal wiki page for each user.	
Userpage prefix	All userpages share a common prefix. The page name will be a concatenation of the prefix and the username. A prefix is required.	

Option	Description	Default
User wizard	Wizard to help users set up their basic settings and account details	
Mini calendar	Displays a personal calendar for each user.	
User tasks		
User notepad		
My bookmarks		
User favorites	Enable users to flag content as their favorite.	
User contacts		
User menu	<i>Unmaintained feature</i>	
Menu user levels	Enables control of the per-group visibility of menu options	
Tagging users	Add support for @username mentions	
User's information page	A personal wiki page for each user.	

Option	Description	Default
Userpage prefix	All userpages share a common prefix. The page name will be a concatenation of the prefix and the username. A prefix is required.	
<b>Option</b>	<b>Description</b>	<b>Default</b>
User wizard	Wizard to help users set up their basic settings and account details	
Mini calendar	Displays a personal calendar for each user.	
User tasks		
User notepad		
My bookmarks		
User favorites	Enable users to flag content as their favorite.	
User contacts		
User menu	<i>Unmaintained feature</i>	
Menu user levels	Enables control of the per-group visibility of menu options	
Tagging users	Add support for @username mentions	
User's information page	A personal wiki page for each user.	
Userpage prefix	All userpages share a common prefix. The page name will be a concatenation of the prefix and the username. A prefix is required.	
<b>Option</b>	<b>Description</b>	<b>Default</b>
User wizard	Wizard to help users set up their basic settings and account details	
Mini calendar	Displays a personal calendar for each user.	
User tasks		
User notepad		
My bookmarks		
User favorites	Enable users to flag content as their favorite.	
User contacts		
User menu	<i>Unmaintained feature</i>	
Menu user levels	Enables control of the per-group visibility of menu options	
User's information page	A personal wiki page for each user.	
Tagging users	Add support for @username mentions	

Option	Description	Default
Userpage prefix	All userpages share a common prefix. The page name will be a concatenation of the prefix and the username. A prefix is required.	
User wizard	Wizard to help users set up their basic settings and account details	
Mini calendar	Displays a personal calendar for each user.	
User tasks		
User notepad		
My bookmarks		
User favorites	Enable users to flag content as their favorite.	
User contacts		
User menu	<i>Unmaintained feature</i>	
Menu user levels	Enables control of the per-group visibility of menu options	
User's information page	A personal wiki page for each user.	
Tagging users	Add support for @username mentions	
Userpage prefix	All userpages share a common prefix. The page name will be a concatenation of the prefix and the username. A prefix is required.	

## Users - User's files

Option	Description	Default
User files		
Store user files in a file gallery	<i>Use the file gallery admin and the individual file gallery settings to manage file storage preferences.</i>	
Storage	Storage settings when file galleries are not used	
Directory path	Specify a directory on this server, for example: /var/www/ It's recommended that this directory not be web-accessible. PHP must be able to read/write to the directory.	
Quota		
Private	Users cannot see each other's files or galleries	
Hidden	Users can see each other's files, but don't see the galleries in listings	

Option	Description	Default
User files		
Store user files in a file gallery	<i>Use the file gallery admin and the individual file gallery settings to manage file storage preferences.</i>	
Storage	Storage settings when file galleries are not used	
Directory path	Specify a directory on this server, for example: /var/www/ It's recommended that this directory not be web-accessible. PHP must be able to read/write to the directory.	
Quota		
Private	Users cannot see each other's files or galleries	
Hidden	Users can see each other's files, but don't see the galleries in listings	

Option	Description	Default
User files		
Store user files in a file gallery	<i>Use the file gallery admin and the individual file gallery settings to manage file storage preferences.</i>	
Storage	Storage settings when file galleries are not used	
Directory path	Specify a directory on this server, for example: /var/www/ It's recommended that this directory not be web-accessible. PHP must be able to read/write to the directory.	
Quota		
Private	Users cannot see each other's files or galleries	
Hidden	Users can see each other's files, but don't see the galleries in listings	

Option	Description	Default
User files		
Store user files in a file gallery	<i>Use the file gallery admin and the individual file gallery settings to manage file storage preferences.</i>	
Storage	Storage settings when file galleries are not used	
Directory path	Specify a directory on this server, for example: /var/www/ It's recommended that this directory not be web-accessible. PHP must be able to read/write to the directory.	
Quota		
Private	Users cannot see each other's files or galleries	
Hidden	Users can see each other's files, but don't see the galleries in listings	

Option	Description	Default
User files		

Option	Description	Default
Store user files in a file gallery	<i>Use the file gallery admin and the individual file gallery settings to manage file storage preferences.</i>	
Storage	Storage settings when file galleries are not used	
Directory path	Specify a directory on this server, for example: /var/www/ It's recommended that this directory not be web-accessible. PHP must be able to read/write to the directory.	
Quota		
Private	Users cannot see each other's files or galleries	
Hidden	Users can see each other's files, but don't see the galleries in listings	

# Users - User info and picture

Option	Description	Default
User information	Specify if the user's information is public or private.	
Show user's real name	Show the user's real name instead of username (log-in name), when possible.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId= <i>(Use for login name and No value assigned for userId)</i>	
Pre-set show user's info on mouseover	Set new users' info to display in a popup when their name is hovered over.	
Users available in search results	Users available within search results. Content related to the user will be included in the index.	
Highlight group		
Show user's contribution on the user information page	View user's contribution on the user information page.	
Display user tracker information on the user information page	Display user tracker information on the user information page <i>Input the user tracker ID then field IDs to be shown, all separated by commas. Example: 1,1,2,3,4 (user tracker ID 1 followed by field IDs 1-4)</i>	
Display who has viewed "my items" on the user information page	This requires activation of tracking of views for various items in the action log	
Length of "who viewed my items" history	Number of days before the current day to consider when displaying "who viewed my items"	
Show to others "who viewed my items" on the user information page	Show to others "who viewed my items" on the user information page. Admins can always see this information.	

Option	Description	Default
Unified user details	Use User Details Page using the Unified Index.	
Use Gravatar for user profile pictures	Always request the Gravatar image for the user profile picture.	
Store full-size copy of profile picture in file gallery		
Size of the small profile picture stored for users		
Crop the profile picture thumbnail to a square		
File gallery in which to store full-size profile picture	Enter the gallery ID here. Create a dedicated gallery that is admin-only for security, or make sure gallery permissions are set so that only admins can edit.	
File ID of default profile picture	File ID of image to use in file gallery as the profile picture if user has no profile picture in file galleries	

Option	Description	Default
User information	Specify if the user's information is public or private.	
Show user's real name	Show the user's real name instead of username (log-in name), when possible.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId=No value assigned ( <i>Use No value assigned for login name and No value assigned for userId</i> )	
Pre-set show user's info on mouseover	Set new users' info to display in a popup when their name is hovered over.	
Users available in search results	Users available within search results. Content related to the user will be included in the index.	
Highlight group		
Show user's contribution on the user information page	View user's contribution on the user information page.	
Display user tracker information on the user information page	Display user tracker information on the user information page <i>Input the user tracker ID then field IDs to be shown, all separated by commas. Example: 1,1,2,3,4 (user tracker ID 1 followed by field IDs 1-4)</i>	
Display who has viewed "my items" on the user information page	This requires activation of tracking of views for various items in the action log	
Length of "who viewed my items" history	Number of days before the current day to consider when displaying "who viewed my items"	
Show to others "who viewed my items" on the user information page	Show to others "who viewed my items" on the user information page. Admins can always see this information.	
Unified user details	Use User Details Page using the Unified Index.	



Option	Description	Default
Use Gravatar for user profile pictures	Always request the Gravatar image for the user profile picture.	
Store full-size copy of profile picture in file gallery		
Size of the small profile picture stored for users		
Crop the profile picture thumbnail to a square		
File gallery in which to store full-size profile picture	Enter the gallery ID here. Create a dedicated gallery that is admin-only for security, or make sure gallery permissions are set so that only admins can edit.	
File ID of default profile picture	File ID of image to use in file gallery as the profile picture if user has no profile picture in file galleries	

Option	Description	Default
User information	Specify if the user's information is public or private.	
Show user's real name	Show the user's real name instead of username (log-in name), when possible.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId=No value assigned ( <i>Use No value assigned for login name and No value assigned for userId</i> )	
Pre-set show user's info on mouseover	Set new users' info to display in a popup when their name is hovered over.	
Users available in search results	Users available within search results. Content related to the user will be included in the index.	
Highlight group		
Show user's contribution on the user information page	View user's contribution on the user information page.	
Display user tracker information on the user information page	Display user tracker information on the user information page <i>Input the user tracker ID then field IDs to be shown, all separated by commas. Example: 1,1,2,3,4 (user tracker ID 1 followed by field IDs 1-4)</i>	
Display who has viewed "my items" on the user information page	This requires activation of tracking of views for various items in the action log	
Length of "who viewed my items" history	Number of days before the current day to consider when displaying "who viewed my items"	
Show to others "who viewed my items" on the user information page	Show to others "who viewed my items" on the user information page. Admins can always see this information.	
Unified user details	Use User Details Page using the Unified Index.	

Option	Description	Default
Use Gravatar for user profile pictures	Always request the Gravatar image for the user profile picture.	
Store full-size copy of profile picture in file gallery		
Size of the small profile picture stored for users		
Crop the profile picture thumbnail to a square		
File gallery in which to store full-size profile picture	Enter the gallery ID here. Create a dedicated gallery that is admin-only for security, or make sure gallery permissions are set so that only admins can edit.	
File ID of default profile picture	File ID of image to use in file gallery as the profile picture if user has no profile picture in file galleries	

Option	Description	Default
User information	Specify if the user's information is public or private.	
Show user's real name	Show the user's real name instead of username (log-in name), when possible.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId=No value assigned ( <i>Use No value assigned for login name and No value assigned for userId</i> )	
Pre-set show user's info on mouseover	Set new users' info to display in a popup when their name is hovered over.	
Users available in search results	Users available within search results. Content related to the user will be included in the index.	
Highlight group		
Show user's contribution on the user information page	View user's contribution on the user information page.	
Display user tracker information on the user information page	Display user tracker information on the user information page <i>Input the user tracker ID then field IDs to be shown, all separated by commas. Example: 1,1,2,3,4 (user tracker ID 1 followed by field IDs 1-4)</i>	
Display who has viewed "my items" on the user information page	This requires activation of tracking of views for various items in the action log	
Length of "who viewed my items" history	Number of days before the current day to consider when displaying "who viewed my items"	
Show to others "who viewed my items" on the user information page	Show to others "who viewed my items" on the user information page. Admins can always see this information.	
Unified user details	Use User Details Page using the Unified Index.	

Option	Description	Default
Use Gravatar for user profile pictures	Always request the Gravatar image for the user profile picture.	
Store full-size copy of profile picture in file gallery		
Size of the small profile picture stored for users		
Crop the profile picture thumbnail to a square		
File gallery in which to store full-size profile picture	Enter the gallery ID here. Create a dedicated gallery that is admin-only for security, or make sure gallery permissions are set so that only admins can edit.	
File ID of default profile picture	File ID of image to use in file gallery as the profile picture if user has no profile picture in file galleries	

Option	Description	Default
User information	Specify if the user's information is public or private.	
Show user's real name	Show the user's real name instead of username (log-in name), when possible.	
URL to go to when clicking on a username	URL to go to when clicking on a username. Default: tiki-user_information.php?userId=No value assigned ( <i>Use No value assigned for login name and No value assigned for userId</i> )	
Pre-set show user's info on mouseover	Set new users' info to display in a popup when their name is hovered over.	
Users available in search results	Users available within search results. Content related to the user will be included in the index.	
Highlight group		
Show user's contribution on the user information page	View user's contribution on the user information page.	
Display user tracker information on the user information page	Display user tracker information on the user information page <i>Input the user tracker ID then field IDs to be shown, all separated by commas. Example: 1,1,2,3,4 (user tracker ID 1 followed by field IDs 1-4)</i>	
Display who has viewed "my items" on the user information page	This requires activation of tracking of views for various items in the action log	
Length of "who viewed my items" history	Number of days before the current day to consider when displaying "who viewed my items"	
Show to others "who viewed my items" on the user information page	Show to others "who viewed my items" on the user information page. Admins can always see this information.	
Unified user details	Use User Details Page using the Unified Index.	

Option	Description	Default
Use Gravatar for user profile pictures	Always request the Gravatar image for the user profile picture.	
Store full-size copy of profile picture in file gallery		
Size of the small profile picture stored for users		
Crop the profile picture thumbnail to a square		
File gallery in which to store full-size profile picture	Enter the gallery ID here. Create a dedicated gallery that is admin-only for security, or make sure gallery permissions are set so that only admins can edit.	
File ID of default profile picture	File ID of image to use in file gallery as the profile picture if user has no profile picture in file galleries	

# Users - User settings

Option	Description	Default
User preferences screen		
Display "My Account" in the application menu	Display "My Account" in the application menu	
XMPP account JID or username	XMPP account JID or username	
XMPP account password	XMPP account password	
XMPP http-bind URL	Full URL to the http-bind. <i>https://xmpp.example.org/http-bind/</i>	
My pages	List all wiki pages edited by the user.	
My blogs	List all blogs and blog posts edited by the user.	
My messages	List all messages and replies by the user.	
My tasks	List all tasks by the user.	
My forum topics	List all forum topics by the user.	
My forum replies	List all forum replies by the user.	
My items	List all tracker items by the user.	

Option	Description	Default
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	
Users can change theme	<i>Users can override the theme with this setting.</i>	
Number of visited pages to remember		
Tasks per page		
Use interface that shows differences in any versions		
Keep closed remarksbox hidden	Remember the alert boxes that users have closed and don't display them again.	
Require admin users to enter their password for some critical actions	User password will be required for critical operations that can compromise the system security or stability, like adding users to the admin group	
Lock user account after a period of inactivity	User account will be locked automatically after a defined period of not logging in or inactivity	
Period of inactivity before account get locked	User account will be locked automatically after this period (in days)	

Option	Description	Default
User preferences screen		
Display "My Account" in the application menu	Display "My Account" in the application menu	
XMPP account JID or username	XMPP account JID or username	
XMPP account password	XMPP account password	
XMPP http-bind URL	Full URL to the http-bind. <i>https://xmpp.example.org/http-bind/</i>	
My pages	List all wiki pages edited by the user.	
My blogs	List all blogs and blog posts edited by the user.	
My messages	List all messages and replies by the user.	
My tasks	List all tasks by the user.	
My forum topics	List all forum topics by the user.	
My forum replies	List all forum replies by the user.	
My items	List all tracker items by the user.	

Option	Description	Default
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	
Users can change theme	<i>Users can override the theme with this setting.</i>	
Number of visited pages to remember		
Tasks per page		
Use interface that shows differences in any versions		
Keep closed remarksbox hidden	Remember the alert boxes that users have closed and don't display them again.	
Require admin users to enter their password for some critical actions	User password will be required for critical operations that can compromise the system security or stability, like adding users to the admin group	
Lock user account after a period of inactivity	User account will be locked automatically after a defined period of not logging in or inactivity	
Period of inactivity before account get locked	User account will be locked automatically after this period (in days)	

Option	Description	Default
User preferences screen		
Display "My Account" in the application menu	Display "My Account" in the application menu	
XMPP account password	XMPP account password	
My pages	List all wiki pages edited by the user.	
My blogs	List all blogs and blog posts edited by the user.	
My messages	List all messages and replies by the user.	
My tasks	List all tasks by the user.	
My forum topics	List all forum topics by the user.	
My forum replies	List all forum replies by the user.	
My items	List all tracker items by the user.	
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	

<b>Option</b>	<b>Description</b>	<b>Default</b>
Users can change theme	<i>Users can override the theme with this setting.</i>	
Number of visited pages to remember		
Tasks per page		
Use interface that shows differences in any versions		
Keep closed remarksbox hidden	Remember the alert boxes that users have closed and don't display them again.	
Require admin users to enter their password for some critical actions	User password will be required for critical operations that can compromise the system security or stability, like adding users to the admin group	
Lock user account after a period of inactivity	User account will be locked automatically after a defined period of not logging in or inactivity	
Period of inactivity before account get locked	User account will be locked automatically after this period (in days)	

<b>Option</b>	<b>Description</b>	<b>Default</b>
User preferences screen		
Display "My Account" in the application menu	Display "My Account" in the application menu	
XMPP account password	XMPP account password	
My pages	List all wiki pages edited by the user.	
My blogs	List all blogs and blog posts edited by the user.	
My messages	List all messages and replies by the user.	
My tasks	List all tasks by the user.	
My forum topics	List all forum topics by the user.	
My forum replies	List all forum replies by the user.	
My items	List all tracker items by the user.	
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	
Users can change theme	<i>Users can override the theme with this setting.</i>	
Number of visited pages to remember		
Tasks per page		
Use interface that shows differences in any versions		

Option	Description	Default
Keep closed remarksbox hidden	Remember the alert boxes that users have closed and don't display them again.	
Require admin users to enter their password for some critical actions	User password will be required for critical operations that can compromise the system security or stability, like adding users to the admin group	

Option	Description	Default
User preferences screen		
Display "My Account" in the application menu	Display "My Account" in the application menu	
XMPP account password	XMPP account password	
My pages	List all wiki pages edited by the user.	
My blogs	List all blogs and blog posts edited by the user.	
My galleries	List all galleries edited by the user.	
My messages	List all messages and replies by the user.	
My tasks	List all tasks by the user.	
My forum topics	List all forum topics by the user.	
My forum replies	List all forum replies by the user.	
My items	List all tracker items by the user.	
Displayed time zone	Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.	
Use 12-hour clock for time selectors	Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.	
Users can change theme	<i>Users can override the theme with this setting.</i>	
Number of visited pages to remember		
Tasks per page		
Use interface that shows differences in any versions		
Keep closed remarksbox hidden	Remember the alert boxes that users have closed and don't display them again.	
Require admin users to enter their password for some critical actions	User password will be required for critical operations that can compromise the system security or stability, like adding users to the admin group	