

# Requirements

This page lists the minimum requirements and recommended settings to install Tiki.

See also Tiki's [Lifecycle](#) and [Browser Compatibility](#).

If you are using a standard [shared webhost](#), your webhost most likely meets these requirements and you should be able to install Tiki with no problems. Tiki is designed to run on shared hosting, using the [LAMP stack](#).

These instructions are useful for people that are configuring their own server for Tiki.

## Tip

A [Server Check](#) script has been developed that will make everything easier! Just upload a single PHP file to your server before installing Tiki and you will get an advice on your server configuration.

## Shared Host

Tiki will run in most shared webhost environments. Many hosts offer Tiki installation via a control panel application (such as Fantastico).

You should verify that your webhost meets the minimum requirements:

- [HTTP server](#)
- [Database](#)
- [PHP](#)

See [Tiki Friendly Hosts](#) for a list of working shared host environments.

# Requirements

## WEBSERVER

You must have a fully operational webserver in order to install and use Tiki. Tiki *should* run on **any** webserver that supports PHP (such as [nginx](#), [Windows IIS](#) or [lighttpd](#)), but is most widely tested and used with [Apache](#). You may need to make minor modifications for non-Apache webserver.

Your webserver should be configured with the following **minimum** requirements:

- 512 MB RAM
- 100 MB free storage

## DATABASE



Tiki requires [MariaDB](#), [MySQL](#) or [Percona Server for MySQL](#).

We are moving to a machine readable format: [https://gitlab.com/tikiwiki/tiki-manager/-/blob/master/config/tiki\\_requirements.yml](https://gitlab.com/tikiwiki/tiki-manager/-/blob/master/config/tiki_requirements.yml)

<b>Tiki</b>	<b>MariaDB</b>	<b>MySQL</b>
<b>Version</b>	<b>Versions</b>	<b>Versions</b>

<b>Tiki27</b>	10.5+	8+
---------------	-------	----

LTS (not  
released  
yet)

<b>Tiki21 to Tiki26</b>	5.5+	5.7+
-----------------------------	------	------

# Notes

MariaDB 10.2.2+ or MySQL 5.7+ are the versions where the InnoDB row format is by default Dynamic, required for some tables.

No known issues as of 2023-06-15

<b>Tiki</b>	<b>MariaDB</b>	<b>MySQL</b>
<b>Version</b>	<b>Versions</b>	<b>Versions</b>

Tiki19 or Tiki20	5.5-10.4	5.5.3-5.7
---------------------	----------	-----------

Tiki18 LTS	5.1-10.4	5.0-5.7
---------------	----------	---------

# Notes

MySQL 5.6+ or MariaDB  
10.1+ are recommended.  
First version to support  
`utf8mb4`

MySQL 5.6+ or MariaDB  
10.1+ are recommended  
as not all features will be  
available at lesser  
versions.

<b>Tiki</b>	<b>MariaDB</b>	<b>MySQL</b>
<b>Version</b>	<b>Versions</b>	<b>Versions</b>

<b>Tiki15</b>	5.0-10.1	5.0-5.6
LTS		

<b>Tiki12</b>	5.1-5.5	5.0-5.5
LTS		

# Notes

In Tiki 15+ Upgrade scripts in in MariaDB 10.1 / MySQL 5.6 may not work from earlier versions of Tiki.

*Unable to load the jQuery Sortable Tables feature.*

The database can be installed in the same physical location of the webserver (that is, as **localhost**) or Tiki can access a remote database.

PHP



We are moving to a machine readable format: [https://gitlab.com/tikiwiki/tiki-manager/-/blob/master/config/tiki\\_requirements.yml](https://gitlab.com/tikiwiki/tiki-manager/-/blob/master/config/tiki_requirements.yml)



<b>Tiki Version</b>	<b>Minimum PHP Version</b>	<b>Maximum PHP Version</b>
-------------------------	------------------------------------	------------------------------------

**Tiki28**

8.1?

8.4

(not  
released  
yet)

**Tiki27**

8.1

8.4

(not  
released  
yet)

# Notes

We'll decide this once  
Tiki27 is released.

Expected to be OK until  
PHP 9.0

Expected to be OK until  
PHP 9.0

<b>Tiki Version</b>	<b>Minimum PHP Version</b>	<b>Maximum PHP Version</b>
-------------------------	------------------------------------	------------------------------------

Tiki26	8.1	8.1 (8.2 and 8.3 as Beta)
--------	-----	---------------------------------

Tiki22, Tiki23, Tiki24 LTS and Tiki25	7.4	7.4
---	-----	-----

# Notes

Related: [PHP 8](#)

<b>Tiki Version</b>	<b>Minimum PHP Version</b>	<b>Maximum PHP Version</b>
-------------------------	------------------------------------	------------------------------------

Tiki21  
LTS

7.2

7.3

Tiki19 or  
Tiki20

7.1

7.2  
(maybe  
7.3 as  
well)

# Notes

You can fairly safely use 7.4 if you disregard or suppress the notices and warnings.

There is known issue with Tiki 20.2 where PHP requirement was bumped up to PHP 7.2 accidentally

<b>Tiki Version</b>	<b>Minimum PHP Version</b>	<b>Maximum PHP Version</b>
-------------------------	------------------------------------	------------------------------------

<b>Tiki18 LTS</b>	5.6	7.2
-----------------------	-----	-----

<b>Tiki15 LTS</b>	5.5	5.6
-----------------------	-----	-----

<b>Tiki12 LTS</b>	5.3	5.6
-----------------------	-----	-----

# Notes

*Unable to load the jQuery Sortable Tables feature.*

Interesting links about PHP lifecycle

- <http://php.net/supported-versions.php>
- <https://wiki.php.net/rfc/releaseprocess>



- <https://w3techs.com/technologies/details/pl-php>

### Note on PHP Memory Limits:

The default `memory_limit` in a standard PHP installation is **128M**, and this should be fine for the vast majority of Tiki installations. Some web hosts install PHP with a lower default. Although Tiki may appear to install successfully, you will continually face issues with pages failing to load and system errors.

To review your PHP Memory Limits, access <http://www.example.com/tiki-phpinfo.php> and review the following values:

- `max_execution_time` = 60 ; Maximum execution time of each script, in seconds
- `max_input_time` = 60 ; Maximum amount of time each script may spend parsing request data
- `memory_limit` = 128M ; Maximum amount of memory a script may consume

For some shared webhosts, these values may not be user-configurable and you may need to request changes from your webhost, whereas in other hosts you are allowed to fine tune these settings for your needs. You can try uncommenting the corresponding lines in the `.htaccess` file at your tiki root folder on the server, like:

---

```
# increase memory php_value memory_limit 128M # increase execution time... php_value max_execution_time 90
```

## MORE INFORMATION

## REQUIRED PHP FUNCTIONS

Some webhosts tend to disable some functions which are required for Tiki to run flawlessly.

### Function

### Notes

**eval()**

Required by Smarty templating engine. Causes "Please contact support about" messages appearing instead of **Modules** when *eval()* is disabled in `php.ini`.

*Unable to load the jQuery Sortable Tables feature.*

## ADDITIONAL LIBRARIES

### Library

### Notes

**libxml**

Required

**DOM**

Required starting from Tiki 19

## Library

### **mbstring**

## Notes

Useful when working with languages that require it

mbstring needs to be compiled with `--enable-mbregex` or otherwise you will be missing functions like `mb_split()` which are needed for example by Smarty.

Since Tiki 17, the `symfony/polyfill-mbstring` compatibility library (via `symfony-console`) is used in core functionality, but `mbstring` is still required for some functionality.

## Library

## Notes

**ctype**

Required

**calendar**

Required

**iconv**

Required by certain Zend Framework validation and parsing classes

**MySQLi**

In Tiki 12+ MySQLi is recommended but the Tiki installer will fall back to the older MySQL driver if MySQLi is unavailable.

## Library

## Notes

**zip**

The ZipArchive class for php must be installed for some features such as [XML Wiki Import-Export](#) and [PluginArchiveBuilder](#)

*Unable to load the jQuery Sortable Tables feature.*

## PHP.INI CONFIGURATION

We recommend using the following configuration in your **php.ini** file:

## PHP.INI Setting

**memory\_limit = 128M**

## **Description**

Specify the maximum memory for PHP scripts.

# PHP.INI Setting

**\_file\_uploads = On**

**upload\_max\_filesize =  
XXM**

**post\_max\_size**

## **Description**

Required to allow uploads (files, images, etc.) to your Tiki

Specify the maximum upload filesize (in MB).



# PHP.INI Setting

```
session.save_path =  
/tmp
```

## Description

The directory where PHP stores session information (for the default handler (*files*)). Ensure that the location exists and is writable. In [Shared Hosting](#) environments, if you do not have access to **/tmp**, use **temp** (no slash) instead.

# PHP.INI Setting

**max\_execution\_time =  
60**

**max\_input\_time = 60**

**default\_charset =  
"utf-8"**

**mbstring.func\_overload  
= 0**

---

## Description

Specify the idle timeout (in seconds). If you experience timeouts (such as when performing Admin functions) you may need to increase these settings.

Specify the default character encoding.

Tiki will not work properly with **`mbstring.func_overload = 7`**.

*Unable to load the jQuery Sortable Tables feature.*

The location of the **`php.ini`** file may vary, depending on your operating system. Some common locations include:

- /etc/php.ini
- /etc/php/php.ini
- /etc/php5/apache2/php.ini (Debian)
- /etc/php/7.x/apache2/php.ini
- \windows\system\php.ini (Windows)

## OPTIONAL SOFTWARE OR LIBRARIES

Some Tiki features require the following additional software or libraries:

---

### **Feature**

Rewrite Tiki's default URLs

Elasticsearch

Manticore Search

---

---

## **Additional Requirements**

Use the [Apache Clean URLs](#) to create shorter, or custom, URLs.

See [Elasticsearch](#) page (requirements section)

See [Manticore Search](#) page (requirements section)

---

# TIKI MANAGER

- Tiki Manager checks which version it can install or upgrade to:  
[https://gitlab.com/tikiwiki/tiki-manager/-/merge\\_requests/233/diffs](https://gitlab.com/tikiwiki/tiki-manager/-/merge_requests/233/diffs)
- Here is the current data:  
[https://gitlab.com/tikiwiki/tiki-manager/-/blob/master/config/tiki\\_requirements.yml](https://gitlab.com/tikiwiki/tiki-manager/-/blob/master/config/tiki_requirements.yml)