

Tracker Settings tab

Overview

Configure general settings to determine how trackers behave.

To Access

From the [Trackers](#) page, click the **Settings** tab.

Related Topics

- [Tracker Admin](#)
- [PluginTracker](#)

Option

Trackers

Synchronize remote tracker

Tracker Import-Export

Description

Database and form generator

Enable a tracker to be cloned on a remote host, and synchronize the data locally on demand.

Allows management of import/export tracker profiles and management of custom list formats.

Default

Enabled

Disabled

Enabled

Option

Duplicate tracker items

Description

Allow copying tracker item information to a new tracker item. If the item has an item-link linked, it will automatically create new child item. This last can be turned on and off per case on the item-link tracker fields options.

Default

Disabled

Option

Tracker item export memory limit

Description

Temporarily adjust the memory limit to use during Tracker item export. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server.

 *for example: 256M*

Default

None

Option

Tracker item export time limit

Description

Temporarily adjust the time limit to use during Tracker item export. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Default

None

Option

Tracker item import memory limit

Description

Temporarily adjust the memory limit to use during Tracker item import. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server.

 *for example: 256M*

Default

None

Option

Tracker item import time limit

Description

Temporarily adjust the time limit to use during Tracker item import. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Default

None

Option

Tracker clear time limit

Warn on edit conflict

Description

Temporarily adjust the time limit to use during Tracker clear. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

When another user is editing a page, spreadsheet or tracker item, you will be warned about a possible conflict. This feature is useful to prevent collisions when editing.

Default

None

Enabled

Option

Inline editing

Tracker list inline editing

Tracker report resize button

Show comments below items

Insert and edit items in a tab

Description

Enable inline editing of certain values.
Currently limited to tracker item fields.

Enable inline editing of all fields on the
tracker list page.

Add a button to resize long tracker reports.

Show comments for a tracker item below the
item itself as in other trackers, instead of
enclosed in a tab

Edit tracker items in a tab instead of a popup
dialog.

Default

Disabled

Enabled

Disabled

Disabled

Disabled

Option

Show tracker status in objectlink

Always notify watchers

Rewrite `tiki-view_tracker.php?itemId=yyy` to
`Prefixyyy` page

Tracker item links use prefix alias

Description

Show the status when doing an objectlink.

This can be used to show the status in tracker screens but not in outputs.

Send item updated notifications to watchers even if nothing has changed.

This redirection uses the wiki prefix alias feature

Links for tracker items will use the prefix alias automatically everywhere.

Default

Enabled

Disabled

Disabled

Enabled

Option

Tracker title in SEFURL

Tracker list order

Description

To display the title, you should disable
`Rewrite tiki-view_tracker.php?itemId=yyy` to
Prefixyyy page`

Default order for the main tracker list.

☰ Id Ascending | Id Descending | Created
Ascending | Created Descending | Name Ascending
| Name Descending | Last Modified Ascending | Last
Modified Descending | Number of Items Ascending |
Number of Items Descending

Default

Enabled

Created Descending

Option

Tracker History Diff Style

Maximum users in drop-down lists

Description

Default style for tracker history.

☰ Original | Side-by-side diff | Inline diff | Unified diff

Use jQuery autocomplete text input to prevent out-of-memory errors and performance issues when the user list is very large.

Default

Side-by-side diff

50 users

Option

Show user's real name

Object selector threshold

Description

Use the user's real name instead of log-in name in the autocomplete selector in trackers

 *This is a global switch for the parameter "Show real name if possible". Requires activation in the options of each User Selector field independently.*

Number of records after which the object selectors will request searching instead of selecting from a list.

Default

Disabled

250 records

Option

Object selector search field

Object selector wildcard search

Refresh item link items when the master is modified

Description

Field or (comma separated) fields to search when filtering in an object selector. e.g.

"content" (default "title")

To be used when item link is used in trackers so that the index remains in good shape when data on the master that is indexed with the detail is modified and used to search on.

Default

Title

Enabled

Enabled

Option

Refresh items list items when related items are created or modified

Allow searching for existing files in the tracker files field

Index Tracker Category names

Description

Use this to enable the ItemsList fields to refresh their content in the search index when related tracker items are created or modified.

Search files using the search index.

Index the names and paths of category field values

 *Requires reindexing*

Default

Disabled

Enabled

Enabled

Option

Change field types

Tracker Field Rules

Numeric field data modification via scroll

Description

Allow field type to be changed after creation.

 *Use with care!*

Conditional rules for tracker fields.

 *Experimental new feature, expect some issues.* 

Allow the numeric field data to be changed on movement of mousepad or mouse scroll

 Disabled | Use default behavior of the browser (browsers have different behaviors)

Default

Enabled

Enabled

Disabled

Option

Allow autoincrement fields start value to be reset to a new value

Default locale for currency formatting

Description

In some use cases like sequential numbers that begin by the current year, e.g. 20210001, the autoincrement value may have to be annually reset. In this case, just update the start value in the field definition.

 *Use with care, potential for data loss.* 

Currency fields use a system locale to format the output of currency values. Set the default one here when none is selected in the field themselves. Visit "Server Check" page for a list of available system locales.

Default

Disabled

None

Option

Sync wiki page name to linked tracker field

Description

When the wiki page is renamed or when the value of the tracker field that is linked to the wiki page is changed, make the corresponding change as well to the other linked via `tiki.wiki.linkedfield` relation.

Default

Disabled

Option

Redirect page views to the linked tracker item

Storage

Description

Redirect the user to the tracker item when trying to view a wiki page that has a linked tracker item via tiki.wiki.linkeditem relation. Can be bypassed by adding `&admin` (`?admin` in `sefurl`) to the URL.

 *To get to the wiki page after activation, you can add `&admin` (`?admin` in `sefurl`) to the URL.*

Location where tracker attachment files are stored

Default

Disabled

Database

Option

Directory path

Require users to fill in tracker information

Tracker ID of tracker required to be filled in

Description

Path of a directory on Tiki's host, such as `/var/www/`. For confidentiality, this directory should not be web accessible. PHP must be able to read/write to the directory.

Require users to fill in a tracker form if not done already by prompting them with a modal dialog.

A tracker for articles must contain an "Articles" field

Default

None

Disabled

None

Option

Mandatory tracker field to check for required filling in

Fields that are asked for in the modal for force-filling

Force users to upload an avatar.

Description

The permname of field that is checked to see if user has completed the form. If field is empty, user has not completed it.

Comma-separated permanent names of fields that are requested in the modal for required filling in. If empty, all fields are requested

Require the user to upload a profile picture if they haven't done so already by prompting them with a modal popup.

Default

None

None

Disabled

Unable to load the jQuery Sortable Tables feature.

Option

Trackers

Synchronize remote tracker

Tracker Import-Export

Duplicate tracker items

Description

Database and form generator

Enable a tracker to be cloned on a remote host, and synchronize the data locally on demand.

Allows management of import/export tracker profiles and management of custom list formats.

Allow copying tracker item information to a new tracker item. If the item has an item-link linked, it will automatically create new child item. This last can be turned on and off per case on the item-link tracker fields options.

Default

Enabled

Disabled

Enabled

Disabled

Option

Tracker item export memory limit

Description

Temporarily adjust the memory limit to use during Tracker item export. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server.

 *for example: 256M*

Default

None

Option

Tracker item export time limit

Description

Temporarily adjust the time limit to use during Tracker item export. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Default

None

Option

Tracker item import memory limit

Description

Temporarily adjust the memory limit to use during Tracker item import. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server.

 *for example: 256M*

Default

None

Option

Tracker item import time limit

Tracker clear time limit

Description

Temporarily adjust the time limit to use during Tracker item import. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Temporarily adjust the time limit to use during Tracker clear. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Default

None

None

Option

Warn on edit conflict

Inline editing

Tracker list inline editing

Tracker report resize button

Show comments below items

Insert and edit items in a tab

Description

When another user is editing a page, spreadsheet or tracker item, you will be warned about a possible conflict. This feature is useful to prevent collisions when editing.

Enable inline editing of certain values. Currently limited to tracker item fields.

Enable inline editing of all fields on the tracker list page.

Add a button to resize long tracker reports.

Show comments for a tracker item below the item itself as in other trackers, instead of enclosed in a tab

Edit tracker items in a tab instead of a popup dialog.

Default

Enabled

Disabled

Enabled

Disabled

Disabled

Disabled

Option

Show tracker status in objectlink

Always notify watchers

Rewrite `tiki-view_tracker.php?itemId=yyy` to Prefixyyy
page

Tracker item links use prefix alias

Description

Show the status when doing an objectlink. This can be used to show the status in tracker screens but not in outputs.

Send item updated notifications to watchers even if nothing has changed.

This redirection uses the wiki prefix alias feature

Links for tracker items will use the prefix alias automatically everywhere.

Default

Enabled

Disabled

Disabled

Enabled

Option

Tracker title in SEFURL

Tracker list order

Tracker History Diff Style

Description

To display the title, you should disable `Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page`

Default order for the main tracker list.

☰ Id Ascending | Id Descending | Created Ascending | Created Descending | Name Ascending | Name Descending | Last Modified Ascending | Last Modified Descending | Number of Items Ascending | Number of Items Descending

Default style for tracker history.

☰ Original | Side-by-side diff | Inline diff | Unified diff

Default

Enabled

Created Descending

Side-by-side diff

Option

Maximum users in drop-down lists

Show user's real name

Object selector threshold

Description

Use jQuery autocomplete text input to prevent out-of-memory errors and performance issues when the user list is very large.

Use the user's real name instead of log-in name in the autocomplete selector in trackers

 *This is a global switch for the parameter "Show real name if possible". Requires activation in the options of each User Selector field independently.*

Number of records after which the object selectors will request searching instead of selecting from a list.

Default

50 users

Disabled

250 records

Option

Object selector search field

Object selector wildcard search

Refresh item link items when the master is modified

Refresh items list items when related items are created or modified

Description

Field or (comma separated) fields to search when filtering in an object selector. e.g. "content" (default "title")

To be used when item link is used in trackers so that the index remains in good shape when data on the master that is indexed with the detail is modified and used to search on.

Use this to enable the ItemsList fields to refresh their content in the search index when related tracker items are created or modified.

Default

Title

Enabled

Enabled

Disabled

Option

Allow searching for existing files in the tracker files field

Format to use for tracker field keys

Index Tracker Category names

Change field types

Description

Search files using the search index.

Choose between field IDs and permanent names for the tracker indexing

☰ Permanent name | Field ID (backward compatibility mode with Tiki 7 and 8)

Index the names and paths of category field values

👉 *Requires reindexing*

Allow field type to be changed after creation.

⚠️ *Use with care!*

Default

Enabled

Permanent name

Enabled

Enabled

Option

Tracker Field Rules

Numeric field data modification via scroll

Allow autoincrement fields start value to be reset to a new value

Description

Conditional rules for tracker fields.

 *Experimental new feature, expect some issues.* 

Allow the numeric field data to be changed on movement of mousepad or mouse scroll

 Disabled | Use default behavior of the browser (browsers have different behaviors)

In some use cases like sequential numbers that begin by the current year, e.g. 20210001, the autoincrement value may have to be annually reset. In this case, just update the start value in the field definition.

 *Use with care, potential for data loss.* 

Default

Enabled

Disabled

Disabled

Option

Default locale for currency formatting

Sync wiki page name to linked tracker field

Description

Currency fields use a system locale to format the output of currency values. Set the default one here when none is selected in the field themselves. Visit "Server Check" page for a list of available system locales.

When the wiki page is renamed or when the value of the tracker field that is linked to the wiki page is changed, make the corresponding change as well to the other linked via `tiki.wiki.linkedfield` relation.

Default

None

Disabled

Option

Redirect page views to the linked tracker item

Storage

Description

Redirect the user to the tracker item when trying to view a wiki page that has a linked tracker item via `tiki.wiki.linkeditem` relation. Can be bypassed by adding `&admin (?admin in sefurl)` to the URL.

 *To get to the wiki page after activation, you can add `&admin (?admin in sefurl)` to the URL.*

Location where tracker attachment files are stored

 Database | Filesystem

Default

Disabled

Database

Option

Directory path

Require users to fill in tracker information

Tracker ID of tracker required to be filled in

Mandatory tracker field to check for required filling in

Description

Path of a directory on Tiki's host, such as `/var/www/`. For confidentiality, this directory should not be web accessible. PHP must be able to read/write to the directory.

Require users to fill in a tracker form if not done already by prompting them with a modal dialog.

A tracker for articles must contain an "Articles" field

The permname of field that is checked to see if user has completed the form. If field is empty, user has not completed it.

Default

None

Disabled

None

None

Option

Fields that are asked for in the modal for force-filling

Force users to upload an avatar.

Description

Comma-separated permanent names of fields that are requested in the modal for required filling in. If empty, all fields are requested

Require the user to upload a profile picture if they haven't done so already by prompting them with a modal popup.

Default

None

Disabled

Unable to load the jQuery Sortable Tables feature.

Option

Trackers

Synchronize remote tracker

Description

Database and form generator

Enable a tracker to be cloned on a remote host, and synchronize the data locally on demand.

Default

Disabled

Disabled

Option

Tracker Import-Export

Duplicate tracker items

Description

Allows management of import/export tracker profiles and management of custom list formats.

Allow copying tracker item information to a new tracker item. If the item has an item-link linked, it will automatically create new child item. This last can be turned on and off per case on the item-link tracker fields options.

Default

Disabled

Disabled

Option

Tracker item export memory limit

Description

Temporarily adjust the memory limit to use during Tracker item export. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server.

 *for example: 256M*

Default

None

Option

Tracker item export time limit

Description

Temporarily adjust the time limit to use during Tracker item export. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Default

None

Option

Tracker item import memory limit

Description

Temporarily adjust the memory limit to use during Tracker item import. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server.

 *for example: 256M*

Default

None

Option

Tracker item import time limit

Tracker clear time limit

Description

Temporarily adjust the time limit to use during Tracker item import. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Temporarily adjust the time limit to use during Tracker clear. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Default

None

None

Option

Warn on edit conflict

Inline editing

Tracker list inline editing

Tracker report resize button

Show comments below items

Description

When another user is editing a page, spreadsheet or tracker item, you will be warned about a possible conflict. This feature is useful to prevent collisions when editing.

Enable inline editing of certain values. Currently limited to tracker item fields.

Enable inline editing of all fields on the tracker list page.

Add a button to resize long tracker reports.

Show comments for a tracker item below the item itself as in other trackers, instead of enclosed in a tab

Default

Enabled

Disabled

Enabled

Disabled

Disabled

Option

Use legacy tracker insertion screen

Show tracker status in objectlink

Always notify watchers

Description

Use the legacy tracker insertion screen (a tab) instead of a popup dialog.

Useful for older trackers using deprecated fields such as Image and File or when more insertion space is useful

Show the status when doing an objectlink. This can be used to show the status in tracker screens but not in outputs.

Send item updated notifications to watchers even if nothing has changed.

Default

Disabled

Enabled

Enabled

Option

Rewrite `tiki-view_tracker.php?itemId=yyy` to Prefixyyy
page

Tracker item links use prefix alias

Tracker title in SEFURL

Tracker list order

Description

This redirection uses the wiki prefix alias feature

Links for tracker items will use the prefix alias automatically everywhere.

To display the title, you should disable `Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page`

Default order for the main tracker list.

☰ Id Ascending | Id Descending | Created Ascending | Created Descending | Name Ascending | Name Descending | Last Modified Ascending | Last Modified Descending | Number of Items Ascending | Number of Items Descending

Default

Disabled

Enabled

Disabled

Created Descending

Option

Tracker History Diff Style

Maximum users in drop-down lists

Show user's real name

Description

Default style for tracker history.

☰ Original | Side-by-side diff | Inline diff | Unified diff

Use jQuery autocomplete text input to prevent out-of-memory errors and performance issues when the user list is very large.

Use the user's real name instead of log-in name in the autocomplete selector in trackers

👉 *This is a global switch for the parameter "Show real name if possible". Requires activation in the options of each User Selector field independently.*

Default

Side-by-side diff

50 users

Disabled

Option

Object selector threshold

Object selector search field

Refresh item link items when the master is modified

Description

Number of records after which the object selectors will request searching instead of selecting from a list.

Field or (comma separated) fields to search when filtering in an object selector. e.g. "content" (default "title")

To be used when item link is used in trackers so that the index remains in good shape when data on the master that is indexed with the detail is modified and used to search on.

Default

250 records

Title

Disabled

Option

Refresh items list items when related items are created or modified

Allow searching for existing files in the tracker files field

Format to use for tracker field keys

Index Tracker Category names

Description

Use this to enable the ItemList fields to refresh their content in the search index when related tracker items are created or modified.

Search files using the search index.

Choose between field IDs and permanent names for the tracker indexing

☰ Permanent name | Field ID (backward compatibility mode with Tiki 7 and 8)

Index the names and paths of category field values

👉 *Requires reindexing*

Default

Disabled

Enabled

Permanent name

Disabled

Option

Change field types

Tracker Field Rules

Numeric field data modification via scroll

Description

Allow field type to be changed after creation.

 *Use with care!*

Conditional rules for tracker fields.

 *Experimental new feature, expect some issues.* 

Allow the numeric field data to be changed on movement of mousepad or mouse scroll

 Disabled | Use default behavior of the browser (browsers have different behaviors)

Default

Disabled

Disabled

Disabled

Option

Allow autoincrement fields start value to be reset to a new value

Default locale for currency formatting

Description

In some use cases like sequential numbers that begin by the current year, e.g. 20210001, the autoincrement value may have to be annually reset. In this case, just update the start value in the field definition.

 *Use with care, potential for data loss.* 

Currency fields use a system locale to format the output of currency values. Set the default one here when none is selected in the field themselves. Visit "Server Check" page for a list of available system locales.

Default

Disabled

None

Option

Sync wiki page name to linked tracker field

Redirect page views to the linked tracker item

Description

When the wiki page is renamed or when the value of the tracker field that is linked to the wiki page is changed, make the corresponding change as well to the other linked via `tiki.wiki.linkedfield` relation.

Redirect the user to the tracker item when trying to view a wiki page that has a linked tracker item via `tiki.wiki.linkeditem` relation. Can be bypassed by adding `&admin (?admin in sefurl)` to the URL.

 *To get to the wiki page after activation, you can add `&admin (?admin in sefurl)` to the URL.*

Default

Disabled

Disabled

Option

Storage

Directory path

Require users to fill in tracker information

Tracker ID of tracker required to be filled in

Description

Location where tracker attachment files are stored

☰ Database | Filesystem

Path of a directory on Tiki's host, such as `/var/www/`. For confidentiality, this directory should not be web accessible. PHP must be able to read/write to the directory.

Require users to fill in a tracker form if not done already by prompting them with a modal dialog.

A tracker for articles must contain an "Articles" field

Default

Database

None

Disabled

None

Option

Mandatory tracker field to check for required filling in

Fields that are asked for in the modal for force-filling

Force users to upload an avatar.

Description

The permname of field that is checked to see if user has completed the form. If field is empty, user has not completed it.

Comma-separated permanent names of fields that are requested in the modal for required filling in. If empty, all fields are requested

Require the user to upload a profile picture if they haven't done so already by prompting them with a modal popup.

Default

None

None

Disabled

Unable to load the jQuery Sortable Tables feature.

Option

Trackers

Synchronize remote tracker

Tracker tabular

Clone tracker items

Description

Database and form generator

Enable a tracker to be cloned on a remote host, and synchronize the data locally on demand.

Allows management of import/export tracker profiles and management of custom list formats.

Allow copying tracker item information to a new tracker item.

Default

Disabled

Disabled

Disabled

Disabled

Option

Tracker item export memory limit

Description

Temporarily adjust the memory limit to use during Tracker item export. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server.

 *for example: 256M*

Default

None

Option

Tracker item export time limit

Description

Temporarily adjust the time limit to use during Tracker item export. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Default

None

Option

Tracker item import memory limit

Description

Temporarily adjust the memory limit to use during Tracker item import. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server.

 *for example: 256M*

Default

None

Option

Tracker item import time limit

Tracker clear time limit

Description

Temporarily adjust the time limit to use during Tracker item import. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Temporarily adjust the time limit to use during Tracker clear. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Default

None

None

Option

Warn on edit conflict

Inline editing

Tracker list inline editing

Tracker report resize button

Show comments below items

Description

When another user is editing a page, spreadsheet or tracker item, you will be warned about a possible conflict. This feature is useful to prevent collisions when editing.

Enable inline editing of certain values. Currently limited to tracker item fields.

Enable inline editing of all fields on the tracker list page.

Add a button to resize long tracker reports.

Show comments for a tracker item below the item itself as in other trackers, instead of enclosed in a tab

Default

Enabled

Disabled

Enabled

Disabled

Disabled

Option

Use legacy tracker insertion screen

Show tracker status in objectlink

Always notify watchers

Description

Use the legacy tracker insertion screen (a tab) instead of a popup dialog.

Useful for older trackers using deprecated fields such as Image and File or when more insertion space is useful

Show the status when doing an objectlink. This can be used to show the status in tracker screens but not in outputs.

Send item updated notifications to watchers even if nothing has changed.

Default

Disabled

Enabled

Enabled

Option

Rewrite `tiki-view_tracker.php?itemId=yyy` to Prefixyyy
page

Tracker item links use prefix alias

Tracker title in SEFURL

Tracker list order

Description

This redirection uses the wiki prefix alias feature

Links for tracker items will use the prefix alias automatically everywhere.

To display the title, you should disable `Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page`

Default order for the main tracker list.

☰ Id Ascending | Id Descending | Created Ascending | Created Descending | Name Ascending | Name Descending | Last Modified Ascending | Last Modified Descending | Number of Items Ascending | Number of Items Descending

Default

Disabled

Enabled

Disabled

Created Descending

Option

Tracker History Diff Style

Maximum users in drop-down lists

Show user's real name

Description

Default style for tracker history.

☰ Original | Side-by-side diff | Inline diff | Unified diff

Use jQuery autocomplete text input to prevent out-of-memory errors and performance issues when the user list is very large.

Use the user's real name instead of log-in name in the autocomplete selector in trackers

👉 *This is a global switch for the parameter "Show real name if possible". Requires activation in the options of each User Selector field independently.*

Default

Side-by-side diff

50 users

Disabled

Option

Object selector threshold

Object selector search field

Refresh item link items when the master is modified

Description

Number of records after which the object selectors will request searching instead of selecting from a list.

Field or (comma separated) fields to search when filtering in an object selector. e.g. "content" (default "title")

To be used when item link is used in trackers so that the index remains in good shape when data on the master that is indexed with the detail is modified and used to search on.

Default

250 records

Title

Disabled

Option

Refresh items list items when related items are created or modified

Allow searching for existing files in the tracker files field

Format to use for tracker field keys

Index Tracker Category names

Description

Use this to enable the ItemList fields to refresh their content in the search index when related tracker items are created or modified.

Search files using the search index.

Choose between field IDs and permanent names for the tracker indexing

☰ Permanent name | Field ID (backward compatibility mode with Tiki 7 and 8)

Index the names and paths of category field values

👉 *Requires reindexing*

Default

Disabled

Enabled

Permanent name

Disabled

Option

Change field types

Tracker Field Rules

Numeric field data modification via scroll

Description

Allow field type to be changed after creation.

⚠️ *Use with care!*

Conditional rules for tracker fields.

⚠️ *Experimental new feature, expect some issues.* 🧪

Allow the numeric field data to be changed on movement of mousepad or mouse scroll

☰ Disabled | Use default behavior of the browser (browsers have different behaviors)

Default

Disabled

Disabled

Disabled

Option

Allow autoincrement fields start value to be reset to a new value

Default locale for currency formatting

Description

In some use cases like sequential numbers that begin by the current year, e.g. 20210001, the autoincrement value may have to be annually reset. In this case, just update the start value in the field definition.

 *Use with care, potential for data loss.* 

Currency fields use a system locale to format the output of currency values. Set the default one here when none is selected in the field themselves. Visit "Server Check" page for a list of available system locales.

Default

Disabled

None

Option

Sync wiki page name to linked tracker field

Redirect page views to the linked tracker item

Description

When the wiki page is renamed or when the value of the tracker field that is linked to the wiki page is changed, make the corresponding change as well to the other linked via `tiki.wiki.linkedfield` relation.

Redirect the user to the tracker item when trying to view a wiki page that has a linked tracker item via `tiki.wiki.linkeditem` relation. Can be bypassed by adding `&admin (?admin in sefurl)` to the URL.

 *To get to the wiki page after activation, you can add `&admin (?admin in sefurl)` to the URL.*

Default

Disabled

Disabled

Option

Storage

Directory path

Require users to fill in tracker information

Tracker ID of tracker required to be filled in

Description

Location where tracker attachment files are stored

Database | Filesystem

Path of a directory on Tiki's host, such as `/var/www/`. For confidentiality, this directory should not be web accessible. PHP must be able to read/write to the directory.

Require users to fill in a tracker form if not done already by prompting them with a modal dialog.

A tracker for articles must contain an "Articles" field

Default

Database

None

Disabled

None

Option

Mandatory tracker field to check for required filling in

Fields that are asked for in the modal for force-filling

Force users to upload an avatar.

Description

The permname of field that is checked to see if user has completed the form. If field is empty, user has not completed it.

Comma-separated permanent names of fields that are requested in the modal for required filling in. If empty, all fields are requested

Require the user to upload a profile picture if they haven't done so already by prompting them with a modal popup.

Default

None

None

Disabled

Option

Exchange rates tracker

Choose tracker

Rate field

Currency field

Description

Allow defining a specific tracker to hold the exchange rates for currency calculations. You should manually create a tracker with at least 3 fields to hold Currency, Rate and Date.

Choose which tracker will store the currency conversion rates used for currency calculations.

Choose the field that stores the exchange rate in the system currency tracker.

Choose the field that stores the currency in the system currency tracker.

Default

Disabled

None

None

None

Option

Date field

Rate direction

Description

Choose the field that stores the exchange rate date in the system currency tracker.

Straight means Base currency is equal to Target multiplied by the exchange rate. Reverse means Base is equal to Target divided by the exchange rate. In both cases, the Base currency should have an exchange rate of 1.00

☰ Straight (Target/Base) | Reverse (Base/Target)

Default

None

Straight (Target/Base)

Unable to load the jQuery Sortable Tables feature.

Option

Trackers

Description

Database and form generator

Default

Disabled

Option

Synchronize remote tracker

Tracker tabular

Clone tracker items

Description

Enable a tracker to be cloned on a remote host, and synchronize the data locally on demand.

Allows management of import/export tracker profiles and management of custom list formats.

Allow copying tracker item information to a new tracker item.

Default

Disabled

Disabled

Disabled

Option

Tracker item export memory limit

Description

Temporarily adjust the memory limit to use during Tracker item export. Depending on the volume of data, some large operations require more memory. Increasing it locally, per operation, allows to keep a lower memory limit globally. Keep in mind that memory usage is still limited to what is available on the server.

 *for example: 256M*

Default

None

Option

Tracker item export time limit

Tracker clear time limit

Description

Temporarily adjust the time limit to use during Tracker item export. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Temporarily adjust the time limit to use during Tracker clear. Depending on the volume of data, some requests may take longer. Increase the time limit locally to resolve the issue. Use reasonable values.

 *for example: 30*

Default

None

None

Option

Inline editing

Tracker list inline editing

Tracker report resize button

Show comments below items

Use legacy tracker insertion screen

Description

Enable inline editing of certain values. Currently limited to tracker item fields.

Enable inline editing of all fields on the tracker list page.

Add a button to resize long tracker reports.

Show comments for a tracker item below the item itself as in other trackers, instead of enclosed in a tab

Use the legacy tracker insertion screen (a tab) instead of a popup dialog.

Useful for older trackers using deprecated fields such as Image and File or when more insertion space is useful

Default

Disabled

Enabled

Disabled

Disabled

Disabled

Option

Show tracker status in objectlink

Always notify watchers

Rewrite `tiki-view_tracker.php?itemId=yyy` to Prefixyyy
page

Tracker item links use prefix alias

Description

Show the status when doing an objectlink. This can be used to show the status in tracker screens but not in outputs.

Send item updated notifications to watchers even if nothing has changed.

This redirection uses the wiki prefix alias feature

Links for tracker items will use the prefix alias automatically everywhere.

Default

Enabled

Enabled

Disabled

Enabled

Option

Tracker title in SEFURL

Tracker list order

Tracker History Diff Style

Description

To display the title, you should disable `Rewrite tiki-view_tracker.php?itemId=yyy to Prefixyyy page`

Default order for the main tracker list.

☰ Id Ascending | Id Descending | Created Ascending | Created Descending | Name Ascending | Name Descending | Last Modified Ascending | Last Modified Descending | Number of Items Ascending | Number of Items Descending

Default style for tracker history.

☰ Original | Side-by-side diff | Inline diff | Unified diff

Default

Disabled

Created Descending

Side-by-side diff

Option

Maximum users in drop-down lists

Show user's real name

Object selector threshold

Description

Use jQuery autocomplete text input to prevent out-of-memory errors and performance issues when the user list is very large.

Use the user's real name instead of log-in name in the autocomplete selector in trackers

 *This is a global switch for the parameter "Show real name if possible". Requires activation in the options of each User Selector field independently.*

Number of records after which the object selectors will request searching instead of selecting from a list.

Default

50 users

Disabled

250 records

Option

Object selector search field

Refresh item link items when the master is modified

Refresh items list items when related items are created or modified

Allow searching for existing files in the tracker files field

Description

Field or (comma separated) fields to search when filtering in an object selector. e.g. "content" (default "title")

To be used when item link is used in trackers so that the index remains in good shape when data on the master that is indexed with the detail is modified and used to search on.

Use this to enable the ItemsList fields to refresh their content in the search index when related tracker items are created or modified.

Search files using the search index.

Default

Title

Disabled

Disabled

Enabled

Option

Format to use for tracker field keys

Index Tracker Category names

Change field types

Tracker Field Rules

Description

Choose between field IDs and permanent names for the tracker indexing

☰ Permanent name | Field ID (backward compatibility mode with Tiki 7 and 8)

Index the names and paths of category field values

👉 *Requires reindexing*

Allow field type to be changed after creation.

⚠️ *Use with care!*

Conditional rules for tracker fields.

⚠️ *Experimental new feature, expect some issues.* 🧪

Default

Permanent name

Disabled

Disabled

Disabled

Option

Numeric field data modification via scroll

Allow autoincrement fields start value to be reset to a new value

Description

Allow the numeric field data to be changed on movement of mousepad or mouse scroll

☰ Disabled | Use default behavior of the browser (browsers have different behaviors)

In some use cases like sequential numbers that begin by the current year, e.g. 20210001, the autoincrement value may have to be annually reset. In this case, just update the start value in the field definition.

⚠ *Use with care, potential for data loss.* 🧪

Default

Disabled

Disabled

Option

Sync wiki page name to linked tracker field

Redirect page views to the linked tracker item

Description

When the wiki page is renamed or when the value of the tracker field that is linked to the wiki page is changed, make the corresponding change as well to the other linked via `tiki.wiki.linkedfield` relation.

Redirect the user to the tracker item when trying to view a wiki page that has a linked tracker item via `tiki.wiki.linkeditem` relation. Can be bypassed by adding `&admin (?admin in sefurl)` to the URL.

 *To get to the wiki page after activation, you can add `&admin (?admin in sefurl)` to the URL.*

Default

Disabled

Disabled

Option

Storage

Directory path

Require users to fill in tracker information

Tracker ID of tracker required to be filled in

Description

Location where tracker attachment files are stored

Database | Filesystem

Path of a directory on Tiki's host, such as `/var/www/`. For confidentiality, this directory should not be web accessible. PHP must be able to read/write to the directory.

Require users to fill in a tracker form if not done already by prompting them with a modal dialog.

A tracker for articles must contain an "Articles" field

Default

Database

None

Disabled

None

Option

Mandatory tracker field to check for required filling in

Fields that are asked for in the modal for force-filling

Force users to upload an avatar.

Description

The permname of field that is checked to see if user has completed the form. If field is empty, user has not completed it.

Comma-separated permanent names of fields that are requested in the modal for required filling in. If empty, all fields are requested

Require the user to upload a profile picture if they haven't done so already by prompting them with a modal popup.

Default

None

None

Disabled

Unable to load the jQuery Sortable Tables feature.

ADDITIONAL SETTINGS INFORMATION

DUPLICATE TRACKER ITEMS (TRACKER_CLONE_ITEM)

The option "Clone tracker items" has been renamed "Duplicate tracker items" all over Tiki since Tiki version 25 to improve user understand and consistency.

This option is applied over all the tracker and allow copying tracker item information to a new tracker item. It is disabled by default.

This option is tracker wide and does not depend of an extra permission. When you enable it, admins or user with the "Can administer trackers (tiki_p_admin_trackers)" will see a additional option in the tracker action menu: "Duplicate".

When duplicating an item, some field like the Category won't be populated and stay blank ready to be edited.

Other field with an auto-assignment option like the user-selector field with assign to creator will then be populated accordingly (if admin duplicate an item, the children items with a user-selector field will be assigned to admin). See [Trackers; Duplicate a trackeritem on an item used in another tracker will create duplication for all the items where the original item is used](#)

Important Notice: The code is also checking if the item has children through item link, if items in other trackers are linked to the parent item using an item link tracker field. If items are found **they are also duplicated** silently. See [Trackers; Duplicate a trackeritem on an item used in another tracker will create duplication for all the items where the original item is used](#)