

## Plugin Media Wiki Table

Introduced in *Tiki3*

Use this [wiki plugin](#) to display a table using MediaWiki syntax.

## Parameters

Display a table using MediaWiki syntax

Introduced in *Tiki 3*.

[Go to the source code](#)

Preferences required: `wikiplugin_mwtable`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		URL		
fancy	(blank) true false	Set to true to apply additional formatting to the table (header style, odd/even rows, etc.). Takes precedence over the <code>wiki_classes</code> parameter.	false	3.0
wiki_classes	(blank) true false	Determines whether wiki style classes will be used for the table and cells (used by default)	true	3.0

## Usage notes

This plugin doesn't support things like templates or the `!row` heading syntax. Column styling overcomes the latter to a degree but, for cross-browser consistency, you are limited by HTML to `border=`, `background=`, `width=` and `visibility=`. You can also use `span=` so that a `col` definition can apply to adjacent columns. `tr` and `td` styling overrides `col`.

## Structure of data

- Optionally, first line (prior to the first | ) contains html attributes for the table element.
- Optionally, next line can specify a caption; line starts with |+ followed by optional html attributes that end with a | followed by the caption text.
- Optionally, html attributes for col elements can be specified next on one or more lines starting with a ?
- Each column's attributes start on a new line with ? or on the same line preceded by ?? and become a col
- Optionally, column headings can be specified next on one or more lines starting with a !
- Each column's heading starts on a new line with ! or on the same line preceded by !!
- Optional html attributes for th end with a | followed by text that becomes the text of a th
- Each row, including the first, starts on a new line with |- , optionally followed by html attributes for the tr element
- Each cell starts on a new line with | or on the same line preceded by ||
- Optional html attributes for the td element end with a | followed by the cell text (so data for one cell can have 1 or 2 | characters. Any other | characters are assumed to be part of the cell text.)

## Examples

## Basic syntax:

```
{MWTABLE(fancy="" wiki_classes="")}data{MWTABLE}
```

## The minimum

This code:

```
{MWTABLE()} |- | Bill || The little house |- | Carol || The big house {MWTABLE}
```

Would produce:

```
Bill   The little house
Carol  The big house
```

As a reference, under `tikineat.css` style, it shows as:



## Include styling

This code:

```
{MWTABLE( wiki_classes="false")} style="width:50%", class="myclass" |+style="font-style:italic;"|My caption ?
width="30%;" ?? style="background-color:yellow;" ! style="background-color:grey;"| Name ! Address |-
style="background-color: red" | style="color: blue;" | Bill | The little house |- | Carol || The big house {MWTABLE}
```

Would produce:

*My caption*

Name	Address
Bill	The little house
Carol	The big house

As a reference, under `tikineat.css` style, it shows as:

