

Plugin Mouseover

Introduced in [Tiki3](#)

Use this [wiki plugin](#) to display hidden content by mousing over text.

Parameters

Display hidden content by mousing over text

Introduced in [Tiki 3](#). Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: `wikiplugin_mouseover`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Hidden content, unless the label parameter is undefined, in which case this is the label.		
label	text	Text displayed on the page. The body is the hidden content.		3.0
url	url	Destination link when mouseover text is clicked. Use <code>http://</code> for external links	<code>javascript:void(0)</code>	3.0
bgcolor	text	Background color to apply to the popup		3.0
class	text	CSS class to apply	<code>plugin-mouseover</code>	4.0
closeDelay	digits	Number of seconds before popup closes	0	5.0
effect	(blank) none slide fade blind_ui clip_ui drop_ui explode_ui fold_ui puff_ui slide_ui	Set the type of show/hide animation that will be used		4.0
height	digits	Mouseover box height. Default: 200px	200	3.0
offsetx	int	Shifts the overlay to the right by the specified number of pixels relative to the cursor. Default: 5	5	3.0
offsety	int	Shifts the overlay lower by the specified number of pixels relative to the cursor. Default: 0	24	3.0

padding	digits	Padding size in pixels		3.0
tag	word	HTML tag to use for the label. Default a	a	9.2
text	text	DEPRECATED Hidden content. The body contains the label.		3.0
textcolor	text	Color to apply to the text in the popup		3.0
width	digits	Mouseover box width. Default: 400px	400	3.0
speed	(blank) fast slow	Set the speed of the animation.		4.0
parse	(blank) y n	Parse the body of the plugin as wiki content (parsed by default)	y	3.0
parselabel	(blank) y n	Parse the label as wiki content (parsed by default)	y	5.0
sticky	(blank) y n	When enabled, popup stays visible until it is clicked.		3.0

Examples

Non-sticky Mouseover

This code:

```
{MOUSEOVER(label="Hello" offsetx="4" offsety="15")}Hello over there. It's fine!{MOUSEOVER}
```

Would produce:

Hello

Sticky Mouseover with Tiki Syntax

This code:

```
{MOUSEOVER(label="Sticky" sticky="y" parse="y" offsetx="4" offsety="15")}This is a "sticky" popup{MOUSEOVER}
```

Would produce:

Sticky