

Plugin Permission

Introduced in [Tiki5](#)

Use this [wiki plugin](#) to display content based on permission settings. It is related to [PluginGroup](#).

Parameters

Display content based on permission settings

Introduced in [Tiki 5](#).

[Go to the source code](#)

Preferences required: `wikiplugin_perm`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Wiki text to display if conditions are met. The body may contain <code>{ELSE}</code> . Text after the marker will be displayed to users not matching the conditions.		
<code>object</code>	text	Name or ID of the object to test if not global or the current object		21.3
<code>type</code>	workspace	Type of object referred to in Object ID		21.3
<code>notperms</code>	text <i>separator:</i> <code> </code>	Pipe-separated list of permissions, any of which will cause the default text not to show. Example: <code>tiki_p_rename tiki_p_edit</code>		5.0
<code>global</code>	(blank) 1 0	Indicate whether the permissions are global or local to the object		5.0
<code>perms</code>	text <i>separator:</i> <code> </code>	Pipe-separated list of permissions, one of which is needed to view the default text. Example: <code>tiki_p_rename tiki_p_edit</code>		5.0

Security

- Be careful not to use this plugin to display secure information if the user can see the source
- Local permissions may not work depending on the place or object the syntax is inserted (ex: works for `tiki-index_raw.php` but not for `tiki-editpage.php`)

Examples

Basic syntax

```
{PERM(perms="tiki_p_view|tiki_p_edit" notperms="tiki_p_rename")}some content{ELSE}other content{PERM}
```