

PluginTabs

Introduced in [Tiki4](#)

Use this [wiki plugin](#) to arrange content into tabs.

Parameters

Arrange content in tabs

Introduced in [Tiki 4](#). Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: `wikiplugin_tabs`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Tabs content, separated by "/////"		
tabs	text	Pipe-separated list of tab titles. Example: <code>tab 1 tab 2 tab 3</code>		4.0
<code>panelbgcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0
<code>panelbordercolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0
<code>panelborderwidth</code>	text	To change the width of panel border in pixels (1 by default). For example: 3 for 3 pixels	1	25.0
<code>panelfontsize</code>	text	To set the size of the text in pixels. For example: 20 for 20 pixels	16	25.0
<code>paneltextcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0
<code>tabactivebgcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0

tabactivetextcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
tabbgcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
tabbordercolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
tabborderwidth	text	To change the width of tabs border in pixels (1 by default). For example: 3 for 3 pixels	1	25.0
tabfontsize	text	To set the size of the tabs text in pixels. For example: 20 for 20 pixels	16	25.0
tabtextcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
name	text	Unique tabset name (if you want the last state to be remembered). Example:user_profile_tabs		4.0
inside_pretty	(blank) n y	Parse pretty tracker variables within tabs	n	8.0
panelborderstyle	(blank) none hidden dotted dashed solid double groove ridge inset outset	Determine the kind of border to apply to the panels	none	25.0
panelfontweight	(blank) normal bold bolder lighter 900	Use to define the thickness of the text characters to be displayed in the panels	normal	25.0
paneltextstyle	(blank) normal italic oblique	Use to change the panels text style	normal	25.0
tabborderstyle	(blank) none hidden dotted dashed solid double groove ridge inset outset	Determine the kind of border to apply to the tabs	none	25.0

direction	(blank) horizontal vertical	Change direction of tabs (horizontal by default).	horizontal	25.0
tabfontstyle	(blank) normal italic oblique	Use to specify the font style of the tabs text	normal	25.0
tabfontweight	(blank) normal bold bolder lighter 900	Use to define the thickness of the text characters to be displayed in the tabs	normal	25.0
toggle	(blank) y n	Allow toggling between tabs and no-tabs view	y	8.0

Example

This code:

```
{TABS(name="user_tabset_01" tabs="Title 1|Title 2|Title3")}This is the content of the first tab ///// This is the content of the second tab ///// This is the content of the third tab {TABS}
```

Would produce:

This is the content of the first tab

This is the content of the second tab

This is the content of the third tab

When clicking on a tab name, the content of each tab is loaded and shown without refreshing the browser window.

And when clicking on the "**No Tabs**" option, the display would change into:



Related pages

- [PluginPageTabs](#)

Aliases

[Plugintabs](#) | [Plugintab](#) | [PluginTab](#) | [Plugin Tabs](#) | [Plugin tabs](#)