

Plugin Tracker Prefill

Introduced in [Tiki2](#)

Use this [wiki plugin](#) for [trackers](#) to display a button with a link to a page containing a tracker plugin [PluginTracker](#). In the parameters, you will be able to specify default values for some fields.

Parameters

Create a button to prefill tracker fields

Introduced in Tiki 2. Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: feature_trackers, wikiplugin_trackerprefill

Parameters	Accepted Values	Description	Default	Since
<code>value1</code>	any string except for HTML and PHP tags	Content that should be used to prefill the field.		2.0
<code>field1</code>	digits	Field ID for the first field		2.0
<code>page</code>	pagename	Tracker page name		2.0
<code>label</code>	text	Button Label.		2.0
<code>urlparams</code>	any string except for HTML and PHP tags	Parameters to pass in the URL, for example, <code>&my_parameter1=123&my_parameter2=q</code>		6.0
<code>value2</code>	any string except for HTML and PHP tags	Content that should be used to prefill the field.		2.0

<code>value3</code>	any string except for HTML and PHP tags	Content that should be used to prefill the field.	2.0
<code>value4</code>	any string except for HTML and PHP tags	Content that should be used to prefill the field.	2.0
<code>value5</code>	any string except for HTML and PHP tags	Content that should be used to prefill the field.	2.0
<code>value6</code>	any string except for HTML and PHP tags	Content that should be used to prefill the field.	2.0
<code>value7</code>	any string except for HTML and PHP tags	Content that should be used to prefill the field.	2.0
<code>value8</code>	any string except for HTML and PHP tags	Content that should be used to prefill the field.	2.0
<code>field2</code>	digits	Field ID for the second field	2.0
<code>field3</code>	digits	Field ID for the third field	2.0
<code>field4</code>	digits	Field ID for the fourth field	2.0
<code>field5</code>	digits	Field ID for the fifth field	2.0
<code>field6</code>	digits	Field ID for the sixth field	2.0
<code>field7</code>	digits	Field ID for the seventh field	2.0
<code>field8</code>	digits	Field ID for the eighth field	2.0

Example

```
{trackerprefill page="Order" label="Order" field1="2" value1="Shoes" field2="3" value2="10"}
```

The above syntax will create a button labelled "Order" that will link to `tiki-index_raw.php?page=Order&prefills=2:3&values[]`=Shoes&`values[]`=10

If the wiki page named "Order" contains a tracker plugin with 2 fields (2 and 3), the tracker form will prefill in the fields 2 and 3 values "Shoes" and "10".