

## Windows Server Install

## Windows 2008R2 Server setup

[ - ]

This documentation provides detailed notes on a successful new installation of [Tiki4.0](#) on a **Windows 2008R2 Server**.

Hopefully this will allow more TikiWiki users to take advantage of a Windows/IIS environment without the need of a WAMP install.

### URL Rewrite module

Proper operation of Tiki versions prior to 8 on IIS requires that the URL Rewrite module for IIS is installed.

- [Download the URL Rewrite Module](#).

## Special setup for img tracker field type

Special setup to show uploaded images from tracker field img is needed. please see here: [Image Tracker Field](#)

## Software used:

- Windows2008R2 Server Standard Edition (x64) - IIS 7
- MySQL 5.1.41 (x64) Community Edition
- MySQL GUI tools 5.0-r17-win32 (optional, but much easier)
- PHP 5.3.1 nts-Win32-VC9 (x86)

## Installed Windows:

- Joined Domain, set static IP. (Running as Administrator)
- Added IIS Role
- Features for IIS:

### *Common HTTP Features*

- Static Content
- Default Document
- Directory Browsing
- HTTP Errors
- HTTP Redirection

### *Application Development*

- ASP.NET
- .Net Extensibility
- CGI
- ISAPI Extensions
- ISAPI Filters

### *Health and Diagnostics*

- HTTP Logging
- Request Monitor

### *Security*

- Request Filtering

### *Performance*

- Static Content Compression

### *Management Tools*

- IIS Management Console

Windows: Turned off IE Enhanced Security

Windows: Ran MS Update installed all important and all optional updates.

Windows: Reboot server

## Installed other software

Installed MySQL (x64) all defaults.

Installed MySQL GUI Tools.

Installed PHP 5.3.1 (x86) default settings installed to C:\PHP

Windows: Created C:\Temp directory

Windows: Under Security Settings, added everyone with full permissions to the following directories:

\*C:\inetpub\wwwroot\

- C:\PHP\
- C:\Program files\MySQL
- C:\Temp

Edited PHP.INI

- include\_path = ".;c:\php\includes" - uncommented (line 787)
- cgi.force\_redirect = 1 - uncommented (line 822)
- fastcgi.impersonate = 1; - uncommented (line 850)
- upload\_tmp\_dir="C:\temp" - changed from c:\windows\temp (line 908)
- session.save\_path="C:\temp" changed from c:\windows\temp (line 909)
- error\_log="C:\temp\php-errors.log" changed from c:\windows\temp (line 910)
- date.timezone = America/New\_York changed from blank (line 962)
- sendmail\_from = my email address changed from blank (line 1056)

Windows: Opened port 3306 in windows firewall for remote MySQL client tools access.

Windows: Unzipped TikiWiki 4.0 to c:\inetpub\wwwroot\tw4

Windows: Created a phpinfo.php file in c:\inetpub\wwwroot to validate the php install.

From LAN workstation:

Verified MySQL remote connectivity and using MySQL Query Browser, created a new schema (database) named Tiki4.

Opened IE8 and connected to the phpinfo.php page to verify PHP install and settings.

Take dog for walk and hoping for success!

From LAN workstation, opened FireFox Browser and pointed to the tw4 path, and got the tiki-install.php page.

-

## TikiWiki 4.0 Install

[\[+\]](#)

Select your language: English

*Click continue*

read the license

*click continue*

## Review the System Requirements

Memory: Tiki has detected your PHP memory\_limit at: 128 MB.

mail: did not test (have not set mail server yet)

Image Processing: Tiki detected: GD bundled (2.0.34 compatible).

*click continue*

## Set the Database Connection

Database Type: MySQL Improved (mysqli). Requires MySQL 4.1+

- Host name: 192.168.0.40
- Database name: tw4
  
- Database User: root
- Database Password: \*\*\*\*\*

*click continue*

Install - A new install will populate the database.

*click install*

## Review the Installation

Installation complete

Installation operations executed successfully: 5469 SQL queries.

*click continue*

## Configure General Settings

Browser Title: KCDI Intranet

Sender email: my email address

HTTPS login: Disabled (no change)

Admin email: my email address

*click to continue*

## Enter Your Tiki

*click Enter Tiki and Lock Installer (Recommended)*

# HomePage

Congratulations

This is the default HomePage for your Tiki. If you are seeing this page, your installation was successful.

admin / admin

*click login*

# Change password enforced

old password: admin

new password: \*\*\*\*\*

repeat password: \*\*\*\*\*

*click change*

# HomePage

Edit Section

Edit Section

Thank you for installing Tiki.

The entire Tiki Community would like to thank you and help you get introduced to Tiki.

---

-

Aliases

---

[Windows Server](#) | [WindowsServer](#)

# Notes from IIS project for Tiki 5

[ - ]

(Spring 2010 notes by jonnyb)

## Issues (install from svn HEAD)

- Writable dirs not detected (by installer or tiki main)
  - Caused major issues, but only had to set /temp, /templates\_c and db/local.php to run
- Mail - errors from zend on smtp (default installation)
  - SMTP probably not running on server
  - Then needs tying into PHP?
  - Tiki SMTP is broken (fails with a timeout, on Windows as well as Unix). Chealer9 20100709
- file write error on new tpl's

### ◦ example error

PHP (5.2.12) ERROR (E\_WARNING): File:

C:\inetpub\wwwroot\tiki\lib\smarty\libs\internals\core.write\_file.php Line: 44 Type: unlink(C:\inetpub\wwwroot\tiki\templates\_c\ en^%%23^230^230491F8%%tiki-list\_blogs.tpl.php) [function.unlink]: No such file or directory

- That function blindly asks to delete a file without knowing whether it exists. This should be fine and most performant (since it saves a filesystem operation) using the PHP @ error-quieting operator, but that operator has no effect on Tiki since it uses custom error handling. This could be considered a PHP/Smarty bug highlighted by Tiki. We have a similar problem with php-openid. Chealer9 20100709



## TikiWiki 5.0 Beta1 Install

I created a new Windows 2008R2 virtual server and using the basics listed above, installed 5.0 Beta 1 successfully.

I decided to use the latest software available, and ran into database errors during the Tiki installation with PHP 5.3.2 nts-Win32-VC9 (x386). This could have resulted in missing a line in the php.ini file, but I am pretty certain everything was in order. After starting over, I went back to 5.3.1 and had no issues.

I also used the latest version of MySQL (5.1.45 x64) with no problems.

Everything else was standard as per above.

Once I had a successful database creation, the page that came up looked like plain html. No formatting at all. However, I was able to change admin password and get into the site. After checking on #tikiwiki, Caarrie pointed me to Admin/Performance. There I unchecked the "Minify CSS" and all of the formatting was perfect! (Thanks again Caarrie). I am not sure if this is a default setting on installation, but if you run into this problem, it is a simple fix.

## Related links

- <https://wikisuite.org/How-to-install-WikiSuite-on-Windows-Server>