

PluginList sublist

New in Tiki27, permitting to improve [PluginList](#), and fixes/enhancements are being backported to the Tiki26 branch. Once it is more stable/robust, it may also be backported to Tiki24.

This was one of the recommendations from this large project: [FOSDEM 2024](#)

Related Merge request: [PluginList SUBLIST MR](#)

Example Usage

PluginList SUBLIST gives the ability to join several trackers and get mixed results into a single array, greatly optimizing the performance when subqueries and sub-list plugins are needed.

Steps to follow:

1. Create a tracker called **Region** with ID, Name as fields (tracker_id = 1)
2. Create an other tracker called **Hospital** with ID, Name and Region (Item Link pointing to region tracker) (tracker_id = 2)
3. Fill all trackers with data as well
4. Apply this code:

```
!!! Stock table template {LIST()} {filter type="trackeritem"} {filter field="tracker_id" exact="2"}  
{SUBLIST(name="region")}{filter field="tracker_id" exact="1"} {filter field="object_id"  
exact="$parent.tracker_field_hospitalRegion$"} {FORMAT(name="name")}{display name="tracker field_regionName"  
default="" }{FORMAT} {SUBLIST} {OUTPUT(template="table")}{column field="hospital" label="Hospital" mode="raw"}  
{column field="region" label="Region" mode="raw"} {OUTPUT}{FORMAT(name="hospital")}{display  
name="tracker_field_hospitalName" default="" }{FORMAT} {FORMAT(name="region")}{display name="region.name"  
default="" }{FORMAT} {LIST}
```

First List Plugin joins tracker 1 (tracker Region) and tracker 2 (tracker Hospital) with an Item Link field in tracker 2 (tracker Hospital) pointing to tracker 1 (tracker Region) called **tracker_field_hospitalRegion**....Sublist filters the results by the ID of the record coming from the parent tracker(here tracker Region).

Output template is using the stock table template with wiki formatting the name field of tracker 1 (tracker Region) and then wiki formatting the table column for region name using nested keys like 'region.name'.

Region is the key name in SUBLIST block, so it adds an array of records in the parent row under the 'region' key. Then, it formats and adds the tracker 1 (tracker Region) field(s) to that key for each parent record.

The given above code in step 4, would produce (accordingly to the data filled in trackers...step 3):

The screenshot shows the Tiki Wiki CMS Groupware interface with a sidebar containing a 'System Menu' with links for Home, Search, Wiki, File Galleries, Trackers, and Settings. The main content area has a title 'hospitals-regions' and a subtitle 'Stock table template'. Below this is a table with two columns: 'Hospital' and 'Region'. The data rows are: Mercy General Hospital (North America), Rio General Hospital (South America), Paris Medical Center (Europe), Beijing Central Hospital (Asia), and Cairo University Hospital (Africa). At the bottom of the table are buttons for 'Edit', 'Rename', 'History', 'Source', and 'More+'. The entire table area is enclosed in a red box. At the bottom of the page, there is a link 'Click to expand'.

Hospital	Region
Mercy General Hospital	North America
Rio General Hospital	South America
Paris Medical Center	Europe
Beijing Central Hospital	Asia
Cairo University Hospital	Africa

Example Using Pivot table

You can use SUBLIST in pivottable as you normally would in a plugin list - define the SUBLIST and either format some of the columns there or leave all columns (skip formatting blocks in sublist). In order for the results to appear in the main pivottable array of data, you must include the fields in the display blocks in the main pivottable.

Assure that you have the two trackers as documented above, then apply this code:

```
{PIVOTTABLE(data="tracker:2" cols="region.regionName" vals="hospitalName" colOrder="key_a_to_z"
rowOrder="key_a_to_z" rendererName="Table" aggregatorName="List Unique Values" inclusions="{}" menuLimit="500"
aggregateDetails="object_type" highlightMine="n" highlightGroup="n" chartHoverBar="y")} {display
name="tracker_field_hospitalName"} {display name="region.tracker_field_regionName"} {SUBLIST(name="region"
required="2")} {filter field="tracker_id" exact="1"} {filter field="object_id" exact="$parent.tracker_field_hospitalRegion$"}
{SUBLIST} {PIVOTTABLE}
```

This example shows how to include 2 remote tracker fields (tracker_field_hospitalName, tracker_field_regionName) in the parent result set using the keys 'tracker_field_hospitalName' and 'region.tracker_field_regionName'. These 2 will appear as fields in the [PluginPivotTable](#) and you would be able to use them as normal fields.

The given above code would produce:

region.regionName	Africa	Asia	Europe	North America	South America	Totals
Totals	Cairo University Hospital	Beijing Central Hospital	Paris Medical Center	Mercy General Hospital	Rio General Hospital	Beijing Central Hospital, Cairo University Hospital, Mercy General Hospital, Paris Medical Center, Rio General Hospital

Click to expand

Related

See also:

- [PluginTrackerList](#)
- [PluginTrackerList To PluginList Converter](#)
- [PluginTracker](#)
- [PluginList](#)
- [PluginPivotTable](#)