

# Tabs 플러그인

추가 참조: [Page Tabs 플러그인](#)

이 [위키 플러그인](#) 을 사용하여 위키 페이지에 탭으로 컨텐츠를 배열하십시오.

## 매개변수

Arrange content in tabs

*Introduced in Tiki 4. Required parameters are in **bold**.*

[Go to the source code](#)

Preferences required: `wikiplugin_tabs`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Tabs content, separated by "////"		
<b>tabs</b>	text	Pipe-separated list of tab titles. Example: <code>tab 1 tab 2 tab 3</code>	4.0	
panelbgcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
panelbordercolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
panelborderwidth	text	To change the width of panel border in pixels (1 by default). For example: 3 for 3 pixels	1	25.0
panelfontsize	text	To set the size of the text in pixels. For example: 20 for 20 pixels	16	25.0
paneltextcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
tabactivebgcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
tabactivetextcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
tabbgcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
tabbordercolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).	25.0	
tabborderwidth	text	To change the width of tabs border in pixels (1 by default). For example: 3 for 3 pixels	1	25.0

<b>tabfontsize</b>	text	To set the size of the tabs text in pixels. For example: 20 for 20 pixels	16	25.0
<b>tabtextcolor</b>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
<b>name</b>	text	Unique tabset name (if you want the last state to be remembered). Example: <code>user_profile_tabs</code>		4.0
<b>inside_pretty</b>	(blank) n y	Parse pretty tracker variables within tabs	n	8.0
<b>panelborderstyle</b>	(blank)  none  hidden  dotted  dashed  solid  double  groove  ridge  inset  outset	Determine the kind of border to apply to the panels	none	25.0
<b>panelfontweight</b>	(blank) normal bold bolder lighter 900	Use to define the thickness of the text characters to be displayed in the panels	normal	25.0
<b>paneltextstyle</b>	(blank) normal italic oblique	Use to change the panels text style	normal	25.0
<b>tabborderstyle</b>	(blank)  none  hidden  dotted  dashed  solid  double  groove  ridge  inset  outset	Determine the kind of border to apply to the tabs	none	25.0
<b>direction</b>	(blank) horizontal vertical	Change direction of tabs (horizontal by default).	horizontal	25.0
<b>tabfontstyle</b>	(blank) normal italic oblique	Use to specify the font style of the tabs text	normal	25.0
<b>tabfontweight</b>	(blank) normal bold bolder lighter 900	Use to define the thickness of the text characters to be displayed in the tabs	normal	25.0

toggle	(blank)	Allow toggling between tabs and no-tabs view	y	8.0
	y			
	n			

## 예제

다음 코드는:

{TABS(name="user\_tabset\_01", tabs="제목 1|제목 2|제목 3")}이란 첫번째 템의 컨텐츠입니다 ///// 이것은 두번째 템의 컨텐츠입니다 ///// 이것은 세번째 템의 컨텐츠입니다 {TABS}

다음의 결과를 야기합니다:

이는 첫번째 템의 컨텐츠입니다

이것은 두번째 템의 컨텐츠입니다

이것은 세번째 템의 컨텐츠입니다

템 이름을 클릭할 때, 각 템의 컨테츠가 로드되며 브라우저 창을 새로고침하지 않고 서버에 연결하지 않고 표시됩니다.

그리고, "No Tabs" 선택사항을 클릭하면, 표시가 다음과 같이 변경됩니다:



## Related pages

- [Wiki Plugin](#) - has links to all plugins and describes how the syntax works for a plugin
  - [Mods Type Wikiplugins](#)

별칭