

Plugin Dialog

Introduced with [Tiki8](#)

Use this [wiki plugin](#) to create a custom pop-up dialog box using jQuery UI.

Parameters

Create a custom popup dialog box

Introduced in Tiki 8. Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: wikiplugin_dialog

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Array		
buttons	text	Use comma-separated values for multiple buttons		8.0
size	sm md lg xl fullscreen	Size of the modal dialog. Default is medium	md	28.0
wiki	pagename	Wiki page to use as dialog body		8.0
buttonsActions	text	JavaScript to perform on button click. Use comma-separated values for multiple buttons		28.0
buttonsClassNames	text	Css class names to apply to the buttons. Use comma-separated values for multiple buttons.		28.0
title	text			8.0
actions	text	JavaScript to perform on button click. Use comma-separated values for multiple buttons		8.0
id	text	Allowing to control the modal via JS. Automatically generated if left empty in the form (it has to be unique)		8.0
openAction	rawhtml_unsafe	JavaScript callback function to execute when dialog opens.		8.0
staticBackdrop	y n	If true, the modal will not close when clicking outside of the modal	n	28.0
autoOpen	(blank) y n	Open the modal automatically	n	8.0
showAnim	y n	Allow the modal to open with a fade in effect	y	8.0
showCloseIcon	y n	Show a close icon in the header of the modal	y	28.0

useWikiContent	y n	Use wiki page content as the dialog body	n	28.0
----------------	--------	--	---	------

Example

This code will cause a pop-up dialog box to appear when this page is loaded:

Plugin

```
{DIALOG(title="World hello Dialog!" buttons="Foo,Bar" actions="alert(\"foo clicked\"),alert(\"you cancelled\")"
showAnim="blind" hideAnim="explode" autoOpen="y" modal="y" wiki="plugin dialog test body"
openAction="testDialog(this);")}Hello World{DIALOG}
```

World hello Dialog!

Foo
Bar

Example with smarty template

The following code will cause a popup dialog window.

Put this in at the end of your template file:

sample.tpl

```
{wikiplugin _name="DIALOG" autoOpen="n" id="wpdialog_bobshop_shipping" title="Shipping Costs" modal="y"
wiki="bobshop_shipping"}{/wikiplugin}
```

Don't forget the underscore "_" before the parameter "_name".

Place this code in your template file at the place you want:

sample.tpl

```
<p onClick='javascript:$( "#wpdialog_bobshop_shipping" ).dialog( "open" );'>Shipping</p>
```

In this example there must be a wikipage called "bobshop_shipping". Feel free to create it.

More info for params "hideAnim" and "showAdnim"

More option for the show and hide animations can be found [here](#).

Related pages

- [Jquery Dialog docs](#)

Aliases

[Plugin Dialog](#) | [Dialog](#)