

Plugin Tracker Item Field

Introduced in [Tiki2](#)

Use this [wiki plugin](#) to display or test the value of a field of a tracker item.

Requirements

- The field must not be hidden
- To test or display a field, you must have the `tiki_p_view_trackers` (or `tiki_p_view_trackers_pending` or `tiki_p_view_trackers_closed` permission depending on the status of the item
- The status can be tested without permission

Parameters

Display or test the value of a tracker item field

Introduced in [Tiki 2](#).

[Go to the source code](#)

Preferences required: `wikiplugin_trackeritemfield`, `feature_trackers`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Wiki text containing an {ELSE} marker.		
value	text	Value to compare against.		2.0
itemId	digits	Numeric value representing the item ID. Default is the user tracker item for the current user.		2.0
list_mode	(blank) y n csv	Set output format. Yes (y) displays tracker item field with truncated values (default); No (n) displays in tracker item field view; Comma Separated Values (csv) outputs without any HTML formatting.	y	25.0
status	(blank) o p c op oc pc opc	Status of the tracker item		2.0
test	(blank) 1 0	Set to Yes (1) to test whether a field is empty (if value parameter is empty) or has a value the same as the value parameter.		2.0
trackerId	digits	Numeric value representing the tracker ID.		2.0
fieldId	digits	Numeric value representing the field ID displayed or tested		2.0
fields	text <i>separator: :</i>	Colon-separated list of field IDs. Default is all fields		2.0

Limitation

The field must be a simple value (not computed, not item list). The tracker item can be specified by its ID with the `itemId` plugin param. If it is not specified and the url used to access the page has a `itemId` parameter, the value of `itemId` parameter will be used. If after this test is not set and if the [User Tracker](#) feature is set on, the user item of the user will be selected.

Examples

For example, you have a user tracker with a field containing the phone number of the user, you can use this plugin with the `fieldId=phone_field_id` to display in the page the phone number of the user looking at the page:

```
{trackeritemfield fieldId="1"}
```

Another example, you want to add a link in a page to a page where a user can fill his user tracker only if the user has no user tracker. You can use this plugin with the `fieldId` that is the user selector field.

```
{TRACKERITEMFIELD(fieldId="1" test="1")}Welcome new member, please visit ((this_page)) to fill up your  
information{TRACKERITEMFIELD}
```

A field can be tested against a value

```
{TRACKERITEMFIELD(fieldId="1" test="1" value="toto")}Yes your name is toto{TRACKERITEMFIELD}
```

See [Tracker Field Types](#) for values to match for special fields such as checkboxes.

If you want to do the same thing with a tracker that is not the user tracker but has only one item per user and has a field user selector/1, you can specify the tracker ID like this

```
{trackeritemfield trackerId="1" fieldId="1"} {TRACKERITEMFIELD(trackerId="1" fieldId="1" test="1")}Please fill out your  
review{TRACKERITEMFIELD}
```

It is also possible to test the status of the user item. For instance if you want to display something only if the item is pending or closed:

```
{TRACKERITEMFIELD(status="pc")}Sorry, your survey is being processed{TRACKERITEMFIELD}
```

It is also possible to test if all the fields of an item are not empty:

```
{TRACKERITEMFIELD(trackerId="1" fields="")}Thank you your form is complete{TRACKERITEMFIELD}
```

It is also possible to test an alternative:

```
{TRACKERITEMFIELD(fieldId="1" test="1")}OK{ELSE}NOT OK{TRACKERITEMFIELD}
```

It is possible to have multiple levels of ELSE:

```
{TRACKERITEMFIELD(fieldId="1" test="1")}OK{ELSE}{TRACKERITEMFIELD(fieldId="2" test="2")}super ok{ELSE}NOT OK{TRACKERITEMFIELD}{TRACKERITEMFIELD}
```

Note the order the other test with always be in the ELSE part.

This plugin is also very useful when you want to show only some filtered values from a tracker field and for empty ones - to hide the messy warnings like "No value for 'tracker_field_xxx'".

```
{LIST()} {pagination max=10} {filter field="tracker_id" content="2"} {OUTPUT(template="table")} {column label="Id" field="itemid" class="text-left" mode="raw"} {column label="object_id" field="object_id"} {column label="Name" field="name" sort="name" class="text-nowrap"} {column label="Discount" field="discount"} {OUTPUT} {FORMAT(name="itemid")}{display name="tracker_field_shopProductId" format="trackerrender"}{FORMAT} {FORMAT(name="object_id")}{display name="object_id"}{FORMAT} {FORMAT(name="name")}{display name="tracker_field_shopProductName"}{FORMAT} {FORMAT(name="discount")} {TRACKERITEMFIELD(trackerId="2" fieldId="143" itemId={display name="object_id" test="0" value=""}) {display name="tracker_field_shopProductDiscount" format="trackerrender"} {TRACKERITEMFIELD} {FORMAT} {LIST}
```

The trick here is to assign itemId value like this:

```
itemId={display name="object_id"}
```

Related

- [PluginTrackerIf](#)
- [PluginTrackerToggle](#)

Aliases

- [Mod trackeritemfield](#)