

## Miscellaneous tab

### Overview

Use this tab to configure additional Look & Feel settings for your site.

### Related Topics

- [Tiki Themes](#)

### To Access

From the [Look and Feel Admin](#) page, click the **Miscellaneous** tab.

Option	Description	Default
Use tabs	Separates page content into tabbed panels	Enabled
Tabs optional	Users can choose not to have tabs. A <b>no tabs</b> button will be displayed.	Enabled
<a href="#">Favicons</a>	Custom favicon image files can be put in the /themes/(themename)/favicons directory, or the default Tiki favicons can be used.	Enabled
Default for img-fluid class used in the IMG plugin	Default option for whether an image produced with the IMG plugin has the img-fluid class - a plugin parameter allows this to be overridden	Enabled
Use context menus for actions (icons)	<i>Currently used in File Galleries only.</i>	Enabled
Use context menus for actions (text)	<i>Currently used in File Galleries only.</i>	Enabled
Locations (breadcrumbs)	<i>Examples: » / &gt; : -&gt; →</i>	»
Choices	<i>Examples:   /   :</i>	
Smarty template usage indicator	Add HTML comment at start and end of each Smarty template (.tpl file) <i>Clear the Tiki system cache for this change to take effect. Use only for development, not in production at a live site, because these warnings are added to emails as well, and are visible to users in the page source. May impact performance</i>	Disabled
Smarty compilation	Indicates when the template cache should be refreshed. Modified   Never check (performance)   Always (development, slow)	Modified
Smarty cache permissions	Permissions that enable Smarty to write to the templates_c directory. User writable (0644)   User & group writable (0664)	User writable (0644)

Option	Description	Default
<a href="#">Provides the current categories to Smarty templates</a>	When enabled, the \$objectCategoryIds variable is set to the identifiers of the categories of the object being viewed. This allows showing alternate content depending on the categories of the current object, but reduces performance.	Disabled
Add base tag in the HTML head section	The base tag specifies a default address for all links on a page.	Disabled

Option	Description	Default
Use tabs	Separates page content into tabbed panels	Enabled
Tabs optional	Users can choose not to have tabs. A <b>no tabs</b> button will be displayed.	Enabled
<a href="#">Favicons</a>	Custom favicon image files can be put in the /themes/(themename)/favicons directory, or the default Tiki favicons can be used.	Enabled
Default for img-fluid class used in the IMG plugin	Default option for whether an image produced with the IMG plugin has the img-fluid class - a plugin parameter allows this to be overridden	Enabled
Use context menus for actions (icons)	<i>Currently used in File Galleries only.</i>	Enabled
Use context menus for actions (text)	<i>Currently used in File Galleries only.</i>	Enabled
Locations (breadcrumbs)	<i>Examples: » / &gt; : -&gt; →</i>	»
Choices	<i>Examples:   /   :</i>	
Smarty template usage indicator	Add HTML comment at start and end of each Smarty template (.tpl file) <i>You need to clear your Tiki template cache for this change to take effect</i> <i>Use only for development, not in production at a live site, because these warnings are added to emails as well, and are visible to users in the page source.</i> <i>May impact performance</i>	Disabled
Smarty compilation	Indicates when the template cache should be refreshed. Modified   Never check (performance)   Always (development, slow)	Modified
Smarty cache permissions	Permissions that enable Smarty to write to the templates_c directory. User writable (0644)   User & group writable (0664)	User writable (0644)

Option	Description	Default
<a href="#">Provides the current categories to Smarty templates</a>	When enabled, the \$objectCategoryIds variable is set to the identifiers of the categories of the object being viewed. This allows showing alternate content depending on the categories of the current object, but reduces performance.	Disabled
Add base tag in the HTML head section	The base tag specifies a default address for all links on a page.	Disabled

Option	Description	Default
Use tabs	Separates page content into tabbed panels	Enabled
Tabs optional	Users can choose not to have tabs. A <b>no tabs</b> button will be displayed.	Enabled
<a href="#">Favicons</a>	Custom favicon image files can be put in the /themes/(themename)/favicons directory, or the default Tiki favicons can be used.	Enabled
Default for img-fluid class used in the IMG plugin	Default option for whether an image produced with the IMG plugin has the img-fluid class - a plugin parameter allows this to be overridden	Enabled
Use context menus for actions (icons)	<i>Currently used in File Galleries only.</i>	Enabled
Use context menus for actions (text)	<i>Currently used in File Galleries only.</i>	Enabled
Locations (breadcrumbs)	<i>Examples: » / &gt; : -&gt; →</i>	»
Choices	<i>Examples:   /   :</i>	
Smarty template usage indicator	Add HTML comment at start and end of each Smarty template (.tpl file) <i>You need to clear your Tiki template cache for this change to take effect</i> <i>Use only for development, not in production at a live site, because these warnings are added to emails as well, and are visible to users in the page source.</i> <i>May impact performance</i>	Disabled
Smarty compilation	Indicates when the template cache should be refreshed. Modified   Never check (performance)   Always (development, slow)	Modified
Smarty cache permissions	Permissions that enable Smarty to write to the templates_c directory. User writable (0644)   User & group writable (0664)	User writable (0644)

Option	Description	Default
<a href="#">Provides the current categories to Smarty templates</a>	When enabled, the \$objectCategoryIds variable is set to the identifiers of the categories of the object being viewed. This allows showing alternate content depending on the categories of the current object, but reduces performance.	Disabled
Add base tag in the HTML head section	The base tag specifies a default address for all links on a page.	Disabled