

Plugin Code

This [wiki plugin](#) is used to display any source code (including wiki syntax) on a page without it being processed. The code is displayed in a gray box in a fixed-width monospaced font. A title can be added to the box and line numbers added. Syntax highlighting is also available, since Tiki7 using [CodeMirror](#) and using GeSHi before that.

Parameters

Introduced in Tiki 1.

[Go to the source code](#)

Preferences required: `wikiplugin_code`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Code to be displayed		
<code>caption</code>	text	Code snippet label.		1
<code>colors</code>	text	Any supported language listed at http://codemirror.net/mode/		17
<code>wrap</code>	(blank) 1 0	Wrap lines of code which do not fit in the display box's width. Enabling avoids overflow or hidden line ends.	1	
<code>theme</code>	default 3024-day 3024-night abcdef ambiance ambiance-mobile base16-dark base16-light bespin blackboard cobalt colorforth dracula eclipse elegant erlang-dark hopscotch icecoder isotope lesser-dark liquibyte material mbo mdn-like midnight monokai neat neo night panda-syntax paraiso-dark paraiso-light pastel-on-dark railscasts rubyblue seti solarized the-matrix tomorrow-night-bright tomorrow-night-eighties ttcn twilight vibrant-ink xq-dark xq-light yeti zenburn	Any supported theme listed at https://codemirror.net/demo/theme.html		17

<code>ln</code>	(blank) 1 0	Show line numbers for each line of code.	1
<code>rtl</code>	(blank) 1 0	Switch the text display from left to right, to right to left (left to right by default)	1
<code>mediawiki</code>	(blank) 1 0	Encloses the code in an HTML code tag, for example: <code>&lt;code&gt;user input&lt;code&gt;</code>	0 8.3

Syntax highlighting

To activate syntax highlighting and enjoy most of the options (lines number, colors, etc), the Code editor (CodeMirror) feature must be enabled at [Control Panels > Editing and Plugins > General Settings \(tab\) > Features \(pane\)](#).

See the list of [CodeMirror](#) supported languages that can be used for the `colors` parameter.

Example

PHP with line numbers

This code:



```
{CODE(colors="php")}
<?php
$menu = $menubar->getHomeMenu();
if($menu->link != "") {
    print "\t<td width=\"7%\" valign=\"top\">\n";
    $menu->printMenu();
    print "\t</td>\n";
}
{CODE}
```

Would produce:



```
<?php
$menu = $menubar->getHomeMenu();
if($menu->link != "") {
    print "\t<td width=\"7%\" valign=\"top\">\n";
    $menu->printMenu();
    print "\t</td>\n";
}
```

Tiki syntax highlighting

Tiki syntax is supported too.

This code:



```
{CODE(colors="tiki")}  
{img attId="57|58|59" desc="desc" alt="Sample Images" thumb="y" stylebox="float: left;  
margin-right:10px"}  
{CODE}
```

Would produce:



```
{img attId="57|58|59" desc="desc" alt="Sample Images" thumb="y" stylebox="float: left;  
margin-right:10px"}
```

Legacy GeSHi Documentation (deprecated in Tiki8)

[+]

Related pages

- [GeSHi - Generic Syntax Highlighter](#)
- [Syntax Highlighter](#)
- [CodeMirror](#)

Aliases

[Plugin Code](#)