

## Plugin Tracker Prefill

Introduced in [Tiki2](#)

Use this [wiki plugin](#) for [trackers](#) to display a button with a link to a page containing a tracker plugin [PluginTracker](#). In the parameters, you will be able to specify default values for some fields.

### Parameters

Create a button to prefill tracker fields

Introduced in Tiki 2. Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: feature\_trackers, wikiplugin\_trackerprefill

| Parameters       | Accepted Values                         | Description                                                                    | Default | Since |
|------------------|-----------------------------------------|--------------------------------------------------------------------------------|---------|-------|
| <b>value1</b>    | any string except for HTML and PHP tags | Content that should be used to prefill the field.                              |         | 2.0   |
| <b>field1</b>    | digits                                  | Field ID for the first field                                                   |         | 2.0   |
| <b>page</b>      | pagename                                | Tracker page name                                                              |         | 2.0   |
| <b>label</b>     | text                                    | Button Label.                                                                  |         | 2.0   |
| <b>urlparams</b> | any string except for HTML and PHP tags | Parameters to pass in the URL, for example, &my_parameter1=123&my_parameter2=q |         | 6.0   |
| <b>value2</b>    | any string except for HTML and PHP tags | Content that should be used to prefill the field.                              |         | 2.0   |
| <b>value3</b>    | any string except for HTML and PHP tags | Content that should be used to prefill the field.                              |         | 2.0   |
| <b>value4</b>    | any string except for HTML and PHP tags | Content that should be used to prefill the field.                              |         | 2.0   |
| <b>value5</b>    | any string except for HTML and PHP tags | Content that should be used to prefill the field.                              |         | 2.0   |

|                     |                                         |                                                   |     |
|---------------------|-----------------------------------------|---------------------------------------------------|-----|
| <code>value6</code> | any string except for HTML and PHP tags | Content that should be used to prefill the field. | 2.0 |
| <code>value7</code> | any string except for HTML and PHP tags | Content that should be used to prefill the field. | 2.0 |
| <code>value8</code> | any string except for HTML and PHP tags | Content that should be used to prefill the field. | 2.0 |
| <code>field2</code> | digits                                  | Field ID for the second field                     | 2.0 |
| <code>field3</code> | digits                                  | Field ID for the third field                      | 2.0 |
| <code>field4</code> | digits                                  | Field ID for the fourth field                     | 2.0 |
| <code>field5</code> | digits                                  | Field ID for the fifth field                      | 2.0 |
| <code>field6</code> | digits                                  | Field ID for the sixth field                      | 2.0 |
| <code>field7</code> | digits                                  | Field ID for the seventh field                    | 2.0 |
| <code>field8</code> | digits                                  | Field ID for the eighth field                     | 2.0 |

## Example

```
{trackerprefill page="Order" label="Order" field1="2" value1="Shoes" field2="3" value2="10"}
```

The above syntax will create a button labelled "Order" that will link to `tiki-index.php?page=Order&prefills=2:3&values[]=Shoes&values[]=10`

If the wiki page named "Order" contains a tracker plugin with 2 fields (2 and 3), the tracker form will prefill in the fields 2 and 3 values "Shoes" and "10".