

# Raw page display

Tiki allows to display wiki page in "raw" format by means of calling a wiki page through [tiki-index\\_raw.php](#) with some extra parameters in the url. This is useful for highly customized content presentation of that wiki page, such as in the case of [JQS5](#) slideshow presentations or exporting file with data from pretty trackers for R scripts (see [PluginR](#) to cite just two examples).

## Usage and Parameters

To show the content of a wiki page in "raw format", you can use a combination of the following parameters in the URL:

Parameter	Accepted values	Default	Effect	Required?	Since
<i>page</i>	text (wiki page names)	default homepage	show that wiki page in raw mode	y	
<i>clean</i>			will show the page without the author & contributor information nor the labels for the buttons at the page bar (edit, source, etc)	n	6.1
<i>download</i>			will show the user a dialog to allow downloading a file on disk with the raw contents of that page instead of displaying it in the browser. Useful to be used in conjunction with the params clean, "textonly" and "filename"	n	6.1
<i>full</i>			will show most of the page with the javascript and css effects associated to it	n	5.0
<i>format</i>	jqs5		will show the page with the required javascript to display the contents as an <a href="#">S5</a> slideshow presentation	n	5.0 (broken in 16.x?)
<i>textonly</i>			will show contents of the page without any html tags, but only the text. Useful to be used in conjunction with the params "clean", "download" and "filename"	n	6.1

Parameter	Accepted values	Default	Effect	Required?	Since
<i>filename</i>	my_custom_script.r	(wiki page name)	will provide a default filename (and extension, if added) to the user in the download dialogue. Useful to be used in conjunction with the params "download"	n	6.1
<i>css</i>			will serve the page as <code>text/css</code> file type instead of <code>text/plain</code> in the download dialogue. Useful to be used in conjunction with the params <i>download</i> , <i>clean</i> and <i>textonly</i>	n	16.3/17.0

## Example 1

This code,

**Syntax for the S5 slideshow presentation**

```
http://doc.tiki.org/tiki-index_raw.php?page=ExampleSlideShow&full&format=jq5
```

Would produce on this site: (click in the url to see it)

[http://doc.tiki.org/tiki-index\\_raw.php?page=ExampleSlideShow&full&format=jq5](http://doc.tiki.org/tiki-index_raw.php?page=ExampleSlideShow&full&format=jq5)

## Example 2

This code,

**Syntax to allow downloading the contents of a page as clean text (no buttons) and in text only mode**

```
http://example.org/tiki-index_raw.php?page=Foo&itemId=33&clean&textonly&download&filename=bar.r
```

Would produce on this site: (click in the url to see it)

[http://example.org/tiki-index\\_raw.php?page=Foo&itemId=33&clean&textonly&download&filename=bar.r](http://example.org/tiki-index_raw.php?page=Foo&itemId=33&clean&textonly&download&filename=bar.r)

alias

---

[Raw display](#) | [Raw](#)