Tabs 플러그인

추가 참조: Page Tabs 플러그인

이 위키 플러그인 을 사용하여 위키 페이지에 탭으로 컨텐츠를 배열하십시오.

매개변수

Arrange content in tabs
Introduced in Tiki 4. Required parameters are in **`bold`**.
Go to the source code
Preferences required: wikiplugin_tabs

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Tabs content, separated by "/////"		
`tabs`	text	Pipe-separated list of tab titles. Example:`tab 1|tab 2|tab 3`		4.0
`panelbgcolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
`panelbordercolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
`panelborderwidth`	text	To change the width of panel border in pixels (1 by default). For example: 3 for 3 pixels	1	25.0
`panelfontsize`	text	To set the size of the text in pixels. For example: 20 for 20 pixels	16	25.0
`paneltextcolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
`tabactivebgcolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
`tabactivetextcolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
`tabbgcolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0

`tabbordercolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
`tabborderwidth`	text	To change the width of tabs border in pixels (1 by default). For example: 3 for 3 pixels	1	25.0
`tabfontsize`	text	To set the size of the tabs text in pixels. For example: 20 for 20 pixels	16	25.0
`tabtextcolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
`name`	text	Unique tabset name (if you want the last state to be remembered). Example:`user_profile_tabs`		4.0
`inside_pretty`	(blank) n y	Parse pretty tracker variables within tabs	n	8.0
`panelborderstyle`	(blank)| none| hidden| dotted| dashed| solid| double| groove| ridge| inset| outset	Determine the kind of border to apply to the panels	none	25.0
`panelfontweight`	(blank) normal bold bolder lighter 900	Use to define the thickness of the text characters to be displayed in the panels	normal	25.0
`paneltextstyle`	(blank) normal italic oblique	Use to change the panels text style	normal	25.0

`tabborderstyle`	(blank)| none| hidden| dotted| dashed| solid| double| groove| ridge| inset| outset	Determine the kind of border to apply to the tabs	none	25.0
`direction`	(blank) horizontal vertical	Change direction of tabs (horizontal by default).	horizontal	25.0
`tabfontstyle`	(blank) normal italic oblique	Use to specify the font style of the tabs text	normal	25.0
`tabfontweight`	(blank) normal bold bolder lighter 900	Use to define the thickness of the text characters to be displayed in the tabs	normal	25.0
`toggle`	(blank) y n	Allow toggling between tabs and no-tabs view	y	8.0

예제

다음 코드는:

{TABS(name="user_tabset_01", tabs="제목 1|제목 2|제목3")}이는 첫번째 탭의 컨텐츠입니다 ///// 이것은 두번째 탭의 컨텐츠입니다 ///// 이것은 세번째 탭의 컨텐츠입니다 {TABS}

다음의 결과를 야기합니다:

이는 첫번째 탭의 컨텐츠입니다

이것은 두번째 탭의 컨텐츠입니다

이것은 세번째 탭의 컨텐츠입니다

탭 이름을 클릭할 때, 각 탭의 컨텐츠가 로드되며 브라우저 창을 새로고침하지않고 서버에 연결하지 않고 표시됩니다.

그리고, "**No Tabs**" 선택사항을 클릭하면, 표시가 다음과 같이 변경됩니다:

Related pages

- Wiki Plugin - has links to all plugins and describes how the syntax works for a plugin
- Mods Type Wikiplugins

별칭

tabs플러그인 | tab플러그인 | Tab플러그인 | Tabs 플러그인 | tabs 플러그인 | 탭 플러그인