

## Tabs 플러그인

추가 참조: [Page Tabs 플러그인](#)

이 위키 플러그인 을 사용하여 위키 페이지에 탭으로 콘텐츠를 배열하십시오.

매개변수

*Introduced in Tiki 4. Required parameters are in **bold**.*

[Go to the source code](#)

*Preferences required:* `wikiplugin_tabs`

| Parameters                      | Accepted Values | Description  | Default | Since |
|---------------------------------|-----------------|--|---------|-------|
| (body of plugin)                |                 | Tabs content, separated by "/////"   |         |       |
| <b>tabs</b>                     | text            | Pipe-separated list of tab titles.<br>Example: <code>tab 1 tab 2 tab 3</code>  |         | 4.0   |
| <code>panelbgcolor</code>       | text            | Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> . |         | 25.0  |
| <code>panelbordercolor</code>   | text            | Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> . |         | 25.0  |
| <code>panelborderwidth</code>   | text            | To change the width of panel border in pixels (1 by default). For example: 3 for 3 pixels  | 1       | 25.0  |
| <code>panelfontsize</code>      | text            | To set the size of the text in pixels. For example: 20 for 20 pixels   | 16      | 25.0  |
| <code>paneltextcolor</code>     | text            | Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> . |         | 25.0  |
| <code>tabactivebgcolor</code>   | text            | Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> . |         | 25.0  |
| <code>tabactivetextcolor</code> | text            | Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> . |         | 25.0  |
| <code>tabbgcolor</code>         | text            | Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> . |         | 25.0  |
| <code>tabbordercolor</code>     | text            | Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> . |         | 25.0  |

|                               |   |   |        |      |
|-------------------------------|---|---|--------|------|
| <code>tabborderwidth</code>   | text  | To change the width of tabs border in pixels (1 by default). For example: 3 for 3 pixels                                      | 1      | 25.0 |
| <code>tabfontsize</code>      | text  | To set the size of the tabs text in pixels. For example: 20 for 20 pixels   | 16     | 25.0 |
| <code>tabtextcolor</code>     | text  | Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5). |        | 25.0 |
| <code>name</code>             | text  | Unique tabset name (if you want the last state to be remembered).<br>Example: <code>user_profile_tabs</code>                  |        | 4.0  |
| <code>inside_pretty</code>    | (blank)<br>n<br>y   | Parse pretty tracker variables within tabs  | n      | 8.0  |
| <code>panelborderstyle</code> | (blank) <br>none <br>hidden <br>dotted <br>dashed <br>solid <br>double <br>groove <br>ridge  inset <br>outset | Determine the kind of border to apply to the panels   | none   | 25.0 |
| <code>panelfontweight</code>  | (blank)<br>normal<br>bold<br>bolder<br>lighter<br>900   | Use to define the thickness of the text characters to be displayed in the panels  | normal | 25.0 |
| <code>paneltextstyle</code>   | (blank)<br>normal<br>italic<br>oblique  | Use to change the panels text style   | normal | 25.0 |

|                             |   |  |            |      |
|-----------------------------|---|--|------------|------|
| <code>tabborderstyle</code> | (blank) <br>none <br>hidden <br>dotted <br>dashed <br>solid <br>double <br>groove <br>ridge  inset <br>outset | Determine the kind of border to apply to the tabs                              | none       | 25.0 |
| <code>direction</code>      | (blank) <br>horizontal <br>vertical   | Change direction of tabs (horizontal by default).                              | horizontal | 25.0 |
| <code>tabfontstyle</code>   | (blank) <br>normal <br>italic <br>oblique   | Use to specify the font style of the tabs text                                 | normal     | 25.0 |
| <code>tabfontweight</code>  | (blank) <br>normal <br>bold <br>bolder <br>lighter <br>900  | Use to define the thickness of the text characters to be displayed in the tabs | normal     | 25.0 |
| <code>toggle</code>         | (blank) <br>y <br>n   | Allow toggling between tabs and no-tabs view                                   | y          | 8.0  |

## 예제

다음 코드는:

```
{TABS(name="user_tabset_01", tabs="제목 1|제목 2|제목3")}이는 첫번째 탭의 컨텐츠입니다
/////
이것은 두번째 탭의 컨텐츠입니다
/////
이것은 세번째 탭의 컨텐츠입니다
{TABS}
```

다음의 결과를 야기합니다:

이는 첫번째 탭의 컨텐츠입니다

이것은 두번째 탭의 컨텐츠입니다

이것은 세번째 탭의 컨텐츠입니다

탭 이름을 클릭할 때, 각 탭의 콘텐츠가 로드되며 브라우저 창을 새로고침하지 않고 서버에 연결하지 않고 표시됩니다.

그리고, "**No Tabs**" 선택사항을 클릭하면, 표시가 다음과 같이 변경됩니다:



#### Related pages

- [Wiki Plugin](#) - has links to all plugins and describes how the syntax works for a plugin
- [Mods Type Wikiplugins](#)

#### 별칭

[tabs플러그인](#) | [tab플러그인](#) | [Tab플러그인](#) | [Tabs 플러그인](#) | [tabs 플러그인](#) | [탭 플러그인](#)