

Tabs 플러그인

추가 참조: [Page Tabs 플러그인](#)

이 위키 플러그인 을 사용하여 위키 페이지에 탭으로 콘텐츠를 배열하십시오.

매개변수

*Introduced in Tiki 4. Required parameters are in **bold**.*

[Go to the source code](#)

Preferences required: `wikiplugin_tabs`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Tabs content, separated by "/////"		
tabs	text	Pipe-separated list of tab titles. Example: <code>tab 1 tab 2 tab 3</code>		4.0
<code>panelbgcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0
<code>panelbordercolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0
<code>panelborderwidth</code>	text	To change the width of panel border in pixels (1 by default). For example: 3 for 3 pixels	1	25.0
<code>panelfontsize</code>	text	To set the size of the text in pixels. For example: 20 for 20 pixels	16	25.0
<code>paneltextcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0
<code>tabactivebgcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0
<code>tabactivetextcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0
<code>tabbgcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0
<code>tabbordercolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: <code>#000</code> or <code>rgba(00, 00, 00, 0.5)</code> .		25.0

<code>tabborderwidth</code>	text	To change the width of tabs border in pixels (1 by default). For example: 3 for 3 pixels	1	25.0
<code>tabfontsize</code>	text	To set the size of the tabs text in pixels. For example: 20 for 20 pixels	16	25.0
<code>tabtextcolor</code>	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
<code>name</code>	text	Unique tabset name (if you want the last state to be remembered). Example: <code>user_profile_tabs</code>		4.0
<code>inside_pretty</code>	(blank) n y	Parse pretty tracker variables within tabs	n	8.0
<code>panelborderstyle</code>	(blank) none hidden dotted dashed solid double groove ridge inset outset	Determine the kind of border to apply to the panels	none	25.0
<code>panelfontweight</code>	(blank) normal bold bolder lighter 900	Use to define the thickness of the text characters to be displayed in the panels	normal	25.0
<code>paneltextstyle</code>	(blank) normal italic oblique	Use to change the panels text style	normal	25.0

<code>tabborderstyle</code>	(blank) none hidden dotted dashed solid double groove ridge inset outset	Determine the kind of border to apply to the tabs	none	25.0
<code>direction</code>	(blank) horizontal vertical	Change direction of tabs (horizontal by default).	horizontal	25.0
<code>tabfontstyle</code>	(blank) normal italic oblique	Use to specify the font style of the tabs text	normal	25.0
<code>tabfontweight</code>	(blank) normal bold bolder lighter 900	Use to define the thickness of the text characters to be displayed in the tabs	normal	25.0
<code>toggle</code>	(blank) y n	Allow toggling between tabs and no-tabs view	y	8.0

예제

다음 코드는:

```
{TABS(name="user_tabset_01", tabs="제목 1|제목 2|제목3")}이는 첫번째 탭의 컨텐츠입니다
/////
이것은 두번째 탭의 컨텐츠입니다
/////
이것은 세번째 탭의 컨텐츠입니다
{TABS}
```

다음의 결과를 야기합니다:

이는 첫번째 탭의 컨텐츠입니다

이것은 두번째 탭의 컨텐츠입니다

이것은 세번째 탭의 컨텐츠입니다

탭 이름을 클릭할 때, 각 탭의 콘텐츠가 로드되며 브라우저 창을 새로고침하지 않고 서버에 연결하지 않고 표시됩니다.

그리고, "**No Tabs**" 선택사항을 클릭하면, 표시가 다음과 같이 변경됩니다:



Related pages

- [Wiki Plugin](#) - has links to all plugins and describes how the syntax works for a plugin
- [Mods Type Wikiplugins](#)

별칭

[tabs플러그인](#) | [tab플러그인](#) | [Tab플러그인](#) | [Tabs 플러그인](#) | [tabs 플러그인](#) | [탭 플러그인](#)