

Die Übersetzung der Seite ist unvollständig.
Es fehlen die Übersetzungen zu 3.x und 2.x

Verschiedene Einstellungen 1

Übersicht

Einstellungen für die gesamte Site

Zugriff


Unter [Allgemeine Verwaltung](#) auf **Verschiedene Einstellungen 1** klicken.

Hinweis

Einige der Einstellungen können während der [Installation](#) konfiguriert werden
In [Tiki2](#), **alle** Funktionen noch auf einem einzelnen Tab.

Verwandte Themen

- [Installation](#)
- [System Log](#)
- [Look and Feel](#)



Verschiedene Einstellungen 1

Einstellung	Beschreibung	Standard
Suche nach neuer Version		
Tiki-Version	Zeigte Deine aktuelle Tiki version. Klicke auf Datenbank neu aufsetzen oder aktualisieren um den Tiki installer zu starten.	

Einstellung	Beschreibung	Standard
Automatisch nach neuer Version suchen	Wenn aktiviert, sucht Tiki automatisch nach einer neuen Version suchen, wenn die Seite Administrator Home aufgerufen wird - je nach Einstellung unter Prüfhäufigkeit . Tip: Melde Dich beim Tiki Newsletter an, um von neuen Version zu erfahren.	Aktiviert
Prüfhäufigkeit	Wie oft Tiki nach einer neuen Version suchen soll. Dieses Feld ist nur sichtbar, wenn Suche nach neuer Version aktiviert ist. Klicke auf Jetzt nach neuer Version suchen um auf eine Aktualisierung zu überprüfen.	wöchentlich
Site-Identität		
Browsertitel	Der Text, der in den TITLE Tag für jede Tikiseite aufgenommen wird. Dieser Text erscheint in der Titelzeile des Browsers des Benutzers .	
Anordnung des Site Titels	Anordnung des Titel in der Titelzeile des Browsers im Zusammenhang zur Beschreibung der aktuellen Seite: Vor , Nach , oder Keine .	Keine
Browsertitel Anzeigemodus	Wenn Brotkrumen verwendet werden wird festgelegt, welcher Browsertitel angezeigt wird: Genauestes Element zuerst , Allgemeinstes Element zuerst , Nur Aktuelles Element , oder Seiten Beschreibung .	Genauestes Element zuerst
Emailabender	Die Antwortadresse von Tiki, wenn Tiki Emailbenachrichtigungen versendet .	
Email		
Zeichensatz in Emails	Gebe hier den Zeichensatz an, den Tiki für seine Emailbenachrichtigungen verwenden soll.	utf-8
Zeilenumbruch in Emails	Gebe hier das Zeilenendzeichen (end-of-line, EOL) ein, dass Tiki für seine Emailbenachrichtigungen verwenden soll: CRLF oder LF .	LF
Mailversand über	Lege fest, ob Tiki Sendmail (die PHP mail() Funktion) oder SMTP zum versenden von Emailbenachrichtigungen verwenden soll.	Sendmail
Emailadresse für die Testmail	Um den Emailversand von Tiki's Emailbenachrichtigungen zu testen, trage eine Emailadresse ein und klicke auf Einstellungen übernehmen	
Protokollierung und Benachrichtigung		

Einstellung	Beschreibung	Standard
PHP Fehler berichten	Lege fest, wie Tiki PHP Fehler berichten soll: keine Fehlerausgabe, Alle PHP Fehler ausgeben , oder Alle PHP Fehler ausser Hinweisen (NOTICES) ausgeben .	Alle PHP Fehler ausser Hinweisen (NOTICES) ausgeben
Nur für Admin sichtbar	Wenn aktiviert, werden Fehler nur Benutzern mit Administratorrechten angezeigt.	Deaktiviert
Auch Smarty Hinweise	Wenn aktiviert, zeigt Tiki auch Smarty Hinweise.	Aktiviert
JavaScript ausschalten	Wenn aktiviert wird Javascript für die gesamte Site deaktiviert, auch wenn der Browser Javascript erlaubt. ⚠ Vorsicht: Nur zum Testen und zur Fehlersuche verwenden. Wenn der Haken gesetzt wird, dann werden viele Tiki Funktionen nicht mehr richtig arbeiten.	Deaktiviert
Mails in Tiki Logs protokollieren	Wenn aktiviert, wird eine Zeile des Typs mail in das System Log mit der Zieladresse und dem Betreff jeder versendeten Email aufgenommen.	Deaktiviert
SQL-Abfragen protokollieren	Wenn aktiviert, werden alle SQL Abfragen in der Tabelle adodb_logsql protokolliert. ⚠ Vorsicht: Aktivier diese Funktion nicht dauerhaft, da sie sehr ressourcenintensiv ist und die Leistung der Site beeinträchtigen kann.	Deaktiviert
Protokolliere Abfragen, die mehr als ... Sekunden benötigen	Wird benutzt um <i>solche</i> Abfragen zu protokollieren, die eine bestimmte Zeit oder länger benötigen.	0,05 Sekunden

Verschiedene Einstellungen 1

Einstellung	Beschreibung	Standard
Suche nach neuer Version		
Tiki-Version	Zeigte Deine aktuelle Tiki version. Klicke auf Datenbank neu aufsetzen oder aktualisieren um den Tiki installer zu starten.	
Automatisch nach neuer Version suchen	Wenn aktiviert, sucht Tiki automatisch nach einer neuen Version suchen, wenn die Seite Administrator Home aufgerufen wird - je nach Einstellung unter Prüfhäufigkeit . Tip: Melde Dich beim Tiki Newsletter an, um von neuen Version zu erfahren.	Aktiviert
Prüfhäufigkeit	Wie oft Tiki nach einer neuen Version suchen soll. Dieses Feld ist nur sichtbar, wenn Suche nach neuer Version aktiviert ist. Klicke auf Jetzt nach neuer Version suchen um auf eine Aktualisierung zu überprüfen.	wöchentlich
Site-Identität		
Browsertitel	Der Text, der in den TITLE Tag für jede Tikiseite aufgenommen wird. Dieser Text erscheint in der Titelzeile des Browsers des Benutzers .	
Anordnung des Site Titels	Anordnung des Titel in der Titelzeile des Browsers im Zusammenhang zur Beschreibung der aktuellen Seite: Vor , Nach , oder Keine .	Keine

Einstellung	Beschreibung	Standard
Browsertitel Anzeigemodus	Wenn Brotkrumen verwendet werden wird festgelegt, welcher Browsertitel angezeigt wird: Genauestes Element zuerst, Allgemeinstes Element zuerst, Nur Aktuelles Element , oder Seiten Beschreibung .	Genauestes Element zuerst
Emailabender	Die Antwortadresse von Tiki, wenn Tiki Emailbenachrichtigungen versendet.	
Email		
Zeichensatz in Emails	Gebe hier den Zeichensatz an, den Tiki für seine Emailbenachrichtigungen verwenden soll.	utf-8
Zeilenumbruch in Emails	Gebe hier das Zeilenendzeichen (end-of-line, EOL) ein, dass Tiki für seine Emailbenachrichtigungen verwenden soll: CRLF oder LF .	LF
Mailversand über	Lege fest, ob Tiki Sendmail (die PHP mail() Funktion) oder SMTP zum versenden von Emailbenachrichtigungen verwenden soll.	Sendmail
Emailadresse für die Testmail	Um den Emailversand von Tiki's Emailbenachrichtigungen zu testen, trage eine Emailadresse ein und klicke auf Einstellungen übernehmen	
Protokollierung und Benachrichtigung		
PHP Fehler berichten	Lege fest, wie Tiki PHP Fehler berichten soll: keine Fehlerausgabe, Alle PHP Fehler ausgeben , oder Alle PHP Fehler ausser Hinweisen (NOTICES) ausgaben .	Alle PHP Fehler ausser Hinweisen (NOTICES) ausgaben
Nur für Admin sichtbar	Wenn aktiviert, werden Fehler nur Benutzern mit Administratorrechten angezeigt.	Deaktiviert
Auch Smarty Hinweise	Wenn aktiviert, zeigt Tiki auch Smarty Hinweise.	Aktiviert
JavaScript ausschalten	Wenn aktiviert wird Javascript für die gesamte Site deaktiviert, auch wenn der Browser Javascript erlaubt. ⚠ Vorsicht: Nur zum Testen und zur Fehlersuche verwenden. Wenn der Haken gesetzt wird, dann werden viele Tiki Funktionen nicht mehr richtig arbeiten.	Deaktiviert
Mails in Tiki Logs protokollieren	Wenn aktiviert, wird eine Zeile des Typs mail in das System Log mit der Zieladresse und dem Betreff jeder versendeten Email aufgenommen.	Deaktiviert

Einstellung	Beschreibung	Standard
SQL-Abfragen protokollieren	Wenn aktiviert, werden alle SQL Abfragen in der Tabelle adodb_logsql protokolliert. ⚠ Vorsicht: Aktivier diese Funktion nicht dauerhaft, da sie sehr ressourcenintensiv ist und die Leistung der Site beeinträchtigen kann.	Deaktiviert
Protokolliere Abfragen, die mehr als ... Sekunden benötigen	Wird benutzt um <i>solche</i> Abfragen zu protokollieren, die eine bestimmte Zeit oder länger benötigen.	0,05 Sekunden



Einstellung	Beschreibung
Release Check	
Tiki version	Displays your current Tiki version. Click Reset or Upgrade Your Database to run the Tiki installer .
Check for updates automatically	If enabled, Tiki will automatically check for new updates (based on your Check frequency selection) each time you access the Admin Home page. Click Check for Updates Now to perform an update check.
Site Identity	
Browser title	The text to include in the
Sender email	The return email address used by Tiki when sending Mail notifications .
Home Page	
Use group homepages	Specify that each group has its own homepage. After a user logs in, they will be taken to the group's home page. Use the Groups management panel to define the homepage for each group. If the Go to group homepage only if login from default homepage option is enabled, the user will be taken to the groups homepage only if they logged in from the Tiki default homepage.
Use TikiWiki feature as homepage	Select the home page for your Tiki. Select from the list of enabled features such as wiki, articles, or blog.
Use different URL as home page	Specify any valid URL as the home page for your Tiki. This must be a fully qualified URL. For example, if you want to use a different wiki page (other than HomePage) as your Tiki's home, use: tiki-index.php?page=PAGENAME . This option will override the Use TikiWiki feature as homepage setting.
Miscellaneous	
Server OS	Select the operating system of the server hosting your Tiki: Unix, Windows, or Other/Unknown. Tiki will attempt to recognize your server.
Smarty security	
Use PEAR::Date library	
Default charset for sending mail:	Specify the character encoding used by Tiki when sending mail notifications .
Mail end of line	Specify the end-of-line (EOL) character used by Tiki when sending mail notifications : CRLF or LF.

Einstellung	Beschreibung
Logging and Reporting	
PHP error reporting level	Specify how Tiki should report any PHP errors: No reporting, All reporting, or All reporting except notices. If Visible to Admin only is enabled, errors will be shown to only the Admin user. If Include Smarty notices is enabled, any Smarty notices will be shown, too.
Log mail in Tiki logs	If enabled, a line of type <code>mail</code> will be included in the System Log with the destination address and subject of each email sent.
Log SQL	If enabled, all SQL queries will be registered in the database in the adodb_logsql table. Use the Log queries using more than option to limit the logging of queries to queries that use a specific amount of time. Caution: Do not enable this feature all the time. It can be very resource intensive and will impact performance.
CSRF Security	
	Require confirmation if possible CSRF detected.
	Protect against CSRF with ticket.

Click the **General** icon  on the [Admin Panel](#) to display the **General** screen. Use the **General Admin** panel to set general Tiki preferences and settings.

These settings apply site-wide to your Tiki. Some General preferences require specific features to be enabled on the [Features Admin](#) panel.

General Preferences

Note: Prior to 1.9.9, you could specify the Tiki theme in the General Preferences. For later releases, use the Administration: Theme page.

Setting	Description
Use group homepages	Specify that each group has its own homepage. After a user logs in, they will be taken to the group's home page. Use the Groups Management panel to define the homepage for each group.

Go to group homepage only if login from default homepage	If enabled, the user will be taken to the group's home only if they logged in from the Tiki default homepage (as defined by the Home Page field).
Use URI as home page	Specify any valid URI as the home page for your Tiki. This must be a fully qualified URI. For example, if you want to use a different wiki page (other than HomePage) as your Tiki's home, use: tiki-index.php?page=PAGENAME .
Home page	Select the home page for your Tiki. Select from the list of enabled features (such as wiki, articles, or blog). Note: This setting will be ignored if you selected the Use URI... setting.
OS	Select the operating system of the server hosting your Tiki: Unix, Windows, or Unknown/Other. Tiki will attempt to recognize your web server.
PHP error reporting level for non-admin	Specify how Tiki should report any PHP errors to non-Admin users. Note: Select Report only for admin to hide error reports from your regular site users and display the errors <i>only</i> to admins. New in 1.10: Select one of three error reporting levels: "No error reporting", "Report all PHP errors" or "Report all errors except notices." Use the "visible to admin only" checkbox to hide errors from end users. Use the "smarty notice reporting" checkbox to add notices from the templating system.
Log Mail in Tiki Logs	If activated, a line of type mail will be added in tiki Logs with the destination email address and the subject for each email sent. If the email is shown to be sent and does not arrive at the destination does not receive the mail it means that the mail server is not configured properly (see sendmail/php documentation) or that the mail has been considered as spam by the destination. If an error occurs, a line of type mail error will be added to Tiki logs (even if the feature is not activated) tw>=1.10
Log SQL	If this feature is checked, all the queries will be registered in the database in the table adodb_logs. Caution: Do not activate this feature all time. It can be very resource intensive! tw >=1.10
Default charset for sending mail	Specify the character set encoding used by Tiki when sending Mail notifications .
Mail end of line	Specify the end of line character used by Tiki when sending Mail notifications : CRLF or LF.

General Settings

Setting	Description
Disallow access to the site	Use this setting to "close" your Tiki (such as for maintenance). Users attempting to access your site will see only a login. Only users with specific permission will be allowed to log in.

Message to display when site is closed	Specify the message that visitors will see when accessing your site. This setting applies only when Disallow access... is selected.
Disallow access when load is above the threshold	Use this option to "close" your Tiki when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in.
Max average server load threshold in the last minute	Define the maximum server load. This setting applies only when Disallow access... is selected.
Message to display when server is too busy	Specify the message that visitors will see when accessing your site if the site is closed due to excessive server load. When the server load falls below the threshold, users will be allowed back into the site.
Open external links in new window	Specify if links to external sites should open in a new browser window. If not selected, all links will reuse the current browser window. Moved to Text Area Admin at least at v2.2
Display modules to all groups always	Specify if all Module are visible to all group — regardless of the specific module settings. If not selected, use the Module Admin page to specify which modules are visible to which groups.
Use cache for external pages	Specify if external pages are cached and stored on your server.
Use cache for external images	Specify if external images are cached and stored on your server.
Use direct pagination links	
Display menus as folders	Specify if menu options be displayed using the folder icon  . If not selected, a + and - will be used instead.
Use gzipped output	Specify if Tiki should use GZIP to compress pages before sending them to the user's browser. Selecting this option will reduce your site's bandwidth usage. See Compression for more information.
Count admin pageviews	Specify if the Tiki statistics will include page views from users with Admin permission.
Hide anonymous-only modules from registered users	Specify if Module with <i>only</i> anonymous permission are visible to non-anonymous users.
Server name (for absolute URIs)	The server name to use when creating absolute URIs.
Browser title	The text to include in the <TITLE> tag for each Tiki page. This will appear in the titlebar of your users' browser.
Temporary directory	A directory on your web server to use for temporary files. Note: You must have write- access to this directory. It is also where your session files if saved on disk will go. If you do not want interference with other application than redefines the session lifetime, it is better to define a directory specific to tikiwiki.
Sender email	The return email address used by Tiki when sending Mail notifications .

Contact user	Specify the user who receives mail from the Contact Us feature. You must enable the Contact Us feature on the Features Admin page.
Store session data in database	Specify if session data will be stored in the database instead of memory. Use this feature to share load between servers.
Session lifetime in minutes	Specify the session time. (0 will use the default session.gc_maxlifetime defines in php.ini). If session uses files, the files will go in the temporary directory.
Use proxy	Specify if your server requires a proxy to access external web pages (i.e. to cache them). If selected, specify the Proxy Host and Proxy Port .
Maximum number of records in listings	Specify the maximum number of records (items) to show when Tiki displays pages.
Help URL	Specify the root URL for your Tiki's online help. To use the default Tiki help on this site, use: <code>http://doc.tikiwiki.org/tiki-index.php?page=</code> Note: This option applies only when the Help System feature has been enabled on the Features Admin page. In 2.0 there is no such feature, there is instead a tick box "Help System:" just above this field, this now turns the help system on and off.

Date and Time Formats

Specify the Long Date, Short Date, Long Time, and Short Time formats. The following table lists the possible format strings:

Day	
%a	Abbreviated weekday name according to the current locale
%A	Full weekday name according to the current locale
%d	Day of the month as a decimal number (range 01 to 31)
%e	Day of the month as a decimal number, a single digit is preceded by a space (range 1 to 31)
%u	Day of the week as a decimal, with 1 representing Monday (range 1 to 7)
%w	Day of the week as a decimal, with 0 being Sunday (range 0 to 6)
%j	Day of the year as a decimal number (range 001 to 366)
Week	
%U	Week number of the current year as a decimal number, starting with the first Sunday as the first day of the first week
%W	Week number of the current year as a decimal number, starting with the first Monday as the first day of the first week
%V	The ISO 8601:1988 week number of the current year as a decimal number, range 01 to 53, where week 1 is the first week that has at least 4 days in the current year, and with Monday as the first day of the week. (Use %G or %g for the year component that corresponds to the week number for the specified timestamp.)
Month	
%b	Abbreviated month name according to the current locale

%B	Full month name according to the current locale
%m	Month as a decimal number (range 01 to 12)
Year	
%C	Century number (the year divided by 100 and truncated to an integer, range 00 to 99)
%G	The 4-digit year corresponding to the ISO week number (see %V). This has the same format and value as %Y, except that if the ISO week number belongs to the previous or next year, that year is used instead.
%g	Like %G, but without the century.
%y	Year as a decimal number without a century (range 00 to 99)
%Y	Year as a decimal number including the century
Time	
%H	Hour as a decimal number using a 24-hour clock (range 00 to 23)
%I	Hour as a decimal number using a 12-hour clock (range 01 to 12)
%M	Minute as a decimal number
%p	Either am or pm according to the given time value, or the corresponding strings for the current locale
%r	Time in a.m. and p.m. notation
%R	Time in 24 hour notation
%S	Second as a decimal number
%T	Current time, equal to %H:%M:%S
Notes	
%c	Preferred date and time representation for the current locale
%x	Preferred date representation for the current locale without the time
%X	Preferred time representation for the current locale without the date
%D	Same as %m/%d/%y
%h	Same as %b
%n	Newline character
%t	Tab character
%Z or %z	Time zone or name or abbreviation
%%	A literal % character

See the [PHP Manual](#) for details.

Other Settings

Setting	Description	Tikiwiki version
When possible, show the real user name instead of login:	Check this box to enable this feature	>= 1.10

Favicon icon file name	Specify the name of the Favorite's Icon (or page icon) for your Tiki. Note: The file must be in your root directory.	>= 1.9. Moved to Look&Feel/other in 1.10
Favicon icon MIME type	Specify the format of the Favicon : PNG, BMP, or X-ICON.	>= 1.9. Moved to Look&Feel/other in 1.10
Locations separator	The icon used in the breadcrumbs when displaying the category or structure path.	>= 1.9
Choices separator:	The character used to separate choices whenever they appear. Examples: / :	>= 1.10
Preference syntax:	"1.9 - \$feature_foobar" recommended for upgraded sites with 1.9.x theme styles not yet upgraded to 1.10 "1.10 - \$prefs.feature_foobar, \$prefs['feature_foobar']" recommended for upgraded sites using already 1.10 compliant theme styles	>= 1.10

- Example for an upgraded site to Tikiwiki 1.10 but still using an old 1.9.x theme style:

Other

When possible, show the real ☐ user name instead of login:

Locations separator: Examples: » / > : -> →

Choices separator: Examples: | / | :

Preference syntax:

1.9 - \$feature_foobar

1.10 - \$prefs.feature_foobar, \$prefs['feature_foobar']

Register This Site

Use this option to register your Tiki with tikiwiki.org and join the [Tiki community](#).

Change Admin Password

Use this option to change your Admin password. Enter a new password (case sensitive), repeat the password for verification, and click **Change Password**.