

Sortable List of Control blocks

Command	Description	Required	see also
ALTERNATE	used in conjunction with the OUTPUT command it can define an alternative output when an individual item (row) from a search/listing has no value.	optional	PluginList output control block
body		optional	
caption		optional	
carousel	wraps the carousel specific parameters and values inside a command OUTPUT with type=carousel	optional	
column	Optionally used when in the command OUTPUT (embraced) the parameter type=table. {column ...} defines the specific configuration of each column of the table. One command per column.	optional	
display	Used to define placement and formatting of individual objects. {display ...} embraced by the FORMAT command.	optional	PluginList display control block
filter	filter is a required command in the LIST body content and is used to define the search query that will be run to gather a set of results from the complete set of objects that have been indexed by the Unified Search. A large number of possible individual parameters can be 'filtered' . Multiple filter commands can be applied in an additive manner, ie the equivalent of an AND operation.	required	
FORMAT	The FORMAT command is used to create individually templated objects that can then be used in any of the individual OUTPUT methods. The FORMAT command allows to apply a wiki template and store it inside a named value. The value can then be used inside an other wiki template, or more usefully inside a smarty template.	optional	PluginList format control block
icon		optional	
list	Up to Tiki 12.3, replaced by 'pagination' The LIST plugin will display 50 results by default but depending on the output you might want to decrease the visible amount of results to improve performance.	optional	

Sortable List of Parameters

Parameter	Command	Description	Version
categories	filter (inline)	Match on the object's directly associated categories.	
code	display (inline)		
content	filter (inline)	Full text search on all of the object's content Additional field argument can be provided to search for other fields instead of the default ones.	
contributors	filter (inline)	user login to search for as the contributors for the content	
deepcategories	filter (inline)	Match on the object's categories or their parents, providing deep searching.	
editable	display (inline)	editable=inline will set the field to be editable online. required: "Inline editing (found in trackers)" and column should be set to mode=raw. <hr/> example: {column label="First Name" field="firstName" mode=raw } ... {FORMAT(name="firstName")}{display name="tracker_field_firstName" format=trackerrender editable=inline }{FORMAT}	11.x
excludeParents	display (inline)		
favorite	filter (inline)	Show only the favorited objects of a certain user.	
field	column (inline)	name of the field(s) of this column corresponds (must be identical) with the parameter "name" of the command "FORMAT"	
field	filter (inline)	to search trackers (for type=trackeritem, specify field; for instance, for tracker field "Foo Bar" with permanent name "foobar", you need to write field=tracker_id_foobar) object type to filter, example: field=tracker_id	

Sortable List of Values

Value	Parameter	Command	Description	Version
carousel	template	OUTPUT (embracing)	Sample using the default Bootstrap Carousel formatting. See: LIST - output command	14.x
medialist	template	OUTPUT (embracing)	Sample using the default media list formatting. See: LIST - output command	13.x
datetime	format	display (inline)	using the short datetime format	8.x
plain	format	display (inline)	as-is, default format optionally in conjunction with parameter 'separator'	
date	format	display (inline)	using the short date format	
imagegrabber	format	display (inline)	automatically grabs images from a source that is provided.	
objectlink	format	display (inline)	uses the value as the label to a link to the object	
snippet	format	display (inline)	to display the initial portion of the a large text optionally in conjunction with parameters 'length' and 'suffix'	
reference	format	display (inline)	to display a link based on the value mandatory in conjunction with parameter 'type' optionally in conjunction with parameter 'separator'	
			<hr/> use "format=reference" for tracker fields which are "page selector" fields, to assure that you link to the page whose name is contained in the tracker, rather than to the tracker record.	
trackerrender	format	display (inline)	to render a tracker field (when using trackerrender the Smarty variable "\$context.search_render" will be "y" and can be used to have different formatting in the trackeroutput Smarty tpl)	