

# <œiŠxí...œ êµ¬ì,,±

í<°í,µ8 ì¬ì,,œ ë,,ìž...ë"

œiŠxí...œ êµ¬ì,,±ì€ ì<œiŠxí...œ ê´€ë¬¬ìžëìœ í•¬ì¬ê,^ í<°í,µì~ ì™,ë¶¶ëì¬ì,,œ ì,, í~ ì,,µì • ì¼ë¶¶ë¼ë¼ ë³€ê²½í•~ë,,ëì í•©ë<^ë<µ. INI í€€ëì¼ì,,  
œê³µí•¬ìœ¼ëìœì,, ê´€ë¬¬ìžë"µì€ ìžì< ë"µì~ ë³"ë" í<°í,µ ì,,µì¹¬ì— ë€€í•¬ì¬ ìµ'ì<¬ êµ¬ì,,±ì,, ë³'ìœ í• ì~ìž"ìšµë<^ë<µ.

í<°í,µ10 ì¬ì,,œ ìf^ëìœ ë,,ìž...ëœ ë, 'ìš©: ì • ì €€ëì¼ëìœë¶¶í,,° ë³"ë"¬ì,, ëìœë"œí•~ëš" ì,, ìfì,¬í• (í"„ëìœí•,, YAML í~•ì<ë, 'ì¬ì,,œ,  
http://profiles.tiki.org/Module+Handler ì™€ ìœ ì,¬í•ê²€). ê´€ë¬¬ì€ë,, ë, 'ë¶¶ëì¬ì,,œ "ë³"ë"¬ì€€ëì¼" ì,, ê²€ìf%óí•¬ì<œì~µ.

í<°í,µ11 ì¬ì,,œ ìf^ëìœ ë,,ìž...ëœ ë, 'ìš©: db/preconfiguration.php í€€ëì¼ì€ ì²<< í<°í,µ ì,,µì¹¬ì<œì— ì œì•^ëœ ë°ì'í,,°ë² ì'ìšµ ë³'ì•^ë, 'ìš©ì,, í¬í•¬í• ì~  
¬ìšµë<^ë<µ. ì'ëš" ê°€ìf ì,,œë²,, ì œê³µìžëìœ í•¬ì¬ê,^ ê³ ê°ì' í<°í,µ ì,,µì¹¬ì"„ëìœë,ëž"ì¬ ì 'ê•¼í•~ê,° ì „ì¬ mysql ì,, ê°ê,° ë<µë¶, ìž,,ì~ ë¹,,ë°€ë²^í,,ì™€  
¬ìš©ìžë³...ìœ¼ëìœ ì,¬ì „ì,,µì • í• ì~ ìž^ë,,ëì í•©ë<^ë<µ.

## <°í,µ í€œ(farm)ê³¼ í~ ìšxí€... íš€ì,¬ì¬ì,,œ ,¬ìš©ê°€ëš¶í•œÂ ìš©ë²•

- BigBlueButton ê³¼ ê°™ì€ ë<µë¶, ì,,œë¹,,ìšµëìœ ì,¬ìš©ìžì~ ê°,,ì,,ì¬ì' ì¬ê²°
- ë©µì¶ì<œì™€ ê°™ì€ ê³ ê,°o ì,,µì •ì,, êµ¬ì,,±
- ì§€ì> ê³,,ìšì ì¼ë¶¶ë°€ ì•,,ë<€ ê,°ëš¶ì,, ë¹,,í™œì,,±í™"
- ì „ì¬ì ìœ¼ëìœ íš¹ì • ê,°ëš¶ì,, ë¹,,í™œì,,±í™"í•¬ìœ¼ëìœì" ë³'ì•^ ì±...ìž,,ìžì¬ê²€ ì•€ëì¼
- tiki\_p\_admin ì,, ì œê³µí•¬ì§€ëš€ ì¼ë¶¶ë ê,°ëš¶ì,, ì 'ê•¼ë¶¶ê°€ëš¶í•~ê²€ ëš€ë"¬
- í~ ìšxí€... íš€ì,¬ëš" ë³"ë" ê,°ëš¶ì,, í•œ ê³³ì¬ ìf"ìž¬í•œ í~ ì<œì<ì,, ì œê³µí•~ê,°ë¼¼ ì>í• ì~ ìž"ìš€ëš€€, ë<µì€ì~ ì,¬ìš©ì€ ì œí•œí• ì~ ìž^ë<µ
  - ì<µì¬~ì ê,°ëš¶
  - ì,,œë²,, ì 'ê•¼ì,, ì¬ê,° ìœ,,í•¬ì¬ ì,¬ìš©ë ì~ ìž^ëš" ê,°ëš¶ (ë€€ë¶¶ë¶¶,ì~ ì,,µì¹¬ì¬ì,,œëš" ê´œì°@ì§€ëš€€, ìœ,,í,µí€œ(WikiFarm)ì¬ì,,œëš" ì<ì€ ì¼ì  
ì•,,ë<^ë<µ)
- ì»"ì,,µí€... íš€ì,¬ëš" ì,¬ìš©ìžì¬ ë€€í•¬ì¬ ë" ë<¬ìœí•œ ê´€ë¬¬ì€ë,,ì,, ëš€ë"µê³ ì<¶ì¬í• ê²fì'ë<µ
- í<°í,µë¼¼ ì'ìš© í"„ëìœê,ëž" ë¹€ë" (í"„ë ìž,,ì>€í¬) ëìœì" ì,¬ìš©

<œïšœí...œ êµ¬ì,,±ì,,Â í™ œì,,±í™ ”

œïšœí...œ êµ¬ì,,±ì€ db/local.php íœœì¼œïœœ¶¶í,,° í™ œì,,±í™ ”ë¬-î¼œšœ í•©ë^ë<œ. í<°í,œ8 ë° ê. í í>,,ì-ì,,œ ìfi,,±ëœ ì,,œì¹~ëš” ê,°ë³,ìœ¼œïœ ìfi,,±ëœ  
œœì¼ ë,´ë¶¶ì- ìf”í”œì,, í-í•í•ê³ ìž^ìšµë<^ë<œ.

db/local.php ë,´ë¶¶ì~ ìf”í”œ êµ¬ì,,±

```
$system_configuration_file = '/etc/tiki.ini'; $system_configuration_identifier = 'client1.example.com';
```

db/local.php ë,´ë¶¶ì~ ë<œëœ, ìf”í”œ êµ¬ì,,±, ìfëœë ê²¼ëïœëœ¼ í-í•

```
$system_configuration_file = 'db/tiki.ini'; $system_configuration_identifier = 'client1.example.com';
```

ì~^ì œëœ¼ ì,-ìš©í•ê²œ ë~ë©´ .htaccess ê°€ í™ œì,,±í™ ”ë¬-ìž^ì-ì,,œ tiki.ini ê°€ ì¼ìž^ìš€ ì•šë,,ëì í•~ëš” ê²fi- ìœ ìí•ì<œìœ

œì,,±í™ ”ë~ë©´, í<°í,œëš” êµ¬ì,,± íœœì¼œïœœ¶¶í,,° ì,, ìfëœ ì<ë³,ìžì- ê,°ë°í•~ì- ì¶”ê°€ ë³...ë ì,, ì½ì-´ë“œì¼ ê²fiž...ë<^ë<œ. ì<ë³,ìžëš” ìž,,ì~ì ê²fi¼ ì~  
ìš€ëšœ, ì,-ìíš, í~ì€ ê³,ìš ìœ í•~ë,~ëœ¼ ìš€ì •í•ê³,° ìœ,,í•~ì- ì,-ìš©ë ì~ ìž^ìšµë<^ë<œ. êµ¬ì,,± íœœì¼ ë,´ë¶¶ì-ëš” ë<œìœ’ êµ¬ì,,± ìí•ë ì~  
ìœ¼ë° ìfiìí ì,-ìš©ë ì~ ìž^ìšµë<^ë<œ.

# Ni êµ¬ì,,±Â íœœì¼

ìf”í”œ INI íœœì¼

```
[global] preference.feature_wysiwyg = "n" preference.feature_sefurl = "y" preference.helpurl = "http://support.example.com/" ; ... more settings ...  
[basic : global] preference.feature_wiki = "y" preference.feature_forums = "n" preference.feature_trackers = "n" ; ... more settings ... [pro : global]  
preference.feature_wiki = "y" ; BBB configured, but user can still toggle on/off preference.bigbluebutton_server_location = "bbb.example.com"  
preference.bigbluebutton_server_salt = "1234abcd1234abcd" ; ... more settings ... [client1.example.com : pro] preference.browsertitle = "Client #1  
Intranet" preference.sender_email = client1@example.com
```

the example above, the following preferences would be set for using the identifier *client1.example.com*:

- feature\_wysiwyg = n
- feature\_sefurl = y
- helpurl = <http://support.example.com/>

- feature\_wiki = y
- bigbluebutton\_server\_location = bbb.example.com
- bigbluebutton\_server\_salt = 1234abcd1234abcd
- browsertitle = Client #1 Intranet
- sender\_email = [client1 at example.com](#)

at the beginning indicates comments

# Disable classes of preferences

Preferences can be disabled by setting a value to each of them individually. However, this process may be long and will require maintenance with the evolutions of Tiki.

Tiki allows to set multiple rule priorities, each verification priority can allow or deny a preference. Rules can be specified at various levels, just like the preference overrides above.

## Various rules

[global] rules.0 = deny experimental new [pro : global] rules.5 = allow new rules.10 = allow feature\_wysiwyg

... [global] rules.0 = deny experimental new [pro : global] rules.5 = allow new rules.10 = allow feature\_wysiwyg

... [pro : global] rules.5 = allow new rules.10 = allow feature\_wysiwyg

## Draconian rules

[global] rules.0 = deny all rules.1 = allow basic

... [global] rules.0 = deny all rules.1 = allow basic

# , -ì „êµ¬ì,, ± íĀĀĒì¼

í,æ°€ ì,¬ì „, ëiœë“œëœ ì“ë”“ë©~ë“œ (on-demand)ìì~ ê°€ìf ë”\_ì< ì,, ì œê³µí• ë•ĀĒ, í”\_ìšxíĀĒ... íšĀĒì,¬ë“xì€ ê° ì,¬ìš©ìžì—ê²ĀĒ ë<xëŸ, ë°ì´í,,°ë² ì´ìšxì™€  
-°ê²° ë³´í•^ë,´ì—ìœ¼œiœ mysql ì,, ì œê³µí• ì~ ìž^ë<x.

xì¹~ ´”„ëiœê•\_ëž“ì~ ë°ì´í,,°ë² ì´ìšx ì—°ê²° ì,,xì • ë<“ê³,,ì— ì ‘ê¼í• ë•ĀĒ, ì‘ëŸ¬í•œ ê°‘ë“xì€ ì,¬ìš©ìžëŸ¼ ìœ,,í•~ì—¬ ì,¬ì „ì— ê„°ž...ë ê²fì´ë”“ă... ì´ëš”  
©”¼ í”ì€ ë<xëŸ, ë°©ì<ì,, ì´ìš©í•~ì—¬ ì œê³µí•~ëš” ê²fë³´ë<x ë” íš“ìœ“ì ì´ë<x.

ëŸ¬í•œ ì •ë³´ëš” ëŸ,,ëª...í•œ ì´ìœ ëiœ db/local.php ë,´ëŸì— í¬í•“ë ì~ ì—†ë<x ê„ ì´ìœ ëš” local.php ê°€ ì´ ë<“ê³,,ì—ëš” ì•,,ìš ìì ìž¬í•~ìš€ ì•šê„°  
•ĀĒ¬\_ì´ë<x.

¼ë ê²fì€ ë<“ìœíž^ db/preconfiguration.php ì— ì ì´í•œ ìx,,ì~ ì£¼ì,,ìfìfœëŸ¼ í•´ìš€í•~ëš” ê²fì´ê³ ì ì´í•œ ê°´ìœ¼œiœ ì±,,ìš°ëš” ê²fì´ë<x:

db/preconfiguration.php