



# ~A¬, A¬~A¬šA©~AªA°€A«šA¥A•œ A¬šA©~A«A²•

- BigBlueButton ~AªA³A¹¼ ~AªA°™ A¬€ A«AªA«A¥A, A¬,,œA«A¹,,A¬šAªA«A;œ A¬,A¬A¬šA©A¬žA¬~ AªA°,A¬,,A¬A¬—†A¬A' A¬—A°~AªA²A°
- ~A«A©AªA¬A°A¬<œA¬™ € AªA°™ A¬€ AªA³A AªA,‰ A¬,,AªA¬A •A¬,, AªAµA¬A¬,,A±
- A¬Aš€A¬> AªA³,,AšA¬~ A¬A¹¼A«A¶€AªA°€ A¬•,,A«A«œ AªA, A°A«šA¥A¬,, A«A¹,,A™ œA¬,,A±A™ ”
- A¬A,,A¬—A¬A¬A A¬œA¹¼A«A;œ AšA¹A¬A • AªA, A°A«šA¥A¬,, A«A¹,,A™ œA¬,,A±A™ ”A-
  - A”A¬œA¹¼A«A;œA¬A” A«A³A' A¬• ^ A¬A±...A¬ž,,A¬žA¬—AªA²œ A¬•œA«A!A¹¼
- tiki\_p\_admin A¬,, A¬A œAªA³AµA•~A¬Aš€A«Ašœ A¬A¹¼A«A¶€ AªA, A°A«šA¥A¬,, A¬A 'AªA·A¹¼A«A¶^AªA°€A«šA¥A•~AªA²œ A«AšœA«”A¬
- A~A, A¬šAªAœ... AšœA¬,A¬A«š” A«AªA”A«”A AªA, A°A«šA¥A¬,, A•œ AªA³A³A¬— A'f'A¬žA¬A-
  - œ A~A, A¬<œA¬A¬,, A¬A œAªA³AµA•~AªA, A°A«A¥A¹¼ A¬>A•A A¬^~ A¬ž^A¬Aš€A«Ašœ, A«AªA¬œA¬~ A¬,A¬A¬šA©A¬€ A¬A œA•œA•A A¬^~ A¬ž^A«Aª
  - A¬<AªA—~A¬A AªA, A°A«šA¥
  - A¬,,œA«A²,, A¬A 'AªA·A¹¼A¬,, A¬—A»AªA, A° A¬œ,,A•~A¬—A¬ A¬,A¬A¬šA©A«A A¬^~ A¬ž^A«š” AªA, A°A«šA¥ (A«œ€A«A¶€A«A¶,,A¬~ A¬,,AªA¬A¹~A¬—A¬,,œA«š” AªA'œA¬A°A®A¬Aš€A«Ašœ, A¬œ,,A,AªAœœ(WikiFarm)A¬—A¬,,œA«š” A¬Aç<A¬€ A¬A¹¼A¬€ A¬•,,A«A^A«Aª)
- A¬A»A”A¬,,AªAœ... AšœA¬,A¬A«š” A¬,A¬A¬šA©A¬žA¬— A«œ€A•~A¬—A¬ A«” A«A”A¬^œA•œ AªA'€A«A!A¬ AœA”A«,,A¬,, A«AšœA«”AªAªA³A A¬<A¶A¬—A' A•A AªA²fA¬A' A«Aª



# INI $\tilde{A}^{\hat{\mu}}\hat{A}\neg\tilde{A}\neg, \hat{A}\pm \tilde{A}\text{E}\text{E}\tilde{A}\neg\hat{A}^{1/4}$

A-f'A"E INI AEEA-A%

```
[global] preference.feature_wysiwyg = "n" preference.feature_sefurl = "y" preference.helpurl = "http://support.example.com/"  
; ... more settings ... [basic : global] preference.feature_wiki = "y" preference.feature_forums = "n" preference.feature_trackers  
= "n" ; ... more settings ... [pro : global] preference.feature_wiki = "y" ; BBB configured, but user can still toggle on/off  
preference.bigbluebutton_server_location = "bbb.example.com" preference.bigbluebutton_server_salt = "1234abcd1234abcd"  
; ... more settings ... [client1.example.com : pro] preference.browsertitle = "Client #1 Intranet" preference.sender_email =  
client1@example.com
```

In the example above, the following preferences would be set for using the identifier *client1.example.com*:

- feature\_wysiwyg = n
- feature\_sefurl = y
- helpurl = <http://support.example.com/>
- feature\_wiki = y
- bigbluebutton\_server\_location = bbb.example.com



[global] rules.0 = deny all rules.1 = allow basic

A~,,A A~A A~,,AxA~A •A~€ A«Â°A°A~—A' A~,, A~A~A•A" A~•A«S" 'tags' A,ÂxA~«A¥A¼ A~,,A~A~šA©A~•A~—A~ A~A •A~•A~— A~ fœA³A•A, A«A A~•, A~š" A³A°€ A~ž^ A«A. A«A~A~«A!A~ A~Aš€A~A •A«~A~Aš€ A~•ŠA«S" A•œ, A«A³A" A«"A A~,,A A~ A, A~,,AxA~A •A~€ 'A³A³ A³A, %' A~œA¼A«A;œ A~—A~A²A" A~Aš,,A«A. .

# A~,,A~A~A,,A³AmA~A~,,A± AœœA~A¼

A«A°A,ÂxA³A°€ A~,,A~A~A,, A«A;œA«"œA«œ A~~A" A«" A«A©~A«"œ (on-demand) A~A~ A³A°€A~f A«A" A, A~A A~,, A~A œA³A³AmA•A A«•œ, A~A, A~šAxAœ... AšœA~,,A~A«"AxA~€ A³A° A~,,A~A~šA©A~žA~—A³A²œ A«AxA«A¥A, A«A°A~A' A~,,A°A«A²A A~A' A~šAxA~™€ A~—A°A³A²A° A«A³A' A~•A«A, A' A~—A~œA¼A«A;œ mysql A~,, A~A œA³A³AmA•A A~^~ A~ž^ A«A.

A~,,AxA~A¹~ A" ,,A«A;œA³A•A, AžA" A~~ A«A°A~A' A,,A°A«A²A A~A' A~šAxA~—A°A³A²A° A~,,AxA~A • A«A" A³A³,,A~— A~A 'A³A•A¼A•A A«•œ, A~A' A«YA~A•œ A³A°' A«"AxA~€ A~,,A~A~šA©A~žA«A¥A¼ A~œ,,A~•A~—A~ A~,,A~A~A,,A~— A³A, A°A~ž... A«A A³A²fA~A' A«" Aš... A~A' A«S" A«A©" A~A¼ A~A¹A~€ A«AxA«A¥A, A«A°A©A~A~,, A~A' A~šA©A~•A~—A~ A~A œA³A³AmA•A~ A«S" A³A²fA«A³A' A«AxA A«" AšA" A~œA" A~A A~A' A«A.

A~A' A«YA~A•œ A~A •A«A³A' A«S" A«A¶,,A«A³...A•œ A~A' A~œA A«A;œ db/local.php A«,A' A«A¶€A~— A~A~A•A" A«A A~^~ A~—†A«AxA A³A•A, A~A' A~œA A«S" local.php A³A°€ A~A' A«A" A³A³,,A~—A«S" A~•, A~Aš A~A;A' A~žA~A•A~Aš€ A~•ŠA³A, A° A«•œA~A~A, A~A' A«A.

A•A' A~•A¼A«A A³A²fA~€ A«A" A~^œAž^ db/preconfiguration.php A~— A~A A~A ^A•œ A~AxA,,A~~ A~AšA¼A~,,A~fA~ fœA«A¥A¼ A•A' A~Aš€A~•A«S" A³A²fA~A' A³A³ A~A A~A ^A•œ A³A°' A~œA¼A«A;œ A~A±,,A~šA°A«S" A³A²fA~A' A«A:

```
<?php // This is Tiki's preconfiguration file. // This holds values which can provide preconfiguration values in the installer, when
local.php does not yet exist // Uncomment and change values as appropriate $host_tiki_preconfig='localhost';
$user_tiki_preconfig='tiki'; $pass_tiki_preconfig='password'; $dbs_tiki_preconfig='tiki_db';
```

## Related

---

- [TRIM](#)
- [Multitiki](#)