



Configuring Machine Learning Models

Configuring a model to make it ready for training involves specifying the data dimension fields, a label field if necessary, any required transformers and a learner. You can get to the model configuration page by finding the model in the Machine Learning **List Models** page, click on the model's actions button and select **Edit**.




Find edit option in model's action menu



Model configuration page


Selecting Dimension and Label Fields

Dimension fields are chosen from a list of fields gotten from the data source tracker. These are shown in a multi-select list interface. Select a field by clicking on it. Select multiple fields by holding down the `Ctrl` keyboard key and clicking on the fields.



Select dimension fields from multi-select list

Chosen dimension fields are the data attributes that model will be trained on. Tiki will leave out all unselected fields. The label field is the data attribute that contains the target to be predicted. A label field is required if the chosen learner is a classifier.




Set label field if required by learner

Some regression-based learners like Gradient Boost will also require a label field specified. In such a case, the data attribute chosen as the label field is usually expected to be of numeric type.

Handling Empty Data Values

Before a sample is used for training, Tiki by default will replace empty numeric fields with 0. Empty categorical fields will remain as empty strings. If you do not want this behaviour, you can make Tiki to simply ignore samples with empty fields by checking the **Ignore items with empty values** option.

A screenshot of the Tiki web interface. At the top, there is a list of quarters (Q3, Q4, Q5, Q6, Q7, Q8, Q9) in a scrollable area. Below this, the 'Label field' is set to 'Class'. A red rectangular box highlights the checkbox labeled 'Ignore items with empty values', which is currently checked. Below the checkbox, the 'ML Model' section shows 'Transformers and Learner' with a 'Select...' dropdown and an 'Enter Arguments' button. At the bottom, there is a blue 'Update' button.

Check the box to ignore empty data values

With this option checked, Tiki will skip any item that contain empty fields during model training, and it will not be used to train the model.

Adding Transformers and Learners

You use transformers to preprocess data before model training. A learner is a machine learning algorithm on which the machine learning model will be based. The type of transformers and learner you choose will depend on the structure and format of the training data and the type of target that you want to predict.

This screenshot shows the 'ML Model' configuration interface. On the left, there are fields for 'Label field' (set to 'Class'), 'Ignore items with empty values' (checked), and 'ML Model'. The 'Transformers and Learner' dropdown menu is open, showing a 'Select...' option. To the right, there is an 'Arguments' section with an 'Enter Arguments' button. An 'Update' button is located at the bottom left.

Choose a transformer or learner


This screenshot shows the 'ML Model' configuration interface with the 'Transformers and Learner' dropdown menu open. The menu displays a list of classifiers under the heading 'Classifiers': AdaBoost, ClassificationTree, ExtraTreeClassifier, GaussianNB, KDNeighbors, KNearestNeighbors (highlighted), LogitBoost, LogisticRegression, MultilayerPerceptron, NaiveBayes, and RadiusNeighbors. The 'Select...' dropdown is visible at the bottom of the list. The 'Update' button is at the bottom left.

Pick a transformer or learner from the list


This screenshot shows the 'ML Model' configuration interface with 'KNearestNeighbors' selected in the 'Transformers and Learner' dropdown menu. The 'Enter Arguments' button in the 'Arguments' section is highlighted with a red box. The 'Update' button is at the bottom left.

Click Enter Arguments to show popup

Add a transformer or a learner by simply selecting it from the dropdown list and clicking on **Enter Arguments** button



Enter arguments



Learner added

A popup will be displayed for you to enter the argument values to be used internally to control the transformer or learning algorithm. Tiki will autofill any left out parameters with default values.

Edit Machine Learning Model

[+ New](#) [Manage](#)

Name: Divorce Predictor

Description: Predict whether a couple will stay married or get divorced.

Source tracker: [Divorce dataset](#)

Dimension fields: Q1, Q2, Q3, Q4, Q5, Q6, Q7, Q8, Q9

Label field: Class

Ignore items with empty values: ☒

ML Model: Transformers and Learner: KNearestNeighbors, Arguments: K Nearest Neighbors (k: 3, weighted: false, kernel: Euclidean)

[Update](#)

[Show PHP error messages](#)

Fully configured

Machine Learning Models

[+ New](#)

ID	Name	Description	Source
1	Divorce Predictor	Predict whether a couple will stay married or get divorced.	Divorce dataset

Success message after configuration

You add transformers in the order in which you want the data processed and you can add as many transformers as you deem fit. As a convention, the learner should be added last and only one learner is required. Adding multiple learners might result in unexpected behaviour.

Tiki internally uses Rubix ML for its Machine Learning functionality, so only transformers and learners available in Rubix ML are supported by Tiki.

Due to Tiki Tracker's robust nature, some data transformations might not be necessary. For example, Numeric String Converter works by converting all numeric values that have been given as categorical values to their equivalent integer and floating point types. Tiki will handle this automatically if the given values belong to a numeric field type in the source tracker. Applying the least possible number of transformers will help reduce model latency.

Related links

- [Machine Learning](#)
- [Preparing Machine Learning Dataset](#)
- [Creating Machine Learning Models](#)
- [Training Machine Learning Models](#)
- [Using Machine Learning Models](#)
- [Rubix ML](#)