

Daily reports

Daily Reports is a new feature in Tiki4, and improved in Tiki8 and Tiki9 that informs you about changes on sites you are watching with one periodic email.

It is a summarised version of the normal notifications and it replaces them.

Enabling the feature

User Watches and Daily Reports have to be enabled. I recommend to enable the My Tiki menu too.

In Tiki6, for instance, you can enable them here:

- Admin Home -> Features -> Show My tiki: check
- Admin Home -> Features -> User Watches: check
- Admin Home -> Features -> Daily Reports: check

Since Tiki8, at least, all three features are found in "Admin Home → Community", and *Show My tiki* is only found in "Admin Home → Community"

If User Watches and Daily Reports are enabled, each user can decide to enable reports, or to further use normal notifications.

Usage



To use reports, go to My Watches in the main application Menu from your tiki site (**MyTiki > My Watches - tiki-user_watches.php**) and adjust your preferences to fit your needs.

User Watches and preferences

[Preferences](#) [MyInfo](#) [My Watches](#)

[No Tabs](#)

[Report Preferences](#) [Sites you are watching](#)

 **Tip** 

Use reports to summarise notifications about objects you are watching.

Use reports

Interval in witch you want to get the reports

Short report HTML-Email Send me an email also if nothing happened
 Detailed report Plain text

[Apply](#)

Prepare the cron job

The next step is to prepare the cron job.

- Before Tiki6:

- Open `tiki-user_reports_send.php` and link `$tikiUrl` in line 15 to your Tikiwiki installation
Since Tiki6 this step is not needed any more.

- Since Tiki9:

- You can call the cron job from external servers, by means of using a token to allow the cron job to be launched remotely.
- You can also, as always, launch the cron job locally from the same server where the tiki is hosted, without using any token.

- Since Tiki12.3:

- You can use Console (`console.php` script) to manage the daily reports on the command line. Therefore, you can now use this feature in MultiTiki setups, appending the param like `--site=sitename.example.com`.

Then you can enable a cronjob. Example for a cronjob that calls the script every day at 3 am:

Since Tiki12.3

```
00 3 * * * cd /var/www; php console.php daily-report:send
```

Or

```
00 3 * * * cd /var/www; php console.php d:s
```

Replace **/var/www** with your **/path/from/root/to/tiki**

In case of Tikis with domains `site1.example.com` & `site2.example.com`, in a *MultiTiki* setup, append an argument like `--site=sitename.example.com`

```
00 3 * * * cd /var/www;php console.php d:s --site=site1.example.com 00 3 * * * cd /var/www;php console.php d:s --site=site2.example.com
```

The above may not work on all server configurations. You are encouraged to test the command first on the console at the server, to check that there is no error message or suspicious warning. If you can't run it this way, the cron may be called through the web server.

```
00 3 * * * wget -O /tmp/out http://localhost/tiki-user_reports_send.php
```

or something like

```
00 3 * * * /usr/local/bin/wget -O - -q -t 1 http://localhost/tiki-user_reports_send.php
```

or even with some command based on the other command **curl** and an associated command (like "mutt", which needs to be installed separately) to send the output of the cron job to an email account. See the example below.

Token access for anonymous users

And since Tiki9, you can use a token in the url to call, in order to allow the cron script to be launched from an external server. An example of using the token and sending the output by email at 5, 11, 17 and 23h each day is shown below

```
0 5,11,17,23 * * * curl 'http://externaldomain.org/tiki-user_reports_send.php?TOKEN=98762542c722d08b14bb54b029389612' 2>/tmp/output.txt | mutt -s "[FOO]tiki-user_reports_send.php?TOKEN=... error output" foo@bar.org < /tmp/output.txt
```

Tip:

For **wget** to work in virtual servers, you need to ensure that you have the package **xterm** installed.

How it works internally

lib/reportslib.php

Contains the main class and all important code for reports.

tiki-user_reports.php

This file is used to enable or disable reports and to set the report preferences. It catches POST requests from tiki-user_watches.php

tiki-user_reports_send.php

This file is the file that initiates sending report emails. It can and may only be called by the server.

If you want to use reports before Tiki6, open the file and set `$tikiUrl` in line 15 to your Tikiwiki installation.

The last step is to enable a cronjob that calls this file.


Once there are some actions done that would send emails to the user, those actions leave a record in the mysql table **tiki_user_reports_cache**, and when the cron job is run, the records in this table will be used to feed the report to be sent to the user by email.

Example of a HTML report:

HTML Message

Daily report from 14.07.2009 (38 changes)

From: clemens-john@gmx.de
To: clemens-john@gmx.de
Date: Yesterday 11:02:24

Spam Status: Bogofilter 

Report for Admin.
Last Report sent on Sunday 14.06.2009.

Changes in detail:

15.06. 17:48: admin replied to the topic Hallo im Forum.
15.06. 17:48: admin replied to the topic Hallo im Forum.
15.06. 17:48: admin replied to the topic Hallo im Forum.
15.06. 18:07: admin replied to the topic Test.
15.06. 19:51: admin replied to the topic Test.
Today 09:53: admin replied to the topic Test.
Today 09:53: admin replied to the topic Test.
Today 10:04: admin replied to the topic Test.
Today 10:04: admin replied to the topic Test.


15.06. 20:04: admin replied to the blog Noch ein Blog .
Today 09:46: admin replied to the blog Was ich so mache .

Yesterday 18:35: admin created the article Blabnlabdfgdf.
Today 10:22: admin created the article dfsdfsdf.
Today 10:33: admin created the article dfsdfsdf.
Today 10:34: admin created the article dfsdfsdf.
Today 10:37: admin created the article sdfsd.
Today 10:43: admin created the article sdasdasd.

Yesterday 18:37: admin edited the article Blabnlabdfgdf.
Yesterday 18:37: admin removed the article Blabnlabdfgdf.
Yesterday 18:37: admin removed the article Blabnlabdfgdf.

Today 09:55: admin removed the wiki page testpage from the category Reports.
Today 10:03: admin removed the file ff-ol.png from the category Reports.
Today 10:36: admin removed the forum Testforum from the category Reports.
Today 10:37: admin removed the image Test from the category Reports.

Today 09:57: admin edited the wikpage testpage (this history, all history)

Description	Type	Encoding	Size
 Daily report from 14.07.2009 (38 changes)	HTML document	quoted-pri...	11.5 KIB

Changing groups of users to receive daily reports by default

It was not until Tiki6.5, 7.3 and 8.0 that a tiki admin could indicate that new users receive daily digests of notification emails by default.

Therefore, many live tiki sites using previous versions of the software since long ago, with potentially hundreds of users already, might not benefit from that performance improvement until all users manually indicated that they wanted to receive daily digests instead of instantaneous emails. However, there is some performance limitation in tiki when you have hundreds of users receiving instantaneous notification emails each time a user adds some new content. This can mean moving from a couple of seconds, on a shared hosting, to have tiki back ready after sending some new comment or tracker item, for instance, into lasting 45 seconds before tiki is ready back after sending all the emails associated to that same action (posting a new comment or tracker item, in this example)

Therefore, it's not rare that an admin would want to change at once a whole group of users from receiving instantaneous emails, to receiving them grouped daily based on a cron job. This change alleviates tiki from sending so many emails with every new action, and brings tiki back to a fast performance from the end user point of view. This change can be applied directly with a SQL query on the database (through phpmyadmin or by other means). If your groups of users is "**foo_group**", then the SQL query to run directly in your mysql db is:

sql code to run directly on the on mysql database

```
INSERT INTO `tiki_user_reports` (`user`, `interval`, `view`, `type`, `time_to_send`, `always_email`, `last_report`)
  (SELECT uu.`login`, 'daily', 'detailed', 'html', '0000-00-00 00:00:00', 1, NOW() FROM `users_users` uu,
`users_usergroups` uug WHERE uug.`groupName` = 'foo_group' AND uu.`userId` = uug.`userId` AND uu.`login`
  NOT IN (SELECT user FROM tiki_user_reports));
```

Related

User Watches

Action log

alias names for this page

Daily Reports for User Watches | DailyReports | PeriodicReports | Periodic Reports | Daily digest | DailyReport | Daily Report