Plugin Accordion

This Tiki plugin allows users to place some content of a Wiki Page in a block that allow to toggle between visible or hidden content using an accordion.
It was added in Tiki 25
https://gitlab.com/tikiwiki/tiki/-/merge_requests/1516

Parameters

Create content within collapsable items
Introduced in Tiki 25. Required parameters are in `bold`.
Go to the source code
Preferences required: wikiplugin_accordion

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Content of the collapsible zones, separated by "/////"		
headers	text	Pipe-separated list of header titles (with or without icon syntax). Example: `{i name='users'} Item 1|Item 2|Item 3`		25
headeractivebgcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
headerbgcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
headerbordercolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
headerborderwidth	text	To change the width of header border in pixels (1 by default). For example: 3 for 3 pixels.	1	25.0
headercontentcolor	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
headerfontsize	text	To set the size of the headers text in pixels. For example: 20 for 20 pixels.	16	25.0

`panelbgcolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
`panelbordercolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
`panelborderwidth`	text	To change the width of panel border in pixels (1 by default). For example: 3 for 3 pixels	1	25.0
`panelcontentcolor`	text	Enter a valid CSS color hex code, or an RGBA value if setting opacity is desired; for example: #000 or rgba(00, 00, 00, 0.5).		25.0
`panelfontsize`	text	To set the size of the panels text in pixels. For example: 20 for 20 pixels.	16	25.0
`headerborderstyle`	(blank)| none| hidden| dotted| dashed| solid| double| groove| ridge| inset| outset	Determine the kind of border to apply to the headers.	none	25.0
`headerfontstyle`	(blank) normal italic oblique	Use to change the headers text style.	normal	25.0
`headerfontweight`	(blank) normal bold bolder lighter 900	Use to change the headers text weight.	normal	25.0
`panelborderstyle`	(blank)| none| hidden| dotted| dashed| solid| double| groove| ridge| inset| outset	Determine the kind of border to apply to the panels.	none	25.0
`paneltextalignment`	(blank) left right center justify	To set the horizontal alignment of the panels text.	left	25.0
`panelfontstyle`	(blank) normal italic oblique	Use to change the panels text style.	normal	25.0

Sample code

{ACCORDION(headers="Item 1|Item 2|Item 3")} Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nullam pharetra placerat consectetur. Nulla semper neque vitae odio euismod eleifend. Sed interdum aliquet commodo. ///// Quisque non maximus enim, id scelerisque lectus. Aenean euismod, risus vel fringilla ullamcorper, nisi orci fermentum quam, vel rutrum diam est vel ligula. ///// Sed placerat enim sed porta volutpat. Sed dolor felis, placerat sed vulputate vel, placerat at justo. Aliquam condimentum finibus velit id pulvinar. {ACCORDION}

Will produce:

Item 1

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nullam pharetra placerat consectetur. Nulla semper neque vitae odio euismod eleifend. Sed interdum aliquet commodo.

Item 2

Quisque non maximus enim, id scelerisque lectus. Aenean euismod, risus vel fringilla ullamcorper, nisi orci fermentum quam, vel rutrum diam est vel ligula.

Item 3

Sed placerat enim sed porta volutpat. Sed dolor felis, placerat sed vulputate vel, placerat at justo. Aliquam condimentum finibus velit id pulvinar.