

Plugin Snarf

Use this [wiki plugin](#) to include the body (HTML) text at the URL given in the `url` argument. It is similar to [Integrator](#).

PARAMETERS

Display the contents of another web page
*Introduced in Tiki 1. Required parameters are in **bold**.*

[Go to the source code](#)

Preferences required: wikiplugin_snarf

Parameters	Accepted Values
------------	-----------------

<code>url</code>	url
------------------	-----

<code>cache</code>	int
--------------------	-----

<code>colors</code>	text
---------------------	------

Description

Full URL to the page to include.

Cache time in minutes. Default is to use site preference,
Set to for no cache.

Syntax highlighting to use for code snippets (Plugin
Code is used for this)

Default	Since
	1
	5.0
	3.0

ajax

text

regex

text

regexres

text

ishtml

(blank)

1

0

ln

(blank)

1

0

Text to click on to fetch the URL via Ajax

PCRE-compliant regular expression pattern to find the parts you want changed

PCRE-compliant regular expression replacement syntax showing what the content should be changed to

Set to Yes () to display the content as is instead of escaping HTML special characters (not set by default).

Set to Yes () to add line numbers to code snippets (not shown by default)

6.0

1

1

3.0

3.0

rtl

(blank)

1

0

wiki

(blank)

1

0

wrap

(blank)

1

0

Switch the text display from left to right to right to left

Parse wiki syntax within the code snippet (not parsed by default).

Enable/disable word wrapping of snippets of code (enabled by default)

3.0

0

3.0

1

3.0

Arbitrary [regex](#) replacement can be done on this content using `regex` and `regexres` , which are used as the first and second arguments to `preg_replace` PHP function, respectively, after pulling out just the `<body>` data.

EXAMPLES

```
{SNARF (url="http://www.livejournal.com/users/rlpowell/2418.html" regex="/*<!-- Content -
->.*?<td>(.*?)</td>.*?</div>(.*?)<hr.*?<!-- \Content -->.*?/s"
regexres="<p>$1</p>$2")}[http://www.livejournal.com/users/rlpowell/2418.html] {SNARF}
```

To include the content of a page of another Tiki installation you can use the following syntax:

```
{snarf url="http://my.foo.bar/tiki-index_raw_raw.php?page=ExamplePage" wrap="1" ishtml="1" cache="20"}
```

 Note

Do NOT type: `"/tiki-index_raw.php?page=..."` BUT `"/tiki-index_raw_raw.php?page=..."`

INCLUDE TIKI.ORG FOOTER PAGE

```
{snarf url="https://tiki.org/tiki-index_raw_raw.php?page=Shared_t_o_footer&clean" ishtml=1}
```

Produces:

(currently output is "broken" in Tiki 20.x on this site )



RELATED PAGES

- <http://wikipedia.org/wiki/regex>
- [PluginInclude](#)
- [PluginTransclude](#)
- [PluginHTMLfeed](#)