

Plugin Tracker Prefill

Introduced in Tiki2

Use this [wiki plugin](#) for [trackers](#) to display a button with a link to a page containing a tracker plugin [PluginTracker](#). In the parameters, you will be able to specify default values for some fields.

PARAMETERS

Create a button to prefill tracker fields

*Introduced in Tiki 2. Required parameters are in **bold**.*

[Go to the source code](#)

Preferences required: feature_trackers, wikiplugin_trackerprefill

Parameters Accepted Values

value1	any string except for HTML and PHP tags
field1	digits
page	pagename
label	text

Description

Content that should be used to prefill the field.

Field ID for the first field

Tracker page name

Button Label.

Default	Since
	2.0
	2.0
	2.0
	2.0

urlparams

any string except for HTML and PHP tags

value2

any string except for HTML and PHP tags

value3

any string except for HTML and PHP tags

value4

any string except for HTML and PHP tags

value5

any string except for HTML and PHP tags

value6

any string except for HTML and PHP tags

value7

any string except for HTML and PHP tags

value8

any string except for HTML and PHP tags

field2

digits

Parameters to pass in the URL, for example,

`&my_parameter1=123&my_parameter2=q`

Content that should be used to prefill the field.

Content that should be used to prefill the field.

Content that should be used to prefill the field.

Content that should be used to prefill the field.

Content that should be used to prefill the field.

Content that should be used to prefill the field.

Content that should be used to prefill the field.

Field ID for the second field

6.0

2.0

2.0

2.0

2.0

2.0

2.0

2.0

2.0

field3	digits
--------	--------

field4	digits
--------	--------

field5	digits
--------	--------

field6	digits
--------	--------

field7	digits
--------	--------

field8	digits
--------	--------

Field ID for the third field

Field ID for the fourth field

Field ID for the fifth field

Field ID for the sixth field

Field ID for the seventh field

Field ID for the eighth field

2.0

2.0

2.0

2.0

2.0

2.0

EXAMPLE

```
{trackerprefill page="Order" label="Order" field1="2" value1="Shoes" field2="3" value2="10"}
```

The above syntax will create a button labelled "Order" that will link to `tiki-index_raw.php?page=Order&prefills=2:3&values[]=Shoes&values[]=10`

If the wiki page named "Order" contains a tracker plugin with 2 fields (2 and 3), the tracker form will prefill in the fields 2 and 3 values "Shoes" and "10".