

Plugin Twitter

Introduced in Tiki7

Use this wiki plugin to display the activity for a Twitter account.

Parameters

Display the activity for a twitter account

*Introduced in Tiki 7. Required parameters are in **bold**.*

[Go to the source code](#)

Preferences required: wikiplugin_twitter

Parameters	Accepted Values	Description	Default	Since
<code>tweet</code>	text	Depends on the type of timeline (Users, Collections, Favorites or Lists). For a User, it is the Account Name (like <code>twitterdev</code>), for Favorites, something like <code>twitterdev/favorites</code> . For lists, something like <code>twitterdev/lists/listname</code> , etc.		7.0
<code>widgetId</code>	digits	Numeric identifier of the widget		13.1
<code>tweetbg</code>		Change the border color used by the widget. Default is theme default.		7.0
<code>height</code>	digits	Height of widget in pixels. Default is <code>300</code> .	300	7.0
<code>tweetcolor</code>		Text color for individual tweets. Default is theme default.		7.0
<code>noborders</code>	(blank) y	Default is with Borders		13.1
<code>nofooter</code>	(blank) y	Default is with Footer		13.1
<code>noheader</code>	(blank) y	Default is with Header		13.1
<code>noscrollbar</code>	(blank) y	Default is with Scrollbar		13.1
<code>theme</code>	(blank) light dark	Embedded timelines are available in light and dark themes for customization. The light theme is for pages that use a light colored background, while the dark theme is for pages that use a dark colored background. Default is <code>light</code> .	light	13.1
<code>shellbg</code>	(blank) transparent	Transparent Shell Background. Default is theme default		7.0
<code>width</code>		Width of widget in pixels or 'auto' to fit to width of page. Default is <code>auto</code> .	auto	7.0

Note that Twitter requires that you have an account on Twitter and that you first create your widget there, so you get
widgetId number from Twitter for the widget

Example

Basic syntax

```
{twitter tweet="tikiwiki" widgetId="xxxxxxxxxx" }
```