

Option

Default order

Section order

Topics

Posts

Posts per day (PPD)

Last post

Visits

Description

Description

Default

Option

Description length

Include category selector in forum list

Forum post categories

Description

Include a dropdown selector in the forum list to choose a category for the post.

Categories available in the category picker for forum posts.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Default order

Section order

Topics

Description

Default

Option

Posts

Posts per day (PPD)

Last post

Visits

Description

Description length

Include category selector in forum list

Description

Include a dropdown selector in the forum list to choose a category for the post.

Default

Option

Forum post categories

Description

Categories available in the category picker for forum posts.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Default order

Section order

Topics

Posts

Posts per day (PPD)

Last post

Description

Default

Option

Visits

Description

Description length

Include category selector in forum list

Forum post categories

Description

Include a dropdown selector in the forum list to choose a category for the post.

Categories available in the category picker for forum posts.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Default order

Description

Default

Option

Topics

Posts

Posts per day (PPD)

Last post

Visits

Description

Description length

Include category selector in forum list

Description

Include a dropdown selector in the forum list to choose a category for the post.

Default

Option

Forum post categories

Description

Categories available in the category picker for forum posts.

Default

Unable to load the jQuery Sortable Tables feature.

FORUMS - GENERAL SETTINGS

Option

Forums

Home forum (main forum)

Forum image file gallery

Rankings

Description

Threaded or flat discussions.

File gallery used to store images for forums

Users can see several charts or rankings about the page.

Default

Option

Accept wiki syntax

Strip wiki markup from outgoing forum emails

Topic archiving

Quick jumps

Replies are empty

Allows quoting in flat forums

Don't display forum thread titles

Description

Convert outgoing emails from forum posts to plain text.

If disabled, replies will quote the original post

Allows users to reply.

Titles of posts usually don't change because they are a direct reply to the parent post. This feature turns off the display of titles in edit forms and forum display.

Default

Option

Do not start messages titles with 'Re:'

Require reply to have a title

First post of a thread can have an empty body

Prevent Nesting of Quote wikipugins when replying

Allow inbound email posts from anyone

Description

Present an empty title input form and require it to be filled in before the forum post is submitted.

Will be a thread title

Strips quote plugin in reply in order to prevent nesting of quote plugins.

Allow messages from non-users in the forums using incoming messages from any email address.

Default

Option

Parse HTML in inbound email posts

Uploaded filenames must match regex

Send moderation email

Approve link in moderation email

Manage thread defaults per-forum

Display thread configuration bar

Description

Attempt to keep the formatting of HTML "rich text" emails if using WYSIWYG.

Experimental Has problems with some HTML emails, especially those with table-based layouts.

Send email to forum moderators when post is queued
Include a link for forum moderators to approve queue
from email

Allows users to override the defaults

Default

Option

Keep settings for all forums during the user session

Display the thread configuration bar only when the number of posts exceeds

Number per page

Default style

Default sort mode

Display forum thread or forum post title in the search engine friendly URL

Description

Default

Option

New email thread for each topic

Forum name search

Forum content search

Topic content search

Unified search for forums and file galleries

Index posts on forum section change.

Description

If enabled each topic a forum will use it's own email thread, instead of all forum posts sharing the same one.

When listing forums

When listing forums

Re-indexes forum posts to match the parent section when the section is changed

Default

Unable to load the jQuery Sortable Tables feature.

Option

Forums

Home forum (main forum)

Forum image file gallery

Rankings

Accept wiki syntax

Strip wiki markup from outgoing forum emails

Topic archiving

Quick jumps

Description

Threaded or flat discussions.

File gallery used to store images for forums

Users can see several charts or rankings about the page.

Convert outgoing emails from forum posts to plain text.

Default

Option

Replies are empty

Allows quoting in flat forums

Don't display forum thread titles

Do not start messages titles with 'Re:'

Require reply to have a title

First post of a thread can have an empty body

Description

If disabled, replies will quote the original post

Allows users to reply.

Titles of posts usually don't change because they are a direct reply to the parent post. This feature turns off the display of titles in edit forms and forum display.

Present an empty title input form and require it to be filled in before the forum post is submitted.

Will be a thread title

Default

Option

Prevent Nesting of Quote wikiplugins when replying

Allow inbound email posts from anyone

Parse HTML in inbound email posts

Uploaded filenames must match regex

Send moderation email

Description

Strips quote plugin in reply in order to prevent nesting of quote plugins.

Allow messages from non-users in the forums using incoming messages from any email address.

Attempt to keep the formatting of HTML "rich text" emails if using WYSIWYG.

Experimental Has problems with some HTML emails, especially those with table-based layouts.

Send email to forum moderators when post is queued

Default

Option

Approve link in moderation email

Manage thread defaults per-forum

Display thread configuration bar

Keep settings for all forums during the user session

Display the thread configuration bar only when the number of posts exceeds

Number per page

Default style

Description

Include a link for forum moderators to approve queue from email

Allows users to override the defaults

Default

Option

Default sort mode

Display forum thread or forum post title in the search engine friendly URL

New email thread for each topic

Forum name search

Forum content search

Topic content search

Unified search for forums and file galleries

Description

If enabled each topic a forum will use it's own email thread, instead of all forum posts sharing the same one.

When listing forums

When listing forums

Default

Option

Index posts on forum section change.

Description

Re-indexes forum posts to match the parent section when the section is changed

Default

Unable to load the jQuery Sortable Tables feature.

Option

Forums

Home forum (main forum)

Forum image file gallery

Rankings

Accept wiki syntax

Description

Threaded or flat discussions.

File gallery used to store images for forums

Users can see several charts or rankings about the page.

Default

Option

Strip wiki markup from outgoing forum emails

Topic archiving

Quick jumps

Replies are empty

Allows quoting in flat forums

Don't display forum thread titles

Do not start messages titles with 'Re:'

Description

Convert outgoing emails from forum posts to plain text.

If disabled, replies will quote the original post

Allows users to reply.

Titles of posts usually don't change because they are a direct reply to the parent post. This feature turns off the display of titles in edit forms and forum display.

Default

Option

Require reply to have a title

First post of a thread can have an empty body

Prevent Nesting of Quote wikiplugins when replying

Allow inbound email posts from anyone

Description

Present an empty title input form and require it to be filled in before the forum post is submitted.

Will be a thread title

Strips quote plugin in reply in order to prevent nesting of quote plugins.

Allow messages from non-users in the forums using incoming messages from any email address.

Default

Option

Parse HTML in inbound email posts

Uploaded filenames must match regex

Send moderation email

Approve link in moderation email

Manage thread defaults per-forum

Display thread configuration bar

Description

Attempt to keep the formatting of HTML "rich text" emails if using WYSIWYG.

Experimental Has problems with some HTML emails, especially those with table-based layouts.

Send email to forum moderators when post is queued
Include a link for forum moderators to approve queue
from email

Allows users to override the defaults

Default

Option

Keep settings for all forums during the user session

Display the thread configuration bar only when the number of posts exceeds

Number per page

Default style

Default sort mode

Display forum thread or forum post title in the search engine friendly URL

Description

Default

Option

New email thread for each topic

Forum name search

Forum content search

Topic content search

Unified search for forums and file galleries

Index posts on forum section change.

Description

If enabled each topic a forum will use it's own email thread, instead of all forum posts sharing the same one.

When listing forums

When listing forums

Re-indexes forum posts to match the parent section when the section is changed

Default

Unable to load the jQuery Sortable Tables feature.

Option

Forums

Home forum (main forum)

Forum image file gallery

Rankings

Accept wiki syntax

Strip wiki markup from outgoing forum emails

Topic archiving

Quick jumps

Description

Threaded or flat discussions.

File gallery used to store images for forums

Users can see several charts or rankings about the page.

Convert outgoing emails from forum posts to plain text.

Default

Option

Replies are empty

Allows quoting in flat forums

Don't display forum thread titles

Do not start messages titles with 'Re:'

Require reply to have a title

First post of a thread can have an empty body

Description

If disabled, replies will quote the original post

Allows users to reply.

Titles of posts usually don't change because they are a direct reply to the parent post. This feature turns off the display of titles in edit forms and forum display.

Present an empty title input form and require it to be filled in before the forum post is submitted.

Will be a thread title

Default

Option

Prevent Nesting of Quote wikiplugins when replying

Allow inbound email posts from anyone

Parse HTML in inbound email posts

Uploaded filenames must match regex

Send moderation email

Description

Strips quote plugin in reply in order to prevent nesting of quote plugins.

Allow posts from non-users in forums using inbound posts from a specified email address.

Attempt to keep the formatting of HTML "rich text" emails if using WYSIWYG.

Experimental Has problems with some HTML emails, especially those with table-based layouts.

Send email to forum moderators when post is queued

Default

Option

Approve link in moderation email

Manage thread defaults per-forum

Display thread configuration bar

Keep settings for all forums during the user session

Display the thread configuration bar only when the number of posts exceeds

Number per page

Default style

Description

Include a link for forum moderators to approve queue from email

Allows users to override the defaults

Default

Option

Default sort mode

Display forum thread or forum post title in the search engine friendly URL

Forum name search

Forum content search

Topic content search

Tiki-indexed search

Use database (full-text) search

Description

When listing forums

When listing forums

Default

Option

Index posts on forum section change.

Description

Re-indexes forum posts to match the parent section when the section is changed

Default

Unable to load the jQuery Sortable Tables feature.

TAGS

Option

Tags

Plugin Tagged

Plugin Add Tag

Show tag cloud

Description

Enables tags to be set on pages and other items for freefo

List similarly tagged objects

Provide an input field for adding a tag to an object

Show the full tag cloud in the list-tags screen.

Default

Option

Maximum number of tags in cloud

Show tags in middle column

Tag Suggestions

Valid characters pattern

Lowercase tags only

Multilingual tags

Description

On pages that have content tagged, this option enables the properties tab when editing a wiki page..

Number of tags to show in tag suggestions

Click on the links below to set or clear a pattern to limit ch

Useful to eliminate characters such as

*ÃfÆ'Ã†â€™ Ãfâ€šÃ,ÂçÃfÆ'Ã,ÂçÃfÂçÃçâ€šÃ¬Ã...Ã;Ãfâ€šÃ,,
which users can enter by mistake instead of a space.*

Convert uppercase characters in tags to lowercase, if this

Permits translation management of tags

Default

Option

"More Like This" algorithm

Minimum number of tags in common

Ordering of tagged objects

Preload random tag

Description

enables tagged material to offer a find potentially related being viewed. Weighted is the same, but items are present

The minimum number of matching tags required for an item

Default sort mode for tagged items

A random tag will be selected on the tag search page (if n

Default

Unable to load the jQuery Sortable Tables feature.

Option

Tags

Plugin Tagged

Plugin Add Tag

Description

Enables tags to be set on pages and other items for freefo

List similarly tagged objects

Provide an input field for adding a tag to an object

Default

Option

Show tag cloud

Maximum number of tags in cloud

Show tags in middle column

Tag Suggestions

Valid characters pattern

Lowercase tags only

Description

Show the full tag cloud in the list-tags screen.

On pages that have content tagged, this option enables the properties tab when editing a wiki page..

Number of tags to show in tag suggestions

Click on the links below to set or clear a pattern to limit ch

Useful to eliminate characters such as

ÃfÆ'Ã†â€™ Ãfâ€šÃ,ÂçÃfÆ'Ã,ÂçÃfÂçÃçâ€šÃ¬Ã...Ã;Ãfâ€šÃ,,

which users can enter by mistake instead of a space.

Convert uppercase characters in tags to lowercase, if this

Default

Option

Multilingual tags

"More Like This" algorithm

Minimum number of tags in common

Ordering of tagged objects

Preload random tag

Description

Permits translation management of tags

enables tagged material to offer a find potentially related being viewed. Weighted is the same, but items are present

The minimum number of matching tags required for an item

Default sort mode for tagged items

A random tag will be selected on the tag search page (if n

Default

Unable to load the jQuery Sortable Tables feature.

Option

Tags

Plugin Tagged

Description

Enables tags to be set on pages and other items for freefo

List similarly tagged objects

Default

Option

Plugin Add Tag

Show tag cloud

Maximum number of tags in cloud

Show tags in middle column

Tag Suggestions

Valid characters pattern

Description

Provide an input field for adding a tag to an object

Show the full tag cloud in the list-tags screen.

On pages that have content tagged, this option enables the properties tab when editing a wiki page..

Number of tags to show in tag suggestions

Click on the links below to set or clear a pattern to limit ch

Useful to eliminate characters such as

ÃfÆ'Ã†â€™ Ãfâ€šÃ,ÂçÃfÆ'Ã,ÂçÃfÂçÃçâ€šÃ¬Ã...Ã;Ãfâ€šÃ,,

which users can enter by mistake instead of a space.

Default

Option

Lowercase tags only

Multilingual tags

"More Like This" algorithm

Minimum number of tags in common

Ordering of tagged objects

Preload random tag

Description

Convert uppercase characters in tags to lowercase, if this

Permits translation management of tags

enables tagged material to offer a find potentially related
being viewed. Weighted is the same, but items are present

The minimum number of matching tags required for an item

Default sort mode for tagged items

A random tag will be selected on the tag search page (if n

Default

Unable to load the jQuery Sortable Tables feature.

Option

Tags

Description

Enables tags to be set on pages and other items for freefo

Default

Option

Plugin Tagged

Plugin Add Tag

Show tag cloud

Maximum number of tags in cloud

Show tags in middle column

Tag Suggestions

Description

List similarly tagged objects

Provide an input field for adding a tag to an object

Show the full tag cloud in the list-tags screen.

On pages that have content tagged, this option enables the properties tab when editing a wiki page..

Number of tags to show in tag suggestions

Default

Option

Valid characters pattern

Lowercase tags only

Multilingual tags

"More Like This" algorithm

Minimum number of tags in common

Ordering of tagged objects

Description

Click on the links below to set or clear a pattern to limit ch

Useful to eliminate characters such as

ÃfÆ'Ã†â€™ Ãfâ€šÃ,ÂçÃfÆ'Ã,ÂçÃfÂçÃçâ€šÃ¬Ã...Ã;Ãfâ€šÃ,

which users can enter by mistake instead of a space.

Convert uppercase characters in tags to lowercase, if this

Permits translation management of tags

enables tagged material to offer a find potentially related

being viewed. Weighted is the same, but items are presen

The minimum number of matching tags required for an ite

Default sort mode for tagged items

Default

Option

Preload random tag

Description

A random tag will be selected on the tag search page (if n

Default

Unable to load the jQuery Sortable Tables feature.

GALLERIES - FEATURES

Option

Image gallery

Home gallery (main gallery)

Rankings

Image Gallery Comments

Description

Collections of images for viewing or downloading (photo albums)

Users can see several charts or rankings about the file.

Users with permission may post threaded comments.

The comments will appear at the bottom of the page.

Default

Option

Slideshow

Storage

Directory path

Image processing library

Uploaded image names must match regex

Uploaded image names cannot match regex

Description

If you change this directory, move any images to the new directory either manually or using the 'Mover' below.

GD 2.3.3 detected. Imagick 0 not detected.

Default

Option

Enable directory batch loading

Batch loading directory

Limit image gallery categories to those under this category

Display image information in a mouseover box

Description

Import large number of files by placing them them in a local directory accessible via a network share, scp, ftp, or other protocols.

You will need to setup a web-readable directory (outside of your web space is better). Then create a way to upload images to that directory.

Needs to be a web-readable directory.

Default

Option

Set display settings for all galleries

Maximum rows per page

Images per row

Thumbnail width

Thumbnail height

Default scale size

Name

Parent

Description

Description

Default

Option

Created

Last modified

User

Images

Visits

Default number of comments per page

Default order of comments

Description

Default

Unable to load the jQuery Sortable Tables feature.

GENERAL - DATE AND TIME

Option

Time zone

Displayed time zone

Long date format

Short date format

Long time format

Short time format

Short JavaScript date format

Description

Indicates the default time zone to use for the server.

Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.

Specify how Tiki displays the date (longer version)

Specify how Tiki displays the date (shorter version)

Specify how Tiki displays the time (longer version)

Specify how Tiki displays the time (shorter version)

Used in jQuery-UI date picker fields

Default

Option

Short JavaScript time format

Fields display order

Start year

End year

Select month in Date Picker

Description

Used in jQuery-UI datetime picker fields

The order date field inputs should be listed in.

Year to show first in dropdown lists.

For example, use "-2" for the current year minus two, or "2010" for a specific year

Year to show last on dropdown lists.

For example, use "+2" for the current year plus two, or "2016" for a specific year

Users can select month in the Date Picker instead of seeing month as text.

Default

Option

Select year in Date Picker

Use 12-hour clock for time selectors

Skip date for same day

jQuery Timeago

Plugin Now

Plugin Countdown

Description

Users can select year in the Date Picker instead of seeing year as text.

Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.

When displaying short date and time, skip date for today. Only time will be displayed.

jQuery plugin for fuzzy timestamps.

Show the current date and time

Display the time until or after a date and time

Default

Option

Plugin Convene

Description

Suggest meeting dates and times and vote to select one

Default

Unable to load the jQuery Sortable Tables feature.

Option

Time zone

Displayed time zone

Long date format

Short date format

Long time format

Description

Indicates the default time zone to use for the server.

Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.

Specify how Tiki displays the date (longer version)

Specify how Tiki displays the date (shorter version)

Specify how Tiki displays the time (longer version)

Default

Option

Short time format

Short JavaScript date format

Short JavaScript time format

Fields display order

Start year

End year

Description

Specify how Tiki displays the time (shorter version)

Used in jQuery-UI date picker fields

Used in jQuery-UI datetime picker fields

The order date field inputs should be listed in.

Year to show first in dropdown lists.

For example, use "-2" for the current year minus two, or "2010" for a specific year

Year to show last on dropdown lists.

For example, use "+2" for the current year plus two, or "2016" for a specific year

Default

Option

Select month in Date Picker

Select year in Date Picker

Use 12-hour clock for time selectors

Skip date for same day

jQuery Timeago

Description

Users can select month in the Date Picker instead of seeing month as text.

Users can select year in the Date Picker instead of seeing year as text.

Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.

When displaying short date and time, skip date for today. Only time will be displayed.

jQuery plugin for fuzzy timestamps.

Default

Option

Plugin Now

Plugin Countdown

Plugin Convene

Description

Show the current date and time

Display the time until or after a date and time

Suggest meeting dates and times and vote to select one

Default

Unable to load the jQuery Sortable Tables feature.

Option

Time zone

Displayed time zone

Long date format

Description

Indicates the default time zone to use for the server.

Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.

Specify how Tiki displays the date (longer version)

Default

Option

Short date format

Long time format

Short time format

Short JavaScript date format

Short JavaScript time format

Fields display order

Start year

Description

Specify how Tiki displays the date (shorter version)

Specify how Tiki displays the time (longer version)

Specify how Tiki displays the time (shorter version)

Used in jQuery-UI date picker fields

Used in jQuery-UI datetime picker fields

The order date field inputs should be listed in.

Year to show first in dropdown lists.

For example, use "-2" for the current year minus two, or "2010" for a specific year

Default

Option

End year

Select month in Date Picker

Select year in Date Picker

Use 12-hour clock for time selectors

Description

Year to show last on dropdown lists.

For example, use "+2" for the current year plus two, or "2016" for a specific year

Users can select month in the Date Picker instead of seeing month as text.

Users can select year in the Date Picker instead of seeing year as text.

Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.

Default

Option

Skip date for same day

jQuery Timeago

Plugin Now

Plugin Countdown

Plugin Convene

Description

When displaying short date and time, skip date for today. Only time will be displayed.

jQuery plugin for fuzzy timestamps.

Show the current date and time.

Display the time until or after a date and time

Suggest meeting dates and times and vote to select one.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Time zone

Description

Indicates the default time zone to use for the server.

Default

Option

Displayed time zone

Long date format

Short date format

Long time format

Short time format

Short JavaScript date format

Short JavaScript time format

Description

Use time zone set from user preferences, or the automatically detected time zone for anonymous (if browser allows). Site default is used as fallback.

Specify how Tiki displays the date (longer version)

Specify how Tiki displays the date (shorter version)

Specify how Tiki displays the time (longer version)

Specify how Tiki displays the time (shorter version)

Used in jQuery-UI date picker fields

Used in jQuery-UI datetime picker fields

Default

Option

Fields display order

Start year

End year

Use 12-hour clock for time selectors

Description

The order date field inputs should be listed in.

Year to show first in dropdown lists.

For example, use "-2" for the current year minus two, or "2010" for a specific year

Year to show last on dropdown lists.

For example, use "+2" for the current year plus two, or "2016" for a specific year

Use the 12-hour clock (with AM and PM) in some edit screens to set the time for publishing new or edited blog posts, articles, etc.

Default

Option

Skip date for same day

jQuery Timeago

Plugin Now

Plugin Countdown

Plugin TimeSheet

Plugin Convene

Description

When displaying short date and time, skip date for today. Only time will be displayed.

jQuery plugin for fuzzy timestamps.

Show the current date and time.

Display the time until or after a date and time

Embed a timesheet into a page

Suggest meeting dates and times and vote to select one.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Server domain name

Browser title

Description

The value that will be used by default as the server domain name of your Tiki site.

Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and require database or shell access to recover it.

Visible label in the browser's title bar on all pages. Also appears in search engine results.

Default

Option

Fallback for tiki base URL

Browser title position

Browser title display mode

Sender email

Description

The full URL to the Tiki base URL including protocol, domain and path (example: <https://example.com/tiki/>), used when the current URL can not be determined, example, when executing from the command line.

Position of the browser title in the full browser bar relative to the current page's descriptor.

When breadcrumbs are used, method to display the browser title.

Email address that will be used as the sender for outgoing emails.

Default

Option

Sender full name

Default character set for sending mail

Email newline character(s)

Apply site styles to HTML emails

Description

Real name that will be used as the sender for outgoing emails

Specify the character encoding used by Tiki when sending mail notifications.

End-of-line (EOL) character used in outgoing emails

Add site CSS to all HTML formatted emails

Default

Option

Mail sender

Amazon SES Key

Amazon SES Secret

Amazon SES Region

Amazon SES version

Elastic Email Username

Description

Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at `./temp/Mail_yyyymmddhhmmss_randomstring.tmp`) to send mail notifications.

Default

Option

Elastic Email Key

Mailgun Domain

Mailgun Key

Mailgun API Endpoint

Mandrill Key

Postage Key

Postmark Key

SendGrid Username

SendGrid Key

Description

Default

Option

SparkPost Key

SMTP server

Authentication

Username

Password

Port

Security

Description

Mail server authentication

Default

Option

Verify HTTPS certificates of remote servers

Local server name

Mail delivery

Description

When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)

Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.

When set to Queue, messages will be stored in the database. Requires using the shell script `php console.php mail-queue:send` to be run for actual delivery.

Default

Option

Catch-all email address

Email footer

Text string used to customise mail templates

Throttle newsletter send rate

Newsletter pause length

Newsletter batch size

Description

Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.

Text appended to outgoing emails.

Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files

Pause for a given amount of seconds before each batch to avoid overloading the mail server.

Number of seconds delay before each batch

Number of emails to send in each batch

Default

Option

Allow sending newsletters through external clients

PHP Error reporting level

PHP errors visible to admin only

Description

Generate mailto links using the recipients as the BCC list.

This will expose the list of email addresses to all users allowed to send newsletters.

Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.

PHP Errors will be shown to only the Admin user.

During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.

Default

Option

Include Smarty notices in the PHP error report

Show generic error message

Generic error message

Description

Tiki will display **Smarty** notices with the PHP error messages.

In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.

Show a generic error message for non admins users. The error is logged to the database.

Message to display to non admin users when an error occurs.

Default

Option

Disable JavaScript

Log mail in Tiki logs

Description

Disable JavaScript for the purpose of testing even if enabled in the browser.

Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.

A line of type mail will be included in the System Log with the destination address and subject of each email sent.

May impact performance

Default

Option

Log SQL

Log queries using more than

Data Source Name (DSN)

Description

All SQL queries will be registered in the database in the `adodb_logsql` table.

Do not enable this feature all the time. It can be very resource intensive and will impact performance.

Use to log only queries that exceed a specific amount of time.

May impact performance

DSN used for connect to the error tracking service.

Default

Option

Sample rate

Track PHP errors

Track JavaScript errors

Description

Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)

Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.

Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.

Default

Option

Enabled

How to trigger Web Cron

Run interval

Token

Scheduler

Delay scheduled time (minutes)

Description

Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.

The amount of time of each run

The token to use when running the cron manually

Provides the ability to run tasks at a scheduled time.

When calculating if the jobs should run, take the delay into consideration

Default

Option

Scheduler stalled after (minutes)

Notify on stalled schedulers

Users to notify on stalled task

Self healing after (minutes)

Description

Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.

Send an email notification when a stalled scheduler is detected.

List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing

Default

Option

Notify on healed schedulers

Users to notify on healed task

Number of logs to keep

Description

Send an email notification when a stalled scheduler is healed.

List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

0 will keep all logs

Default

Unable to load the jQuery Sortable Tables feature.

Option

Server domain name

Browser title

Description

The value that will be used by default as the server domain name of your Tiki site.

Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and require database or shell access to recover it.

Visible label in the browser's title bar on all pages. Also appears in search engine results.

Default

Option

Fallback for tiki base URL

Browser title position

Browser title display mode

Sender email

Description

The full URL to the Tiki base URL including protocol, domain and path (example: <https://example.com/tiki/>), used when the current URL can not be determined, example, when executing from the command line.

Position of the browser title in the full browser bar relative to the current page's descriptor.

When breadcrumbs are used, method to display the browser title.

Email address that will be used as the sender for outgoing emails.

Default

Option

Sender full name

Default character set for sending mail

Email newline character(s)

Apply site styles to HTML emails

Description

Real name that will be used as the sender for outgoing emails

Specify the character encoding used by Tiki when sending mail notifications.

End-of-line (EOL) character used in outgoing emails

Add site CSS to all HTML formatted emails

Default

Option

Mail sender

Amazon SES Key

Amazon SES Secret

Amazon SES Region

Amazon SES version

Elastic Email Username

Description

Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at `./temp/Mail_yyyymmddhhmmss_randomstring.tmp`) to send mail notifications.

Default

Option

Elastic Email Key

Mailgun Domain

Mailgun Key

Mailgun API Endpoint

Mandrill Key

Postage Key

Postmark Key

SendGrid Username

SendGrid Key

Description

Default

Option

SparkPost Key

SMTP server

Authentication

Username

Password

Port

Security

Description

Mail server authentication

Default

Option

Verify HTTPS certificates of remote servers

Local server name

Mail delivery

Description

When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)

Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.

When set to Queue, messages will be stored in the database. Requires using the shell script `php console.php mail-queue:send` to be run for actual delivery. Only works with SMTP mail.

Default

Option

Catch-all email address

Email footer

Text string used to customise mail templates

Throttle newsletter send rate

Newsletter pause length

Newsletter batch size

Description

Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.

Text appended to outgoing emails.

Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files

Pause for a given amount of seconds before each batch to avoid overloading the mail server.

Number of seconds delay before each batch

Number of emails to send in each batch

Default

Option

Allow sending newsletters through external clients

PHP Error reporting level

PHP errors visible to admin only

Description

Generate mailto links using the recipients as the BCC list.

This will expose the list of email addresses to all users allowed to send newsletters.

Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.

PHP Errors will be shown to only the Admin user.

During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.

Default

Option

Include Smarty notices in the PHP error report

Show generic error message

Generic error message

Description

Tiki will display **Smarty** notices with the PHP error messages.

In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.

Show a generic error message for non admins users. The error is logged to the database.

Message to display to non admin users when an error occurs.

Default

Option

Disable JavaScript

Log mail in Tiki logs

Description

Disable JavaScript for the purpose of testing even if enabled in the browser.

Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.

A line of type mail will be included in the System Log with the destination address and subject of each email sent.

May impact performance

Default

Option

Log SQL

Log queries using more than

Data Source Name (DSN)

Description

All SQL queries will be registered in the database in the `adodb_logsql` table.

Do not enable this feature all the time. It can be very resource intensive and will impact performance.

Use to log only queries that exceed a specific amount of time.

May impact performance

DSN used for connect to the error tracking service.

Default

Option

Sample rate

Track PHP errors

Track JavaScript errors

Description

Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)

Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.

Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.

Default

Option

Enabled

How to trigger Web Cron

Run interval

Token

Scheduler

Delay scheduled time (minutes)

Description

Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.

The amount of time of each run

The token to use when running the cron manually

Provides the ability to run tasks at a scheduled time.

When calculating if the jobs should run, take the delay into consideration

Default

Option

Scheduler stalled after (minutes)

Notify on stalled schedulers

Users to notify on stalled task

Self healing after (minutes)

Description

Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.

Send an email notification when a stalled scheduler is detected.

List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing

Default

Option

Notify on healed schedulers

Users to notify on healed task

Number of logs to keep

Description

Send an email notification when a stalled scheduler is healed.

List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

0 will keep all logs

Default

Unable to load the jQuery Sortable Tables feature.

Option

Browser title

Description

Visible label in the browser's title bar on all pages. Also appears in search engine results.

Default

Option

Fallback for tiki base URL

Browser title position

Browser title display mode

Sender email

Description

The full URL to the Tiki base URL including protocol, domain and path (example: <https://example.com/tiki/>), used when the current URL can not be determined, example, when executing from the command line.

Position of the browser title in the full browser bar relative to the current page's descriptor.

When breadcrumbs are used, method to display the browser title.

Email address that will be used as the sender for outgoing emails.

Default

Option

Sender full name

Default character set for sending mail

Email newline character(s)

Apply site styles to HTML emails

Description

Real name that will be used as the sender for outgoing emails

Specify the character encoding used by Tiki when sending mail notifications.

End-of-line (EOL) character used in outgoing emails

Add site CSS to all HTML formatted emails

Default

Option

Mail sender

Amazon SES Key

Amazon SES Secret

Amazon SES Region

Amazon SES version

Elastic Email Username

Description

Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at `./temp/Mail_yyyymmddhhmmss_randomstring.tmp`) to send mail notifications.

Default

Option

Elastic Email Key

Mailgun Domain

Mailgun Key

Mailgun API Endpoint

Mandrill Key

Postage Key

Postmark Key

SendGrid Username

SendGrid Key

Description

Default

Option

SparkPost Key

SMTP server

Authentication

Username

Password

Port

Security

Description

Mail server authentication

Default

Option

Verify HTTPS certificates of remote servers

Local server name

Mail delivery

Description

When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)

Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.

When set to Queue, messages will be stored in the database. Requires using the shell script `php console.php mail-queue:send` to be run for actual delivery. Only works with SMTP mail.

Default

Option

Catch-all email address

Email footer

Text string used to customise mail templates

Throttle newsletter send rate

Newsletter pause length

Newsletter batch size

Description

Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.

Text appended to outgoing emails.

Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files

Pause for a given amount of seconds before each batch to avoid overloading the mail server.

Number of seconds delay before each batch

Number of emails to send in each batch

Default

Option

Allow sending newsletters through external clients

PHP Error reporting level

PHP errors visible to admin only

Description

Generate mailto links using the recipients as the BCC list.

This will expose the list of email addresses to all users allowed to send newsletters.

Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.

PHP Errors will be shown to only the Admin user.

During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.

Default

Option

Include Smarty notices in the PHP error report

Disable JavaScript

Description

Tiki will display **Smarty** notices with the PHP error messages.

In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.

Disable JavaScript for the purpose of testing even if enabled in the browser.

Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.

Default

Option

Log mail in Tiki logs

Log SQL

Log queries using more than

Description

A line of type mail will be included in the System Log with the destination address and subject of each email sent.

May impact performance

All SQL queries will be registered in the database in the adodb_logsql table.

Do not enable this feature all the time. It can be very resource intensive and will impact performance.

Use to log only queries that exceed a specific amount of time.

May impact performance

Default

Option

Data Source Name (DSN)

Track PHP errors

Track JavaScript errors

Enabled

How to trigger Web Cron

Run interval

Description

DSN used for connect to the error tracking service.

Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.

Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.

Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.

The amount of time of each run

Default

Option

Token

Scheduler

Delay scheduled time (minutes)

Scheduler stalled after (minutes)

Notify on stalled schedulers

Description

The token to use when running the cron manually

Provides the ability to run tasks at a scheduled time.

When calculating if the jobs should run, take the delay into consideration

Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.

Send an email notification when a stalled scheduler is detected.

Default

Option

Users to notify on stalled task

Self healing after (minutes)

Notify on healed schedulers

Description

List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing

Send an email notification when a stalled scheduler is healed.

Default

Option

Users to notify on healed task

Number of logs to keep

Description

List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

0 will keep all logs

Default

Unable to load the jQuery Sortable Tables feature.

Option

Upgrade cycle

Description

Tiki upgrade frequency for this site to check against.

Default

Option

Check for updates automatically

Check frequency

Description

Tiki will automatically check for new updates each time you access the Admin Home page, based on your Check frequency selection.

Subscribe to the Tiki Newsletter to be notified of new releases. <https://doc.tiki.org/Newsletters>

How often Tiki should check for updates. This field applies only if "Check for updates automatically" is enabled.

Click "Check for Updates Now" to perform an update check.

Default

Option

Browser title

Server domain name

Fallback for tiki base URL

Browser title position

Description

Visible label in the browser's title bar on all pages. Also appears in search engine results.

The value that will be used by default as the server domain name of your Tiki site.

The full URL to the Tiki base URL including protocol, domain and path (example: <https://example.com/tiki/>), used when the current URL can not be determined, example, when executing from the command line.

Position of the browser title in the full browser bar relative to the current page's descriptor.

Default

Option

Browser title display mode

Sender email

Sender full name

Default character set for sending mail

Email newline character(s)

Apply site styles to HTML emails

Description

When breadcrumbs are used, method to display the browser title.

Email address that will be used as the sender for outgoing emails.

Real name that will be used as the sender for outgoing emails

Specify the character encoding used by Tiki when sending mail notifications.

End-of-line (EOL) character used in outgoing emails

Add site CSS to all HTML formatted emails

Default

Option

Mail sender

SMTP server

Authentication

Username

Password

Port

Description

Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at `./temp/Mail_yyyymmddhhmmss_randomstring.tmp`) to send mail notifications.

Mail server authentication

Default

Option

Security

Verify HTTPS certificates of remote servers

Local server name

Description

When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)

Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.

Default

Option

Mail delivery

Email footer

Text string used to customise mail templates

Throttle newsletter send rate

Newsletter pause length

Description

When set to Queue, messages will be stored in the database. Requires using the shell script `php console.php mail-queue:send` to be run for actual delivery. Only works with SMTP mail.

Text appended to outgoing emails.

Text string used to customise mail templates and added as a preference in the appropriate mail tpl files

Pause for a given amount of seconds before each batch to avoid overloading the mail server.

Number of seconds delay before each batch

Default

Option

Newsletter batch size

Allow sending newsletters through external clients

PHP Error reporting level

Description

Number of emails to send in each batch

Generate mailto links using the recipients as the BCC list.

This will expose the list of email addresses to all users allowed to send newsletters.

Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.

Default

Option

PHP errors visible to admin only

Include Smarty notices in the PHP error report

Description

PHP Errors will be shown to only the Admin user.

During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.

Tiki will display **Smarty** notices with the PHP error messages.

In most cases, Smarty notices can be safely ignored.

However, they may be useful in the development process when unexpected issues occur.

Default

Option

Disable JavaScript

Log mail in Tiki logs

Description

Disable JavaScript for the purpose of testing even if enabled in the browser.

Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.

A line of type mail will be included in the System Log with the destination address and subject of each email sent.

May impact performance

Default

Option

Log SQL

Log queries using more than

Enabled

Description

All SQL queries will be registered in the database in the `adodb_logsql` table.

Do not enable this feature all the time. It can be very resource intensive and will impact performance.

Use to log only queries that exceed a specific amount of time.

May impact performance

Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.

Default

Option

How to trigger Web Cron

Run interval

Token

Scheduler

Scheduler stalled after (minutes)

Notify on stalled schedulers

Description

The amount of time of each run

The token to use when running the cron manually

Provides the ability to run tasks at a scheduled time.

Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.

Send an email notification when a stalled scheduler is detected.

Default

Option

Users to notify on stalled task

Self healing after (minutes)

Notify on healed schedulers

Description

List of users/emails separated by comma to be notified when a scheduler task is set to stalled. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing

Send an email notification when a stalled scheduler is healed.

Default

Option

Users to notify on healed task

Number of logs to keep

Description

List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex:

admin,operations@example.com **If empty, the email will be sent to all administrators.**

0 will keep all logs

Default

Unable to load the jQuery Sortable Tables feature.

GENERAL - GENERAL SETTINGS

Option

Temporary directory

Use proxy

Proxy host name

Port

Proxy username

Description

Directory on your server, relative to your Tiki installation, for storing temporary files. Tiki must have full read and write access to this directory.

Specify if this Tiki site requires a proxy to access the internet. If enabled, the proxy Host name (either with or without the http:// prefix), Port settings, Username, and Password can be specified.

Proxy host - without http:// or similar, just the host name

Proxy port

Default

Option

Proxy password

HTTP lookup: skip framesets

Load balancer

Description

When performing an HTTP request to an external source, verify if the result is a frameset and use heuristic to provide the real content.

Activate this only if the server is behind a load balancer (or reverse proxy). This enables logging the IP of the user rather than the IP of the proxy server

Default

Option

Tiki is behind a frontend-proxy/load-balancer that rewrites ports

Access-Control-Allow-Origin

Description

Activate this only if the server is behind a frontend-proxy/load-balancer (or reverse proxy) that rewrites ports. This enables Tiki to use the `HTTP_X_FORWARDED_PROTO` parameter set by the proxy, to provide correct links.

Domains allowed to make "CORS" (Cross-Origin Resource Sharing or Cross-Domain Ajax) requests from this server.

One URI per line, for example,

"http://www.example.com" or "" for any site*

Default

Option

Use CURL for HTTP connections

Realtime Tiki

Realtime port

Path to the php binary

Description

Use CURL instead of sockets for server to server HTTP connections, when sockets are not available.

Use built-in websockets server within Tiki to enable realtime communication features of the app. See help page for more information on how to start the server.

The port used to access this server; if not specified, port 8080 will be used

If not specified, port 8080 will be used

Path to the php command line binary to be used by tiki when calling command line programs

Default

Option

Multi-domain

Switch domain when switching perspective

Default domain for non categorized content

Description

Enable domain names to be mapped to perspectives and simulate multiple domains hosted with the same Tiki installation.

Important: Different domains have different login sessions and, even in the case of subdomains, an understanding of session cookies is needed to make it work

The domain (hostname only) to be used when redirecting the user if he tries to read content that is not bound to the category/perspective configured for the current domain.

Default

Option

Multi-domain Configuration

Session storage location

Description

Comma-separated values mapping the domain name to the perspective ID.

One domain per line with a comma separating it from the perspective ID. For example: tiki.org,1

Select where the session information should be stored. Memcache sessions require memcache to be configured.

Default

Option

Session lifetime

Session cookie name

Description

Session lifetime

Expressed as minutes. This is the minimum time logged in. To be the exact time, adjustments must be made in `.htaccess session.gc_probability` and `session.gc_divisor` to 1. Be careful - changing the probability may affect server performance.

Session cookie name used instead of the PHP default configuration

Default

Option

Site terminal

Site terminal configuration

Description

Allows users to be directed to a specific perspective depending on the origin IP address. Can be used inside intranets to use different configurations for users depending on their departments or discriminate people in web contexts. Unspecified IPs will fall back to default behavior, including multi-domain handling. Manually selected perspectives take precedence over this.

Provides the mapping from subnets to perspective.

One per line. Network prefix in CIDR notation (address/mask size), separated by comma with the perspective ID. Example: 192.168.12.0/24,12

Default

Option

Contact us

Allow anonymous visitors to use the "Contact Us" feature.

Display contact priority

Contact user

Stats

Description

A basic contact form a visitor can use to contact the site admin

You can use Trackers to create custom Contact Us forms.

Allow anonymous visitors to use the "Contact Us" feature.

Display contact priority option

User to contact

Record basic statistics about major Tiki features (number of wiki pages, size of file galleries, etc.)

Default

Option

Referrer stats

Count admin pageviews

Terms and Conditions

Terms of Use page name

Minimum age

Description

Record domain name of sites that send visitors to this Tiki.

Include pageviews by Admin when reporting stats.

Automatically present a terms of use page to be accepted by users accessing the site.

Wiki page for Terms of Use content. The page may be translated using the multilingual feature.

When presenting the terms of use, request age.

0 to ignore age validation

Default

Option

Help system

Help URL

Description

Activates links to Tiki documentation. You can specify a Help URL that contains customized help pages. By default, the Help system uses <http://doc.tiki.org/>

The default help system may not be complete. You can contribute to the Tiki documentation, which is a community-edited wiki.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Temporary directory

Description

Directory on your server, relative to your Tiki installation, for storing temporary files. Tiki must have full read and write access to this directory.

Default

Option

Use proxy

Proxy host name

Port

Proxy username

Proxy password

Description

Specify if this Tiki site requires a proxy to access the internet. If enabled, the proxy Host name (either with or without the http:// prefix), Port settings, Username, and Password can be specified.

Proxy host - without http:// or similar, just the host name

Proxy port

Default

Option

HTTP lookup: skip framesets

Load balancer

Tiki is behind a frontend-proxy/load-balancer that rewrites ports

Description

When performing an HTTP request to an external source, verify if the result is a frameset and use heuristic to provide the real content.

Activate this only if the server is behind a load balancer (or reverse proxy). This enables logging the IP of the user rather than the IP of the proxy server

Activate this only if the server is behind a frontend-proxy/load-balancer (or reverse proxy) that rewrites ports. This enables Tiki to use the `HTTP_X_FORWARDED_PROTO` parameter set by the proxy, to provide correct links.

Default

Option

Access-Control-Allow-Origin

Use CURL for HTTP connections

Realtime Tiki

Description

Domains allowed to make "CORS" (Cross-Origin Resource Sharing or Cross-Domain Ajax) requests from this server.

One URI per line, for example,

"http://www.example.com" or "" for any site*

Use CURL instead of sockets for server to server HTTP connections, when sockets are not available.

Use built-in websockets server within Tiki to enable realtime communication features of the app. See help page for more information on how to start the server.

Default

Option

Realtime port

Path to the php binary

Multi-domain

Description

The port used to access this server; if not specified, port 8080 will be used

If not specified, port 8080 will be used

Path to the php command line binary to be used by tiki when calling command line programs

Enable domain names to be mapped to perspectives and simulate multiple domains hosted with the same Tiki installation.

Default

Option

Switch domain when switching perspective

Default domain for non categorized content

Description

Important: Different domains have different login sessions and, even in the case of subdomains, an understanding of session cookies is needed to make it work

The domain (hostname only) to be used when redirecting the user if he tries to read content that is not bound to the category/perspective configured for the current domain.

Default

Option

Multi-domain Configuration

Session storage location

Description

Comma-separated values mapping the domain name to the perspective ID.

One domain per line with a comma separating it from the perspective ID. For example: tiki.org,1

Select where the session information should be stored. Memcache sessions require memcache to be configured.

Default

Option

Session lifetime

Session cookie name

Description

Session lifetime

Expressed as minutes. This is the minimum time logged in. To be the exact time, adjustments must be made in `.htaccess session.gc_probability` and `session.gc_divisor` to 1. Be careful - changing the probability may affect server performance.

Session cookie name used instead of the PHP default configuration

Default

Option

Site terminal

Site terminal configuration

Description

Allows users to be directed to a specific perspective depending on the origin IP address. Can be used inside intranets to use different configurations for users depending on their departements or discriminate people in web contexts. Unspecified IPs will fall back to default behavior, including multi-domain handling. Manually selected perspectives take precedence over this.

Provides the mapping from subnets to perspective.

One per line. Network prefix in CIDR notation (address/mask size), separated by comma with the perspective ID. Example: 192.168.12.0/24,12

Default

Option

Contact us

Allow anonymous visitors to use the "Contact Us" feature.

Display contact priority

Contact user

Stats

Description

A basic contact form a visitor can use to contact the site admin

You can use Trackers to create custom Contact Us forms.

Allow anonymous visitors to use the "Contact Us" feature.

Display contact priority option

User to contact

Record basic statistics about major Tiki features (number of wiki pages, size of file galleries, etc.)

Default

Option

Referrer stats

Count admin pageviews

Terms and Conditions

Terms of Use page name

Minimum age

Description

Record domain name of sites that send visitors to this Tiki.

Include pageviews by Admin when reporting stats.

Automatically present a terms of use page to be accepted by users accessing the site.

Wiki page for Terms of Use content. The page may be translated using the multilingual feature.

When presenting the terms of use, request age.

0 to ignore age validation

Default

Option

Help system

Help URL

Description

Activates links to Tiki documentation. You can specify a Help URL that contains customized help pages. By default, the Help system uses <http://doc.tiki.org/>

The default help system may not be complete. You can contribute to the Tiki documentation, which is a community-edited wiki.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Temporary directory

Description

Directory on your server, relative to your Tiki installation, for storing temporary files. Tiki must have full read and write access to this directory.

Default

Option

Use proxy

Proxy host name

Port

Proxy username

Proxy password

Description

Specify if this Tiki site requires a proxy to access the internet. If enabled, the proxy Host name (either with or without the http:// prefix), Port settings, Username, and Password can be specified.

Proxy host - without http:// or similar, just the host name

Proxy port

Default

Option

HTTP lookup: skip framesets

Load balancer

Tiki is behind a frontend-proxy/load-balancer that rewrites ports

Description

When performing an HTTP request to an external source, verify if the result is a frameset and use heuristic to provide the real content.

Activate this only if the server is behind a load balancer (or reverse proxy). This enables logging the IP of the user rather than the IP of the proxy server

Activate this only if the server is behind a frontend-proxy/load-balancer (or reverse proxy) that rewrites ports. This enables Tiki to use the `HTTP_X_FORWARDED_PROTO` parameter set by the proxy, to provide correct links.

Default

Option

Access-Control-Allow-Origin

Use CURL for HTTP connections

Multi-domain

Description

Domains allowed to make "CORS" (Cross-Origin Resource Sharing or Cross-Domain Ajax) requests from this server.

One URI per line, for example,

"http://www.example.com" or "" for any site*

Use CURL instead of sockets for server to server HTTP connections, when sockets are not available.

Enable domain names to be mapped to perspectives and simulate multiple domains hosted with the same Tiki installation.

Default

Option

Switch domain when switching perspective

Default domain for non categorized content

Description

Important: Different domains have different login sessions and, even in the case of subdomains, an understanding of session cookies is needed to make it work

The domain (hostname only) to be used when redirecting the user if he tries to read content that is not bound to the category/perspective configured for the current domain.

Default

Option

Multi-domain Configuration

Session storage location

Description

Comma-separated values mapping the domain name to the perspective ID.

One domain per line with a comma separating it from the perspective ID. For example: tiki.org,1

Select where the session information should be stored. Memcache sessions require memcache to be configured.

Default

Option

Session lifetime

Session cookie name

Description

Session lifetime

Expressed as minutes. This is the minimum time logged in. To be the exact time, adjustments must be made in `.htaccess session.gc_probability` and `session.gc_divisor` to 1. Be careful - changing the probability may affect server performance.

Session cookie name used instead of the PHP default configuration

Default

Option

Site terminal

Site terminal configuration

Description

Allows users to be directed to a specific perspective depending on the origin IP address. Can be used inside intranets to use different configurations for users depending on their departments or discriminate people in web contexts. Unspecified IPs will fall back to default behavior, including multi-domain handling. Manually selected perspectives take precedence over this.

Provides the mapping from subnets to perspective.

One per line. Network prefix in CIDR notation (address/mask size), separated by comma with the perspective ID. Example: 192.168.12.0/24,12

Default

Option

Contact us

Allow anonymous visitors to use the "Contact Us" feature.

Display contact priority

Contact user

Stats

Description

A basic contact form a visitor can use to contact the site admin

You can use Trackers to create custom Contact Us forms.

Allow anonymous visitors to use the "Contact Us" feature.

Display contact priority option

User to contact

Record basic statistics about major Tiki features (number of wiki pages, size of file galleries, etc.)

Default

Option

Referrer stats

Count admin pageviews

Terms and Conditions

Terms of Use page name

Minimum age

Description

Record domain name of sites that send visitors to this Tiki.

Include pageviews by Admin when reporting stats.

Automatically present a terms of use page to be accepted by users accessing the site.

Wiki page for Terms of Use content. The page may be translated using the multilingual feature.

When presenting the terms of use, request age.

0 to ignore age validation

Default

Option

Help system

Help URL

Description

Activates links to Tiki documentation. You can specify a Help URL that contains customized help pages. By default, the Help system uses <http://doc.tiki.org/>

The default help system may not be complete. You can contribute to the Tiki documentation, which is a community-edited wiki.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Temporary directory

Description

Directory on your server, relative to your Tiki installation, for storing temporary files. Tiki must have full read and write access to this directory.

Default

Option

Use proxy

Proxy host name

Port

Proxy username

Proxy password

Description

Specify if this Tiki site requires a proxy to access the internet. If enabled, the proxy Host name (either with or without the http:// prefix), Port settings, Username, and Password can be specified.

Proxy host - without http:// or similar, just the host name

Proxy port

Default

Option

HTTP lookup: skip framesets

Load balancer

Tiki is behind a frontend-proxy/load-balancer that rewrites ports

Description

When performing an HTTP request to an external source, verify if the result is a frameset and use heuristic to provide the real content.

Activate this only if the server is behind a load balancer (or reverse proxy). This enables logging the IP of the user rather than the IP of the proxy server

Activate this only if the server is behind a frontend-proxy/load-balancer (or reverse proxy) that rewrites ports. This enables Tiki to use the `HTTP_X_FORWARDED_PROTO` parameter set by the proxy, to provide correct links.

Default

Option

Access-Control-Allow-Origin

Use CURL for HTTP connections

Multi-domain

Description

Domains allowed to make "CORS" (Cross-Origin Resource Sharing or Cross-Domain Ajax) requests from this server.

One URI per line, for example,

"http://www.example.com" or "" for any site*

Use CURL instead of sockets for server to server HTTP connections, when sockets are not available.

Enable domain names to be mapped to perspectives and simulate multiple domains hosted with the same Tiki installation.

Default

Option

Switch domain when switching perspective

Default domain for non categorized content

Description

Important: Different domains have different login sessions and, even in the case of subdomains, an understanding of session cookies is needed to make it work

The domain (hostname only) to be used when redirecting the user if he tries to read content that is not bound to the category/perspective configured for the current domain.

Default

Option

Multi-domain Configuration

Session storage location

Description

Comma-separated values mapping the domain name to the perspective ID.

One domain per line with a comma separating it from the perspective ID. For example: tiki.org,1

Select where the session information should be stored. Memcache sessions require memcache to be configured.

Default

Option

Session lifetime

Session cookie name

Description

Session lifetime

Expressed as minutes. This is the minimum time logged in. To be the exact time, adjustments must be made in `.htaccess session.gc_probability` and `session.gc_divisor` to 1. Be careful - changing the probability may affect server performance.

Session cookie name used instead of the PHP default configuration

Default

Option

Site terminal

Site terminal configuration

Description

Allows users to be directed to a specific perspective depending on the origin IP address. Can be used inside intranets to use different configurations for users depending on their departements or discriminate people in web contexts. Unspecified IPs will fall back to default behavior, including multi-domain handling. Manually selected perspectives take precedence over this.

Provides the mapping from subnets to perspective.

One per line. Network prefix in CIDR notation (address/mask size), separated by comma with the perspective ID. Example: 192.168.12.0/24,12

Default

Option

Contact us

Allow anonymous visitors to use the "Contact Us" feature.

Display contact priority

Contact user

Stats

Description

A basic contact form a visitor can use to contact the site admin

You can use Trackers to create custom Contact Us forms.

Allow anonymous visitors to use the "Contact Us" feature.

Display contact priority option

User to contact

Record basic statistics about major Tiki features (number of wiki pages, size of file galleries, etc.)

Default

Option

Referrer stats

Count admin pageviews

Terms and Conditions

Terms of Use page name

Minimum age

Description

Record domain name of sites that send visitors to this Tiki.

Include pageviews by Admin when reporting stats.

Automatically present a terms of use page to be accepted by users accessing the site.

Wiki page for Terms of Use content. The page may be translated using the multilingual feature.

When presenting the terms of use, request age.

0 to ignore age validation

Default

Option

Help system

Help URL

Description

Activates links to Tiki documentation. You can specify a Help URL that contains customized help pages. By default, the Help system uses <http://doc.tiki.org/>

The default help system may not be complete. You can contribute to the Tiki documentation, which is a community-edited wiki.

Default

Unable to load the jQuery Sortable Tables feature.

GENERAL - NAVIGATION

Option

SmartMenus

Menu user levels

Featured links

Use folder icons for menu section (parent) items

Menu icons

Description

Add "SmartMenus" to Bootstrap menus. See smartmenus.org for more.

Enables control of the per-group visibility of menu options

A simple menu system to display external web pages in a new browser tab or an iframe within the site, etc.

When a menu isn't set as a Bootstrap or CSS menu, use folder icons for menu section items (rather than plus/minus signs).

Allows icons to be defined for menu entries

Default

Option

Default path for the icons

Edit menu icon

Use group homepages

Go to the group homepage only if logging in from the default homepage

Use the top page of a Tiki feature as the homepage

Description

Adds an icon on the navbar to edit menu entries

Users can be directed to different pages upon logging in, depending on their default group.

Select the Tiki feature to provide the site homepage.
Only enabled features are listed.

Default

Option

Use custom homepage

Homepage URL

Homepage Browser title

Wiki homepage

Home blog (main blog)

Home forum (main forum)

Description

Use the top page of a Tiki feature or another homepage

This option will override the Use Tiki feature as homepage setting.

Customize Browser title for the custom homepage

The default home page of the wiki when no other page is specified. The page will be created if it does not already exist.

Default

Option

Home file gallery (main file gallery)

Domain prefix handling

Domain redirects

Description

Select the default file gallery

Strip or automatically add the "www." prefix on domain names to standardize URLs.

When the site is accessed through specific domain names, redirect to an alternate domain preserving the URL. Useful for domain name transitions, like tikiwiki.org to tiki.org.

One entry per line, with each entry a comma-separated list: old domain, new domain

Default

Option

Redirect on error

Redirect to similar wiki page

On permission denied, display login module

Send to URL

Description

On an error, refresh to the homepage as specified on the Admin General page.

If a requested page doesn't exist, redirect to a similarly named page

If an anonymous visitor attempts to access a page for which permission is not granted, Tiki will automatically display the Log-in module. Alternatively, use the Send to URL field to display a specific page (relative to your Tiki installation) instead.

URL to redirect to on "permission denied"

Default

Option

The URL that the anonymous user is redirected to when a page is not found

URL the user is redirected to after account validation

Alternate registration page

Description

The default page a Registered user sees after account validation is "tiki-information.php?msg=Account validated successfully".

Default: tiki-information.php?msg=Account validated successfully.

Enter URL of a custom registration page. Tiki will automatically redirect default registration page (tiki-register.php) to this page.

Default

Option

URL Suffix Cleaner

URL to go to when clicking on a username

Sitemap protocol

Description

When the requested page does not exist, tests removing 1 or 2 of the last characters from the URL to see if it gets an existing page.

URL to go to when clicking on a username. Default: `tiki-user_information.php?userId=` (*Use for login name and No value assigned for userId*)

Allows generating site maps based on the Sitemap protocol, in the form of XML documents. Mostly used to facilitate indexation of a site by web search engines.

Default

Option

Close site

Title

Message

Description

Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.

Default

Option

Close site when server load is above the threshold

Maximum average server load threshold in the last minute

Site Busy Title

Description

Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.

Default

Option

Site Busy Message

Breadcrumbs

Prefix breadcrumbs with "Location : "

Site location bar

Larger font

Use page description

Namespace

Description

Indicates the navigation path through parent pages to the current page.

Unmaintained feature

Place the term "Location:" in the breadcrumbs.

Enable namespaces feature for wiki pages.

Default

Option

Namespace separator

Hide namespace indicator in structure path

Center text using

: instead of

Page name display stripper

Description

Select the character, symbol, or text to use as the namespace separator.

Hide namespace indicator in structure path.

Useful to avoid conflicts with C++ scope operators or default namespace separator

The character(s) to use as a delimiter in the page name. The portion of the name after the character(s) will not be displayed. If the page name display stripper conflicts with the namespace separator, the namespace is used and the page name display is not stripped.

Default

Unable to load the jQuery Sortable Tables feature.

Option

SmartMenus

Menu user levels

Featured links

Use folder icons for menu section (parent) items

Menu icons

Description

Add "SmartMenus" to Bootstrap menus. See smartmenus.org for more.

Enables control of the per-group visibility of menu options

A simple menu system to display external web pages in a new browser tab or an iframe within the site, etc.

When a menu isn't set as a Bootstrap or CSS menu, use folder icons for menu section items (rather than plus/minus signs).

Allows icons to be defined for menu entries

Default

Option

Default path for the icons

Edit menu icon

Use group homepages

Go to the group homepage only if logging in from the default homepage

Use the top page of a Tiki feature as the homepage

Description

Adds an icon on the navbar to edit menu entries

Users can be directed to different pages upon logging in, depending on their default group.

Select the Tiki feature to provide the site homepage.
Only enabled features are listed.

Default

Option

Use custom homepage

Homepage URL

Homepage Browser title

Wiki homepage

Home blog (main blog)

Home forum (main forum)

Description

Use the top page of a Tiki feature or another homepage

This option will override the Use Tiki feature as homepage setting.

Customize Browser title for the custom homepage

The default home page of the wiki when no other page is specified. The page will be created if it does not already exist.

Default

Option

Home file gallery (main file gallery)

Domain prefix handling

Domain redirects

Description

Select the default file gallery

Strip or automatically add the "www." prefix on domain names to standardize URLs.

When the site is accessed through specific domain names, redirect to an alternate domain preserving the URL. Useful for domain name transitions, like tikiwiki.org to tiki.org.

One entry per line, with each entry a comma-separated list: old domain, new domain

Default

Option

Redirect on error

Redirect to similar wiki page

On permission denied, display login module

Send to URL

Description

On an error, refresh to the homepage as specified on the Admin General page.

If a requested page doesn't exist, redirect to a similarly named page

If an anonymous visitor attempts to access a page for which permission is not granted, Tiki will automatically display the Log-in module. Alternatively, use the Send to URL field to display a specific page (relative to your Tiki installation) instead.

URL to redirect to on "permission denied"

Default

Option

The URL that the anonymous user is redirected to when a page is not found

URL the user is redirected to after account validation

Alternate registration page

Description

The default page a Registered user sees after account validation is "tiki-information.php?msg=Account validated successfully".

Default: tiki-information.php?msg=Account validated successfully.

Enter URL of a custom registration page. Tiki will automatically redirect default registration page (tiki-register.php) to this page.

Default

Option

URL Suffix Cleaner

URL Fragment Guesser

URL to go to when clicking on a username

Description

When the requested page does not exist, tests removing 1 or 2 of the last characters from the URL to see if it gets an existing page.

Scroll to the closest anchor when the one indicated in the URL is missing in a page.

URL to go to when clicking on a username. Default: `tiki-user_information.php?userId=No value assigned` (*Use No value assigned for login name and No value assigned for userId*)

Default

Option

Sitemap protocol

Close site

Title

Description

Allows generating site maps based on the Sitemap protocol, in the form of XML documents. Mostly used to facilitate indexation of a site by web search engines.

Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.

Default

Option

Message

Close site when server load is above the threshold

Maximum average server load threshold in the last minute

Description

Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.

Default

Option

Site Busy Title

Site Busy Message

Breadcrumbs

Prefix breadcrumbs with "Location : "

Site location bar

Larger font

Use page description

Description

Indicates the navigation path through parent pages to the current page.

Unmaintained feature

Place the term "Location:" in the breadcrumbs.

Default

Option

Namespace

Namespace separator

Hide namespace indicator in structure path

Center text using

: instead of

Description

Enable namespaces feature for wiki pages.

Select the character, symbol, or text to use as the namespace separator.

Hide namespace indicator in structure path.

Useful to avoid conflicts with C++ scope operators or default namespace separator

Default

Option

Page name display stripper

Description

The character(s) to use as a delimiter in the page name. The portion of the name after the character(s) will not be displayed. If the page name display stripper conflicts with the namespace separator, the namespace is used and the page name display is not stripped.

Default

Unable to load the jQuery Sortable Tables feature.

Option

SmartMenus

CSS menus

Description

Add "SmartMenus" to Bootstrap menus. See smartmenus.org for more.

Use CSS-styled (Suckerfish) vertical and horizontal menus.

Default

Option

Superfish

Menu user levels

Featured links

Use folder icons for menu section (parent) items

Menu icons

Default path for the icons

Description

Adds animation effects to CSS "Suckerfish" menus.

Enables control of the per-group visibility of menu options

A simple menu system to display external web pages in a new browser tab or an iframe within the site, etc.

When a menu isn't set as a Bootstrap or CSS menu, use folder icons for menu section items (rather than plus/minus signs).

Allows icons to be defined for menu entries

Default

Option

Edit menu icon

Use group homepages

Go to the group homepage only if logging in from the default homepage

Use the top page of a Tiki feature as the homepage

Use custom homepage

Description

Adds an icon on the navbar to edit menu entries

Users can be directed to different pages upon logging in, depending on their default group.

Select the Tiki feature to provide the site homepage.
Only enabled features are listed.

Use the top page of a Tiki feature or another homepage
This option will override the Use Tiki feature as homepage setting.

Default

Option

Homepage URL

Homepage Browser title

Wiki homepage

Home blog (main blog)

Home forum (main forum)

Home file gallery (main file gallery)

Description

Customize Browser title for the custom homepage

The default home page of the wiki when no other page is specified. The page will be created if it does not already exist.

Select the default file gallery

Default

Option

Domain prefix handling

Domain redirects

Redirect on error

Description

Strip or automatically add the "www." prefix on domain names to standardize URLs.

When the site is accessed through specific domain names, redirect to an alternate domain preserving the URL. Useful for domain name transitions, like tikiwiki.org to tiki.org.

One entry per line, with each entry a comma-separated list: old domain, new domain

On an error, refresh to the homepage as specified on the Admin General page.

Default

Option

Redirect to similar wiki page

On permission denied, display login module

Send to URL

The URL that the anonymous user is redirected to when a page is not found

Description

If a requested page doesn't exist, redirect to a similarly named page

If an anonymous visitor attempts to access a page for which permission is not granted, Tiki will automatically display the Log-in module. Alternatively, use the Send to URL field to display a specific page (relative to your Tiki installation) instead.

URL to redirect to on "permission denied"

Default

Option

URL the user is redirected to after account validation

Alternate registration page

Description

The default page a Registered user sees after account validation is "tiki-information.php?msg=Account validated successfully".

Default: tiki-information.php?msg=Account validated successfully.

Enter URL of a custom registration page. Tiki will automatically redirect default registration page (tiki-register.php) to this page.

Default

Option

URL to go to when clicking on a username

Sitemap protocol

Description

URL to go to when clicking on a username. Default: `tiki-user_information.php?userId=No value assigned` (*Use No value assigned for login name and No value assigned for userId*)

Allows generating site maps based on the Sitemap protocol, in the form of XML documents. Mostly used to facilitate indexation of a site by web search engines.

Default

Option

Close site

Title

Message

Description

Use this setting to \"close\" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.

Default

Option

Close site when server load is above the threshold

Maximum average server load threshold in the last minute

Site Busy Title

Description

Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.

Default

Option

Site Busy Message

Breadcrumbs

Prefix breadcrumbs with "Location : "

Site location bar

Larger font

Use page description

Namespace

Description

Indicates the navigation path through parent pages to the current page.

Unmaintained feature

Place the term "Location:" in the breadcrumbs.

Enable namespaces feature for wiki pages.

Default

Option

Namespace separator

Hide namespace indicator in structure path

Center text using

: instead of

Page name display stripper

Description

Select the character, symbol, or text to use as the namespace separator.

Hide namespace indicator in structure path.

Useful to avoid conflicts with C++ scope operators or default namespace separator

The character(s) to use as a delimiter in the page name. The portion of the name after the character(s) will not be displayed. If the page name display stripper conflicts with the namespace separator, the namespace is used and the page name display is not stripped.

Default

Unable to load the jQuery Sortable Tables feature.

Option

CSS menus

Superfish

Menu user levels

Featured links

Use folder icons for menu section (parent) items

Description

Use CSS-styled (Suckerfish) vertical and horizontal menus.

Adds animation effects to CSS "Suckerfish" menus.

Enables control of the per-group visibility of menu options

A simple menu system to display external web pages in a new browser tab or an iframe within the site, etc.

When a menu isn't set as a Bootstrap or CSS menu, use folder icons for menu section items (rather than plus/minus signs).

Default

Option

Menu icons

Default path for the icons

Edit menu icon

Use group homepages

Go to the group homepage only if logging in from the default homepage

Use the top page of a Tiki feature as the homepage

Description

Allows icons to be defined for menu entries

Adds an icon on the navbar to edit menu entries

Users can be directed to different pages upon logging in, depending on their default group.

Select the Tiki feature to provide the site homepage.
Only enabled features are listed.

Default

Option

Use custom homepage

Homepage URL

Homepage Browser title

Wiki homepage

Home blog (main blog)

Home forum (main forum)

Description

Use the top page of a Tiki feature or another homepage

This option will override the Use Tiki feature as homepage setting.

Customize Browser title for the custom homepage

The default home page of the wiki when no other page is specified. The page will be created if it does not already exist.

Default

Option

Home file gallery (main file gallery)

Home gallery (main gallery)

Domain prefix handling

Domain redirects

Description

Select the default file gallery

Strip or automatically add the "www." prefix on domain names to standardize URLs.

When the site is accessed through specific domain names, redirect to an alternate domain preserving the URL. Useful for domain name transitions, like tikiwiki.org to tiki.org.

One entry per line, with each entry a comma-separated list: old domain, new domain

Default

Option

Redirect on error

Redirect to similar wiki page

On permission denied, display login module

Send to URL

Description

On an error, refresh to the homepage as specified on the Admin General page.

If a requested page doesn't exist, redirect to a similarly named page

If an anonymous visitor attempts to access a page for which permission is not granted, Tiki will automatically display the Log-in module. Alternatively, use the Send to URL field to display a specific page (relative to your Tiki installation) instead.

URL to redirect to on "permission denied"

Default

Option

The URL that the anonymous user is redirected to when a page is not found

URL the user is redirected to after account validation

Alternate registration page

Description

The default page a Registered user sees after account validation is "tiki-information.php?msg=Account validated successfully".

Default: tiki-information.php?msg=Account validated successfully.

Enter URL of a custom registration page. Tiki will automatically redirect default registration page (tiki-register.php) to this page.

Default

Option

URL to go to when clicking on a username

Sitemap protocol

Description

URL to go to when clicking on a username. Default: `tiki-user_information.php?userId=No value assigned` (*Use No value assigned for login name and No value assigned for userId*)

Allows generating site maps based on the Sitemap protocol, in the form of XML documents. Mostly used to facilitate indexation of a site by web search engines.

Default

Option

Close site

Title

Message

Description

Use this setting to \"close\" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site.

Default

Option

Close site when server load is above the threshold

Maximum average server load threshold in the last minute

Site Busy Title

Description

Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site.

Default

Option

Site Busy Message

Breadcrumbs

Prefix breadcrumbs with "Location : "

Site location bar

Larger font

Use page description

Namespace

Description

Indicates the navigation path through parent pages to the current page.

Unmaintained feature

Place the term "Location:" in the breadcrumbs.

Enable namespaces feature for wiki pages.

Default

Option

Namespace separator

Hide namespace indicator in structure path

Center text using

: instead of

Description

Select the character, symbol, or text to use as the namespace separator.

Hide namespace indicator in structure path.

Useful to avoid conflicts with C++ scope operators or default namespace separator.

Useful to avoid conflicts with C++ scope operators or default namespace separator

Default

Option

Page name display stripper

Description

The character(s) to use as a delimiter in the page name. The portion of the name after the character(s) will not be displayed. If the page name display stripper conflicts with the namespace separator, the namespace is used and the page name display is not stripped.

Default

Unable to load the jQuery Sortable Tables feature.

INTERNATIONALIZATION (I18N)

Option

Default language

Default admin language

Description

The site language is used when no other language is spec

The site language is used in admin section when no other

Default

Option

Wiki link format

Default character set for sending mail

Multilingual

Detect browser language

Description

Level of special characters acceptable in wiki links for page names
éàî

*"Strict" includes only basic characters such as a-z and 0-9
in page names should not use "strict".*

Specify the character encoding used by Tiki when sending emails

Enables internationalization features and multilingual support

Look up the user's preferred language through browser preferences

Default

Option

Show pages in user's preferred language

Users can choose the language of their interface

Restrict supported languages

Available languages

Description

When accessing a page which has an equivalent in the user's preferred language, the user is redirected to the page in that language. Based on the user's preferred language, the user is redirected to the page in that language.

user's preferred language is determined by the user's browser language preferences. If the user's browser language preferences are not set, the user is redirected to the page in the user's preferred language.

Allow users to change the language of the menus and labels on the site.

Limit the languages made available on the site.

Use Ctrl+Click to select multiple languages.

By default, all languages supported by Tiki are available on the site. You can limit the languages to a subset.

Default

Option

Language inclusion threshold

Display available translations

Display available translations as dropdown

Synchronize page and site language

Restrict search language by default

Translation assistant

Description

When the number of languages is restricted on the site, all languages are added to the preferred language list, even if unspecified by the user, and are displayed in the specified languages.

Display list of available languages and offer to switch language and articles action buttons.

Instead of a simple icon to list available languages or translation list.

Changing the page language also changes the site language.

Only search content that is in the interface language, other languages are not searched.

Track translation operations between pages.

Default

Option

Urgent translation notifications

Incomplete translation notice

Display all languages in a single page

Quantify change size

Allow minor edits of wiki pages

User watches translations

Description

Enable changes to be flagged as urgent, so translations are

When a page is translated to a new language, a notice will indicate that the translation is not yet complete.

List all languages as options in the page-language dropdown

In addition to tracking the changes, track the change size of the page is.

Minor edits don't flag new content for translation and don't ("Watch minor edits" is enabled).

Default

Option

Multilingual structures

Multilingual tags

Synchronize multilingual categories

Synchronized categories

Multilingual dynamic variables

Plugin Translate

Description

Structures search for equivalent pages in other languages

May cause performance problems with larger structures.

Permits translation management of tags

Make sure that the categories of the translations are sync

List of categories affected by the multilingual synchronization
will be used as a white list (the only categories allowed) or
those specified).

Make dynamic variable content language-specific.

Translate text to the user language

Default

Option

Plugin Language

Plugin Translated

Use database for translation

Manage contribution of translated strings

Record untranslated strings

Machine translation

Description

Show alternative content based on the page language

Create multilingual links

Use the database to store the translated strings and allow *Edit, export and import languages*

Offers to set whether each translated string should be con

Keep track of the unsuccessful attempts to translate string

Uses machine translation to translate the content of the si
relies on external services that may not be free. Google T

Default

Option

Machine translation implementation

Google Translate API Key

Bing Translate Client ID

Bing Translate Client Secret

Enable machine translation of wiki pages

Certain pages redirect to homepage when language is changed

Description

Select between alternate implementations for machine translation. Different API keys may be required.

The key must be generated from the Google console. Choose the appropriate key for your application.

The application must be registered.

The application must be registered.

Makes additional languages available to the list of languages.

Default

Option

List of pages that redirect

Description

List of names of pages that always redirect to the homepage

Separate page names by commas

Default

Unable to load the jQuery Sortable Tables feature.

Option

Default language

Default admin language

Wiki link format

Description

The site language is used when no other language is specified.

The site language is used in admin section when no other language is specified.

Level of special characters acceptable in wiki links for page names:

`´`î`

"Strict" includes only basic characters such as a-z and 0-9.

in page names should not use "strict".

Default

Option

Default character set for sending mail

Multilingual

Detect browser language

Show pages in user's preferred language

Users can choose the language of their interface

Restrict supported languages

Description

Specify the character encoding used by Tiki when sending

Enables internationalization features and multilingual support

Look up the user's preferred language through browser preferences

When accessing a page which has an equivalent in the user's preferred

page. Based on the

user's preferred language, Tiki will automatically redirect the user to the

Tiki preferences.

Allow users to change the language of the menus and labels

Limit the languages made available on the site.

Use Ctrl+Click to select multiple languages.

Default

Option

Available languages

Language inclusion threshold

Display available translations

Display available translations as dropdown

Synchronize page and site language

Description

By default, all languages supported by Tiki are available on the site. This plugin allows you to restrict the languages to a subset.

When the number of languages is restricted on the site, all languages are added to the preferred language list, even if unspecified by the administrator. This plugin allows you to restrict the specified languages.

Display list of available languages and offer to switch language and articles action buttons.

Instead of a simple icon to list available languages or translation list.

Changing the page language also changes the site language.

Default

Option

Restrict search language by default

Translation assistant

Urgent translation notifications

Incomplete translation notice

Display all languages in a single page

Quantify change size

Description

Only search content that is in the interface language, other

Track translation operations between pages.

Enable changes to be flagged as urgent, so translations are

When a page is translated to a new language, a notice will indicate that the translation is not yet complete.

List all languages as options in the page-language dropdown

In addition to tracking the changes, track the change size of the page is.

Default

Option

Allow minor edits of wiki pages

User watches translations

Multilingual structures

Multilingual tags

Synchronize multilingual categories

Synchronized categories

Description

Minor edits don't flag new content for translation and don't flag content for translation (if "Watch minor edits" is enabled).

Structures search for equivalent pages in other languages.
May cause performance problems with larger structures.

Permits translation management of tags

Make sure that the categories of the translations are synchronized

List of categories affected by the multilingual synchronization
will be used as a white list (the only categories allowed) or as a black list (all categories except those specified).

Default

Option

Multilingual dynamic variables

Plugin Translate

Plugin Language

Plugin Translated

Use database for translation

Manage contribution of translated strings

Record untranslated strings

Description

Make dynamic variable content language-specific.

Translate text to the user language

Show alternative content based on the page language

Create multilingual links

Use the database to store the translated strings and allow

Edit, export and import languages

Offers to set whether each translated string should be con

Keep track of the unsuccessful attempts to translate string

Default

Option

Machine translation

Machine translation implementation

Google Translate API Key

Bing Translate Client ID

Bing Translate Client Secret

Enable machine translation of wiki pages

Description

Uses machine translation to translate the content of the site. Relies on external services that may not be free. Google Translate.

Select between alternate implementations for machine translation. Different API keys may be required.

The key must be generated from the Google console. Choose.

The application must be registered.

The application must be registered.

Makes additional languages available to the list of languages.

Default

Option

Certain pages redirect to homepage when language is changed

List of pages that redirect

Description

List of names of pages that always redirect to the homepage
Separate page names by commas

Default

Unable to load the jQuery Sortable Tables feature.

Option

Default language

Default admin language

Description

The site language is used when no other language is spec

The site language is used in admin section when no other

Default

Option

Wiki link format

Default character set for sending mail

Multilingual

Detect browser language

Description

Level of special characters acceptable in wiki links for page names
éàî

*"Strict" includes only basic characters such as a-z and 0-9
in page names should not use "strict".*

Specify the character encoding used by Tiki when sending emails

Enables internationalization features and multilingual support

Look up the user's preferred language through browser preferences

Default

Option

Show pages in user's preferred language

Users can choose the language of their interface

Restrict supported languages

Available languages

Description

When accessing a page which has an equivalent in the user's preferred language, the user is redirected to the page in that language. Based on the user's preferences, the user is redirected to the page in that language.

user's preferred language. Based on the user's preferences, the user is redirected to the page in that language. Tiki preferences.

Allow users to change the language of the menus and labels.

Limit the languages made available on the site.

Use Ctrl+Click to select multiple languages.

By default, all languages supported by Tiki are available on the site. You can limit the languages to a subset.

Default

Option

Language inclusion threshold

Display available translations

Display available translations as dropdown

Synchronize page and site language

Restrict search language by default

Translation assistant

Description

When the number of languages is restricted on the site, all languages are added to the preferred language list, even if unspecified by the user, and are displayed in the specified languages.

Display list of available languages and offer to switch language for articles and articles action buttons.

Instead of a simple icon to list available languages or translations, use a language list.

Changing the page language also changes the site language.

Only search content that is in the interface language, other languages are not searched.

Track translation operations between pages.

Default

Option

Urgent translation notifications

Incomplete translation notice

Display all languages in a single page

Quantify change size

Allow minor edits of wiki pages

User watches translations

Description

Enable changes to be flagged as urgent, so translations are

When a page is translated to a new language, a notice will indicate that the translation is not yet complete.

List all languages as options in the page-language dropdown

In addition to tracking the changes, track the change size of the page is.

Minor edits don't flag new content for translation and don't ("Watch minor edits" is enabled).

Default

Option

Multilingual structures

Multilingual tags

Synchronize multilingual categories

Synchronized categories

Multilingual dynamic variables

Plugin Translate

Description

Structures search for equivalent pages in other languages

May cause performance problems with larger structures.

Permits translation management of tags

Make sure that the categories of the translations are sync

List of categories affected by the multilingual synchronization
will be used as a white list (the only categories allowed) or
those specified).

Make dynamic variable content language-specific.

Translate text to the user language

Default

Option

Plugin Language

Plugin Translated

Use database for translation

Manage contribution of translated strings

Record untranslated strings

Machine translation

Description

Show alternative content based on the page language.

Create multilingual links

Use the database to store the translated strings and allow *Edit, export and import languages*

Offers to set whether each translated string should be con

Keep track of the unsuccessful attempts to translate string

Uses machine translation to translate the content of the si
relies on external services that may not be free. Google T

Default

Option

Machine translation implementation

Google Translate API Key

Bing Translate Client ID

Bing Translate Client Secret

Enable machine translation of wiki pages

Certain pages redirect to homepage when language is changed

Description

Select between alternate implementations for machine translation. Different API keys may be required.

The key must be generated from the Google console. Choose the appropriate key.

The application must be registered.

The application must be registered.

Makes additional languages available to the list of languages.

Default

Option

List of pages that redirect

Description

List of names of pages that always redirect to the homepage

Separate page names by commas

Default

Unable to load the jQuery Sortable Tables feature.

Option

Default language

Default admin language

Wiki link format

Description

The site language is used when no other language is specified.

The site language is used in admin section when no other language is specified.

Level of special characters acceptable in wiki links for page names:

`´`î`

"Strict" includes only basic characters such as a-z and 0-9.

in page names should not use "strict".

Default

Option

Default character set for sending mail

Multilingual

Detect browser language

Show pages in user's preferred language

Users can choose the language of their interface

Restrict supported languages

Description

Specify the character encoding used by Tiki when sending

Enables internationalization features and multilingual support

Look up the user's preferred language through browser preferences

When accessing a page which has an equivalent in the user's preferred

page. Based on the

user's preferred language, Tiki will automatically redirect the user to the

Tiki preferences.

Allow users to change the language of the menus and labels

Limit the languages made available on the site.

Use Ctrl+Click to select multiple languages.

Default

Option

Available languages

Language inclusion threshold

Display available translations

Display available translations as dropdown

Synchronize page and site language

Description

By default, all languages supported by Tiki are available on the site. This plugin allows you to restrict the languages to a subset.

When the number of languages is restricted on the site, all languages are added to the preferred language list, even if unspecified by the administrator. This plugin allows you to restrict the specified languages.

Display list of available languages and offer to switch language and articles action buttons.

Instead of a simple icon to list available languages or translate list.

Changing the page language also changes the site language.

Default

Option

Restrict search language by default

Translation assistant

Urgent translation notifications

Incomplete translation notice

Display all languages in a single page

Quantify change size

Description

Only search content that is in the interface language, other

Track translation operations between pages.

Enable changes to be flagged as urgent, so translations are

When a page is translated to a new language, a notice will indicate that the translation is not yet complete.

List all languages as options in the page-language dropdown

In addition to tracking the changes, track the change size of the page is.

Default

Option

Allow minor edits of wiki pages

User watches translations

Multilingual structures

Multilingual tags

Synchronize multilingual categories

Synchronized categories

Description

Minor edits don't flag new content for translation and don't flag content for translation (if "Watch minor edits" is enabled).

Structures search for equivalent pages in other languages.
May cause performance problems with larger structures.

Permits translation management of tags

Make sure that the categories of the translations are synchronized

List of categories affected by the multilingual synchronization
will be used as a white list (the only categories allowed) or as a black list (all categories except those specified).

Default

Option

Multilingual dynamic variables

Plugin Translate

Plugin Language

Plugin Translated

Use database for translation

Manage contribution of translated strings

Record untranslated strings

Description

Make dynamic variable content language-specific.

Translate text to the user language

Show alternative content based on the page language.

Create multilingual links

Use the database to store the translated strings and allow

Edit, export and import languages

Offers to set whether each translated string should be con

Keep track of the unsuccessful attempts to translate string

Default

Option

Machine translation

Machine translation implementation

Google Translate API Key

Bing Translate Client ID

Bing Translate Client Secret

Enable machine translation of wiki pages

Description

Uses machine translation to translate the content of the site. Relies on external services that may not be free. Google Translate.

Select between alternate implementations for machine translation. Different API keys may be required.

The key must be generated from the Google console. Choose the language to translate to.

The application must be registered.

The application must be registered.

Makes additional languages available to the list of languages.

Default

Option

Certain pages redirect to homepage when language is changed

List of pages that redirect

Description

List of names of pages that always redirect to the homepage
Separate page names by commas

Default

Unable to load the jQuery Sortable Tables feature.

INTERTIKI - CLIENT

Option

Intertiki

Description

Allows several Tiki sites (slaves) to get authentication from

Default

Option

Client key for this site

Intertiki shared cookie

Master Tiki server

Import user preferences

Description

This must match the shared key entered in the Master Tiki server's shared key field.

Causes a user who logs into or out of either the slave or master to log out of all other sites.

The remember me login feature must be on.

Master Tiki server that this client will obtain user authorization from.

Overrides manually registered local users

Client Tiki will copy the user preferences from the master server.

This will overwrite local user preferences every time the user logs in.

Default

Option

Import user groups

Limit group import

Description

Groups the user belongs to on the master server will be imported.

This will overwrite local groups every time a user logs in.

This list will limit the group import feature to only those groups listed.

Comma-separated list of case-sensitive imported groups.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Intertiki

Client key for this site

Description

Allows several Tiki sites (slaves) to get authentication from

This must match the shared key entered in the

Master `MasterKey`™ `MasterKey`, `MasterKey`, `MasterKey` `MasterKey`...`MasterKey`;
key field.

Default

Option

Intertiki shared cookie

Master Tiki server

Import user preferences

Import user groups

Description

Causes a user who logs into or out of either the slave or master to log out of all other sites.

The remember me login feature must be on.

Master Tiki server that this client will obtain user authorization.

Overrides manually registered local users

Client Tiki will copy the user preferences from the master.

This will overwrite local user preferences every time the user logs in.

Groups the user belongs to on the master server will be in effect.

This will overwrite local groups every time a user logs in.

Default

Option

Limit group import

Description

This list will limit the group import feature to only those groups listed below.

Comma-separated list of case-sensitive imported groups.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Intertiki

Client key for this site

Intertiki shared cookie

Description

Allows several Tiki sites (slaves) to get authentication from

This must match the shared key entered in the

Master `AuthKey`™ `AuthKey`, `AuthKey`, `AuthKey` `AuthKey`...`AuthKey` key field.

Causes a user who logs into or out of either the slave or master of all other sites.

The remember me login feature must be on.

Default

Option

Master Tiki server

Import user preferences

Import user groups

Limit group import

Description

Master Tiki server that this client will obtain user authorization

Overrides manually registered local users

Client Tiki will copy the user preferences from the master

This will overwrite local user preferences every time the user logs in.

Groups the user belongs to on the master server will be imported

This will overwrite local groups every time a user logs in.

This list will limit the group import feature to only those groups

Comma-separated list of case-sensitive imported groups.

Default

Unable to load the jQuery Sortable Tables feature.

Option

Intertiki

Client key for this site

Intertiki shared cookie

Master Tiki server

Description

Allows several Tiki sites (slaves) to get authentication from

This must match the shared key entered in the

Master `AuthKey`™ `AuthKey`, `AuthKey`, `AuthKey`™ `AuthKey`...`;`
key field.

Causes a user who logs into or out of either the slave or m
of all other sites.

The remember me login feature must be on.

Master Tiki server that this client will obtain user authoriza

Overrides manually registered local users

Default

Option

Import user preferences

Import user groups

Limit group import

Description

Client Tiki will copy the user preferences from the master

This will overwrite local user preferences every time the u

Groups the user belongs to on the master server will be in

This will overwrite local groups every time a user logs in.

This list will limit the group import feature to only those gr

Comma-separated list of case-sensitive imported groups.

Default

Unable to load the jQuery Sortable Tables feature.

INTERTIKI - MASTER SERVER

Option

This site is a master server

Description

Default

Option

Access log file

Errors log file

Description

location, from your tiki root dir, where you want the access log file stored.

location, from your tiki root dir, where you want the error log file stored

Default

Unable to load the jQuery Sortable Tables feature.

Option

This site is a master server

Access log file

Description

location, from your tiki root dir, where you want the access log file stored.

Default

Option

Errors log file

Description

location, from your tiki root dir, where you want the error log file stored

Default

Unable to load the jQuery Sortable Tables feature.

Option

This site is a master server

Access log file

Errors log file

Description

location, from your tiki root dir, where you want the access log file stored.

location, from your tiki root dir, where you want the error log file stored

Default

Unable to load the jQuery Sortable Tables feature.

Option

This site is a master server

Access log file

Errors log file

Description

location, from your tiki root dir, where you want the access log file stored.

location, from your tiki root dir, where you want the error log file stored

Default

Unable to load the jQuery Sortable Tables feature.