

ì<œìŠ¤í...œ êµ¬ì,,±

í[°]í, ø8 ì—ì„œ ë„ìž...ë„

íœlŠxí...œ ëµ—ì, ±ì€ ìœlŠxí...œ ë'ë|—ìžé|œ i•~í—ì—ê, ^ í[°]i, xí~ lTM, ë¶ë|—ì, œ l, í~ l, xí • i^{1/4}ë¶ë¥^{1/4}
ë³ë€^{2/1}í~ë „ëí i•©ë<^ë<x. INI íŒŒí^{1/4}ì, ì œë³µí•“ìœ^{1/4}ëiœí”, ê'ë|—ìžé“xí€ ìžì^k ë“xí~ ë^a“ë” í[°]i, xì l¹~l—
ëŒŒí•~í—ì xí~ ëµ—ì, ±ì, ë³“ìœ i• l[^]~l^z lSMë<^ë<x.

í^oí,¤10 i-ì,,œ if'ëiœ ë,,ìž...ëœ ë, `íš©: i • íŒŒì¼ëiœë¶í,,° ë¤"ë"“ì,, eïœë"œí•~ëŠ" i,, ífl, -í• (í,,ëiœí,, YAML í~•ì<ë, `í-ì,,œ, <http://profiles.tiki.org/Module+Handler> i™€ ìœ i,-í•~ê²Œ). ê'ë|¬ íŒ"ë,, ë, `ë¶í-ì,,œ "ë¤"ë"“ íŒŒì¼" i,, ê²ëìf‰óí•~ì<œí~¤.

í<óí,¤11 i–i,,œ if’ëiœ ë,,iž...ëœ ë, ‘iš©: db/preconfiguration.php íŒŒí¼i€ ï²« í<óí,¤ i,,¤i¹`í<œi— i œi·^ëœ
ë°i „°ë² i „iŠ¤ ë³`i·^ë, ‘iš©i,, i–i·^í· i^~ iž^iŠµë<^ë<¤. i „ëŠ” ê°ëif i,,œë²,, i œë³µižëiœ i·^í—¬ê, ^ ê³ ê°i
í<óí,¤ i,,¤i¹`í” „ëiœê·,ëž”i— i „ë·^í·^ê, ^ i „,— mysql i,, ê°ê, ^ ë<¤ë¥, iž, „i`í^ ë¹ „ë°ëë²^í, „i™ë
i, ¬iš©ižë¤...iœ^í·^ëiœ i,, „i,,¤i ·i· i^~ iž^ë, „ëi í·^ë<¤.

Í<°í, æ íŒœ(farm)ê³¼ í~ „íŠæíŒ... íšŒì, ¬ì—ì,,œ
ì, ¬ìš©ê°€ëŠ¥í•œ íš©ë²•

- BigBlueButton ê³¹/₄ ê°™ ï€ ë<¤ë¥, ï„œë¹ „ïŠ¤ëiœ ï„¬ïš©ïži~ ê° „ì„ì—†ì’ ì—°ê²º
 - ë©¤ì¹¤œì™ € ê°™ ï€ ê³ ê‰ ï„¤ì •ì, êµ¬ì„±
 - ï§ëì» ê³ „ïši~ ï¹/₄ë¶€ê°€ ï„ „ë<Œ ê „°ëŠ¥ì„ ë¹ „í™ œì„±í™ ”
 - ï „ì—ì ìœ¹/₄ëiœ íŠì• ë „°ëŠ¥ì„ ë¹ „í™ œì„±í™ ”í „œ¹/₄ëiœì” ê³ „ì•^ ì±...ìž„ìži—ê²Œ ì•Œë¹/₄
 - tiki_p_admin ï„, ï œê³µí„ ~ï§ëë§Œ ï¹/₄ë¶€ ê „°ëŠ¥ì„, ï „ê¹/₄ë¶€ê°€ëëŠ¥í•~ê²Œ ë§Œë“-
 - í~ „ïŠ¤ëŒ... íšŒì„—ëŠ” è„“ë” ê „°ëŠ¥ì„, í•œ ê³³— íf’ìž—í•œ í~ „ìœíì„, ï œê³µí„ ~ê „°ë¥¹/₄ ì• „ì~ ìž~ï§ëë§Œ, ë<¤Œì~ „ì„¬ïš©ì€ ïœí•œí• „ì~ ìž~ë<
 - ï„¤í—~ì „ê „°ëŠ¥
 - ï„œë², „ì „ê „œ„ „ì—„ì „¬ïš©ë „ì~ ìž~ëŠ” ê „°ëŠ¥ (ëŒ€ë¶€ë¶„ „ì „¤ì¹~ì—„œëŠ”
 - ê „œì„@ï§ëë§Œ, ïœ„ „ìœíŒœ(WikiFarm) „ì— „œëŠ” ì¢*ë* „ì¹/₄ì€ „ì• „ë<¤)
 - ì» „ì„¤Œ... íšŒì„—ëŠ” „ì„¬ïš©ìži— ëŒ€í• „ì— „ë” ë< „ì~œí•œ ê „’ë! „ì„ëŒë“œê³ „ì„¶ì— „í• ê²fi’ „ë<
 - í< „œë¥¹/₄ „ì„¬ïš© „ì„ „œœê„ „ëž” „ë¹Œœë” (í” „ë „ìž „ì„Œí—) „œœì” „ì„¬ïš©

ì<œìŠœí...œ êµ¬ì,,±ì,, í™ œì,,±í™ ”

í<oeiŠxí...œ êµ¬ì,±ì€ db/local.php íŒŒì¼œíœë¶í, „ í™ œì,±í™ ”ë~ì-ì¼œëŒ í·©ë<ë<x. í°í,¤8 ëº ê„ í’ í, „ì-ì,œ ìƒ„±éœ ì, „¤ì¹~ëŠ” ê, „œ¹¼œíœ ìƒ„±éœ íŒŒì¼ ë, „ë¶í, „ í·í•~í•~ê³ iž~ìŠµë<ë<x.

```
$system configuration file = '/etc/tiki.ini'; $system configuration identifier = 'client1.example.com';
```

db/local.php ë, ´ë¶€ì˜ ë«¤ë¥, if˜í”Œ êµ¬ì„±, ifëŒ€ ê²¹/₂ëíœë¥¹/₄ í¬í”

```
$system configuration file = 'db/tiki.ini'; $system configuration identifier = 'client1.example.com';
```

í i ~í ì œë¥¼ ì, -iš©í•~ê²Œ ë~ë©' .htaccess ê°€ í™ œì„±í™"ë~l-`íž`l-`ì„œ tiki.ini ê°€ ì½íž`ì§€ ì•Šë„ëi í•~ëŠ" ê²fi— ìœ ì~í•~ì`ì<œì~¤.

í™œì„±í™"ë˜ë@' , í°í, æŠ" êµ¬ì„± íŒŒí¼ëíœë¶í„° ì„íƒœì<ë³, ïžì— ê„°ë~í•~ì—ì ¶í"ê°ë„ë„ë 1ì„

ì½ì-` ë“œì½ ê²fiž...ë[^]ë<œ. ì<œ³,ižëŠ” iž,,i~i~ ê²fi½ i~^ iž^i§ëëŒ, ì,-i’íŠ, i~¹i¢ ê³,,iš iœ’ í•~ë, ~ë¥½ i§ëì •í•~ê, ° ìœ,,i•~i- -i,-iš©ë i~^ iž^iŠµë<^ë<œ. êµ-ì,,± iŒŒì½ ë, ‘ë¶ëì—ëŠ” ë<œìœ’ êµ-ì,,±i’ i •i~ë i~^ iž^iœ½ë©° ifitì` i,-iš©ë i~^ iž^iŠµë<^ë<œ.

INI êµ-ì,,± iŒŒì½

if”í”Œ INI iŒŒì½

```
[global] preference.feature_wysiwyg = "n" preference.feature_sefurl = "y" preference.helpurl = "http://support.example.com/" ; ... more settings ... [basic : global] preference.feature_wiki = "y" preference.feature_forums = "n" preference.feature_trackers = "n" ; ... more settings ... [pro : global] preference.feature_wiki = "y" ; BBB configured, but user can still toggle on/off preference.bigbluebutton_server_location = "bbb.example.com" preference.bigbluebutton_server_salt = "1234abcd1234abcd" ; ... more settings ... [client1.example.com : pro] preference.browsertitle = "Client #1 Intranet" preference.sender_email = client1@example.com
```

In the example above, the following preferences would be set for using the identifier *client1.example.com*:

- feature_wysiwyg = n
- feature_sefurl = y
- helpurl = <http://support.example.com/>
- feature_wiki = y
- bigbluebutton_server_location = bbb.example.com
- bigbluebutton_server_salt = 1234abcd1234abcd
- browsertitle = Client #1 Intranet
- sender_email = [client1 at example.com](mailto:client1@example.com)

; at the beginning indicates comments

Disable classes of preferences

Preferences can be disabled by setting a value to each of them individually. However, this process may be long and will require maintenance with the evolutions of Tiki.

Tiki allows to set multiple rule priorities, each verification priority can allow or deny a preference. Rules can be specified at various levels, just like the preference overrides above.

Various rules

```
[global] rules.0 = deny experimental new [pro : global] rules.5 = allow new rules.10 = allow feature_wysiwyg
```

ìœ,,i~i~ì œì-ì,,œ, pro i<œ³,ižë¥½ i,-iš©í•~ëŠ” i,-i’íŠ,ëŠ” if^ ê, °ëŠ¥ê³½ wsyswyg (ì<œí—~i i~i~ë¹/4ê³ ifœê· ë~i- iž^iŒ) i,, i,-iš©í•~ë,,ëi i- ^iš©ë ê²fi’ê³ , if^ i<œí—~i ê, °ëŠ¥ë“œ,, i-í•”í• ê²fi’ë<œ, i•~i§ëëŒ, ê³½ê±°ì~ i<œí—~i ê, °ëŠ¥ë“ i-í•, iž^ iœí•œœ ê²fi’ë<œ. ê³’ë<œ ët’i¢ iš°i,, i~œiœ, ê°¢ iš°i,, i~œ½ëiœ i‰ê°¢ë~ê³ ífif‰oì¢ i½i¹~ëœ ë, iš©ì` ë°œê²-ë~ë©’ ë©^i¶œ ê²fi’ë<œ.

draconian i œê³µìžëŠ” ë<œiŒê³½ ê°™i¢ ê²fi,, i,-iš©í• i~^ë,, iž^ë<œ:

[global] rules.0 = deny all rules.1 = allow basic

ì, í~, ì,, xì •ì€ ë°°í— `í,, í—í·”í·~ëŠ' 'tags' í, xë¥¼ ì, -ìš©í·~ì—í—ì •í~í— ífœé·, ë í• „ìš” è°€ íz^ë<x. ë<-ë!-ìš€ì •ë~ìš€ ì·ŠëŠ”í·œ, ë¤”ë“ ì,, í~, ì,, xì •ì€ 'ê³ ê,%o'ìœ¼ë!œ ì—ê”ì§,,ë<x..

ì, ñì „êµñì,, ± íŒŒì^{1/4}

db/preconfiguration.php

```
<?php // This is Tiki's preconfiguration file. // This holds values which can provide preconfiguration  
values in the installer, when local.php does not yet exist // Uncomment and change values as  
appropriate $host_tiki_preconfig='localhost'; $user_tiki_preconfig='tiki';  
$pass_tiki_preconfig='password'; $dbs_tiki_preconfig='tiki db';
```

Related

- TRIM
 - Multitiki